Edition 1

one
LIGHT

Lighting Catalogue

2020




one
LIGHT

Message from our CEO

We are all very proud and excited to present our biggest and best catalogue so far, ONE Light 2020 – Edition 1.

On behalf of the entire ONE Light team, I would like to take this opportunity to welcome all our new customers to our distribution network.

In 2019, we expanded our global presence by starting cooperation with partners in 14 new countries. Our products are now present in South America and Australia. It gives us great pleasure to see new partners trusting us and seeing our existing partners growing with us.

During this past year, we also upgraded our website and our B2B portal, giving our partners and their customers quick access to our products and their characteristics. Obtaining data sheets, IES files, installation manuals, CE certificates as well as checking the stock availability has never been easier.

In addition, we have introduced more than 600 new item codes, new designs, and new ideas.

In year 2020, we plan to improve our website further by introducing an E-shop and order system for all our registered customers.

We thank you for your ongoing support and your trust in ONE Light. We are dedicated more than ever to continue the hard work in order to provide the best possible quality in products and services.

Yiotis Demetriou
CEO
ONE Light Ltd



"Do it with passion or forget it!"

The Company

Founded in 2011 ONE Light supplies technical lighting to retailers, wholesalers and distributor partners across 65 countries globally. ONE Light specialises in modern design LED lighting offering quality at affordable prices.



Warehouse

Operating from it's modern 5000m^2 warehouse, ONE Light provides 99% stock availability on all catalogue products. All orders can be prepared for dispatch within 24hours.



Graphics Department

Our graphics department designs every single product package and catalogues. All item photos are taken in our own photo studio.





Technical Department

ONE Light products are tested to meet the technical and quality standards demanded by our international customers.



Online Catalogue Order

To get a copy of our latest catalogue fill in the application form on our website.



I would like to receive the ONE Light catalogue:

Name *

Company Name

Company Website

Email address *

Tel No.

Country *

–

Profession *

- Lighting retailer (Shop)
- Lighting wholesaler / distributor
- Lighting installer / electrician
- Architect / Designer
- Private use
- Other

Type verification code *

5149

ORDER

Why ONE Light?

Choose ONE Light as your lighting partner.

1-DAY Delivery

Have your lighting products the moment you need them. ONE Light's fast delivery service promises shipment within 24hours from order confirmation. Our exports staff will quote the best freight rate for your orders. We offer competitive worldwide sea and air freight rates.





99% Stock Availability

ONE Light's capability of immediate delivery is based on the fact that 99% of all catalogue items are in stock and ready for delivery from our new 5000m^2 warehouse.

Packaging

ONE Light's new packaging is fresh and eye catching, designed to clearly display the information and the product. The ranges are colour coded for easy identification and to stand out on the shelf.

LED HALO FLUO HQI



Products

With over 2000 product codes covering the majority of your technical lighting needs, ONE Light provides a one stop solution to satisfy most of the customers searching for quality lighting.

B2B Customer Login

All the info you need to know.. on your screen with a touch of a button.

Online Features

Connect with our B2B customer login application on our website to access all the information you will need to work with ONE Light.



Info On B2B Application



- Product availability & arrival dates
- Open orders
- Photos
- Product data sheets
- Installation manuals
- IES files
- CE certificates
- Account statements

Symbols

Decoding our catalogue.



YEARS OF WARRANTY

2 YEAR 3 YEAR 5 YEAR

NEW PRODUCTS

new

CLASS PROTECTION

III

ENERGY CLASS

A-A++ B-A++

IP RATING

IP20 IP65

LED BUILT IN

LED BUILT IN

EUROPEAN CONFORMITY MARK

CE

ITEMS OFFERED AT SPECIAL PRICE

offer

MOUNTING POSITION

INDOOR/OUTDOOR INSTALLATION

ROTATION RANGE

ADJUSTABLE 2 directions

ADJUSTABLE 1 direction

COLOUR RENDERING INDEX

80 CRI

DARK LIGHT

DARK LIGHT

IMPACT PROTECTION RATING

IK08

PIECES PER BOX

SENSOR

DIMMABLE

DIMMABLE

CEILING DEPTH REQUIRED

CUTOUT HOLE

LIGHT DISTRIBUTION & BEAM ANGLE

30°

PUSH TO DIM

PUSH TO DIM

CABLE LENGTH

FAST CONNECTION

QUICK FIX

MAXIMUM UNDERWATER DEPTH

1m max

Colour Codes

Decoding our colours.







one

NEW PRODUCTS 2020

EDITION 2

10105H | 10W | MR16 | GU10 | Die cast



A-A++ 10105H/W

new

DARK LIGHT

IP20

5 YEAR



10105H/B



10105H/BS



050182 | Rings for 10105H | Aluminium



050182/W White

new

IP20



050182/B Black



050182/BS Brass

Example



10105H/B + 050182/W + 050182R/W

050182R | Round base for 10105H | Aluminium



050182R/W White

new

IP20



050182R/B Black



050182R/BS Brass

Example



10105H/B + 050182/BS + 050182R/B

050182RA | Square base for 10105H | Aluminium



050182RA/W White

new

IP20



050182RA/B Black



050182RA/BS Brass

Example



10105H/B + 050182/BS + 050182RA/BS

050182RB | Double Square base for 10105H | Aluminium



050182RB/W White

new

IP20



050182RB/B Black



050182RB/BS Brass

Example



10105H/W + 050182/BS + 050182RB/W

Order Code	Colour	Watts	Input	Class					Notes
10105H/W	White	10W	100-240V		15cm	64mm	100mm	50	-
10105H/B	Black	10W	100-240V		15cm	64mm	100mm	50	-
10105H/BS	Brass	10W	100-240V		15cm	64mm	100mm	50	-

Recessed Spots Fixed



10105R1P | 50W | MR16 | GU10 | Aluminium









Order Code	Colour	Watts	Input	Class					Notes
10105R1P/W	White	50W	100-240V		15cm	68mm	120mm	50	Prismatic glass



10105R2P | 50W | MR16 | GU10 | Aluminium









Order Code	Colour	Watts	Input	Class					Notes
10105R2P/W	White	50W	100-240V		15cm	82mm	130mm	50	Prismatic glass



10105E1 | 50W | MR16 | GU10 | Aluminium









Order Code	Colour	Reflector	Watts	Input	Class					Notes
10105E1/W/B	White	Black	50W	100-240V		15cm	62mm	100mm	50	-
10105E1/B/GL	Black	Gold	50W	100-240V		15cm	62mm	100mm	50	-



10108D/W/W

10108D | 8W | COB LED | Die cast

new
DARK LIGHT
IP20

LED BUILT IN
80 CRI
CE
3 YEAR



10108D/B/W



10108D/BS/W



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
10108D/W/W	White	Warm white	3000K	8W	600lm	36°	230V		73mm	90mm	50	Complete with 300mA driver
10108D/B/W	Black	Warm white	3000K	8W	600lm	36°	230V		73mm	90mm	50	Complete with 300mA driver
10108D/BS/W	Brass	Warm white	3000K	8W	600lm	36°	230V		73mm	90mm	50	Complete with 300mA driver



10108R/W/W

10108R | 8W | COB LED | Die cast

new
IP20

LED BUILT IN
80 CRI
CE
3 YEAR



10108R/B/W



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
10108R/W/W	White	Warm white	3000K	8W	560lm	60°	230V		68mm	50mm	50	Complete with 350mA driver
10108R/B/W	Black	Warm white	3000K	8W	560lm	60°	230V		68mm	50mm	50	Complete with 350mA driver



10108A | 8W | COB LED | Die cast | Assymetric reflector

new
DARK LIGHT
IP20

LED BUILT IN
80 CRI
CE
3 YEAR





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
10108A/W/W	White	Warm white	3000K	8W	560lm	50°	230V		68mm	85mm	50	Complete with 350mA driver



50108A | 8W | COB LED | Die cast | Assymetric reflector

new
DARK LIGHT
IP20

LED BUILT IN
80 CRI
CE
3 YEAR





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
50108A/W/W	White	Warm white	3000K	8W	560lm	50°	230V		73x73mm	85mm	50	Complete with 350mA driver

10108D1 | 8W | COB LED | Die cast



A-A++

new DARK LIGHT IP20 | LED BUILT IN | 80 CRI | CE | 5 YEAR





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
10108D1/W/W	White	Warm white	3000K	8W	560lm	36°	230V		73mm	105mm	50	Complete with 300mA driver

10106DC | 6W | COB LED | Die cast



A-A++ 10106DC/W/W

new DARK LIGHT IP20 | LED BUILT IN | 90 CRI | DIMMABLE | QUICK FIX | CE | 5 YEAR



10106DC/B/W



Suitable for 89008 driver.



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
10106DC/W/W	White	Warm white	3000K	6W	570lm	36°	350mA	III	40cm	55mm	75mm	50	Requires 350mA driver
10106DC/B/W	Black	Warm white	3000K	6W	570lm	36°	350mA	III	40cm	55mm	75mm	50	Requires 350mA driver

10112DC | 12W | COB LED | Die cast



A-A++ 10112DC/W/W

new DARK LIGHT IP20 | LED BUILT IN | 90 CRI | DIMMABLE | QUICK FIX | CE | 5 YEAR



10112DC/B/W



Suitable for 89015A driver.



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
10112DC/W/W	White	Warm white	3000K	12W	1100lm	36°	700mA	III	40cm	75mm	90mm	50	Requires 700mA driver
10112DC/B/W	Black	Warm white	3000K	12W	1100lm	36°	700mA	III	40cm	75mm	90mm	50	Requires 700mA driver

10118DC | 18W | COB LED | Die cast



A-A++ 10118DC/W/W

new DARK LIGHT IP20 | LED BUILT IN | 90 CRI | DIMMABLE | QUICK FIX | CE | 5 YEAR



10118DC/B/W



Suitable for 89030C driver.



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
10118DC/W/W	White	Warm white	3000K	18W	1750lm	36°	500mA	III	40cm	94mm	100mm	30	Requires 500mA driver
10118DC/B/W	Black	Warm white	3000K	18W	1750lm	36°	500mA	III	40cm	94mm	100mm	30	Requires 500mA driver



10106DH | 6W | COB LED | Die cast

Complete with honeycomb.







Suitable for 89008 driver.



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
10106DH/W/W	White	Warm white	3000K	6W	500lm	36°	350mA	III	40cm	63mm	60mm	50	Requires 350mA driver



10112DH | 12W | COB LED | Die cast

Complete with honeycomb.







Suitable for 89015A driver.



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
10112DH/W/W	White	Warm white	3000K	12W	1000lm	36°	700mA	III	40cm	72mm	60mm	50	Requires 700mA driver



10118DH | 18W | COB LED | Die cast

Complete with honeycomb.







Suitable for 89030C driver.



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
10118DH/W/W	White	Warm white	3000K	18W	1500lm	36°	500mA	III	40cm	91mm	70mm	30	Requires 500mA driver



A-A++

10101LA | 2W | LED | Die cast

new

IP44

LED BUILT IN

80 CRI

DIMMABLE

QUICK FIX

3 YEAR



Suitable for 89004A driver.



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
10101LA/W/W	White	Warm white	3000K	2W	150lm	36°	700mA	III	200cm	27mm	55mm	100	Requires 700mA driver



A-A++ 10108H/W/W

10108H | 8W | COB LED | Die cast

new

DARK LIGHT

IP54

LED BUILT IN

90 CRI

3 YEAR



10108H/B/W



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
10108H/W/W	White	Warm white	3000K	8W	600lm	36°	230V		75mm	70mm	50	Complete with 200mA driver
10108H/B/W	Black	Warm white	3000K	8W	600lm	36°	230V		75mm	70mm	50	Complete with 200mA driver



A-A++

10107DF | 7W | SMD LED | Fire Rated | Metal

Complete with white ring.

new

IP65

LED BUILT IN

80 CRI

TRIAC

DIMMABLE

FIRE RATED

3 YEAR





Optional rings.
Order code 050178/B Black
050178/C Chrome



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
10107DF/W	White	Warm white	3000K	7W	500lm	60°	230V		65mm	90mm	36	Complete with dimmable driver

50106B | 6W | COB LED | Die cast



A-A++ 50106B/W/W

new

IP20

LED BUILT IN

90 CRI

CE

3 YEAR



50106B/B/W



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
50106B/W/W	White	Warm white	3000K	6W	480lm	38°	230V	☐	50x45mm	70mm	50	Complete with 135mA driver
50106B/B/W	Black	Warm white	3000K	6W	480lm	38°	230V	☐	50x45mm	70mm	50	Complete with 135mA driver

50306B | 12W | COB LED | Die cast



A-A++ 50306B/W/W

new

IP20

LED BUILT IN

90 CRI

CE

3 YEAR



50306B/B/W



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
50306B/W/W	White	Warm white	3000K	12W	960lm	38°	230V	☐	124x45mm	70mm	48	Complete with 300mA driver
50306B/B/W	Black	Warm white	3000K	12W	960lm	38°	230V	☐	124x45mm	70mm	48	Complete with 300mA driver

50406B | 16W | COB LED | Die cast



A-A++ 50406B/W/W

new

IP20

LED BUILT IN

90 CRI

CE

3 YEAR



50406B/B/W



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
50406B/W/W	White	Warm white	3000K	16W	1280lm	38°	230V	☐	85x85mm	70mm	36	Complete with 400mA driver
50406B/B/W	Black	Warm white	3000K	16W	1280lm	38°	230V	☐	85x85mm	70mm	36	Complete with 400mA driver

50506B | 20W | COB LED | Die cast



A-A++ 50506B/W/W

new

IP20

LED BUILT IN

90 CRI

CE

3 YEAR



50506B/B/W



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
50506B/W/W	White	Warm white	3000K	20W	1600lm	38°	230V	☐	200x45mm	70mm	20	Complete with 500mA driver
50506B/B/W	Black	Warm white	3000K	20W	1600lm	38°	230V	☐	200x45mm	70mm	20	Complete with 500mA driver

Recessed Spots Fixed LED



A-A++ 50906B/W/W

50906B | 36W | COB LED | Die cast

new

IP20

LED BUILT IN

90 CRI

CE

3 YEAR



50906B/B/W



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
50906B/W/W	White	Warm white	3000K	36W	2880lm	38°	230V		125x125mm	70mm	18	Complete with 850mA driver
50906B/B/W	Black	Warm white	3000K	36W	2880lm	38°	230V		125x125mm	70mm	18	Complete with 850mA driver



A-A++ 50006B/W/W

50006B | 40W | COB LED | Die cast

new

IP20

LED BUILT IN

90 CRI

CE

3 YEAR



50006B/B/W



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
50006B/W/W	White	Warm white	3000K	40W	3200lm	38°	230V		386x45mm	70mm	15	Complete with 1000mA driver
50006B/B/W	Black	Warm white	3000K	40W	3200lm	38°	230V		386x45mm	70mm	15	Complete with 1000mA driver

Recessed Spots Adjustable



E-A++

11105A1 | 50W | MR16 | GU10 | Aluminium

new

IP20

ADJUSTABLE

CE

5 YEAR



Complete with 0950G.



Order Code	Colour	Watts	Input	Class					Notes
11105A1/BBS	Brushed brass	50W	100-240V		15cm	68mm	120mm	100	-

11102DB | 2W | COB LED | Super narrow beam | Die cast



A-A++

new

IP20

LED BUILT IN

80 CRI

DIMMABLE

QUICK FIX

ADJUSTABLE

3 YEAR



Suitable for 89004A driver.



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
11102DB/W/W	White	Warm white	3000K	2W	140lm	3°	700mA	III	40cm	52mm	65mm	100	Requires 700mA driver

11110E | 10W | COB LED | Die cast



A-A++ 11110E/W/W

new

DARK LIGHT

IP20

LED BUILT IN

80 CRI

ADJUSTABLE

3 YEAR



11110E/B/W



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
11110E/W/W	White	Warm white	3000K	10W	850lm	30°	230V		85mm	80mm	40	Complete with 250mA driver
11110E/B/W	Black	Warm white	3000K	10W	850lm	30°	230V		85mm	80mm	40	Complete with 250mA driver

11120E | 20W | COB LED | Die cast



A-A++ 11120E/W/W

new

DARK LIGHT

IP20

LED BUILT IN

80 CRI

ADJUSTABLE

3 YEAR



11120E/B/W



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
11120E/W/W	White	Warm white	3000K	20W	1700lm	30°	230V		140mm	110mm	20	Complete with 500mA driver
11120E/B/W	Black	Warm white	3000K	20W	1700lm	30°	230V		140mm	110mm	20	Complete with 500mA driver

11130E | 30W | COB LED | Die cast



A-A++ 11130E/W/W

new

DARK LIGHT

IP20

LED BUILT IN

80 CRI

ADJUSTABLE

3 YEAR



11130E/B/W



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
11130E/W/W	White	Warm white	3000K	30W	2550lm	30°	230V		200mm	95mm	10	Complete with 750mA driver
11130E/B/W	Black	Warm white	3000K	30W	2550lm	30°	230V		200mm	95mm	10	Complete with 750mA driver

Recessed Spots Adjustable LED



A-A++

11106M | 6W | COB LED | Die cast

new

IP20

LED BUILT IN · 90 CRI · DIMMABLE · QUICK FIX · ADJUSTABLE · CE · 3 YEAR



Suitable for 89008 driver.



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
11106M/W/W	White	Warm white	3000K	6W	540lm	24°	350mA	III	40cm	55mm	95mm	60	Requires 350mA driver



A-A++

51106M | 6W | COB LED | Die cast

new

IP20

LED BUILT IN · 90 CRI · DIMMABLE · QUICK FIX · ADJUSTABLE · CE · 3 YEAR



Suitable for 89008 driver.



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
51106M/W/W	White	Warm white	3000K	6W	540lm	24°	350mA	III	40cm	58x58mm	95mm	60	Requires 350mA driver



A-A++

51206M | 2x6W | COB LED | Die cast

new

IP20

LED BUILT IN · 90 CRI · DIMMABLE · QUICK FIX · ADJUSTABLE · CE · 3 YEAR



Suitable for 2x89008 driver.



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
51206M/W/W	White	Warm white	3000K	2x6W	2x540lm	24°	350mA	III	40cm	108x58mm	95mm	36	Requires 2x350mA drivers



A-A++

51306M | 3x6W | COB LED | Die cast

new

IP20

LED BUILT IN · 90 CRI · DIMMABLE · QUICK FIX · ADJUSTABLE · CE · 3 YEAR



Suitable for 3x89008 driver.



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
51306M/W/W	White	Warm white	3000K	3x6W	3x540lm	24°	350mA	III	40cm	150x58mm	95mm	24	Requires 3x350mA drivers



51406B/W/W

51406B | 16W | COB LED | Die cast





51406B/B/W





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
51406B/W/W	White	Warm white	3000K	16W	1280lm	38°	230V		100x100mm	100mm	30	Complete with 400mA driver
51406B/B/W	Black	Warm white	3000K	16W	1280lm	38°	230V		100x100mm	100mm	30	Complete with 400mA driver



51506B/W/W

51506B | 20W | COB LED | Die cast





51506B/B/W



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
51506B/W/W	White	Warm white	3000K	20W	1600lm	38°	230V		212x55mm	70mm	30	Complete with 500mA driver
51506B/B/W	Black	Warm white	3000K	20W	1600lm	38°	230V		212x55mm	70mm	30	Complete with 500mA driver

Downlights Fixed LED



10116FD/W/BS

10116FD | 16W | SMD 2835 | Die cast





10116FD/B/BS



Order Code	Colour	Reflector	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class				Notes
10116FD/W/BS	White	Brass	Warm white	3000K	16W	800lm	230V		155mm	80mm	20	Complete with 300mA driver
10116FD/B/BS	Black	Brass	Warm white	3000K	16W	800lm	230V		155mm	80mm	20	Complete with 300mA driver

10110U | 10W | SMD 2835 | Die cast







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
10110U/W/C	White	Cool white	4000K	10W	750lm	100°	230V		86mm	55mm	40	Complete with 200mA driver
10110U/W/W	White	Warm white	3000K	10W	750lm	100°	230V		86mm	55mm	40	Complete with 200mA driver

10124U | 24W | SMD 2835 | Die cast







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
10124U/W/C	White	Cool white	4000K	24W	1800lm	100°	230V		160mm	55mm	20	Complete with 500mA driver
10124U/W/W	White	Warm white	3000K	24W	1800lm	100°	230V		160mm	55mm	20	Complete with 500mA driver

10130U | 30W | SMD 2835 | Die cast







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
10130U/W/C	White	Cool white	4000K	30W	2250lm	100°	230V		205mm	65mm	20	Complete with 750mA driver
10130U/W/W	White	Warm white	3000K	30W	2250lm	100°	230V		205mm	65mm	20	Complete with 750mA driver
10130U/B/C	Black	Cool white	4000K	30W	2250lm	100°	230V		205mm	65mm	20	Complete with 750mA driver
10130U/B/W	Black	Warm white	3000K	30W	2250lm	100°	230V		205mm	65mm	20	Complete with 750mA driver



10107UV | 7W | SMD 2835 | Die cast

Adjustable colour temperature.



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
10107UV/W	White	Daylight-Cool white-Warm white	6000K-4000K-3000K	7W	525lm	100°	230V		70mm	60mm	40	Complete with 180mA driver



10113UV | 13W | SMD 2835 | Die cast

Adjustable colour temperature.



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
10113UV/W	White	Daylight-Cool white-Warm white	6000K-4000K-3000K	13W	975lm	100°	230V		120mm	70mm	20	Complete with 300mA driver



10120UV | 20W | SMD 2835 | Die cast

Adjustable colour temperature.



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
10120UV/W	White	Daylight-Cool white-Warm white	6000K-4000K-3000K	20W	1500lm	100°	230V		170mm	75mm	20	Complete with 550mA driver



10130UV | 30W | SMD 2835 | Die cast

Adjustable colour temperature.



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
10130UV/W	White	Daylight-Cool white-Warm white	6000K-4000K-3000K	30W	2250lm	100°	230V		210mm	80mm	20	Complete with 700mA driver



7820 | 4,8W/m | SMD 2216 | 70LEDs/m

3M Double face adhesive.

new IP20 | LED BUILT IN | 90 CRI | DIMMABLE | CE | 5 YEAR



Supplied in 5m roll.



Dimming remote control.
Order code 20030.



Order Code	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
7820/UW	Ultra warm white	2200K	4,8W/m	384lm/m	24V DC	III	40	Requires 24V DC driver



7835 | 14,4W/m | SMD 2835 | 70LEDs/m

3M Double face adhesive.

new IP20 | LED BUILT IN | 90 CRI | DIMMABLE | CE | 5 YEAR



Supplied in 5m roll.



Dimming remote control.
Order code 20030.



Order Code	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
7835/UW	Ultra warm white	2200K	14,4W/m	1060lm/m	24V DC	III	40	Requires 24V DC driver



7844 | 11W/m | COB LED

3M Double face adhesive.

new IP20 | LED BUILT IN | 90 CRI | DIMMABLE | CE | 5 YEAR



Supplied in 5m roll.



Dimming remote control.
Order code 20030.



Order Code	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
7844/C	Cool white	4000K	11W/m	1045lm/m	24V DC	III	20	Requires 24V DC driver
7844/W	Warm white	3000K	11W/m	935lm/m	24V DC	III	20	Requires 24V DC driver
7844/EW	Extra warm white	2700K	11W/m	935lm/m	24V DC	III	20	Requires 24V DC driver



7841 | 14,4W/m | SMD 2835 | 140LEDs | Silicone

new IP66 | LED BUILT IN | 90 CRI | DIMMABLE | CE | 5 YEAR



Supplied in 5m roll.



Fixing clips.
Order code 7841F.



Order Code	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
7841/C	Cool white	4000K	14,4W/m	360lm/m	24V DC	III	1	Requires 24V DC driver
7841/W	Warm white	3000K	14,4W/m	320lm/m	24V DC	III	1	Requires 24V DC driver



7868 | 3,4W/m | LED | 30LEDs/m | Festive lighting | PVC

Connect maximum 100m / Cut every 1m.

new

IP65

LED BUILT IN



Supplied in 50m roll.



13mm





7868C
Connector + shrinking sleeve.



7868P
230V Power supply for 50m.



7868F Fixing clip.



7868E End cup.

Order Code	Light Colour	CCT (K)	Watts	Input	Class		Notes
7868/D	Daylight	6000K	3,4W/m	230V	☐	50m roll	Complete with 7868P power supply
7868/EW	Extra warm white	2700K	3,4W/m	230V	☐	50m roll	Complete with 7868P power supply



7866/D
Supplied in 10m roll.

7866 | 7W | LED | 100LEDs | Festive lighting | PVC

Connect maximum 100m.

new

IP54

LED BUILT IN



7866/EW
Supplied in 10m roll.



7866/BL
Supplied in 10m roll.



Optional 5m waterproof extension cable.
Order code 7866E.



Order Code	Light Colour	CCT (K)	Watts	Input	Class		Notes
7866/D	Daylight	6000K	7W	230V	☐	10	Complete with power supply
7866/EW	Extra warm white	2700K	7W	230V	☐	10	Complete with power supply
7866/BL	Blue	-	7W	230V	☐	10	Complete with power supply



7866F/D
Supplied in 10m roll.

7866F | 7W | LED | 100LEDs | Flashing lights | Festive lighting | PVC

Connect maximum 100m.

new

IP54

LED BUILT IN



7866F/EW
Supplied in 10m roll.



7866F/BL
Supplied in 10m roll.



Optional 5m waterproof extension cable.
Order code 7866E.



Order Code	Light Colour	CCT (K)	Watts	Input	Class		Notes
7866F/D	Daylight	6000K	7W	230V	☐	10	Complete with power supply
7866F/EW	Extra warm white	2700K	7W	230V	☐	10	Complete with power supply
7866F/BL	Blue	-	7W	230V	☐	10	Complete with power supply

Track Spots

65105NT | 10W | MR16 | GU10 | Aluminium



new
DARK LIGHT
IP20

ADJUSTABLE
5 YEAR







Order Code	Colour	Reflector	Watts	Input	Class		Notes
65105NT/BBS	Brushed brass	Black	10W			24	
65105NT/MG	Metal grey	Black	10W			24	

65524T | 12W | COB LED | Aluminium

Honeycomb.



new
DARK LIGHT
IP20

LED BUILT IN
80 CRI
ADJUSTABLE
3 YEAR









Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
65524T/W/W	White	Warm white	3000K	12W	1000lm	36°	230V		24	Complete with 250mA driver
65524T/B/W	Black	Warm white	3000K	12W	1000lm	36°	230V		24	Complete with 250mA driver
65524T/BBS/W	Brushed brass	Warm white	3000K	12W	1000lm	36°	230V		24	Complete with 250mA driver

65306BT | 12W | COB LED | Die cast



new
IP20

LED BUILT IN
90 CRI
ADJUSTABLE
3 YEAR







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input			Notes
65306BT/W/W	White	Warm white	3000K	12W	960lm	38°	230V		30	Complete with 300mA driver
65306BT/B/W	Black	Warm white	3000K	12W	960lm	38°	230V		30	Complete with 300mA driver

65506BT | 20W | COB LED | Die cast



new
IP20

LED BUILT IN
90 CRI
ADJUSTABLE
3 YEAR







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
65506BT/W/W	White	Warm white	3000K	20W	1600lm	38°	230V		20	Complete with 500mA driver
65506BT/B/W	Black	Warm white	3000K	20W	1600lm	38°	230V		20	Complete with 500mA driver



A-A++ 65024TA/W/W

65024TA | 15x1W | LED | Linear system | Aluminium

new

IP20

LED BUILT IN

80 CRI

±45° ADJUSTABLE

3 YEAR



65024TA/B/W





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
65024TA/W/W	White	Warm white	3000K	15x1W	1200lm	30°	230V	⏚	10	AC LED
65024TA/B/W	Black	Warm white	3000K	15x1W	1200lm	30°	230V	⏚	10	AC LED

Tracks



40002A/W

40002A | 16A | 2m Square track | 3-phase | Aluminium

5 YEAR

new



40002A/B



Order Code	Colour	Input	Ampere	Class		Notes
40002A/W	White	100-240V	16A	⏚	10	-
40002A/B	Black	100-240V	16A	⏚	10	-



38150AR | 40W | SMD 2835 | Recessed linear system | Aluminium

Can be connected in line.

LED BUILT IN · 80 CRI · CE · 3 YEAR · new · IP20 · UGR19





Complete with 4pcs fixing clips, 4pcs connectors & 2pcs end cups.



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
38150AR/W/C	White	Cool white	4000K	40W	3600lm	120°	230V		1200x68mm	80mm	12	Complete with 1000mA driver
38150AR/W/W	White	Warm white	3000K	40W	3600lm	120°	230V		1200x68mm	80mm	12	Complete with 1000mA driver



38150BR/W/C

38150BR | 40W | SMD 3030 | Recessed linear system | Aluminium

Can be connected in line.

LED BUILT IN · 80 CRI · CE · 3 YEAR · new · DARK LIGHT · IP20 · UGR17



38150BR/B/C



Complete with 4pcs fixing clips, 4pcs connectors & 2pcs end cups.



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
38150BR/W/C	White	Cool white	4000K	40W	4000lm	34°	230V		1280x68mm	80mm	12	Complete with 1000mA driver
38150BR/W/W	White	Warm white	3000K	40W	4000lm	34°	230V		1280x68mm	80mm	12	Complete with 1000mA driver
38150BR/B/C	Black	Cool white	4000K	40W	4000lm	34°	230V		1280x68mm	80mm	12	Complete with 1000mA driver
38150BR/B/W	Black	Warm white	3000K	40W	4000lm	34°	230V		1280x68mm	80mm	12	Complete with 1000mA driver



38140AU/W/W

38140AU | 40W Downlight + Uplight | SMD 2835 | Linear suspended | Aluminium

LED BUILT IN · 80 CRI · CE · 3 YEAR · new · IP20



38140AU/B/W



Complete with 3m suspension kit.



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
38140AU/W/C	White	Cool white	4000K	40W	3600lm	230V		12	Complete with 900mA driver
38140AU/W/W	White	Warm white	3000K	40W	3600lm	230V		12	Complete with 900mA driver
38140AU/B/C	Black	Cool white	4000K	40W	3600lm	230V		12	Complete with 900mA driver
38140AU/B/W	Black	Warm white	3000K	40W	3600lm	230V		12	Complete with 900mA driver



A-A++ 38152R/W/C

38152R | 40W | LED | Recessed linear system | Aluminium

Can be connected in line.

new

IP20

LED BUILT IN

80 CRI

CE

3 YEAR



38152R/W/W



Complete with 4pcs fixing clips, 4pcs connectors & 2pcs end cups.



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
38152R/W/C	White	Cool white	4000K	40W	3600lm	120°	230V		1200x60mm	80mm	12	Complete with 1000mA driver
38152R/W/W	White	Warm white	3000K	40W	3600lm	120°	230V		1200x60mm	80mm	12	Complete with 1000mA driver



A-A++ 38152RC/W/C

38152RC | 8W | LED | Corner for 38152R | Aluminium

new

IP20

LED BUILT IN

80 CRI

CE

3 YEAR



38152RC/W/W



Complete with 4pcs fixing clips, 4pcs connectors & 2pcs end cups.



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
38152RC/W/C	White	Cool white	4000K	8W	720lm	120°	230V		160x160x60mm	80mm	10	Complete with 250mA driver
38152RC/W/W	White	Warm white	3000K	8W	720lm	120°	230V		160x160x60mm	80mm	10	Complete with 250mA driver



A-A++ 38152RL/W/C

38152RL | 10W | LED | Ceiling to wall corner for 38152R | Aluminium

new

IP20

LED BUILT IN

80 CRI

CE

3 YEAR



38152RL/W/W



Complete with 4pcs fixing clips, 4pcs connectors & 2pcs end cups.



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
38152RL/W/C	White	Cool white	4000K	10W	900lm	120°	230V		100x100x60mm	80mm	6	Complete with 200mA driver
38152RL/W/W	White	Warm white	3000K	10W	900lm	120°	230V		100x100x60mm	80mm	6	Complete with 200mA driver



12105E1/B/GL

12105E1 | 10W | MR16 | GU10 | Aluminium

new
DARK LIGHT
IP20
5 YEAR



12105E1/W/B





Order Code	Colour	Reflector	Watts	Input	Class		Notes
12105E1/W/B	White	Black	10W	100-240V		20	-
12105E1/B/GL	Black	Gold	10W	100-240V		20	-



12105E2/B/GL

12105E2 | 10W | MR16 | GU10 | Aluminium

new
DARK LIGHT
IP20
5 YEAR



12105E2/W/B





Order Code	Colour	Reflector	Watts	Input	Class		Notes
12105E2/W/B	White	Black	10W	100-240V		20	-
12105E2/B/GL	Black	Gold	10W	100-240V		20	-



12105E3/B/GL

12105E3 | 10W | MR16 | GU10 | Aluminium

new
DARK LIGHT
IP20
5 YEAR



12105E3/W/B





Order Code	Colour	Reflector	Watts	Input	Class		Notes
12105E3/W/B	White	Black	10W	100-240V		20	-
12105E3/B/GL	Black	Gold	10W	100-240V		20	-

12105N | 10W | MR16 | GU10 | Aluminium



A-A++ 12105N/BBS

new

DARK LIGHT

IP20

5 YEAR



12105N/MG



Order Code	Colour	Reflector	Watts	Input	Class		Notes
12105N/BBS	Brushed brass	Black	10W	100-240V		36	-
12105N/MG	Metal grey	Black	10W	100-240V		36	-

12105M | 10W | MR16 | GU10 | Aluminium + plastic reflector

Reflector must be ordered separately.



A-A++ 12105M/BBS + 050112/B

new

DARK LIGHT

IP20

5 YEAR



12105M/MG + 050112/B





050112/W White | 050112/B Black | 050112/G Grey | 050112/BS Brass | new 050112/ABS Antique brass | 050112/GL Gold | 050112/CU Copper | new 050112/DC Dark chrome

Order Code	Colour	Watts	Input	Class		Notes
12105M/BBS	Brushed brass	10W	100-240V		20	-
12105M/MG	Metal grey	10W	100-240V		20	-

12105MA | 10W | MR16 | GU10 | Aluminium + plastic reflector

Reflector must be ordered separately.



A-A++ 12105MA/W + 050112/GL

new

DARK LIGHT

IP20

5 YEAR



12105MA/B + 050112/BS



12105MA/BBS + 050112/B



12105MA/MG + 050112/B





050112/W White | 050112/B Black | 050112/G Grey | 050112/BS Brass | new 050112/ABS Antique brass | 050112/GL Gold | 050112/CU Copper | new 050112/DC Dark chrome

Order Code	Colour	Watts	Input	Class		Notes
12105MA/W	White	10W	100-240V		20	-
12105MA/B	Black	10W	100-240V		20	-
12105M/BBS	Brushed brass	10W	100-240V		20	-
12105MA/MG	Metal grey	10W	100-240V		20	-

Wall & Ceiling



A-A++ 12105F/W

12105F | 10W | MR16 | GU10 | Aluminium

new

DARK LIGHT

IP20

5 YEAR



12105F/MG



Order Code	Colour	Watts	Input	Class		Notes
12105F/W	White	10W	100-240V		30	-
12105F/MG	Metal grey	10W	100-240V		30	-



A-A++

12105H | 10W | MR16 | GU10 | Aluminium

new

IP20

5 YEAR



Suitable for GU10 LED lamp.



Order Code	Colour	Watts	Input	Class		Notes
12105H/BS	Brass	10W	100-240V		30	-

Wall & Ceiling LED



A-A++ 12107V/W/W

12107V | 7W | LED | Dimmable | Aluminium

new

IP20

LED BUILT IN

80 CRI

TRIAC DIMMABLE

3 YEAR



12107V/B/W





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
12107V/W/W	White	Warm white	3000K	7W	500lm	40°	230V		20	AC LED
12107V/B/W	Black	Warm white	3000K	7W	500lm	40°	230V		20	AC LED



A-A++

12107B | 7W | COB LED | Dimmable | Aluminium

new

IP20

LED BUILT IN

90 CRI

TRIAC DIMMABLE

CE

2 YEAR







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
12107B/W/W	White	Warm white	3000K	7W	550lm	36°	230V		36	Complete with 350mA driver



12106B/W/W

12106B | 6W | COB LED | Aluminium

new

IP20

LED BUILT IN

90 CRI

CE

3 YEAR



12106B/B/W





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
12106B/W/W	White	Warm white	3000K	6W	480lm	38°	230V		60	Complete with 120mA driver
12106B/B/W	Black	Warm white	3000K	6W	480lm	38°	230V		60	Complete with 120mA driver



A-A++ 12406B/W/W

12406B | 15W | COB LED | Aluminium

new

IP20

LED BUILT IN

90 CRI

CE

3 YEAR



12406B/B/W





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
12406B/W/W	White	Warm white	3000K	15W	1200lm	38°	230V		30	Complete with 350mA driver
12406B/B/W	Black	Warm white	3000K	15W	1200lm	38°	230V		30	Complete with 350mA driver



A-A++ 12906B/W/W

12906B | 30W | COB LED | Aluminium

new

IP20

LED BUILT IN

90 CRI

CE

3 YEAR



12906B/B/W





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
12906B/W/W	White	Warm white	3000K	30W	2400lm	38°	230V		12	Complete with 700mA driver
12906B/B/W	Black	Warm white	3000K	30W	2400lm	38°	230V		12	Complete with 700mA driver



12108X | 8W | COB LED | Dimmable | Aluminium

new

IP20

LED BUILT IN · 90 CRI · TRIAC DIMMABLE · ADJUSTABLE · CE · 3 YEAR







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
12108X/W/W	White	Warm white	3000K	8W	640lm	36°	230V		36	Complete with 350mA driver



12108XA | 8W | COB LED | Dimmable | Aluminium

new

IP20

LED BUILT IN · 90 CRI · TRIAC DIMMABLE · ADJUSTABLE · CE · 3 YEAR







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
12108XA/W/W	White	Warm white	3000K	8W	640lm	36°	230V		36	Complete with 350mA driver



12208XA | 2x8W | COB LED | Aluminium

new

IP20

LED BUILT IN · 90 CRI · ADJUSTABLE · CE · 3 YEAR







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
12208XA/W/W	White	Warm white	3000K	2x8W	2x640lm	36°	100-240V		24	Complete with 350mA driver



67472 | 2x6W | SMD 2835 | ABS + PC

LED BUILT IN
80 CRI
2 YEAR
new
IP65





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
67472/AN/W	Anthracite	Warm white	3000K	2x6W	2x500lm	230V		20	Complete with 300mA driver



67472A | 6W | SMD 2835 | ABS + PC

LED BUILT IN
80 CRI
2 YEAR
new
IP65





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
67472A/AN/W	Anthracite	Warm white	3000K	6W	500lm	230V		20	Complete with 300mA driver



67474 | 10W | LED | Die cast

LED BUILT IN
80 CRI
2 YEAR
new
IP54





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
67474/AN/W	Anthracite	Warm white	3000K	10W	700lm	230V		12	AC LED



67474A | 10W | LED | Die cast

LED BUILT IN
80 CRI
2 YEAR
new
IP54





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
67474A/AN/W	Anthracite	Warm white	3000K	10W	700lm	230V		12	AC LED



67474B | 10W | AC LED | Die cast









Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
67474B/AN/W	Anthracite	Warm white	3000K	10W	700lm	230V	⏚	12	AC LED



65142 | 3W | LED | Aluminium

Wall light / Reading light.









Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
65142/W/W	White	Warm white	3000K	3W	160lm	230V	⏚	12	Complete with 700mA driver



65738 | 3W | LED | Aluminium









Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
65738/BBS/W	Brushed brass	Warm white	3000K	3W	160lm	36°	100-240V	⏚	24	Complete with 700mA driver

62026A | 15W | SMD 2835 | Metal + PMMA



new

IP20

LED BUILT IN

2 YEAR







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
62026A/W	White	Warm white	3000K	15W	1050lm	230V	⏚	5	Complete with driver

62026B | 24W | SMD 2835 | Metal + PMMA



new

IP20

LED BUILT IN

2 YEAR







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
62026B/W	White	Warm white	3000K	24W	1700lm	230V	⏚	5	Complete with driver

62026C | 30W | SMD 2835 | Metal + PMMA



new

IP20

LED BUILT IN

2 YEAR







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
62026C/W	White	Warm white	3000K	30W	2150lm	230V	⏚	5	Complete with driver

62154 | 24W | SMD 2835 | Iron + Plastic



62154/W/W

new

IP20

LED BUILT IN

80 CRI

2 YEAR



62154/B/W



62154/C/W





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
62154/W/W	White	Warm white	3000K	24W	1560lm	230V	⏚	1	Complete with 200mA driver
62154/B/W	Black	Warm white	3000K	24W	1560lm	230V	⏚	1	Complete with 200mA driver
62154/C/W	Chrome	Warm white	3000K	24W	1560lm	230V	⏚	1	Complete with 200mA driver

62152 | 40W | SMD 2835 | Aluminium

Super slim.



A-A++ 62152/W/W

new

IP20

LED BUILT IN

80 CRI

CE

3 YEAR



62152/B/W



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
62152/W/C	White	Cool white	4000K	40W	2800lm	230V		5	Complete with 700mA driver
62152/W/W	White	Warm white	3000K	40W	2800lm	230V		5	Complete with 700mA driver
62152/B/W	Black	Warm white	3000K	40W	2800lm	230V		5	Complete with 700mA driver

62152A | 40W | SMD 2835 | Aluminium

Super slim.



A-A++ 62152A/W/W

new

IP20

LED BUILT IN

80 CRI

CE

3 YEAR



62152A/B/W



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
62152A/W/C	White	Cool white	4000K	40W	2800lm	230V		5	Complete with 700mA driver
62152A/W/W	White	Warm white	3000K	40W	2800lm	230V		5	Complete with 700mA driver
62152A/B/W	Black	Warm white	3000K	40W	2800lm	230V		5	Complete with 700mA driver

62146 | 55W | SMD 2835 | Iron + PS



A-A++

new

IP20

LED BUILT IN

80 CRI

CE

3 YEAR





120°

Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
62146/B/W	Black	Warm white	3000K	55W	4100lm	120°	230V		1	Complete with 600mA driver

62146A | 50W | SMD 2835 | Iron + PS



A-A++

new

IP20

LED BUILT IN

80 CRI

CE

3 YEAR





120°

Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
62146A/B/W	Black	Warm white	3000K	50W	4100lm	120°	230V		1	Complete with 480mA driver



A-A++

62134N | 32W | SMD 2835 | Metal

new

IP20

LED BUILT IN

80 CRI

CE

3 YEAR







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
62134N/BBS/W	Brushed brass	Warm white	3000K	32W	1750lm	120°	230V	⏚	1	Complete with 750mA driver



A-A++

62144N | 50W | SMD 2835 | Metal

new

IP20

LED BUILT IN

80 CRI

CE

3 YEAR







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
62144N/BBS/W	Brushed brass	Warm white	3000K	50W	2750lm	120°	230V	⏚	1	Complete with 1200mA driver



A-A++ 67452/W/W

67452 | 30W | SMD 2835 | Aluminium

new

DARK LIGHT

IP20

LED BUILT IN

80 CRI

CE

3 YEAR



67452/B/W





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
67452/W/W	White	Warm white	3000K	30W	2000lm	230V	⏚	1	Complete with 500mA driver
67452/B/W	Black	Warm white	3000K	30W	2000lm	230V	⏚	1	Complete with 500mA driver



A-A++ 63105M/BBS + 050112/B

63105M | 10W | MR16 | GU10 | Aluminium + plastic reflector

Reflector must be ordered separately.

new DARK LIGHT IP20 5 YEAR CE



63105M/MG + 050112/B







050112/W White



050112/B Black



050112/G Grey



050112/BS Brass



new 050112/ABS Antique brass



050112/GL Gold



050112/CU Copper



new 050112/DC Dark chrome

Order Code	Colour	Watts	Input	Class		Notes
63105M/BBS	Brushed brass	10W	100-240V		12	-
63105M/MG	Metal grey	10W	100-240V		12	-



A-A++ 63105MA/W + 050112/GL

63105MA | 10W | MR16 | GU10 | Aluminium + plastic reflector

Reflector must be ordered separately.

new DARK LIGHT IP20 CE 5 YEAR



63105MA/B + 050112/BS



63105MA/BBS + 050112/B



63105MA/MG + 050112/B





050112/W White



050112/B Black



050112/G Grey



050112/BS Brass



new 050112/ABS Antique brass



050112/GL Gold



050112/CU Copper



new 050112/DC Dark chrome

Order Code	Colour	Watts	Input	Class		Notes
63105MA/W	White	10W	100-240V		12	-
63105MA/B	Black	10W	100-240V		12	-
63105MA/BBS	Brushed brass	10W	100-240V		12	-
63105MA/MG	Metal grey	10W	100-240V		12	-



61076 | 40W | E27 | Metal + white fabric shade

new

IP20

2 YEAR



Suitable for E27 LED lamp.



Order Code	Colour	Watts	Input	Class		Notes
61076/BBS	Brushed brass	40W	100-240V		12	With ON/OFF Switch



61078 | 40W | E27 | Metal + white fabric shade

new

IP20

2 YEAR



Suitable for E27 LED lamp.



Order Code	Colour	Watts	Input	Class		Notes
61078/BBS	Brushed brass	40W	100-240V		8	With ON/OFF Switch



61082A | 3,3W | SMD LED | Touch switch | Dimmable | Die cast

Rechargeable USB socket.

new

IP65

LED BUILT IN

80 CRI

DIMMABLE

IK06

2 YEAR



61082A/B



Charging time: 6Hrs
Working time: 9Hrs

Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Class		Notes
61082A/W	White	Warm white	3000K	3,3W	200lm		6	2x2200mAh lithium battery
61082A/B	Black	Warm white	3000K	3,3W	200lm		6	2x2200mAh lithium battery



61084 | 2W | SMD LED | Touch switch | 3-Step dimming | Metal + PC

Rechargeable USB socket.

new

IP44

LED BUILT IN

3-STEP DIMMABLE

2 YEAR





Charging time: 4Hrs
Working time: 8Hrs

Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Class		Notes
61084/B	Black	Warm white	3000K	2W	80lm		8	2200mAh lithium battery



62144NB | 50W | SMD 2835 | Metal

LED BUILT IN · 80 CRI · CE · 2 YEAR · new · IP20







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
62144NB/BBS/W	Brushed brass	Warm white	3000K	50W	2750lm	230V	⏚	1	Complete with 1200mA driver



63046A | 45W | SMD 2835 | Steel + aluminium

LED BUILT IN · 80 CRI · CE · 2 YEAR · new · IP20







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
63046A/B	Black	Warm white	3000K	45W	2700lm	230V	⏚	1	Complete with driver



63112 | 60W | SMD 2835 | Metal + Plastic

LED BUILT IN · 80 CRI · CE · 2 YEAR · new · IP20





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
63112/W	White	Warm white	3000K	60W	4800lm	230V	⏚	1	Complete with 1300mA driver



63114/W/W

63114 | 40W | SMD 2835 | Metal + ABS

LED BUILT IN · 80 CRI · CE · 2 YEAR · new · IP20



63114/B/W





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
63114/W/W	White	Warm white	3000K	40W	2400lm	230V	⏚	1	Complete with 1000mA driver
63114/B/W	Black	Warm white	3000K	40W	2400lm	230V	⏚	1	Complete with 1000mA driver



A-A++ 65105N/BBS

65105N | 10W | MR16 | GU10 | Aluminium

new DARK LIGHT IP20

ADJUSTABLE

5 YEAR



65105N/MG



Order Code	Colour	Reflector	Watts	Input	Class		Notes
65105N/BBS	Brushed brass	Black	10W	100-240V		24	-
65105N/MG	Metal grey	Black	10W	100-240V		24	-



A-A++ 65205N/BBS

65205N | 2x10W | MR16 | GU10 | Aluminium

new DARK LIGHT IP20

ADJUSTABLE

5 YEAR



65205N/MG



Order Code	Colour	Reflector	Watts	Input	Class		Notes
65205N/BBS	Brushed brass	Black	2x10W	100-240V		12	-
65205N/MG	Metal grey	Black	2x10W	100-240V		12	-



A-A++ 65305N/BBS

65305N | 3x10W | MR16 | GU10 | Aluminium

new DARK LIGHT IP20

ADJUSTABLE

5 YEAR



65305N/MG



Order Code	Colour	Reflector	Watts	Input	Class		Notes
65305N/BBS	Brushed brass	Black	3x10W	100-240V		12	-
65305N/MG	Metal grey	Black	3x10W	100-240V		12	-



A-A++ 65105NA/BBS

65105NA | 10W | MR16 | GU10 | Aluminium

With switch.

new DARK LIGHT IP20

ADJUSTABLE

5 YEAR



65105NA/MG



Order Code	Colour	Reflector	Watts	Input	Class		Notes
65105NA/BBS	Brushed brass	Black	10W	100-240V		24	-
65105NA/MG	Metal grey	Black	10W	100-240V		24	-



68078 | 2W | LED | Aluminium

new
DARK LIGHT
IP20

LED BUILT IN
80 CRI
DIMMABLE
QUICK FIX
3 YEAR



Suitable for 89004A driver.



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class					Notes
68078/W/W	White	Warm white	3000K	2W	80lm	700mA	III	30cm	80x25mm	60mm	100	Requires 700mA driver



68006N | 1W | LED | Die cast

Cover plate must be ordered separately.

new
DARK LIGHT
IP44

LED BUILT IN
3 YEAR







050176/W White



050176/B Black



050176/G Grey



050176/BBS Brushed brass

Order Code	Colour	Light Colour	CCT (K)	Watts	Input	Class					Notes
68006N/W	White	Warm white	3000K	1W	230V	⧈	12cm	70x70mm	60mm	1	Complete with 350mA driver



69056A | 3W | COB LED | Aluminium







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
69056A/W	Aluminium	Warm white	3000K	3W	240lm	38°	24V DC	III	200cm	50mm	100mm+300mm drainage	50	Requires 24V DC driver



69056B | 7W | COB LED | Aluminium







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
69056B/W	Aluminium	Warm white	3000K	7W	560lm	38°	24V DC	III	200cm	60mm	100mm+300mm drainage	36	Requires 24V DC driver



69056C | 9W | COB LED | Aluminium







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
69056C/W	Aluminium	Warm white	3000K	9W	720lm	38°	24V DC	III	200cm	70mm	135mm+300mm drainage	24	Requires 24V DC driver



7055B/RGB | 24x1,5W | LED | RGB | Aluminium

Connect maximum 5pcs.







Order Code	Colour	Light Colour	Watts	Beam Angle	Input	Class			Notes
7055B/RGB	Grey	RGB	24x1,5W	30°	24V DC	III	100cm	12	Requires 24V DC driver



7028CA | 10W | SMD 2835 | Die cast + tempered glass







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class			Notes
7028CA/W/C	White	Cool white	4000K	10W	900lm	110°	230V		30cm	60	AC LED



7028CB | 30W | SMD 2835 | Die cast + tempered glass







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class			Notes
7028CB/W/C	White	Cool white	4000K	30W	2700lm	110°	230V		30cm	30	AC LED



7028CC | 50W | SMD 2835 | Die cast + tempered glass







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class			Notes
7028CC/W/C	White	Cool white	4000K	50W	4500lm	110°	230V		30cm	20	AC LED



7028CD | 100W | SMD 2835 | Die cast + tempered glass







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class			Notes
7028CD/W/C	White	Cool white	4000K	100W	9000lm	110°	230V		30cm	10	AC LED



89006P | 2-6W | 350mA

new

IP66



Order Code	Input	Power	Output	Class	Dimmable		Notes
89006P	230V	2-6W	350mA	⧈	NO	100	-



89006PC | 1,5-6W | 500mA

new

IP66



Order Code	Input	Power	Output	Class	Dimmable		Notes
89006PC	230V	1,5-6W	500mA	⧈	NO	100	-



89006PA | 2-6W | 700mA

new

IP66



Order Code	Input	Power	Output	Class	Dimmable		Notes
89006PA	230V	2-6W	700mA	⧈	NO	100	-



89015CT | 7,5-15W | 500mA | TRIAC | Dimmable

new

IP20



Order Code	Input	Power	Output	Class	Dimmable		Notes
89015CT	230V	7,5-15W	500mA	⧈	YES	100	-

9G04A | 4W | LED | E27

Decorative lamps.



9G04A/A



9G04A/DC



Order Code	Lampholder	Glass Colour	Watts	Input	Dimmable	
9G04A/A	E27	Amber	4W	230V	NO	50
9G04A/DC	E27	Dark chrome	4W	230V	NO	50

9G04D | 4W | LED | E27

Decorative lamps.



9G04D/A



9G04D/DC



Order Code	Lampholder	Glass Colour	Watts	Input	Dimmable	
9G04D/A	E27	Amber	4W	230V	NO	10
9G04D/DC	E27	Dark chrome	4W	230V	NO	10

9G04E | 4W | LED | E27

Decorative lamps.



9G04E/A



9G04E/DC



Order Code	Lampholder	Glass Colour	Watts	Input	Dimmable	
9G04E/A	E27	Amber	4W	230V	NO	6
9G04E/DC	E27	Dark chrome	4W	230V	NO	6

9G04F | 4W | LED | E27

Decorative lamps.



9G04F/A



9G04F/DC



Order Code	Lampholder	Glass Colour	Watts	Input	Dimmable	
9G04F/A	E27	Amber	4W	230V	NO	6
9G04F/DC	E27	Dark chrome	4W	230V	NO	6

9G04H | 4W | LED | E27

Decorative lamps.



9G04H/A



9G04H/DC



Order Code	Lampholder	Glass Colour	Watts	Input	Dimmable	
9G04H/A	E27	Amber	4W	230V	NO	25
9G04H/DC	E27	Dark chrome	4W	230V	NO	25

9G08B | 8W | LED | E27

Decorative lamps.



9G08B/A



9G08B/DC



Order Code	Lampholder	Glass Colour	Watts	Input	Dimmable	
9G08B/A	E27	Amber	8W	230V	NO	6
9G08B/DC	E27	Dark chrome	8W	230V	NO	6

9G08C | 8W | LED | E27

Decorative lamps.



9G08C/A



9G08C/DC



Order Code	Lampholder	Glass Colour	Watts	Input	Dimmable	
9G08C/A	E27	Amber	8W	230V	NO	6
9G08C/DC	E27	Dark chrome	8W	230V	NO	6

9G08D | 8W | LED | E27

Decorative lamps.



9G08D/A



9G08D/DC



Order Code	Lampholder	Glass Colour	Watts	Input	Dimmable	
9G08D/A	E27	Amber	8W	230V	NO	6
9G08D/DC	E27	Dark chrome	8W	230V	NO	6



9G08E/A

9G08E | 8W | LED | E27

Decorative lamps.



9G08E/DC



Order Code	Lampholder	Glass Colour	Watts	Input	Dimmable	
9G08E/A	E27	Amber	8W	230V	NO	6
9G08E/DC	E27	Dark chrome	8W	230V	NO	6



9G08K/A

9G08K | 8W | LED | E27

Decorative lamps.



9G08K/DC



Order Code	Lampholder	Glass Colour	Watts	Input	Dimmable	
9G08K/A	E27	Amber	8W	230V	NO	6
9G08K/DC	E27	Dark chrome	8W	230V	NO	6



9G02H/RGB | 2W | LED | E27

Decorative lamps.





Order Code	Lampholder	Light Colour	Watts	Input	Dimmable	
9G02H/RGB	E27	RGB	2W	230V	NO	25



050180 | Fast cable connector | 32A | Max. 4mm wires

100

new



0800BA | Waterproof connection box 1 IN / 1 OUT | 16A | 450V | Cable diameter 0,5-1,5mm

100

new

IP67





0800C | Waterproof connection box 2 IN / 2 OUT | 24A | 450V | Cable diameter 4-14mm

100

new

IP67



01 | Recessed Spots Fixed

pages 03-36

03

10102


10102GL

04

10105X


10105XS

05

10103


10105

06

10105GU

07

10105CM

08

10105A1

09

10105ALG


50105ALG

10

10105ALG

11

10105TG


50105TG


10105T


50105T

12

10105D1


10105D2


10105DG

13

10105D4


10105D5


10110T

14

10105D3


50105D7

15

10105D9

16

10105AD


10105D8

17

10105M/W

18

10105M/B

19

10105MD/W


10105MD/B

20

50105MA

21

50105M

22

50205D

23

10105L

24

10105F

25

10105CJ

26

10105R


50105R

27

10105V

10105R1

28

10105R2

29

10105GL1

10105GL2

30

50105GL

50105GL1

31

10105AC

10105AR

50105AR

32

50105GL4

10105GT1

33

10105GT2

50105GT1

50105GT2

34

10105TR

35

10105RM

050099 Reflectors

36

50105RM

050098 Reflectors

02 | Recessed Spots Fixed LED

pages 39-68

39

10101L

10101D

40

10103B

41

10103R

10103D

10103DE

42

10103DL

43

10103L

50103L

50401L

50601L

44

10103N

45

10107Z

10112Z

10120Z

46

10107K

050104 Reflectors

10112L

10112LR Reflectors

47

10107D

10107DA

48

10107DC

10112E

10112C

10112TD

49

10105FD/W

10110FD/W

10115FD/W

50

10105FD/B

10110FD/B

10115FD/B

51

10112H

10112R

050162 Rings

52

10105W

10107W

53

10107DL

10107WP

10112TP

54

10107HC


10107WD


10107DB


10113P

55

10107P


10112P

56

10103P


10103NP


10106P

57

10102H


10107H

58

10106PF


050042 Rings


050042A Rings

59

50102B


50202B

60

50302B


50502B


50902B

61

50107B


50207B


50307B


50507B

62

10104M


50104M

63

10107C


10107R


10103GL


10103A

64

10101G


10103G


10106G

65

10101C


50101

66

10107BT


50103GT4

67

10101TR


10103TR

68

10103BTR

03 | Recessed Spots Adjustable

pages 71-100

71

11103A


11105

72

11105GU

73

11103C

11105C

11105CF

74

11105CGU

51105CGU

75

11105CD

51105CD

76

11105GU3

77

51103

51105

78

51105GU

51105GA

79

51105AB

80

11105ABG

51105ABG

51205ABG

81

11105ABGL

82

11105AL

11105AC

51103AB

83

11105U

11105UA

11105UB

84

51105U

51105UA

85

11105D4

11105DT

11105TG

11105CDG

11105E

86

51105TG

51105CDG

51105DG

51105D

87

11105TA

88

51105TA

89

11105M/W

90

11105M/B

91

11105A1

11105B1

92

11105D7

51105B1

51105D7

93

11105D5

11105D6

11105D8

51105D5

94

11105N

51105N

51205N

95

51105B

51205B

51305B

96

51105R

97

51105F

98

11105GT5

11105GT4

99


51105GT4


11105UTR


11105DTR


11105TR


51105TR

100


51010TR


51020TR

04 | Recessed Spots Adjustable LED

pages 103-134

103


11103B

104


11102


11101D

105


11101B


51101W


51101B


51101AL

106


51201AL


51301AL


51401AL

107


11103LC


51103LC

108


11103N

109


11103L


11103LW


11103LB


11303L

110


51103L


51103LW


51103LB

111


11107B


51107

112


11106DB

113


11112


51112

114


11106K


11106KD


11109KD

115


11106A


11110A

116


51106A


51110A

117


11112H

050086 Rings

050086A Ring

51112H

050088 Rings

050088A Ring

118

11104K

050100 Rings

119

11107K

050102 Rings

11103E

120

11112D

11103D

11112TA

51112TA

11112DL

121

11103BD

11107DA

122

11107FD

11107DL

11112E

51112E

51212E

123

11107H

124

11113E

51113E

125

11103P

11107WD

126

11207WD

11107P

11107D

127

11108LA

128

11103M

11108M

11110B

129

11107F

11207M

130

11107RA

131

11112RA

11112RB

11111C

132

51111C

51211C

11107C

133

11207C

11106PF

050044 Rings

134

11107BT

05 | Downlights Fixed
pages 137-142

137

10007

138

10004

139

10115BF


10220BF


50115BF


50220BF

140

10215D


10220D


10220E


10220CF

141

10220T


50220T

142

10220GT1


50220GT1

06 | Downlights Fixed LED
pages 121-186

145

10108F


10112F


10120F

146

10103FA


10108FA


10112FA

147

10118FA


10130FA


10140F

148

10148PE

149

50108F


50116F

150

50122F


50130F

151

50108FA


50116FA

152

50122FA


50130FA


50148PE

153

50140E

154

50140AE


50148E


50143F


50148AE

155

50140U


50140AU

50148U

50148AU

156

50140W

50140AW

157

50136P

158

50136RP

159

50148RE

50160E

160

10108FD

10116FD

10122FD

161

10103T

10107T

10115T

162

10124T

10130T

163

10115

10124

164

10110C

10120C

10130C

10130CR

165

10107CA

10110CA

166

10115CA

10120CA

10130CA

10160CA

167

10107CD

10115CD

168

10130CD

10140CD

169

10108ED/W/B

10112ED/W/B

170

10130ED/W/B

10108ED/W/BS

10112ED/W/BS

10130ED/W/BS

171

10105K

10110K

172

10120K

10130K

10130KA

173

50105K

174

50120K

50130K

10120

10142

10100 Rings

175

10140P

10112

10128

176

10107KD

10112KD

177

10105E

10115E

10130A
178

10113A

10150T
179

50120B

50220B

50130B
180

10109D

10122D

181

50122D

10109FD

10120FD
182

10107B

10113B

10118B

10125B
183

10110G

10115G
184

10120G


10130G

10150G
185

10106CF

10108CF
186

10115CF

050146 Base

10130CF

050148 Base

07 | Downlights Adjustable
pages 189-202

189

11110D

11070RD
190

11110N

51110N

51210N

51310N
191

11110U

51110
192

11110AB
193

51110AB

194

51210AB

51310AB
195

11110AD

51110AD
196

11110ATR

51110ATR
197

11110GT1

51110GT1
198

11110H
199

51100R

51200R

51300R

51400R

51401R

11100R

51200AR

51300AR

51400AR
200

11110R

11070R

11106R
201

51100TR

51200TR
202

11110TR

11150TR

11070TR

08 | Downlights Adjustable LED
pages 205-222

205

11130BT
206

11106LB

11109L

11112L

11118L
207

11138

51125

51138
208

51120

51220

51130

51230
209

11150A

51125A

11125B
210

11120B

11140B

11150B
211

51109B

51120B

212

51140B

51209B

51240B
213

11112TR

11118TR

11140TR
214

51115TR

51120TR

51140TR

51220TR
215

11115C

11120C

11130C
216

51140

51145
217

11115E
218

11107R

11114R

11125R
219

11118H

11115F

11125F
220

11110F

11112F

11120F
221

11135L

11130B

11140L
222

11115RA

11125RA

09 | LED Strips & Profiles

pages 225-266

225

7821

7831

Accessories for 7821 & 7831
226

7823

7833
227

7820

Accessories for 7820
228

7820W

7820AW

Accessories for 7820W & 7820AW
229

7829
230

7835C

Accessories for 7835C
231

7830

7835

Accessories for 7830 & 7835
232

7835W

7827
233

7813L

7820L

7820WL

Accessories for 7820WL
234

7820V

7835V

Accessories for 7820V & 7835V
235

7825

7870

7875
236

7845

7887
237

7880

7882

7885
238

7835/DEW

20032
239

7820/BL

7820W/BL
240

7820A/RGB

7830A/RGBW

7820C/A
241

7830/RGB

Accessories for 7830/RGB

7830/RGBW
242

7830W/RGB

7827
243

7901

7836

7902
244

7904

7905
245

7912

7912A

050122
246

7910

7910A

050122
247

7908A

7908

7937T
248

7906

7906A

7906B

7906C

7906D
249

7916
250

7901R

7902R

7904R
251

7906R

7912R

252

7910R

7910AR
253

7900TR

7901TR

7904TR

7906TR

7904ATR
254

7918

7914R

7915R
255

7840

7842
256

38104B

38108B

38114B
257

38104L

38115L
258

38207L

38215L

38230L
259

38103

38105

38110

12122
260

38102A

38102B

38102C

38101A

38101B

38101C

38101D
261

7850

Accessories for 7850

7860

Accessories for 7860
262

7862

Accessories for 7862
263

38001A

38002A

38005A

38006 / 38007
264

7811

Accessories for 7811
265

7810/D

7810/BL

7810/R

7810/P

7810/RBL
266

7814

7818

Accessories for 7810

7815

7815B

10 | Track Spots

pages 269-300

269

65608T
270

65610AT

65620AT
271

65611T

65612T
272

65614T

65616T
273

65611NT/W

65612NT/W

65614NT/W
274

65611NT/B

65612NT/B

65614NT/B
275

65642AT/W

65642BT/W

65642CT/W
276

65642AT/B

65642BT/B

65642CT/B
277

65646T

65108T

65632T

65632CT
278

65640AT

65640BT
279

65620TA

65620T

65620T2
280

65628T

65630T

65626T
281

65618T

65619T

65624T

65638T
282

65226T

65622T
283

65644T

65652T
284

65650T

285

65648T

65018T

65025T
286

65024T

65026T
287

65020T

65042T

65510T
288

65009T

65010T
289

65010B

65112T

65114T
290

65736T

65719T
291

65835T

65834T
292

65935T

65934T
293

65012T
294

65019T

65011T

65016T

65008T

65013T
295

65534T

65514T
296

65235T

65234T
297

65520T
298

65519T

65518T

65522T

65105NT

65105NAT
299

65111AT
300

65118AT

11 | Tracks

pages 303-308

303

40003A

41002A

41030
304

65100/BASE

41020

41004A

41010A

41008A
305

41012A

41016A
306

41024A

41022A

41026R

41032
307

40003

41002

41004

41010

41008
308

41012

41016

41018

41022

41020

12 | Office & Kitchen

pages 311-318

311

38135A
312

38236D

38258D

38236DL

38236DF

38258DF
313

38225M

38248M
314

38120L

38135L
315

38248L

38150A

38150E

050170C

050170
316

38150B

38150C
317

38150BU

38150E

050170C

318


050170


38154A


38154M

13 | Wall & Ceiling

pages 321-358

321


62110B


62210B

322


62110


62110A


62210A


62310A

323


38108J

324


60038


60040


60042


60054

325


12105M


050112 Reflectors

326


12105N


12105NA


12205NA

327


12105E


12105D

328


12105AL

329


12105T


12205T

330


12105TA


12205TA

331


12105Y


12205Y

332


12105YA


12205YA

333


12140


12140G


12142


12138G

334


12144


12144A

335


12105B


12205B

336


12105AB


12105AC

337

12132

12126

12124

12134

12120

338

67300

67164

67162

339

60056

6017

6017A

6030

340

6017G

6012

6022

6005

341

67302

67302A

67228

342

67160

67163

343

67400A

67400B

344

67400D

67400E

345

67426

67426A

346

67130CD

67130DD

347

67130C

67130E

348

67130

67130D

67130F

67130A

349

67132C

67132E

67132

350

67132D

67132F

67132A

351

67204B

67204

67206

352

67208B

67208

67210

353

67104P

67106P

67134E

67134A

354

67216

67214

355

67328

67328A

67292
356

67420

67420A

67420B
357

67032
358

67030

14 | Wall & Ceiling LED

pages 361-424

361

67454
362

60008A

60008

65102

62401AL
363

65746

65746A

65742

65746R
364

65746B


65738

65738A

65744
365

65110A

65110C

65110D

65110B
366

65110E

65110F
367

12109LA


12108LA

12208LA
368

12107F

12112LA

65107
369

6028

60032

60034

67434
370

12101


60004

60001

60010
371

67424

67424A

67424B

67364
372

67444C

67442B

67442C

67442
373

7046P
374

67346

67346A
375

12106C

12110D

12104M

12115A
376

12107K

12107KA

050106 Rings
377

12115D

12124D
378

12108C

12122C
379

12106CA

12107AL

12211L
380

12107B

12207B

12307B
381

12115L

12125L

12135L
382

12107LD

12115LD

12125LD
383

12108FD

12116FD
384

12115LA

12125LA

12130LA
385

12112Z

12120Z

12130Z
386

12112ZA

12120ZA
387

12110HA

12115HA
388

67380

389

67380A

67138C/G

67138D/G
390

67138C

67138D
391

67138E
392

67138F
393

67138

67138A
394

67138EL



15 | Plafo

pages 427-460



436

62130F

62122F

62130AF
437

62140AE

62140RE
438

62140F

62140AF

62140RF
439

62018F

62018AF
440

62030F

62038F

62046F
441

62140FB

62160FB
442

67436

67436A

67438

67438A
443

67280E
444

67280EA

67282E

67282
445

67282A

67282EA

6728ON

6728OAN

6728OBN

6728OANE
446

67282N
447

67282AN

67282BN

67282ANE

67362

67363
448

67362A

67363A

67384
449

67384A

67366
450

67366E

67368

67368M
451

67370

67372
452

62100

62200

62300
453

67316A

64002
454

64004

64006

64008
455

64010

62130N
456

62132N

62142N

62144N

62132NA
457

62142NA

62135NA

62160

62160A
458

62118D

62125D

62150D
459

67404M

67404

67404A

62025
460

67402

67390

67448

67448A

16 | Bathroom & Mirror

pages 463-470

463

38115C

38120C
464

38114DL

38114EL

38121EL

38114CL
465

38121D

38114C
466

38114DE

38114EE

38114GE

38114CE
467

38110BD

38114GL

38124
468

60204

60106

60106A
469

60107A

60107B

470


60107C


60107D

17 | Pendants

pages 473-484

473


63036


63038

474


63105N


63105M


050112 Reflectors


63105L

475


63001


63002

476


63108


63108A

477


63040


63042


63044

478


63020


63026

479


63016A


63022


63022A


63022B

480


0990


0992

481


65110P

482


38018


38016

483


63070D


63270

484


63034


63025L


63030L

18 | Decorative

pages 487-512

487


10101C4


10101C5

488


10105C4

489


61048A


61048B

490


61050A


61050B


63052

491


61046

61076

61078

492

65138

61044

61074

61080

493

61044A

61042A

494

61082

495

9C006

9C008

9C004A

496

9C004B

9C002

497

61058A

498

61036

61038

499

61038B

63046

63046A

63046B

63048

500

63050

501

62144NB

502

62142NB

62180NB

503

62148A

62148B

62148D

504

63110C

63110D

61070

505

61068

61068B

61072

506

61066

61066T

507

65740

65740A

508

65105N

65205N


65305N


65105NA

509

65105A


65305B

510

61040

511

0994

512

63028


63028A


63028B

19 | Wall Recessed & Inground

pages 515-544

515

68054


68006


68007

516

68005


68005/BOX


68008


68008/BOX

517

68052


68052A

518

68046


68048


68050

519

68070A

520

68004B


68070


68004


68004A

521

68030

522

68032

523

68074


68074A


68074B

524

68076

525

68076A


68058

526

68060


68072A


68072B


68072C

527

68068


68068A

68068C

528

68062

68064

68066

529

68022

68024

68012

68016

530

68044

531

69042M

69042

532

69042A

69042B

69044

533

68001

68002

68003

534

68001/BL

68002/R

535

69016G

69016AG

69016BG

536

69016

69016A

69016B

537

69028

69012

538

69052

69052A

539

69040

69050

69050A

69026

540

69054

69054A

541

69006G

69008G

542

69046G

69048G

543

69006

69008

544

69003

69002

69002/RGB

20 | Garden & Underwater

pages 547-574

547

7070

7068

67456

67458

548

67198G

67198AG

67464G

549

7046

550

7047

551

67196BG

552

67196A

67196B

67196C

553

7008L

7008A

7010

7010A

554

7052B

67432

7052

555

67428

556

67462

557

67094

558

67098

67090

67092

67100

559

67102

67180

67182

560

67250

67250A

561

67270

67236

67236A

67238

67238A

562

67234

67234A

563

67470

67470A

564

67460A

67460B

565

67358

566

67036

67034

567

67410

568

67410A

569

67010W

67286

67004

570

67408

571

67406

67406A

67406B

67406C

572

67406D

67406E

574

69032

69036

69034

21 | Industrial & Floodlights

pages 577-610

577

38136P

38218P

38236P

578

38118E

38136E

38158E

38218E

38236E

38258E

579

38118L

38118M

38136M

38158M

580

38236M

38258M

581

38118LC

38136LC

38145LC

582

38236LC

38245LC

38118LA

583

38136LA

38145LA

584

38136R

38236R

585

38120E

38140E

38165E

586

38220E

38240E

587 38265E 7056 7056A 7056B
588 63200A
589 63100E
590 63100F 63150F 63200F 22002
591 7020
592 7030 7022
593 7028A/AN/RGB 7028B/AN/RGB 7028AR 7028BR
594 7028A 7028B 7032
595 7048 7060 7028BE
596 7038 7040 7040E
597 7034B 7034C 7034D
598 7028A
599 7028AB 7028E 7062A
600 7064 7066
601 7028CA 7028CB 7028CC
602 7028CD 7028CE
603 7028CF 7028AG 7028BG 7028CG
604 7050A 7050B 7050C
605 7058
606 7055A 7055B
607 70080 70090
608 70100 70101
609 70108 70104 70105
610 70110

22 | Emergency Lights

pages 613-620

613 89002
614 67366E 67284LE 67280ANE 67282ANE 67446EM
615 89406 89406R
616 89404 89402
617 89005A/EME
618 89005/EME
619 89009/EME
620 89143F

23 | LED Drivers

pages 623-642

623

89028M

89028AM
624

89004

89004C

89004A
625

89008

89015

89020
626

89030C

89006A

89008A

89015A

89030A
627

89008CT

89012BT

89016T

89018DT

89022ET

89030AT
628

89015T

89006AT

89015AT

89048T
629

89109E

89110E
630

89008W

89015W

89030W

89075W

89200WN
631

89015V

89030V

89060V

89075V
632

89100V

89150V

89200V
633

89060WD
634

89040VT

89075VT

89100VT
635

89030VL

89060VL

89075VL

89100VL

89150VL
636

89060VLD

89100VLD

89150VLD

89100VLL

89060VN

89100VN

89150VN

89200VN

89350VN
638

89100VND

89200VND
639

89100VP

89150VP

89200VP

89030VD

89075L
641

89027D

89030D

89050D
642

89020L

89025L

89045L

89050L

24 | LED Control & Dimming

pages 645-650

645

22000

22020
646

22004

22006

22008

22010
647

89024D

89024E
648

89010D

89100L

89100

89302

89302A
650

20030

20032

20034

20036

25 | Lamps

pages 653-698

653

7106GPH

9407G

8010L
654

7103LG

7103BLG

7105BLG
655

7102ALG

7102LG

7103ALG

7106ALG
656

7109ALG

7103ALGD

7103ALGT

7106ALGD

7103ALG/DW
657

7103A

7105

7105SR

7101AL
658

7201G
659

7350

7350G
660

7303

7304A
661

7301G

7303G

7304G

7305G
662

7304AG

7305AG
663

7306G

7308G

7306LG
664

7307BG

7307CG

7301GD

7306LGD

7306GD
665

7308GD

7305CG/C/120
666

7305CG/W

7306CG

7306CBG

7306KGD
667

7306CGD

7306GC

7306GCD
668

7301

7350G

7305G/RGB
669

7306CG/BL

7312M/AL/W

7305M
670

7312M

7310H
671

7306A

9R23/BL
672

9R23/R

9G06F
673

7315G
674

7315GB

7513AGD

7315GD
675

7375R

7513A

7515A
676

7510R

10106NA
677

7521R

7512D
678

7524D

7524BD
679

7605L

7610L

7612L
680

7615L

7604

7610A
681

7610

7615
682

7610A

7630A

9F01
683

9F07L

9F07LD

9C04A
684

9C06B

9C06BD

9G07B

9G12B
685

9G12BD

9G12D

9G10L
686

9G10M

9G10V

9G09/RGBW

9G20L
687

9G20LD

9G09P/../E

9G09P/../B
688

9G20P

9G20N

9G50N
689

9G80N

9G03RAD

9T05RD

9G04RAD
690

9G06RD

9C02R

9G03R

691


9G06R


9G06RD


9G01/W


9G06M


9G01/../E


9G01/../B

692


9S13/GR/E


9S23/Y/E

693


9922L


9932L

694


9940L


9011L


9021L


9021LB


9026L

695


9007L


9009L


9012L

696


9018L


9022L

697


9032L


8107


8213/W/4SR


8218


8218/D/4SR


8226/W/4SR

698


8007/W


8015

26 | Accessories

pages 701-706

701


89003/EXT


89006A/EXT

702


0903F


0903M


0904F


0904M


0800B


0800A


60000


7010P

703


0950GA


0950G

0950GB

0802

704

70020

70028

70026

705

094004

062002

706

70038

70036

70034

70032

27 | Advertising & Marketing

pages 709-710

709

060020 / 060020A

060016

060018

060008

710

060010

060012

060014

060026
060027 / 060028

060029 / 060030

one

PRODUCT CATALOGUE 2020

EDITION 1





01

Recessed Spots Fixed

Pages 03-36

MR11 | MR16 | G4 | GU4 | GU5,3 | GU10

Die cast | Glass | Aluminium | Metal | Gypsum | Semi trimless

IP20 IP43 IP44 IP65

DARK LIGHT





Star Lights G4



E-A++ 10102/MC

10102 | 20W | G4 | Die cast

IP20

offer



Suitable for G4 LED lamp.





E-A++ 10102/BS

10102 | 20W | G4 | Die cast

IP20

offer



Suitable for G4 LED lamp.





E-A++ 10102GL/BL

10102GL | 20W | G4 | Glass

IP20

offer



Suitable for G4 LED lamp.





E-A++ 10102GL/Y

10102GL | 20W | G4 | Glass

IP20

offer



Suitable for G4 LED lamp.



Order Code	Colour	Watts	Input	Class					Notes
10102/MC	Brushed chrome	20W	12V	III	40cm	24mm	30mm	100	-
10102/BS	Brass	20W	12V	III	40cm	24mm	30mm	100	-
10102GL/BL	Blue	20W	12V	III	40cm	33mm	50mm	100	-
10102GL/Y	Yellow	20W	12V	III	40cm	33mm	50mm	100	-



Classic MR16

10105X | 50W | MR16 | GU5,3 | Die cast



E-A++ 10105X/C

IP20



10105X/W



10105X | 50W | MR16 | GU5,3 | Die cast



E-A++ 10105X/MC

IP20



10105X/BS



10105XS | 50W | MR16 | GU5,3 | Pressed metal



E-A++ 10105XS/C

IP20



10105XS/MC



Order Code	Colour	Watts	Input	Class					Notes
10105X/W	White	50W	12V	III	40cm	63mm	60mm	100	-
10105X/C	Chrome	50W	12V	III	40cm	63mm	60mm	100	-
10105X/MC	Brushed chrome	50W	12V	III	40cm	63mm	60mm	100	-
10105X/BS	Brass	50W	12V	III	40cm	63mm	60mm	100	-
10105XS/C	Chrome	50W	12V	III	40cm	63mm	60mm	100	-
10105XS/MC	Brushed chrome	50W	12V	III	40cm	63mm	60mm	100	-



Classic MR11 & MR16



E-A++ 10103/BS

10103 | 35W | MR11 | GU4 | Die cast

IP20

offer



Suitable for MR11 LED lamp.





E-A++ 10103/BBS

10103 | 35W | MR11 | GU4 | Die cast

IP20

offer



Suitable for MR11 LED lamp.





E-A++ 10105/W

10105 | 50W | MR16 | GU5,3 | Die cast

IP20







E-A++ 10105/MC

10105 | 50W | MR16 | GU5,3 | Die cast

IP20





Order Code	Colour	Watts	Input	Class					Notes
10103/BS	Brass	35W	12V	III	40cm	51mm	45mm	100	-
10103/BBS	Brushed brass	35W	12V	III	40cm	51mm	45mm	100	-
10105/W	White	50W	12V	III	40cm	70mm	60mm	100	-
10105/MC	Brushed chrome	50W	12V	III	40cm	70mm	60mm	100	-



Classic MR16



E-A++ 10105GU/W

10105GU | 50W | MR16 | GU10 | Die cast

IP20



Complete with 0950G.





E-A++ 10105GU/G

10105GU | 50W | MR16 | GU10 | Die cast

IP20



Complete with 0950G.





E-A++ 10105GU/C

10105GU | 50W | MR16 | GU10 | Die cast

IP20



Complete with 0950G.





E-A++ 10105GU/MC

10105GU | 50W | MR16 | GU10 | Die cast

IP20



Complete with 0950G.



Order Code	Colour	Watts	Input	Class					Notes
10105GU/W	White	50W	100-240V		15cm	70mm	150mm	100	-
10105GU/G	Grey	50W	100-240V		15cm	70mm	150mm	100	-
10105GU/C	Chrome	50W	100-240V		15cm	70mm	150mm	100	-
10105GU/MC	Brushed chrome	50W	100-240V		15cm	70mm	150mm	100	-

The Cement Range





A-A++

10105CM | 10W | MR16 | GU10 | Cement + aluminium reflector

new

DARK LIGHT

IP20

5 YEAR









Order Code	Colour	Watts	Input	Class					Notes
10105CM	Cement	10W	100-240V		15cm	95mm	120mm	12	-



The Dual Ring Range

Aluminium



E-A++ 10105A1/W

10105A1 | 50W | MR16 | GU10 | Aluminium

IP20



Complete with 0950G.





E-A++ 10105A1/B

10105A1 | 50W | MR16 | GU10 | Aluminium

IP20



Complete with 0950G.





E-A++ 10105A1/AL

10105A1 | 50W | MR16 | GU10 | Aluminium

IP20



Complete with 0950G.



Order Code	Colour	Watts	Input	Class					Notes
10105A1/W	White	50W	100-240V		15cm	68mm	120mm	100	-
10105A1/B	Black	50W	100-240V		15cm	68mm	120mm	100	-
10105A1/AL	Aluminium	50W	100-240V		15cm	68mm	120mm	100	-



The Dark Light Range

Aluminium

10105ALG | 50W | MR16 | GU10 | Aluminium



E-A++ 10105ALG/W

DARK LIGHT

IP20



10105ALG/AL



10105ALG | 50W | MR16 | GU10 | Aluminium



E-A++ 10105ALG/B

DARK LIGHT

IP20



Complete with 0950GB.



50105ALG | 50W | MR16 | GU10 | Aluminium



E-A++ 50105ALG/W

DARK LIGHT

IP20





50105ALG | 50W | MR16 | GU10 | Aluminium



E-A++ 50105ALG/AL

DARK LIGHT

IP20





Order Code	Colour	Watts	Input	Class					Notes
10105ALG/W	White	50W	100-240V		15cm	78mm	150mm	50	-
10105ALG/B	Black	50W	100-240V		15cm	78mm	150mm	50	-
10105ALG/AL	Aluminium	50W	100-240V		15cm	78mm	150mm	50	-
50105ALG/W	White	50W	100-240V		15cm	78mm	150mm	50	-
50105ALG/AL	Aluminium	50W	100-240V		15cm	78mm	150mm	50	-





E-A++ 10105ALG/W/B

10105ALG | 50W | MR16 | GU10 | Aluminium

new DARK LIGHT IP20 5 YEAR



Complete with 0950GB.





E-A++ 10105ALG/W/GL

10105ALG | 50W | MR16 | GU10 | Aluminium

new DARK LIGHT IP20 5 YEAR



Complete with 0950GB.





E-A++ 10105ALG/B/GL

10105ALG | 50W | MR16 | GU10 | Aluminium

new DARK LIGHT IP20 5 YEAR



Complete with 0950GB.



Order Code	Colour	Reflector	Watts	Input	Class					Notes
10105ALG/W/B	White	Black	50W	100-240V		15cm	78mm	150mm	50	-
10105ALG/W/GL	White	Gold	50W	100-240V		15cm	78mm	150mm	50	-
10105ALG/B/GL	Black	Gold	50W	100-240V		15cm	78mm	150mm	50	-



The Semi Trimless Dark Light Range



E-A++ 10105TG/W

10105TG | 50W | MR16 | GU10 | Semi trimless | Aluminium

DARK LIGHT
IP20



10105TG/B





E-A++

50105TG | 50W | MR16 | GU10 | Semi trimless | Die cast

DARK LIGHT
IP20







E-A++

10105T | 50W | MR16 | GU5,3 | Semi trimless | Aluminium

DARK LIGHT
IP20







E-A++

50105T | 50W | MR16 | GU5,3 | Semi trimless | Die cast

DARK LIGHT
IP20





Order Code	Colour	Watts	Input	Class					Notes
10105TG/W	White	50W	100-240V		15cm	75mm	170mm	50	-
10105TG/B	Black	50W	100-240V		15cm	75mm	170mm	50	-
50105TG/W	White	50W	100-240V		15cm	76x76mm	120mm	50	-
10105T/BE	Beige	50W	12V		40cm	75mm	130mm	100	-
50105T/BE	Beige	50W	12V		40cm	75x75mm	130mm	100	-



The Semi Dark Light Range

Aluminium



E-A++ 10105D1/W

10105D1 | 50W | MR16 | GU10 | Aluminium

5 YEAR

IP20



10105D1/B







E-A++ 10105D2/W

10105D2 | 50W | MR16 | GU10 | Aluminium

5 YEAR

IP20



10105D2/B







E-A++

10105DG | 50W | MR16 | GU10 | Semi trimless | Aluminium

5 YEAR

DARK LIGHT

IP20





Order Code	Colour	Watts	Input	Class					Notes
10105D1/W	White	50W	100-240V		15cm	62mm	120mm	50	-
10105D1/B	Black	50W	100-240V		15cm	62mm	120mm	50	-
10105D2/W	White	50W	100-240V		15cm	62mm	120mm	50	-
10105D2/B	Black	50W	100-240V		15cm	62mm	120mm	50	-
10105DG/W	White	50W	100-240V		15cm	76mm	155mm	50	-



The Dark Light Range



10105D4 | 50W | MR16 | GU10 | Aluminium

DARK LIGHT
IP20
5 YEAR



Complete with 0950G.





10105D5 | 50W | MR16 | GU10 | Aluminium

DARK LIGHT
IP20
5 YEAR



Complete with 0950G.





10110T | 75W | R111 | G53 | Semi trimless | Pressed metal

DARK LIGHT
IP20
offer
5 YEAR



Suitable for R111 LED lamp.



Order Code	Colour	Watts	Input	Class					Notes
10105D4/W	White	50W	100-240V		15cm	68mm	140mm	50	-
10105D4/B	Black	50W	100-240V		15cm	68mm	140mm	50	-
10105D5/W	White	50W	100-240V		15cm	68mm	130mm	50	-
10110T/W	White	75W	12V		40cm	175mm	210mm	8	-



The Dark Light Dual Ring Range

Aluminium



E-A++

10105D3 | 50W | MR16 | GU10 | Aluminium

DARK LIGHT

IP20



Complete with 0950G.





E-A++

50105D7 | 50W | MR16 | GU10 | Aluminium

DARK LIGHT

IP20



Complete with 0950G.



Order Code	Colour	Watts	Input	Class					Notes
10105D3/W	White	50W	100-240V		15cm	68mm	120mm	100	-
50105D7/W	White	50W	100-240V		15cm	80mm	120mm	50	-



Recessed Cylinders

Aluminium



10105D9 | 50W | MR16 | GU10 | Aluminium

new DARK LIGHT IP20

5 YEAR

CE



Complete with 0950GB.



E-A++ 10105D9/W/B



10105D9 | 50W | MR16 | GU10 | Aluminium

new DARK LIGHT IP20

5 YEAR

CE



Complete with 0950GB.



E-A++ 10105D9/W/GL



10105D9 | 50W | MR16 | GU10 | Aluminium

new DARK LIGHT IP20

5 YEAR

CE



Complete with 0950GB.



E-A++ 10105D9/B/B



10105D9 | 50W | MR16 | GU10 | Aluminium

new DARK LIGHT IP20

5 YEAR

CE



Complete with 0950GB.



E-A++ 10105D9/B/GL

Order Code	Colour	Reflector	Watts	Input	Class					Notes
10105D9/W/B	White	Black	50W	100-240V		15cm	62mm	100mm	50	-
10105D9/W/GL	White	Gold	50W	100-240V		15cm	62mm	100mm	50	-
10105D9/B/B	Black	Black	50W	100-240V		15cm	62mm	100mm	50	-
10105D9/B/GL	Black	Gold	50W	100-240V		15cm	62mm	100mm	50	-



Semi Trimless Dark Light

Aluminium



E-A++

10105AD | 50W | MR16 | GU10 | Aluminium

DARK LIGHT

5 YEAR

IP20







E-A++ 10105D8/W/GL

10105D8 | 50W | MR16 | GU10 | Aluminium

new

DARK LIGHT

5 YEAR

IP20



10105D8/W/B



Complete with 0950GB.





E-A++ 10105D8/B/GL

10105D8 | 50W | MR16 | GU10 | Aluminium

new

DARK LIGHT

5 YEAR

IP20



10105D8/B/B



Complete with 0950GB.



Order Code	Colour	Reflector	Watts	Input	Class					Notes
10105AD/W	White	Black	50W	100-240V		15cm	64mm	130mm	36	-
10105D8/W/B	White	Black	50W	100-240V		15cm	62mm	130mm	50	-
10105D8/W/GL	White	Gold	50W	100-240V		15cm	62mm	130mm	50	-
10105D8/B/B	Black	Black	50W	100-240V		15cm	62mm	130mm	50	-
10105D8/B/GL	Black	Gold	50W	100-240V		15cm	62mm	130mm	50	-



The Chill Out Range

Round



A-A++ 10105M/W/W

10105M | 10W | MR16 | GU10 | Aluminium body + plastic reflector

DARK LIGHT IP20



Complete with 0950GB.





A-A++ 10105M/W/B

10105M | 10W | MR16 | GU10 | Aluminium body + plastic reflector

DARK LIGHT IP20



Complete with 0950GB.





A-A++ 10105M/W/BS

10105M | 10W | MR16 | GU10 | Aluminium body + plastic reflector

DARK LIGHT IP20



Complete with 0950GB.





A-A++ 10105M/W/CU

10105M | 10W | MR16 | GU10 | Aluminium body + plastic reflector

DARK LIGHT IP20



Complete with 0950GB.



Order Code	Colour	Reflector	Watts	Input	Class					Notes
10105M/W/W	White	White	10W	100-240V		15cm	70mm	120mm	50	-
10105M/W/B	White	Black	10W	100-240V		15cm	70mm	120mm	50	-
10105M/W/BS	White	Brass	10W	100-240V		15cm	70mm	120mm	50	-
10105M/W/CU	White	Copper	10W	100-240V		15cm	70mm	120mm	50	-



The Chill Out Range

Round

10105M | 10W | MR16 | GU10 | Aluminium body + plastic reflector



A-A++ 10105M/B/W

DARK LIGHT

IP20



Complete with 0950GB.



10105M | 10W | MR16 | GU10 | Aluminium body + plastic reflector



A-A++ 10105M/B/B

DARK LIGHT

IP20



Complete with 0950GB.



10105M | 10W | MR16 | GU10 | Aluminium body + plastic reflector



A-A++ 10105M/B/BS

DARK LIGHT

IP20



Complete with 0950GB.



10105M | 10W | MR16 | GU10 | Aluminium body + plastic reflector



A-A++ 10105M/B/CU

DARK LIGHT

IP20



Complete with 0950GB.



Order Code	Colour	Reflector	Watts	Input	Class					Notes
10105M/B/W	Black	White	10W	100-240V		15cm	70mm	120mm	50	-
10105M/B/B	Black	Black	10W	100-240V		15cm	70mm	120mm	50	-
10105M/B/BS	Black	Brass	10W	100-240V		15cm	70mm	120mm	50	-
10105M/B/CU	Black	Copper	10W	100-240V		15cm	70mm	120mm	50	-

The Chill Out Range

Round



A-A++ 10105MD/W/W

10105MD | 10W | MR16 | GU10 | Aluminium body + plastic reflector

DARK LIGHT IP20



Complete with 0950GB.





A-A++ 10105MD/W/B

10105MD | 10W | MR16 | GU10 | Aluminium body + plastic reflector

DARK LIGHT IP20



Complete with 0950GB.





A-A++ 10105MD/W/BS

10105MD | 10W | MR16 | GU10 | Aluminium body + plastic reflector

DARK LIGHT IP20



Complete with 0950GB.





A-A++ 10105MD/W/C

10105MD | 10W | MR16 | GU10 | Aluminium body + plastic reflector

DARK LIGHT IP20



Complete with 0950GB.





A-A++ 10105MD/W/GL

10105MD | 10W | MR16 | GU10 | Aluminium body + plastic reflector

DARK LIGHT IP20



Complete with 0950GB.



Order Code	Colour	Reflector	Watts	Input	Class					Notes
10105MD/W/W	White	White	10W	100-240V		15cm	70mm	120mm	50	-
10105MD/W/B	White	Black	10W	100-240V		15cm	70mm	120mm	50	-
10105MD/W/BS	White	Brass	10W	100-240V		15cm	70mm	120mm	50	-
10105MD/W/C	White	Chrome	10W	100-240V		15cm	70mm	120mm	50	-
10105MD/W/GL	White	Gold	10W	100-240V		15cm	70mm	120mm	50	-



The Chill Out Range

Round



A-A++ 10105MD/B/B

10105MD | 10W | MR16 | GU10 | Aluminium body + plastic reflector

DARK LIGHT

IP20



Complete with 0950GB.





A-A++ 10105MD/B/BS

10105MD | 10W | MR16 | GU10 | Aluminium body + plastic reflector

DARK LIGHT

IP20



Complete with 0950GB.



Order Code	Colour	Reflector	Watts	Input	Class					Notes
10105MD/B/B	Black	Black	10W	100-240V	⏚	15cm	70mm	120mm	50	-
10105MD/B/BS	Black	Brass	10W	100-240V	⏚	15cm	70mm	120mm	50	-



The Assymetric Chill Out Range

Square



A-A++ 50105MA/W/W

50105MA | 10W | MR16 | GU10 | Aluminium body + plastic reflector — Assymetric for shelf illumination.

DARK LIGHT IP20



Assymetric.





A-A++ 50105MA/W/B

50105MA | 10W | MR16 | GU10 | Aluminium body + plastic reflector — Assymetric for shelf illumination.

DARK LIGHT IP20



Assymetric.





A-A++ 50105MA/B/B

50105MA | 10W | MR16 | GU10 | Aluminium body + plastic reflector — Assymetric for shelf illumination.

DARK LIGHT IP20



Assymetric.



Order Code	Colour	Reflector	Watts	Input	Class					Notes
50105MA/W/W	White	White	10W	100-240V		15cm	76x76mm	150mm	50	Assymetric
50105MA/W/B	White	Black	10W	100-240V		15cm	76x76mm	150mm	50	Assymetric
50105MA/B/B	Black	Black	10W	100-240V		15cm	76x76mm	150mm	50	Assymetric



The Chill Out Range
Square



A-A++ 50105M/W/BS

50105M | 10W | MR16 | GU10 | Aluminium body + plastic reflector

5 YEAR

DARK LIGHT

IP20



50105M/W/CU



Complete with 0950GB.





A-A++ 50105M/B/W

50105M | 10W | MR16 | GU10 | Aluminium body + plastic reflector

5 YEAR

DARK LIGHT

IP20



50105M/B/B



Complete with 0950GB.





A-A++ 50105M/B/BS

50105M | 10W | MR16 | GU10 | Aluminium body + plastic reflector

5 YEAR

DARK LIGHT

IP20



50105M/B/CU



Complete with 0950GB.



Order Code	Colour	Reflector	Watts	Input	Class					Notes
50105M/W/BS	White	Brass	10W	100-240V		15cm	76x76mm	130mm	50	-
50105M/W/CU	White	Copper	10W	100-240V		15cm	76x76mm	130mm	50	-
50105M/B/W	Black	White	10W	100-240V		15cm	76x76mm	130mm	50	-
50105M/B/B	Black	Black	10W	100-240V		15cm	76x76mm	130mm	50	-
50105M/B/BS	Black	Brass	10W	100-240V		15cm	76x76mm	130mm	50	-
50105M/B/CU	Black	Copper	10W	100-240V		15cm	76x76mm	130mm	50	-



The Dark Light Range Pro

Aluminium



E-A++ 50205D/W

50205D | 2x50W | MR16 | GU5,3 | Aluminium

DARK LIGHT

IP20







E-A++ 50205D/AL

50205D | 2x50W | MR16 | GU5,3 | Aluminium

DARK LIGHT

IP20





Order Code	Colour	Watts	Input	Class					Notes
50205D/W	White	2x50W	12V	III	40cm	220x110mm	130mm	20	-
50205D/AL	Aluminium	2x50W	12V	III	40cm	220x110mm	130mm	20	-



10105F/MC



10105L/MC

The Dark Light Range 12V

Steel



E-A++ 10105L/C

10105L | 50W | MR16 | GU5,3 | Adjustable ring | Steel

DARK LIGHT

IP20







E-A++ 10105L/MC

10105L | 50W | MR16 | GU5,3 | Adjustable ring | Steel

DARK LIGHT

IP20







E-A++

10105F | 50W | MR16 | GU5,3 | Adjustable ring | Steel

DARK LIGHT

IP20





Order Code	Colour	Watts	Input	Class					Notes
10105L/C	Chrome	50W	12V	III	40cm	90mm	95mm	50	-
10105L/MC	Brushed chrome	50W	12V	III	40cm	90mm	95mm	50	-
10105F/MC	Brushed chrome	50W	12V	III	40cm	90mm	90mm	50	-



The Bathroom Range

Die cast



E-A++ 10105CJ/MC/5

10105CJ | 50W | MR16 | GU5,3 | Die cast

DARK LIGHT · IP43 · offer · 5 YEAR







E-A++ 10105CJ/BS/5

10105CJ | 50W | MR16 | GU5,3 | Die cast

DARK LIGHT · IP43 · offer · 5 YEAR







E-A++ 10105CJ/ABS/5

10105CJ | 50W | MR16 | GU5,3 | Die cast

DARK LIGHT · IP43 · offer · 5 YEAR





Order Code	Colour	Watts	Input	Class					Notes
10105CJ/MC/5	Brushed chrome	50W	12V	III	40cm	102mm	120mm	50	-
10105CJ/BS/5	Brass	50W	12V	III	40cm	102mm	120mm	50	-
10105CJ/ABS/5	Antique brass	50W	12V	III	40cm	102mm	120mm	50	-



The Bathroom Range IP44

Die cast

10105R | 50W | MR16 | GU5,3 | Die cast



E-A++ 10105R/W

IP44



10105R/B



10105R | 50W | MR16 | GU5,3 | Die cast



E-A++ 10105R/MC

IP44





50105R | 50W | MR16 | GU5,3 | Die cast



E-A++ 50105R/W

IP44





50105R | 50W | MR16 | GU5,3 | Die cast



E-A++ 50105R/MC

IP44





Order Code	Colour	Watts	Input	Class					Notes
10105R/W	White	50W	12V	III	40cm	70mm	100mm	50	-
10105R/B	Black	50W	12V	III	40cm	70mm	100mm	50	-
10105R/MC	Brushed chrome	50W	12V	III	40cm	70mm	100mm	50	-
50105R/W	White	50W	12V	III	40cm	70mm	100mm	50	-
50105R/MC	Brushed chrome	50W	12V	III	40cm	70mm	100mm	50	-

The IP65 GU10 Range



E-A++

IP65

10105V | 50W | MR16 | GU10 | Die cast





Order Code	Colour	Watts	Input	Class					Notes
10105V/G	Grey	50W	100-240V	⏚	100cm	78mm	120mm	24	-



The Bathroom Range IP65
Aluminium



E-A++ 10105R1/W

10105R1 | 50W | MR16 | GU10 | Aluminium

IP65







E-A++ 10105R1/AL

10105R1 | 50W | MR16 | GU10 | Aluminium

IP65







E-A++

10105R2 | 50W | MR16 | GU10 | Aluminium

DARK LIGHT

IP65





Order Code	Colour	Watts	Input	Class					Notes
10105R1/W	White	50W	100-240V		15cm	68mm	120mm	50	-
10105R1/AL	Aluminium	50W	100-240V		15cm	68mm	120mm	50	-
10105R2/W	White	50W	100-240V		15cm	82mm	130mm	50	-



Round Decorative Spots

Natural aluminium + glass



E-A++

10105GL1 | 50W | MR16 | GU5,3 | Natural aluminium + glass

IP20







E-A++

10105GL2 | 50W | MR16 | GU5,3 | Natural aluminium + glass

IP20

offer





Order Code	Colour	Watts	Input	Class					Notes
10105GL1/AL	Aluminium	50W	12V	III	40cm	60mm	50mm	50	-
10105GL2/AL	Aluminium	50W	12V	III	40cm	60mm	50mm	50	-



50105GL/AL



10105GL1/AL



50105GL1/AL

Square Decorative Spots

Natural aluminium + glass



E-A++

50105GL | 50W | MR16 | GU5,3 | Natural aluminium + glass

IP20







E-A++

50105GL1 | 50W | MR16 | GU5,3 | Natural aluminium + glass

IP20





Order Code	Colour	Watts	Input	Class					Notes
50105GL/AL	Aluminium	50W	12V	III	40cm	60mm	50mm	50	-
50105GL1/AL	Aluminium	50W	12V	III	40cm	60mm	50mm	50	-



The Decorative Spots

Natural aluminium



10105AC | 50W | MR16 | GU5,3 | Natural aluminium

IP20







10105AR | 50W | MR16 | GU5,3 | Natural aluminium

IP20
offer







50105AR | 50W | MR16 | GU5,3 | Natural aluminium

IP20
offer





Order Code	Colour	Watts	Input	Class					Notes
10105AC/AL	Aluminium	50W	12V	III	40cm	60mm	60mm	50	-
10105AR/AL	Aluminium	50W	12V	III	40cm	70mm	75mm	50	-
50105AR/AL	Aluminium	50W	12V	III	40cm	70mm	75mm	50	-

The Decorative Spot

50105GL4 | 35W | MR16 | GU10 | Metal + glass



E-A++

IP20

offer





Order Code	Colour	Watts	Input	Class					Notes
50105GL4/MC	Brushed chrome	35W	100-240V		15cm	88mm	130mm	50	-



Trimless Gypsum



10105GT1 | 50W | MR16 | GU10 | Trimless | Gypsum

IP20



Suitable for GU10 LED lamp.





10105GT2 | 50W | MR16 | GU10 | Trimless | Gypsum

DARK LIGHT

IP20



Suitable for GU10 LED lamp.





50105GT1 | 50W | MR16 | GU10 | Trimless | Gypsum

IP20



Suitable for GU10 LED lamp.





50105GT2 | 50W | MR16 | GU10 | Trimless | Gypsum

DARK LIGHT

IP20



Suitable for GU10 LED lamp.



Order Code	Colour	Watts	Input	Class					Notes
10105GT1	White	50W	100-240V		15cm	102mm	100mm	24	-
10105GT2	White	50W	100-240V		15cm	132mm	150mm	24	-
50105GT1	White	50W	100-240V		15cm	102x102mm	100mm	24	-
50105GT2	White	50W	100-240V		15cm	122x122mm	150mm	24	-



The Chill Out Trimless Range

Aluminium



10105TR | 50W | MR16 | GU10 | Trimless | Aluminium

DARK LIGHT
IP20





E-A++ 10105TR/W



10105TR | 50W | MR16 | GU10 | Trimless | Aluminium

DARK LIGHT
IP20





E-A++ 10105TR/B



10105TR | 50W | MR16 | GU10 | Trimless | Aluminium

DARK LIGHT
IP20





E-A++ 10105TR/BS

Order Code	Colour	Watts	Input	Class					Notes
10105TR/W	White	50W	100-240V		15cm	65mm	120mm	60	-
10105TR/B	Black	50W	100-240V		15cm	65mm	120mm	60	-
10105TR/BS	Brass	50W	100-240V		15cm	65mm	120mm	60	-



The Chill Out Trimless Range

Round



10105RM | 10W | MR16 | GU10 | Trimless | Die cast body + plastic reflector Reflector must be ordered separately.

DARK LIGHT

IP20







050099/W White | 050099/G Grey | 050099/C Chrome | 050099/BS Brass | 050099/GL Gold | 050099/CU Copper

Order Code	Colour	Watts	Input	Class					Notes
10105RM	White	10W	100-240V	⏚	15cm	90mm	130mm	50	-



050098/C

050098/B

050098/CU

50105RM + 050098/G

The Chill Out Trimless Range

Square



A-A++ 50105RM + 050098/BS

50105RM | 10W | MR16 | GU10 | Trimless | Die cast body + plastic reflector Reflector must be ordered separately.

DARK LIGHT

IP20







050098/W White | 050098/B Black | 050098/G Grey | 050098/C Chrome | 050098/GL Gold | 050098/CU Copper

Order Code	Colour	Watts	Input	Class					Notes
50105RM	White	10W	100-240V	⏚	15cm	85x75mm	130mm	50	-





02

Recessed Spots Fixed LED

Pages 39-68

COB LED | SMD LED

Die cast | Aluminium | Plastic | Gypsum | Acrylic | Trimless

IP20 IP44 IP54 IP65

DIMMABLE DARK LIGHT QUICK FIX FIRE RATED 80 CRI 85 CRI 90 CRI 2 YEAR 3 YEAR





10101D/B/W

10101L/B/W

10101L/W/W

The Super Mini Series



A-A++ 10101L/W/W

10101L | 1W | LED | Aluminium

Driver can not pass through the cutout hole.

LED BUILT IN · 85 CRI · DIMMABLE · QUICK FIX · IP44 · CE · 3 YEAR



10101L/W/BL





A-A++ 10101L/B/W

10101L | 1W | LED | Aluminium

Driver can not pass through the cutout hole.

new · LED BUILT IN · 85 CRI · DIMMABLE · QUICK FIX · IP44 · CE · 3 YEAR







A-A++ 10101D/W/W

10101D | 1W | LED | Die cast

Driver can not pass through the cutout hole.

new · DARK LIGHT · LED BUILT IN · 80 CRI · DIMMABLE · QUICK FIX · IP20 · CE · 3 YEAR



Removable head.





A-A++ 10101D/B/W

10101D | 1W | LED | Die cast

Driver can not pass through the cutout hole.

new · DARK LIGHT · LED BUILT IN · 80 CRI · DIMMABLE · QUICK FIX · IP20 · CE · 3 YEAR



Removable head.



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class					Notes
10101L/W/W	White	Warm white	3000K	1W	70lm	350mA	III	100cm	12mm	30mm	100	Requires 350mA driver
10101L/W/BL	White	Blue	-	1W	-	350mA	III	100cm	12mm	30mm	100	Requires 350mA driver
10101L/B/W	Black	Warm white	3000K	1W	70lm	350mA	III	100cm	12mm	30mm	100	Requires 350mA driver
10101D/W/W	White	Warm white	3000K	1W	60lm	350mA	III	40cm	20mm	45mm	100	Requires 350mA driver
10101D/B/W	Black	Warm white	3000K	1W	60lm	350mA	III	40cm	20mm	45mm	100	Requires 350mA driver



The 1W/3W LED Spots

Aluminium



A-A++ 10103B/W/W

10103B | 1W/3W | COB LED | Aluminium — 1W@350mA / 3W@700mA





A-A++ 10103B/B/W

10103B | 1W/3W | COB LED | Aluminium — 1W@350mA / 3W@700mA





A-A++ 10103B/AL/W

10103B | 1W/3W | COB LED | Aluminium — 1W@350mA / 3W@700mA



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
10103B/W/W	White	Warm white	3000K	1W/3W	200lm@3W	40°	350mA/700mA		40cm	35mm	50mm	100	Requires 350mA/700mA driver
10103B/B/W	Black	Warm white	3000K	1W/3W	200lm@3W	40°	350mA/700mA		40cm	35mm	50mm	100	Requires 350mA/700mA driver
10103B/AL/W	Aluminium	Warm white	3000K	1W/3W	200lm@3W	40°	350mA/700mA		40cm	35mm	50mm	100	Requires 350mA/700mA driver



The 1W/3W LED Dark Light Range



A-A++

10103R | 1W/3W | COB LED | Aluminium

1W@350mA / 3W@700mA

LED BUILT IN · 80 CRI · DIMMABLE · QUICK FIX · DARK LIGHT · IP20 · CE · 2 YEAR







A-A++

10103D | 1W/3W | COB LED | Aluminium

1W@350mA / 3W@700mA

LED BUILT IN · 80 CRI · DIMMABLE · QUICK FIX · DARK LIGHT · IP20 · CE · 2 YEAR







A-A++ 10103DE/W/W

10103DE | 1W/3W | COB LED | Aluminium

1W@350mA / 3W@700mA

new · LED BUILT IN · 80 CRI · DIMMABLE · QUICK FIX · DARK LIGHT · IP20 · CE · 2 YEAR







A-A++ 10103DE/B/W

10103DE | 1W/3W | COB LED | Aluminium

1W@350mA / 3W@700mA

new · LED BUILT IN · 80 CRI · DIMMABLE · QUICK FIX · DARK LIGHT · IP20 · CE · 2 YEAR





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class	S				Notes
10103R/W/W	White	Warm white	3000K	1W/3W	200lm@3W	40°	350mA/700mA	III	40cm	50mm	65mm	50	Requires 350mA/700mA driver
10103D/W/W	White	Warm white	3000K	1W/3W	200lm@3W	40°	350mA/700mA	III	40cm	43mm	65mm	100	Requires 350mA/700mA driver
10103DE/W/W	White	Warm white	3000K	1W/3W	200lm@3W	38°	350mA/700mA	III	40cm	38mm	60mm	50	Requires 350mA/700mA driver
10103DE/B/W	Black	Warm white	3000K	1W/3W	200lm@3W	38°	350mA/700mA	III	40cm	38mm	60mm	50	Requires 350mA/700mA driver



The 1W/3W LED Dark Light Range



A-A++ 10103DL/W/B/W

10103DL | 1W/3W | COB LED | Aluminium — 1W@350mA / 3W@700mA

new DARK LIGHT IP20 — LED BUILT IN — 80 CRI — DIMMABLE — QUICK FIX — CE — 2 YEAR







A-A++ 10103DL/W/BS/W

10103DL | 1W/3W | COB LED | Aluminium — 1W@350mA / 3W@700mA

new DARK LIGHT IP20 — LED BUILT IN — 80 CRI — DIMMABLE — QUICK FIX — CE — 2 YEAR







A-A++ 10103DL/B/B/W

10103DL | 1W/3W | COB LED | Aluminium — 1W@350mA / 3W@700mA

new DARK LIGHT IP20 — LED BUILT IN — 80 CRI — DIMMABLE — QUICK FIX — CE — 2 YEAR







A-A++ 10103DL/B/BS/W

10103DL | 1W/3W | COB LED | Aluminium — 1W@350mA / 3W@700mA

new DARK LIGHT IP20 — LED BUILT IN — 80 CRI — DIMMABLE — QUICK FIX — CE — 2 YEAR





Order Code	Colour	Reflector	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
10103DL/W/B/W	White	Black	Warm white	3000K	1W/3W	200@3W	36°	350mA/700mA	III	40cm	40mm	70mm	50	Requires 350mA/700mA driver
10103DL/W/BS/W	White	Brass	Warm white	3000K	1W/3W	200@3W	36°	350mA/700mA	III	40cm	40mm	70mm	50	Requires 350mA/700mA driver
10103DL/B/B/W	Black	Black	Warm white	3000K	1W/3W	200@3W	36°	350mA/700mA	III	40cm	40mm	70mm	50	Requires 350mA/700mA driver
10103DL/B/BS/W	Black	Brass	Warm white	3000K	1W/3W	200@3W	36°	350mA/700mA	III	40cm	40mm	70mm	50	Requires 350mA/700mA driver



Fixed Spots

10103L | 3x1W | LED | Natural aluminium



A-A++

LED BUILT IN · DIMMABLE · QUICK FIX · CE · IP20 offer · 2 YEAR



Suitable for 89004 driver.



50103L | 3x1W | LED | Natural aluminium



A-A++

LED BUILT IN · DIMMABLE · QUICK FIX · CE · IP20 offer · 2 YEAR



Suitable for 89004 driver.



50401L | 4x1W | LED | Natural aluminium



A-A++

LED BUILT IN · DIMMABLE · QUICK FIX · CE · IP20 offer · 2 YEAR





50601L | 6x1W | LED | Natural aluminium



A-A++

LED BUILT IN · DIMMABLE · QUICK FIX · CE · IP20 offer · 2 YEAR





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
10103L/D/35	Aluminium	Daylight	6000K	3x1W	180lm	35°	350mA		40cm	60mm	40mm	100	Requires 350mA driver
10103L/W/35	Aluminium	Warm white	3000K	3x1W	135lm	35°	350mA		40cm	60mm	40mm	100	Requires 350mA driver
50103L/D/35	Aluminium	Daylight	6000K	3x1W	180lm	35°	350mA		40cm	60mm	40mm	100	Requires 350mA driver
50103L/W/35	Aluminium	Warm white	3000K	3x1W	135lm	35°	350mA		40cm	60mm	40mm	100	Requires 350mA driver
50401L/D/35	Aluminium	Daylight	6000K	4x1W	240lm	35°	350mA		40cm	80x80mm	40mm	50	Requires 350mA driver
50401L/W/35	Aluminium	Warm white	3000K	4x1W	180lm	35°	350mA		40cm	80x80mm	40mm	50	Requires 350mA driver
50601L/D/35	Aluminium	Daylight	6000K	6x1W	360lm	35°	350mA		40cm	118x80mm	40mm	50	Requires 350mA driver
50601L/W/35	Aluminium	Warm white	3000K	6x1W	270lm	35°	350mA		40cm	118x80mm	40mm	50	Requires 350mA driver



3W LED Glass Lens
Aluminium



A-A++ 10103N/W/W/35

10103N | 3x1W | LED | Aluminium

LED BUILT IN
DIMMABLE
QUICK FIX
IP20
offer
2 YEAR





Suitable for 89004 driver.





A-A++ 10103N/B/W/35

10103N | 3x1W | LED | Aluminium

LED BUILT IN
DIMMABLE
QUICK FIX
IP20
offer
2 YEAR





Suitable for 89004 driver.





A-A++ 10103N/AL/W/35

10103N | 3x1W | LED | Aluminium

LED BUILT IN
DIMMABLE
QUICK FIX
IP20
offer
2 YEAR





Suitable for 89004 driver.



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
10103N/W/D/35	White	Daylight	6000K	3x1W	180lm	35°	350mA	III	40cm	60mm	45mm	100	Requires 350mA driver
10103N/W/W/35	White	Warm white	3000K	3x1W	135lm	35°	350mA	III	40cm	60mm	45mm	100	Requires 350mA driver
10103N/B/D/35	Black	Daylight	6000K	3x1W	180lm	35°	350mA	III	40cm	60mm	45mm	100	Requires 350mA driver
10103N/B/W/35	Black	Warm white	3000K	3x1W	135lm	35°	350mA	III	40cm	60mm	45mm	100	Requires 350mA driver
10103N/AL/D/35	Aluminium	Daylight	6000K	3X1W	180lm	35°	350mA	III	40cm	60mm	45mm	100	Requires 350mA driver
10103N/AL/W/35	Aluminium	Warm white	3000K	3x1W	135lm	35°	350mA	III	40cm	60mm	45mm	100	Requires 350mA driver



The Retro Dark Light Range

10107Z | 7W | COB LED | Die cast + plastic



A-A++ 10107Z/W/W

LED BUILT IN · 80 CRI · CE · 3 YEAR · DARK LIGHT · IP20



10107Z/B/W



Complete with Black & Brass reflectors.



10112Z | 12W | COB LED | Die cast + plastic



A-A++ 10112Z/W/W

LED BUILT IN · 80 CRI · CE · 3 YEAR · DARK LIGHT · IP20



10112Z/B/W



Complete with Black & Brass reflectors.



10120Z | 20W | COB LED | Die cast + plastic



A-A++ 10120Z/W/W

LED BUILT IN · 80 CRI · CE · 3 YEAR · DARK LIGHT · IP20



10120Z/B/W



Complete with Black & Brass reflectors.



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
10107Z/W/W	White	Warm white	3000K	7W	560lm	45°	230V	☐	65mm	80mm	40	Complete with 160mA driver
10107Z/B/W	Black	Warm white	3000K	7W	560lm	45°	230V	☐	65mm	80mm	40	Complete with 160mA driver
10112Z/W/W	White	Warm white	3000K	12W	960lm	45°	230V	☐	82mm	88mm	30	Complete with 300mA driver
10112Z/B/W	Black	Warm white	3000K	12W	960lm	45°	230V	☐	82mm	88mm	30	Complete with 300mA driver
10120Z/W/W	White	Warm white	3000K	20W	1600lm	45°	230V	☐	105mm	105mm	20	Complete with 500mA driver
10120Z/B/W	Black	Warm white	3000K	20W	1600lm	45°	230V	☐	105mm	105mm	20	Complete with 500mA driver



10107K/W/W + 050104/CU

10112L/W/W + 10112LR/B

10112L/B/W + 10112LR/BS

The COB Dark Light Range

Interchangeable Reflector



A-A++ 10107K/W/W + 050104/B

10107K | 7W | COB LED | Aluminium

Ring must be ordered separately.

LED BUILT IN · 80 CRI · DIMMABLE · QUICK FIX · DARK LIGHT · IP20 · CE · 3 YEAR



10107K/B/W + 050104/BS





050104/W White



050104/B Black



050104/C Chrome



050104/BS Brass



050104/CU Copper



A-A++ 10112L/W/W+10112LR/BS

10112L | 12W | COB LED | Aluminium

Reflecor must be ordered separately.

LED BUILT IN · 80 CRI · DIMMABLE · QUICK FIX · DARK LIGHT · IP20 · CE · 2 YEAR



10112L/B/W+10112LR/W





10112LR/W White



10112LR/B Black



10112LR/G Matt chrome



10112LR/C Chrome



10112LR/BS Brass



10112LR/CU Copper

Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class	S				Notes
10107K/W/W	White	Warm white	3000K	7W	550lm	35°	700mA	III	40cm	76mm	100mm	30	Requires 700mA driver
10107K/B/W	Black	Warm white	3000K	7W	550lm	35°	700mA	III	40cm	76mm	100mm	30	Requires 700mA driver
10112L/W/W	White	Warm white	3000K	12W	1100lm	40°	700mA	III	40cm	75mm	100mm	50	Requires 700mA driver
10112L/B/W	Black	Warm white	3000K	12W	1100lm	40°	700mA	III	40cm	75mm	100mm	50	Requires 700mA driver



The 7W Dark Light Range



A-A++

10107D | 7W | COB LED | Die cast

LED BUILT IN · 90 CRI · DIMMABLE · QUICK FIX · DARK LIGHT · IP20 · CE · 3 YEAR







A-A++

10107DA | 7W | COB LED | Die cast

LED BUILT IN · 90 CRI · DIMMABLE · QUICK FIX · DARK LIGHT · IP20 · CE · 3 YEAR







A-A++ 10107DC/W/W

10107DC | 7W | COB LED | Die cast

LED BUILT IN · 80 CRI · CE · 2 YEAR · DARK LIGHT · IP20







A-A++ 10107DC/B/W

10107DC | 7W | COB LED | Die cast

LED BUILT IN · 80 CRI · CE · 2 YEAR · DARK LIGHT · IP20





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class	S				Notes
10107D/W/W	White	Warm white	3000K	7W	530lm	36°	700mA	III	40cm	77mm	90mm	60	Requires 700mA driver
10107DA/W/W	White	Warm white	3000K	7W	530lm	36°	700mA	III	40cm	97mm	120mm	30	Requires 700mA driver
10107DC/W/W	White	Warm white	3000K	7W	560lm	50°	230V	□	15cm	55mm	110mm	50	Complete with 300mA driver
10107DC/B/W	Black	Warm white	3000K	7W	560lm	50°	230V	□	15cm	55mm	110mm	50	Complete with 300mA driver



The 12W Dark Light Range



A-A++

10112E | 12W | COB LED | Die cast

LED BUILT IN · 80 CRI · DIMMABLE · QUICK FIX · DARK LIGHT · IP20 · CE · 2 YEAR







A-A++

10112C | 12W | COB LED | Die cast

LED BUILT IN · 80 CRI · DIMMABLE · QUICK FIX · DARK LIGHT · IP20 · CE · 2 YEAR







A-A++ 10112TD/W/W

10112TD | 12W | COB LED | Die cast

new · LED BUILT IN · 80 CRI · CE · 3 YEAR · DARK LIGHT · IP20







A-A++ 10112TD/B/W

10112TD | 12W | COB LED | Die cast

new · LED BUILT IN · 80 CRI · CE · 3 YEAR · DARK LIGHT · IP20





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
10112E/W/C	White	Cool white	4000K	12W	1100lm	40°	700mA	III	40cm	75mm	110mm	50	Requires 700mA driver
10112E/W/W	White	Warm white	3000K	12W	1100lm	40°	700mA	III	40cm	75mm	110mm	50	Requires 700mA driver
10112C/W/W	White	Warm white	3000K	12W	1100lm	40°	700mA	III	40cm	75mm	135mm	50	Requires 700mA driver
10112TD/W/C	White	Cool white	4000K	12W	960lm	20°	230V	□	-	82mm	100mm	50	Complete with 300mA driver
10112TD/W/W	White	Warm white	3000K	12W	960lm	20°	230V	□	-	82mm	100mm	50	Complete with 300mA driver
10112TD/B/C	Black	Cool white	4000K	12W	960lm	20°	230V	□	-	82mm	100mm	50	Complete with 300mA driver
10112TD/B/W	Black	Warm white	3000K	12W	960lm	20°	230V	□	-	82mm	100mm	50	Complete with 300mA driver



10115FD/W/W

10110FD/B/W

10105FD/W/W

The Dark Light Pro Range

Aluminium



A-A++ 10105FD/W/W

10105FD | 5W | COB LED | Aluminium

LED BUILT IN · 80 CRI · CE · 2 YEAR · DARK LIGHT · IP20







A-A++ 10110FD/W/W

10110FD | 10W | COB LED | Aluminium

LED BUILT IN · 80 CRI · CE · 2 YEAR · DARK LIGHT · IP20







A-A++ 10115FD/W/W

10115FD | 15W | COB LED | Aluminium

LED BUILT IN · 80 CRI · CE · 2 YEAR · DARK LIGHT · IP20





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
10105FD/W/W	White	Warm white	3000K	5W	300lm	24°	230V	⧈	50mm	120mm	50	Complete with 300mA driver
10110FD/W/W	White	Warm white	3000K	10W	800lm	24°	230V	⧈	68mm	130mm	50	Complete with 300mA driver
10115FD/W/W	White	Warm white	3000K	15W	1275lm	24°	230V	⧈	80mm	150mm	20	Complete with 350mA driver



The Dark Light Pro Range

Aluminium



A-A++ 10105FD/B/W

10105FD | 5W | COB LED | Aluminium

LED BUILT IN · 80 CRI · CE · 2 YEAR · DARK LIGHT · IP20







A-A++ 10110FD/B/W

10110FD | 10W | COB LED | Aluminium

LED BUILT IN · 80 CRI · CE · 2 YEAR · DARK LIGHT · IP20







A-A++ 10115FD/B/W

10115FD | 15W | COB LED | Aluminium

LED BUILT IN · 80 CRI · CE · 2 YEAR · DARK LIGHT · IP20





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
10105FD/B/W	Black	Warm white	3000K	5W	300lm	24°	230V	⧈	50mm	120mm	50	Complete with 300mA driver
10110FD/B/W	Black	Warm white	3000K	10W	800lm	24°	230V	⧈	68mm	130mm	50	Complete with 300mA driver
10115FD/B/W	Black	Warm white	3000K	15W	1275lm	24°	230V	⧈	80mm	150mm	20	Complete with 350mA driver





10112H | 12W | COB LED | Aluminium

LED BUILT IN
80 CRI
DIMMABLE
QUICK FIX
DARK LIGHT
IP20
2 YEAR







10112R | 12W | COB LED | Aluminium

Ring must be ordered separately.

new
LED BUILT IN
80 CRI
DIMMABLE
QUICK FIX
DARK LIGHT
IP20
2 YEAR







050162/W White



050162/B Black



050162/AL Aluminium



050162/DC Dark chrome



050162/GL Gold

Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
10112H/W/W	White	Warm white	3000K	12W	850lm	40°	700mA	III	40cm	87mm	100mm	50	Requires 700mA driver
10112H/W/EW	White	Extra warm white	2700K	12W	850lm	40°	700mA	III	40cm	87mm	100mm	50	Requires 700mA driver
10112R/B/W	Black	Warm white	3000K	12W	1100lm	50°	700mA	III	40cm	68mm	90mm	50	Requires 700mA driver



10107W/AL/W

10105W/AL/W

The COB Bathroom IP44 Range

Aluminium



A-A++

10105W | 5W | COB LED | Aluminium

LED BUILT IN

80 CRI

CE

2 YEAR

IP44







A-A++

10107W | 7W | COB LED | Aluminium

LED BUILT IN

80 CRI

CE

2 YEAR

IP44





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
10105W/AL/W	Aluminium	Warm white	3000K	5W	425lm	30°	230V	☐	57mm	90mm	30	Complete with 500mA driver
10107W/AL/W	Aluminium	Warm white	3000K	7W	507lm	30°	100-240V	☐	68mm	95mm	30	Complete with 700mA driver



10112TP/W/C

10107WP/W/W

10107DL/W/W

The COB Dark Light IP44 Range



10107DL | 7W | COB LED | Aluminium

LED BUILT IN · 80 CRI · DIMMABLE · QUICK FIX · DARK LIGHT · IP44 · 3 YEAR · A-A++







10107WP | 7W | COB LED | Die cast

LED BUILT IN · 80 CRI · DIMMABLE · QUICK FIX · DARK LIGHT · IP44 · 3 YEAR · A-A++ 10107WP/W/W



10107WP/B/W





10112TP | 12W | COB LED | Die cast

LED BUILT IN · 80 CRI · DIMMABLE · QUICK FIX · DARK LIGHT · IP44 · 2 YEAR · A-A++ 10112TP/W/W



10112TP/B/W



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
10107DL/W/W	White	Warm white	3000K	7W	450lm	38°	700mA	III	40cm	42mm	100mm	50	Requires 700mA driver
10107WP/W/W	White	Warm white	3000K	7W	500lm	38°	700mA	III	40cm	56mm	100mm	50	Requires 700mA driver
10107WP/B/W	Black	Warm white	3000K	7W	500lm	38°	700mA	III	40cm	56mm	100mm	50	Requires 700mA driver
10112TP/W/C	White	Cool white	4000K	12W	1100lm	38°	700mA	III	40cm	75mm	110mm	50	Requires 700mA driver
10112TP/W/W	White	Warm white	3000K	12W	1100lm	38°	700mA	III	40cm	75mm	110mm	50	Requires 700mA driver
10112TP/W/EW	White	Extra warm white	2700K	12W	1100lm	38°	700mA	III	40cm	75mm	110mm	50	Requires 700mA driver
10112TP/B/W	Black	Warm white	3000K	12W	1100lm	38°	700mA	III	40cm	75mm	110mm	50	Requires 700mA driver



The COB IP54 Range

10107HC | 7W | COB LED | Die cast

Complete with honeycomb.



A-A++ 10107HC/W/W

new · DARK LIGHT · IP54 · LED BUILT IN · 90 CRI · DIMMABLE · QUICK FIX · CE · 3 YEAR



10107HC/B/W



10107WD | 7W | COB LED | Die cast



A-A++

DARK LIGHT · IP54 · LED BUILT IN · 90 CRI · DIMMABLE · QUICK FIX · CE · 3 YEAR





10107DB | 7W | COB LED | Aluminium



A-A++

DARK LIGHT · IP54 · LED BUILT IN · 80 CRI · DIMMABLE · QUICK FIX · CE · 3 YEAR





10113P | 15W | COB LED | Natural aluminium



A-A++

LED BUILT IN · 80 CRI · CE · 3 YEAR · IP54





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
10107HC/W/W	White	Warm white	3000K	7W	460lm	36°	700mA		40cm	68mm	75mm	60	Requires 700mA driver
10107HC/B/W	Black	Warm white	3000K	7W	460lm	36°	700mA		40cm	68mm	75mm	60	Requires 700mA driver
10107WD/W/C	White	Cool white	4000K	7W	530lm	36°	700mA		40cm	75mm	110mm	50	Requires 700mA driver
10107WD/W/W	White	Warm white	3000K	7W	500lm	36°	700mA		40cm	75mm	110mm	50	Requires 700mA driver
10107DB/W/C	White	Cool white	4000K	7W	500lm	36°	700mA		40cm	60mm	80mm	50	Requires 700mA driver
10107DB/W/W	White	Warm white	3000K	7W	500lm	36°	700mA		40cm	60mm	80mm	50	Requires 700mA driver
10113P/AL/W	Aluminium	Warm white	3000K	15W	1000lm	50°	100-240V		-	75mm	120mm	30	Complete with 700mA driver





A-A++ 10107P/W/W

10107P | 7W | COB LED | Die cast

LED BUILT IN · 80 CRI · DIMMABLE · QUICK FIX · IP64 · CE · 2 YEAR



10107P/W/C





A-A++ 10112P/W/W

10112P | 12W | COB LED | Die cast

LED BUILT IN · 80 CRI · DIMMABLE · QUICK FIX · IP64 · CE · 2 YEAR



10112P/B/W





A-A++ 10112P/AL/W

10112P | 12W | COB LED | Natural aluminium

LED BUILT IN · 80 CRI · DIMMABLE · QUICK FIX · IP64 · CE · 2 YEAR





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
10107P/W/W	White	Warm white	3000K	7W	630lm	40°	700mA	III	40cm	70mm	105mm	50	Requires 700mA driver
10112P/W/C	White	Warm white	3000K	12W	1100lm	40°	700mA	III	40cm	70mm	105mm	50	Requires 700mA driver
10112P/W/W	White	Cool white	4000K	12W	1100lm	40°	700mA	III	40cm	70mm	105mm	50	Requires 700mA driver
10112P/B/W	Black	Warm white	3000K	12W	1100lm	40°	700mA	III	40cm	70mm	105mm	50	Requires 700mA driver
10112P/AL/W	Aluminium	Warm white	3000K	12W	1100lm	40°	700mA	III	40cm	70mm	105mm	50	Requires 700mA driver
10112P/MC/W	Brushed chrome	Warm white	3000K	12W	1100lm	40°	700mA	III	40cm	70mm	105mm	50	Requires 700mA driver



The IP65 Bathroom Range



A-A++ 10103P/W/W

10103P | 1W/3W | COB LED | Aluminium

1W@350mA / 3W@700mA

LED BUILT IN · 80 CRI · DIMMABLE · QUICK FIX · IP65 · CE · 2 YEAR



10103P/AL/W



Suitable for 89004 driver.





A-A++ 10103P/B/W

10103P | 1W/3W | COB LED | Aluminium

1W@350mA / 3W@700mA

LED BUILT IN · 80 CRI · DIMMABLE · QUICK FIX · IP65 · CE · 2 YEAR



10103P/AL/W



Suitable for 89004 driver.





A-A++ 10103NP/AL/W/35

10103NP | 3x1W | LED | Natural aluminium

LED BUILT IN · DIMMABLE · QUICK FIX · CE · IP65 · 2 YEAR · offer



10103NP/AL/D/35



Suitable for 89004 driver.





A-A++ 10106P/W/W

10106P | 6W | SMD 2835 | Plastic

LED BUILT IN · 80 CRI · CE · 2 YEAR · IP65



10106P/W/C





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
10103P/W/C	White	Cool white	4000K	1W/3W	200lm@3W	30°	350mA/700mA	III	60cm	37mm	60mm	100	Requires 350mA/700mA driver
10103P/W/W	White	Warm white	3000K	1W/3W	190lm@3W	30°	350mA/700mA	III	60cm	37mm	60mm	100	Requires 350mA/700mA driver
10103P/B/W	Black	Warm white	3000K	1W/3W	190lm@3W	30°	350mA/700mA	III	60cm	37mm	60mm	100	Requires 350mA/700mA driver
10103P/B/BL	Black	Blue	-	1W/3W	-	60°	350mA/700mA	III	60cm	37mm	60mm	100	Requires 350mA/700mA driver
10103P/AL/D	Aluminium	Daylight	6000K	1W/3W	210lm@3W	30°	350mA/700mA	III	60cm	37mm	60mm	100	Requires 350mA/700mA driver
10103P/AL/C	Aluminium	Cool white	4000K	1W/3W	200lm@3W	30°	350mA/700mA	III	60cm	37mm	60mm	100	Requires 350mA/700mA driver
10103P/AL/W	Aluminium	Warm white	3000K	1W/3W	190lm@3W	30°	350mA/700mA	III	60cm	37mm	60mm	100	Requires 350mA/700mA driver
10103NP/AL/D/35	Aluminium	Daylight	6000K	3x1W	180lm	35°	350mA	III	200cm	70mm	70mm	50	Requires 350mA driver
10103NP/AL/W/35	Aluminium	Warm white	3000K	3x1W	135lm	35°	350mA	III	200cm	70mm	70mm	50	Requires 350mA driver
10106P/W/C	White	Cool white	4000K	6W	440lm	100°	230V		-	68mm	80mm	48	Complete with driver
10106P/W/W	White	Warm white	3000K	6W	415lm	100°	230V		-	68mm	80mm	48	Complete with driver



The Dark Light IP65 Range

Aluminium



A-A++ 10102H/W/W

10102H | 2W | LED | Aluminium

LED BUILT IN · 85 CRI · DIMMABLE · QUICK FIX · DARK LIGHT · IP65 · CE · 3 YEAR







A-A++ 10102H/B/W

10102H | 2W | LED | Aluminium

LED BUILT IN · 85 CRI · DIMMABLE · QUICK FIX · DARK LIGHT · IP65 · CE · 3 YEAR







A-A++

10107H | 7W | COB LED | Aluminium

LED BUILT IN · 90 CRI · DIMMABLE · CE · DARK LIGHT · IP65 · 3 YEAR





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
10102H/W/C	White	Cool white	4000K	2W	100lm	30°	700mA	III	100cm	30mm	50mm	100	Requires 700mA driver
10102H/W/W	White	Warm white	3000K	2W	100lm	30°	700mA	III	100cm	30mm	50mm	100	Requires 700mA driver
10102H/B/W	Black	Warm white	3000K	2W	100lm	30°	700mA	III	100cm	30mm	50mm	100	Requires 700mA driver
10107H/W/C	White	Cool white	4000K	7W	530lm	36°	700mA	III	40cm	60mm	90mm	60	Requires 700mA driver
10107H/W/W	White	Warm white	3000K	7W	500lm	36°	700mA	III	40cm	60mm	90mm	60	Requires 700mA driver



The Fire Rated IP65 Range



A-A++

10106PF | 6W | COB LED | Fire Rated | Die cast

Ring must be ordered separately.

LED BUILT IN

80 CRI

DIMMABLE

QUICK FIX

IP65

FIRE RATED

3 YEAR



Dimensions are complete with the ring.





050042/W White



050042/B Black



050042/C Chrome



050042A/C Chrome

Order Code	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
10106PF/C	Cool white	4000K	6W	530lm	40°	350mA	III	40cm	68mm	90mm	20	Requires 350mA driver
10106PF/W	Warm white	3000K	6W	500lm	40°	350mA	III	40cm	68mm	90mm	20	Requires 350mA driver





A-A++ 50102B/W/W

50102B | 2W | LED | Die cast

new IP20 | LED BUILT IN | 80 CRI | DIMMABLE | QUICK FIX | CE | 3 YEAR







A-A++ 50102B/B/W

50102B | 2W | LED | Die cast

new IP20 | LED BUILT IN | 80 CRI | DIMMABLE | QUICK FIX | CE | 3 YEAR







A-A++ 50202B/W/W

50202B | 2x2W | LED | Die cast

new IP20 | LED BUILT IN | 80 CRI | DIMMABLE | QUICK FIX | CE | 3 YEAR







A-A++ 50202B/B/W

50202B | 2x2W | LED | Die cast

new IP20 | LED BUILT IN | 80 CRI | DIMMABLE | QUICK FIX | CE | 3 YEAR





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
50102B/W/W	White	Warm white	3000K	2W	160lm	30°	700mA	III	30cm	36x36mm	60mm	100	Use 89004A driver
50102B/B/W	Black	Warm white	3000K	2W	160lm	30°	700mA	III	30cm	36x36mm	60mm	100	Use 89004A driver
50202B/W/W	White	Warm white	3000K	2x2W	2x160lm	30°	700mA	III	30cm	66x36mm	60mm	60	Use 89008A driver
50202B/B/W	Black	Warm white	3000K	2x2W	2x160lm	30°	700mA	III	30cm	66x36mm	60mm	60	Use 89008A driver



Shop Square Boxes

50302B | 3x2W | LED | Die cast



A-A++ 50302B/W/W

new

IP20

LED BUILT IN

80 CRI

DIMMABLE

QUICK FIX

3 YEAR



50302B/B/W



50502B | 5x2W | LED | Die cast



A-A++ 50502B/W/W

new

IP20

LED BUILT IN

80 CRI

DIMMABLE

QUICK FIX

3 YEAR



50502B/B/W



50902B | 10x2W | LED | Die cast



A-A++ 50902B/W/W

new

IP20

LED BUILT IN

80 CRI

DIMMABLE

QUICK FIX

3 YEAR



50902B/B/W



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
50302B/W/W	White	Warm white	3000K	3x2W	3x160lm	30°	700mA	III	30cm	97x36mm	60mm	50	Use 89008A driver
50302B/B/W	Black	Warm white	3000K	3x2W	3x160lm	30°	700mA	III	30cm	97x36mm	60mm	50	Use 89008A driver
50502B/W/W	White	Warm white	3000K	5x2W	5x160lm	30°	700mA	III	30cm	137x36mm	60mm	30	Use 89015A driver
50502B/B/W	Black	Warm white	3000K	5x2W	5x160lm	30°	700mA	III	30cm	137x36mm	60mm	30	Use 89015A driver
50902B/W/W	White	Warm white	3000K	10x2W	10x160lm	30°	700mA	III	30cm	272x36mm	60mm	20	Use 89030A driver
50902B/B/W	Black	Warm white	3000K	10x2W	10x160lm	30°	700mA	III	30cm	272x36mm	60mm	20	Use 89030A driver



Shop Square Boxes

Aluminium + steel



A-A++

50107B | 6,5W | COB LED | Aluminium + steel

LED BUILT IN · 90 CRI · DIMMABLE · QUICK FIX · IP20 · CE · 3 YEAR







A-A++

50207B | 2x6,5W | COB LED | Aluminium + steel

LED BUILT IN · 90 CRI · DIMMABLE · QUICK FIX · IP20 · CE · 3 YEAR







A-A++

50307B | 3x6,5W | COB LED | Aluminium + steel

LED BUILT IN · 90 CRI · DIMMABLE · QUICK FIX · IP20 · CE · 3 YEAR







A-A++

50507B | 5x6,5W | COB LED | Aluminium + steel

LED BUILT IN · 90 CRI · DIMMABLE · QUICK FIX · IP20 · CE · 3 YEAR





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
50107B/W/W	White	Warm white	3000K	6,5W	550lm	36°	350mA		40cm	57x57mm	90mm	60	Use 89008 driver
50207B/W/W	White	Warm white	3000K	2x6,5W	2x550lm	36°	350mA		40cm	108x57mm	90mm	36	Use 89015 driver
50307B/W/W	White	Warm white	3000K	3x6,5W	3x550lm	36°	350mA		40cm	150x57mm	90mm	24	Use 89020 driver
50507B/W/W	White	Warm white	3000K	5x6,5W	5x550lm	36°	350mA		40cm	240x57mm	90mm	16	Use 1x89015 & 1x89020 drivers



The Cement Look Recessed

Cement + black reflector



10104M | 4,5W | COB LED | Cement + black reflector

LED BUILT IN
90 CRI
3 YEAR
DARK LIGHT
IP20







50104M | 4,5W | COB LED | Cement + black reflector

LED BUILT IN
90 CRI
3 YEAR
DARK LIGHT
IP20





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
10104M/W	Cement	Warm white	3000K	4,5W	350lm	40°	100-240V	☐	72mm	70mm	18	Complete with 350mA driver
50104M/W	Cement	Warm white	3000K	4,5W	350lm	40°	100-240V	☐	72mm	70mm	18	Complete with 350mA driver



LED Decorative Range



A-A++

10107C | 7W | COB LED | Ambient colour light | Die cast

LED BUILT IN
80 CRI
DIMMABLE
QUICK FIX
IP20
CE
2 YEAR



Interchangeable rings.





A-A++

10107R | 5W | SMD 3030 | Aluminium

LED BUILT IN
80 CRI
QUICK FIX
CE
DARK LIGHT
2 YEAR
IP20







A-A++

10103GL | 3x1W | LED | Aluminium + acrylic

LED BUILT IN
DIMMABLE
QUICK FIX
CE
IP20
offer
2 YEAR





Suitable for 89004 driver.





A-A++ Warm white + Daylight

10103A | 3x1W + 18 SMD LED Ring | LED | Natural aluminium + PC

Colours can be switched separately.

LED BUILT IN
DIMMABLE
QUICK FIX
CE
IP42
offer
2 YEAR



Daylight + Blue



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class	S				Notes
10107C/W/W	White	Warm white	3000K	7W	635lm	40°	700mA		40cm	88mm	90mm	64	Requires 700mA driver
10107R/W/W	White	Warm white	3000K	5W	270lm	-	100-240V		-	95mm	60mm	30	Complete with 350mA driver
10103GL/D	-	Daylight	6000K	3x1W	180lm	-	350mA		40cm	55mm	50mm	36	Requires 350mA driver
10103GL/W	-	Warm white	3000K	3x1W	135lm	-	350mA		40cm	55mm	50mm	36	Requires 350mA driver
10103A/D/BL	Aluminium	Daylight + Blue	6000K	3/1,8W	-	-	350mA		40cm	77mm	50mm	100	Requires 2x350mA drivers
10103A/W/D	Aluminium	Warm white + Daylight	3000K+6000K	3/1,8W	-	-	350mA		40cm	77mm	50mm	100	Requires 2x350mA drivers



The LED Glass Range



10101G | 1W | LED | Acrylic

IP20 offer

LED BUILT IN · DIMMABLE · QUICK FIX · CE · 3 YEAR





Suitable for 89004 driver.





10103G | 3W | LED | Acrylic

IP20 offer

LED BUILT IN · DIMMABLE · QUICK FIX · CE · 3 YEAR





Suitable for 89004 driver.





10106G | 6W | LED | Acrylic

IP20 offer

LED BUILT IN · DIMMABLE · QUICK FIX · CE · 3 YEAR





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class	S				Notes
10101G/D	Clear	Daylight	6000K	1W	60lm	350mA		40cm	40mm	45mm	80	Requires 350mA driver
10103G/D	Clear	Daylight	6000K	3W	145lm	350mA		40cm	66mm	50mm	64	Requires 350mA driver
10103G/W	Clear	Warm white	3000K	3W	100lm	350mA		40cm	66mm	50mm	64	Requires 350mA driver
10106G/D	Clear	Daylight	6000K	6W	295lm	350mA		40cm	100mm	60mm	32	Requires 350mA driver
10106G/W	Clear	Warm white	3000K	6W	205lm	350mA		40cm	100mm	60mm	32	Requires 350mA driver



10101C/C/D



50101/AL/D

LED Spots



A-A++

10101C | 1W | LED | Cabinet light | Steel

LED BUILT IN

IP20

offer







A-A++ 50101/AL/D

50101 | 9x0,2W | LED | Natural aluminium

LED BUILT IN

IP20

offer



offer 50101/AL/BL



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
10101C/C/D	Chrome	Daylight	6000K	1W	50lm	90°	12V AC		30cm	50mm	25mm	100	Requires 12V AC transformer
50101/AL/D	Aluminium	Daylight	6000K	9x0,2W	60lm	90°	230V		-	60mm	40mm	50	Complete with driver
50101/AL/BL	Aluminium	Blue	-	9x0,2W	-	90°	230V		-	60mm	40mm	50	Complete with driver



50103GT4/W



10107BT/W/W



10107BT/B/W

The Trimless Range



A-A++ 10107BT/W/W

10107BT | 7W | COB LED | Trimless | Die cast

LED BUILT IN
80 CRI
DIMMABLE
QUICK FIX
DARK LIGHT
IP54
3 YEAR







A-A++ 10107BT/B/W

10107BT | 7W | COB LED | Trimless | Die cast

new
LED BUILT IN
80 CRI
DIMMABLE
QUICK FIX
DARK LIGHT
IP54
3 YEAR







A-A++

50103GT4 | 2,5W | SMD LED | Trimless | Gypsum

LED BUILT IN
80 CRI
DARK LIGHT
IP44
2 YEAR





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
10107BT/W/W	White	Warm white	3000K	7W	500lm	38°	700mA	III	40cm	83mm	90mm	30	Requires 700mA driver
10107BT/B/W	Black	Warm white	3000K	7W	500lm	38°	700mA	III	40cm	83mm	90mm	30	Requires 700mA driver
50103GT4/W	White	Warm white	3000K	2,5W	15lm	-	100-240V		-	121x121mm	70mm	24	Complete with 700mA driver



The Trimless Mini Range

Aluminium



10101TR | 1W | COB LED | Trimless | Aluminium

Driver can not pass through the cutout hole.





Suitable for 89004 driver.





10103TR | 3W | COB LED | Trimless | Aluminium

Driver 89004 can pass through the cutout hole.





Suitable for 89004 driver.



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
10101TR/W/W	White	Warm white	3000K	1W	90lm	45°	350mA	III	200cm	40mm	50mm	40	Requires 350mA driver
10103TR/W/W	White	Warm white	3000K	3W	250lm	36°	350mA	III	40cm	50mm	50mm	60	Requires 350mA driver 89004



The Trimless Mini Range

Aluminium



A-A++ 10103BTR/W/W

10103BTR | 3W | COB LED | Aluminium

LED BUILT IN · 90 CRI · DIMMABLE · QUICK FIX · DARK LIGHT · IP20 · CE · 3 YEAR





Suitable for 89004 driver.





A-A++ 10103BTR/B/W

10103BTR | 3W | COB LED | Aluminium

LED BUILT IN · 90 CRI · DIMMABLE · QUICK FIX · DARK LIGHT · IP20 · CE · 3 YEAR





Suitable for 89004 driver.





A-A++ 10103BTR/BS/W

10103BTR | 3W | COB LED | Aluminium

LED BUILT IN · 90 CRI · DIMMABLE · QUICK FIX · DARK LIGHT · IP20 · CE · 3 YEAR





Suitable for 89004 driver.



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
10103BTR/W/W	White	Warm white	3000K	3W	240lm	36°	350mA	III	40cm	40mm	80mm	100	Requires 350mA driver
10103BTR/B/W	Black	Warm white	3000K	3W	240lm	36°	350mA	III	40cm	40mm	80mm	100	Requires 350mA driver
10103BTR/BS/W	Brass	Warm white	3000K	3W	240lm	36°	350mA	III	40cm	40mm	80mm	100	Requires 350mA driver





03

Recessed Spots Adjustable

Pages 71-100

MR11 | MR16 | GU4 | GU5,3 | GU10

Die cast | Natural aluminium | Steel | Gypsum | Cement | Trimless

IP20

ADJUSTABLE ADJUSTABLE DARK LIGHT 5 YEAR





The Classic Adjustable Round



11103A | 35W | MR11 | GU4 | Die cast





11105 | 50W | MR16 | GU5,3 | Die cast



Order Code	Colour	Watts	Input	Class					Notes
11103A/MC	Brushed chrome	35W	12V		40cm	57mm	35mm	100	-
11105/C	Chrome	50W	12V		40cm	75mm	55mm	100	-
11105/MC	Brushed chrome	50W	12V		40cm	75mm	55mm	100	-
11105/BS	Brass	50W	12V		40cm	75mm	55mm	100	-



11105GU | 50W | MR16 | GU10 | Die cast



E-A++ 11105GU/G



Complete with 0950G.





11105GU/W



11105GU/B



11105GU/C



11105GU/MC

Order Code	Colour	Watts	Input	Class					Notes
11105GU/W	White	50W	100-240V		15cm	75mm	95mm	100	-
11105GU/B	Black	50W	100-240V		15cm	75mm	95mm	100	-
11105GU/G	Grey	50W	100-240V		15cm	75mm	95mm	100	-
11105GU/C	Chrome	50W	100-240V		15cm	75mm	95mm	100	-
11105GU/MC	Brushed chrome	50W	100-240V		15cm	75mm	95mm	100	-



The Lock Ring Range

Die cast

11103C | 35W | MR11 | GU4 | Die cast



E-A++

ADJUSTABLE

IP20

5 YEAR

offer



Suitable for MR11 LED lamp.



11105C | 50W | MR16 | GU5,3 | Die cast



E-A++ 11105C/W

ADJUSTABLE

IP20

5 YEAR







11105C/G



11105C/MC



offer

11105C/ABS



offer

11105C/N

11105CF | 35W | MR16 | GU10 | Firehood | Die cast



E-A++ 11105CF/W

ADJUSTABLE

IP20

5 YEAR



11105CF/MC





Order Code	Colour	Watts	Input	Class					Notes
11103C/C	Chrome	35W	12V	III	40cm	63mm	40mm	100	-
11105C/W	White	50W	12V	III	40cm	82mm	60mm	100	-
11105C/G	Grey	50W	12V	III	40cm	82mm	60mm	100	-
11105C/N	Natural	50W	12V	III	40cm	82mm	60mm	100	-
11105C/MC	Brushed chrome	50W	12V	III	40cm	82mm	60mm	100	-
11105C/ABS	Antique brass	50W	12V	III	40cm	82mm	60mm	100	-
11105CF/W	White	35W	100-240V	I	-	87mm	180mm	50	-
11105CF/MC	Brushed chrome	35W	100-240V	I	-	87mm	180mm	50	-



The Lock Ring GU10 Range

Die cast



E-A++ 11105CGU/W

11105CGU | 50W | MR16 | GU10 | Die cast





IP20



Complete with 0950G.





11105CGU/G



11105CGU/C



11105CGU/MC



E-A++ 51105CGU/W

51105CGU | 50W | MR16 | GU10 | Die cast





IP20



51105CGU/MC



Complete with 0950G.



Order Code	Colour	Watts	Input	Class					Notes
11105CGU/W	White	50W	100-240V		15cm	82mm	95mm	100	-
11105CGU/G	Grey	50W	100-240V		15cm	82mm	95mm	100	-
11105CGU/C	Chrome	50W	100-240V		15cm	82mm	95mm	100	-
11105CGU/MC	Brushed chrome	50W	100-240V		15cm	82mm	95mm	100	-
51105CGU/W	White	50W	100-240V		15cm	78mm	100mm	100	-
51105CGU/MC	Brushed chrome	50W	100-240V		15cm	78mm	100mm	100	-





E-A++

11105CD | 50W | MR16 | GU5,3 | Die cast

ADJUSTABLE

DARK LIGHT

IP20







E-A++

51105CD | 50W | MR16 | GU5,3 | Die cast

ADJUSTABLE

DARK LIGHT

IP20





Order Code	Colour	Watts	Input	Class					Notes
11105CD/MC	Brushed chrome	50W	12V	III	40cm	85mm	100mm	50	-
51105CD/MC	Brushed chrome	50W	12V	III	40cm	85mm	100mm	50	-



Box Set

Die cast



E-A++

11105GU3 | 4W (x3) | MR16 | GU10 | Die cast

Set of 3pcs.

ADJUSTABLE

IP20

Includes 3pcs
GU10 LED lamps.



3000K 38° 320lm.







Order Code	Colour	Watts	Input	Class					Notes
11105GU3/MC/W	Brushed chrome	4W (x3)	230V	⏚	15cm	75mm	95mm	20	Complete with 7304BG/W/38 lamps



The Classic Square

Die cast



E-A++

51103 | 35W | MR11 | GU4 | Die cast



ADJUSTABLE

5 YEAR

IP20

offer

Suitable for MR11 LED lamp.





E-A++ 51105/W

51105 | 50W | MR16 | GU5,3 | Die cast



ADJUSTABLE

5 YEAR

IP20





E-A++ 51105/C

51105 | 50W | MR16 | GU5,3 | Die cast



ADJUSTABLE

5 YEAR

IP20

51105/MC



Order Code	Colour	Watts	Input	Class					Notes
51103/MC	Brushed chrome	35W	12V		40cm	56mm	45mm	100	-
51105/W	White	50W	12V		40cm	75mm	65mm	100	-
51105/C	Chrome	50W	12V		40cm	75mm	65mm	100	-
51105/MC	Brushed chrome	50W	12V		40cm	75mm	65mm	100	-



The Classic Square GU10

Die cast



E-A++ 51105GU/W

51105GU | 50W | MR16 | GU10 | Die cast

ADJUSTABLE

5 YEAR

IP20



Complete with 0950G.





E-A++ 51105GU/MC

51105GU | 50W | MR16 | GU10 | Die cast

ADJUSTABLE

5 YEAR

IP20



Complete with 0950G.





E-A++ 51105GA/W

51105GA | 50W | MR16 | GU10 | Die cast

ADJUSTABLE

5 YEAR

IP20

offer



Supplied with GU10 50W halogen lamp.





E-A++ 51105GA/MC

51105GA | 50W | MR16 | GU10 | Die cast

ADJUSTABLE

5 YEAR

IP20

offer



Supplied with GU10 50W halogen lamp.



Order Code	Colour	Watts	Input	Class					Notes
51105GU/W	White	50W	100-240V		15cm	73mm	100mm	100	-
51105GU/MC	Brushed chrome	50W	100-240V		15cm	73mm	100mm	100	-
51105GA/W	White	50W	230V		15cm	73mm	100mm	50	Supplied with GU10 lamp
51105GA/MC	Brushed chrome	50W	230V		15cm	73mm	100mm	50	Supplied with GU10 lamp

The Dual Ring Range
Aluminium

51105AB | 50W | MR16 | GU5,3 | Aluminium







Order Code	Colour	Watts	Input	Class					Notes
51105AB/AL	Aluminium	50W	12V	III	40cm	80mm	75mm	50	-



The Dual Ring GU10 Range

Aluminium



E-A++ 11105ABG/W

11105ABG | 50W | MR16 | GU10 | Aluminium

ADJUSTABLE

5 YEAR

IP20



11105ABG/AL



Complete with 0950GB.





E-A++ 51105ABG/W

51105ABG | 50W | MR16 | GU10 | Aluminium

ADJUSTABLE

5 YEAR

IP20



51105ABG/AL



Complete with 0950GB.





E-A++ 51205ABG/W

51205ABG | 2x50W | MR16 | GU10 | Aluminium

ADJUSTABLE

5 YEAR

IP20



51205ABG/AL



Complete with 0950GB.



Order Code	Colour	Watts	Input	Class					Notes
11105ABG/W	White	50W	100-240V		15cm	80mm	100mm	50	-
11105ABG/AL	Aluminium	50W	100-240V		15cm	80mm	100mm	50	-
51105ABG/W	White	50W	100-240V		15cm	80mm	100mm	50	-
51105ABG/AL	Aluminium	50W	100-240V		15cm	80mm	100mm	50	-
51205ABG/W	White	2x50W	100-240V		15cm	162x82mm	100mm	20	-
51205ABG/AL	Aluminium	2x50W	100-240V		15cm	162x82mm	100mm	20	-



The Dual Ring Range
Aluminium



E-A++ 11105ABGL/W

11105ABGL | 50W | MR16 | GU10 | Aluminium



ADJUSTABLE

5 YEAR

IP20

Leaf springs.



Complete with 0950G.





E-A++ 11105ABGL/B

11105ABGL | 50W | MR16 | GU10 | Aluminium



ADJUSTABLE

5 YEAR

IP20

Leaf springs.



Complete with 0950G.



Order Code	Colour	Watts	Input	Class					Notes
11105ABGL/W	White	50W	100-240V		15cm	80mm	100mm	50	-
11105ABGL/B	Black	50W	100-240V		15cm	80mm	100mm	50	-



11105AC/AL



11105AL/AL



51103AB/AL

The Dual Ring Range

Natural aluminium



E-A++

11105AL | 50W | MR16 | GU5,3 | Natural aluminium

ADJUSTABLE

5 YEAR

IP20



Leaf springs.





E-A++

11105AC | 50W | MR16 | GU5,3 | Natural aluminium

ADJUSTABLE

5 YEAR

IP20







E-A++

51103AB | 35W | MR11 | GU4 | Natural aluminium

ADJUSTABLE

5 YEAR

IP20



Suitable for MR11 LED lamp.



Order Code	Colour	Watts	Input	Class					Notes
11105AL/AL	Aluminium	50W	12V	III	40cm	68mm	70mm	50	-
11105AC/AL	Aluminium	50W	12V	III	40cm	75mm	60mm	50	-
51103AB/AL	Aluminium	35W	12V	III	40cm	60mm	60mm	50	-



Round Retro Range GU10

Aluminium



11105U | 50W | MR16 | GU10 | Aluminium





11105UA | 50W | MR16 | GU10 | Aluminium





11105UB | 50W | MR16 | GU10 | Aluminium



Order Code	Colour	Watts	Input	Class					Notes
11105U/W	White	50W	100-240V		15cm	72mm	120mm	50	-
11105UA/W	White	50W	100-240V		15cm	72mm	120mm	50	-
11105UB/W	White	50W	100-240V		15cm	72mm	120mm	50	-



Square Retro Range GU10
Aluminium



E-A++

51105U | 50W | MR16 | GU10 | Aluminium

ADJUSTABLE

5 YEAR

IP20







E-A++

51105UA | 50W | MR16 | GU10 | Aluminium

ADJUSTABLE

5 YEAR

IP20





Order Code	Colour	Watts	Input	Class					Notes
51105U/W	White	50W	100-240V	⏚	15cm	72mm	120mm	50	-
51105UA/W	White	50W	100-240V	⏚	15cm	72mm	120mm	50	-

Dark Light Round Spots



E-A++

11105D4 | 50W | MR16 | GU10 | Aluminium

ADJUSTABLE

DARK LIGHT

5 YEAR

IP20



Complete with 0950G.





E-A++

11105DT | 50W | MR16 | GU10 | Aluminium

ADJUSTABLE

DARK LIGHT

5 YEAR

IP20



Complete with 0950G.





E-A++

11105TG | 50W | MR16 | GU10 | Die cast

ADJUSTABLE

DARK LIGHT

5 YEAR

IP20



Complete with 0950G.





E-A++

11105CDG | 50W | MR16 | GU10 | Die cast

ADJUSTABLE

DARK LIGHT

5 YEAR

IP20



Complete with 0950G.





E-A++

11105E | 50W | MR16 | GU10 | Die cast

ADJUSTABLE

DARK LIGHT

5 YEAR

IP20



Complete with 0950G.



Order Code	Colour	Watts	Input	Class					Notes
11105D4/W	White	50W	100-240V		15cm	75mm	140mm	50	-
11105DT/W	White	50W	100-240V		15cm	95mm	140mm	50	-
11105TG/W	White	50W	100-240V		15cm	85mm	110mm	50	-
11105CDG/W	White	50W	100-240V		15cm	90mm	110mm	50	-
11105E/W	White	50W	100-240V		15cm	75mm	120mm	100	-



Dark Light Square Spots

Die cast



51105TG | 50W | MR16 | GU10 | Die cast

ADJUSTABLE
DARK LIGHT
IP20
5 YEAR



Complete with 0950G.





51105CDG | 50W | MR16 | GU10 | Die cast

ADJUSTABLE
DARK LIGHT
IP20
5 YEAR



Complete with 0950G.





51105DG | 50W | MR16 | GU10 | Die cast

ADJUSTABLE
DARK LIGHT
IP20
5 YEAR



Complete with 0950G.





51105D | 50W | MR16 | GU5,3 | Die cast

ADJUSTABLE
DARK LIGHT
IP20
5 YEAR





Order Code	Colour	Watts	Input	Class					Notes
51105TG/W	White	50W	100-240V		15cm	80x80mm	110mm	50	-
51105CDG/W	White	50W	100-240V		15cm	90mm	110mm	50	-
51105DG/W	White	50W	100-240V		15cm	80x80mm	85mm	50	-
51105D/G	Grey	50W	12V		40cm	80x80mm	85mm	50	-

Dark Light Round

Metal



E-A++

11105TA | 50W | MR16 | GU10 | Metal



DARK LIGHT

IP20



Complete with 0950G.



Order Code	Colour	Watts	Input	Class					Notes
11105TA/W	White	50W	100-240V	⏚	15cm	80mm	130mm	36	-



Dark Light Square

Metal



E-A++ 51105TA/W

51105TA | 50W | MR16 | GU10 | Metal

ADJUSTABLE

5 YEAR

DARK LIGHT

IP20



Complete with 0950G.





E-A++ 51105TA/B

51105TA | 50W | MR16 | GU10 | Metal

ADJUSTABLE

5 YEAR

DARK LIGHT

IP20



Complete with 0950G.





E-A++ 51105TA/G

51105TA | 50W | MR16 | GU10 | Metal

ADJUSTABLE

5 YEAR

DARK LIGHT

IP20



Complete with 0950G.



Order Code	Colour	Watts	Input	Class					Notes
51105TA/W	White	50W	100-240V		15cm	80x80mm	150mm	36	-
51105TA/B	Black	50W	100-240V		15cm	80x80mm	150mm	36	-
51105TA/G	Grey	50W	100-240V		15cm	80x80mm	150mm	36	-



The Chill Out Range



A-A++ 11105M/W/W

11105M | 10W | MR16 | GU10 | Aluminium body + plastic reflector

ADJUSTABLE

5 YEAR

DARK LIGHT

IP20



Complete with 0950GB.





A-A++ 11105M/W/B

11105M | 10W | MR16 | GU10 | Aluminium body + plastic reflector

ADJUSTABLE

5 YEAR

DARK LIGHT

IP20



Complete with 0950GB.





A-A++ 11105M/W/BS

11105M | 10W | MR16 | GU10 | Aluminium body + plastic reflector

ADJUSTABLE

5 YEAR

DARK LIGHT

IP20



Complete with 0950GB.





A-A++ 11105M/W/CU

11105M | 10W | MR16 | GU10 | Aluminium body + plastic reflector

ADJUSTABLE

5 YEAR

DARK LIGHT

IP20



Complete with 0950GB.



Order Code	Colour	Reflector	Watts	Input	Class					Notes
11105M/W/W	White	White	10W	100-240V		15cm	70mm	120mm	50	-
11105M/W/B	White	Black	10W	100-240V		15cm	70mm	120mm	50	-
11105M/W/BS	White	Brass	10W	100-240V		15cm	70mm	120mm	50	-
11105M/W/CU	White	Copper	10W	100-240V		15cm	70mm	120mm	50	-



The Chill Out Range



A-A++ 11105M/B/B

11105M | 10W | MR16 | GU10 | Aluminium body + plastic reflector





Complete with 0950GB.





A-A++ 11105M/B/BS

11105M | 10W | MR16 | GU10 | Aluminium body + plastic reflector





Complete with 0950GB.





A-A++ 11105M/B/CU

11105M | 10W | MR16 | GU10 | Aluminium body + plastic reflector





Complete with 0950GB.



Order Code	Colour	Reflector	Watts	Input	Class					Notes
11105M/B/B	Black	Black	10W	100-240V		15cm	70mm	120mm	50	-
11105M/B/BS	Black	Brass	10W	100-240V		15cm	70mm	120mm	50	-
11105M/B/CU	Black	Copper	10W	100-240V		15cm	70mm	120mm	50	-



The Round Clip In Range

Aluminium



E-A++ 11105A1/W

11105A1 | 50W | MR16 | GU10 | Aluminium

ADJUSTABLE

5 YEAR

IP20



11105A1/AL



11105A1/B





E-A++ 11105B1/W

11105B1 | 50W | MR16 | GU10 | Aluminium

ADJUSTABLE

5 YEAR

IP20



11105B1/AL.



Complete with 0950G.





E-A++

11105D7 | 50W | MR16 | GU10 | Aluminium

ADJUSTABLE

5 YEAR

IP20





Complete with 0950G.



Order Code	Colour	Watts	Input	Class					Notes
11105A1/W	White	50W	100-240V		15cm	68mm	120mm	100	-
11105A1/B	Black	50W	100-240V		15cm	68mm	120mm	100	-
11105A1/AL	Aluminium	50W	100-240V		15cm	68mm	120mm	100	-
11105B1/W	White	50W	100-240V		15cm	72mm	120mm	100	-
11105B1/AL	Aluminium	50W	100-240V		15cm	72mm	120mm	100	-
11105D7/W	White	50W	100-240V		15cm	82mm	130mm	50	-





E-A++ 51105B1/W

51105B1 | 50W | MR16 | GU10 | Aluminium

ADJUSTABLE

5 YEAR

IP20



51105B1/AL



Complete with 0950G.





E-A++

51105D7 | 50W | MR16 | GU10 | Aluminium

ADJUSTABLE

5 YEAR

IP20





Complete with 0950G.



Order Code	Colour	Watts	Input	Class					Notes
51105B1/W	White	50W	100-240V	⏚	15cm	72mm	120mm	50	-
51105B1/AL	Aluminium	50W	100-240V	⏚	15cm	72mm	120mm	50	-
51105D7/W	White	50W	100-240V	⏚	15cm	82mm	130mm	50	-



The Dark Light Tube Range

Aluminium



E-A++

11105D5 | 50W | MR16 | GU10 | Aluminium

ADJUSTABLE

5 YEAR

DARK LIGHT

IP20



Complete with 0950G.





E-A++

11105D6 | 50W | MR16 | GU10 | Aluminium

ADJUSTABLE

5 YEAR

DARK LIGHT

IP20



Complete with 0950G.





E-A++

11105D8 | 50W | MR16 | GU10 | Aluminium

ADJUSTABLE

5 YEAR

DARK LIGHT

IP20



Complete with 0950G.





E-A++

51105D5 | 50W | MR16 | GU10 | Aluminium

ADJUSTABLE

5 YEAR

DARK LIGHT

IP20



Complete with 0950G.



Order Code	Colour	Watts	Input	Class					Notes
11105D5/W	White	50W	100-240V		15cm	75mm	130mm	50	-
11105D6/W	White	50W	100-240V		15cm	75mm	130mm	50	-
11105D8/W	White	50W	100-240V		15cm	76mm	130mm	60	-
51105D5/W	White	50W	100-240V		15cm	75mm	130mm	50	-



11105N/W



51205N/W

Semi Dark Light GU10 Series

Die cast



E-A++

11105N | 50W | MR16 | GU10 | Die cast

ADJUSTABLE

5 YEAR

IP20



Complete with 0950G.





E-A++

51105N | 50W | MR16 | GU10 | Die cast

ADJUSTABLE

5 YEAR

IP20



Complete with 0950G.





E-A++

51205N | 2x50W | MR16 | GU10 | Die cast

ADJUSTABLE

5 YEAR

IP20



Complete with 0950G.



Order Code	Colour	Watts	Input	Class					Notes
11105N/W	White	50W	100-240V		15cm	97mm	130mm	50	-
51105N/W	White	50W	100-240V		15cm	97x97mm	130mm	50	-
51205N/W	White	2x50W	100-240V		15cm	187x97mm	130mm	25	-



Natural Aluminium Square



E-A++

51105B | 50W | MR16 | GU5,3 | Natural aluminium

ADJUSTABLE

5 YEAR

IP20







E-A++

51205B | 2x50W | MR16 | GU5,3 | Natural aluminium

ADJUSTABLE

5 YEAR

IP20







E-A++

51305B | 3x50W | MR16 | GU5,3 | Natural aluminium

ADJUSTABLE

5 YEAR

IP20





Order Code	Colour	Watts	Input	Class					Notes
51105B/AL	Aluminium	50W	12V	III	40cm	77x77mm	70mm	50	-
51205B/AL	Aluminium	2x50W	12V	III	40cm	167x77mm	70mm	25	-
51305B/AL	Aluminium	3x50W	12V	III	40cm	252x77mm	70mm	15	-

The 12V Box Square



E-A++

51105R | 50W | MR16 | GU5,3 | Die cast

ADJUSTABLE

5 YEAR

IP20





Order Code	Colour	Watts	Input	Class					Notes
51105R/G	Grey	50W	12V		40cm	95x95mm	120mm	18	-

Square GU10
Die cast

51105F | 50W | MR16 | GU10 | Die cast







Order Code	Colour	Watts	Input	Class					Notes
51105F/G	Grey	50W	100-240V		15cm	115x115mm	145mm	12	-



11105GT5



11105GT4



51105GT4

The Trimless GU10 Range

Gypsum



11105GT5 | 50W | MR16 | GU10 | Trimless | Gypsum









11105GT4 | 50W | MR16 | GU10 | Trimless | Gypsum









51105GT4 | 50W | MR16 | GU10 | Trimless | Gypsum







Order Code	Colour	Watts	Input	Class					Notes
11105GT5	White	50W	100-240V	⏚	15cm	207x207mm	160mm	12	-
11105GT4	White	50W	100-240V	⏚	15cm	156mm	140mm	12	-
51105GT4	White	50W	100-240V	⏚	15cm	156x156mm	140mm	12	-



The Trimless GU10 Range



E-A++

11105UTR | 50W | MR16 | GU10 | Trimless | Die cast

ADJUSTABLE

5 YEAR

DARK LIGHT

IP20







E-A++

11105DTR | 50W | MR16 | GU10 | Trimless | Aluminium

ADJUSTABLE

5 YEAR

DARK LIGHT

IP20







E-A++ 11105TR/W

11105TR | 50W | MR16 | GU10 | Trimless | Die cast

ADJUSTABLE

5 YEAR

DARK LIGHT

IP20



Complete with 0950G.



11105TR/B





E-A++

51105TR | 50W | MR16 | GU10 | Trimless | Die cast

ADJUSTABLE

5 YEAR

DARK LIGHT

IP20



Complete with 0950G.



Order Code	Colour	Watts	Input	Class					Notes
11105UTR/W	White	50W	100-240V		20cm	105mm	120mm	20	-
11105DTR/W	White	50W	100-240V		15cm	90mm	120mm	36	-
11105TR/W	White	50W	100-240V		15cm	82mm	120mm	50	-
11105TR/B	Black	50W	100-240V		15cm	82mm	120mm	50	-
51105TR/W	White	50W	100-240V		15cm	83x83mm	120mm	50	-



Trimless Box

Die cast



51010TR | 50W | MR16 | GU10 | Trimless | Die cast







51020TR | 2x50W | MR16 | GU10 | Trimless | Die cast





Order Code	Colour	Watts	Input	Class				Notes
51010TR/W	White	50W	100-240V		97,5x97,5mm	150mm	16	-
51010TR/B	Black	50W	100-240V		97,5x97,5mm	150mm	16	-
51020TR/W	White	2x50W	100-240V		181x97,5mm	150mm	12	-
51020TR/B	Black	2x50W	100-240V		181x97,5mm	150mm	12	-





04

Recessed Spots Adjustable LED

Pages 103-134

COB LED | SMD LED | LED

Die cast | Natural aluminium | Plastic | Trimless

IP20 IP40 IP44 IP54

ADJUSTABLE ADJUSTABLE DIMMABLE DARK LIGHT QUICK FIX FIRE RATED 80 CRI 85 CRI 90 CRI 2 YEAR 3 YEAR





11103B/AL/W



11103B/B/W



11103B/W/W

The 1W/3W Mini Series

Aluminium



A-A++ 11103B/W/W

11103B | 1W/3W | COB LED | Aluminium — 1W@350mA / 3W@700mA

LED BUILT IN · 80 CRI · DIMMABLE · QUICK FIX · IP20 · ADJUSTABLE · CE · 2 YEAR







A-A++ 11103B/B/W

11103B | 1W/3W | COB LED | Aluminium — 1W@350mA / 3W@700mA

LED BUILT IN · 80 CRI · DIMMABLE · QUICK FIX · IP20 · ADJUSTABLE · CE · 2 YEAR







A-A++ 11103B/AL/W

11103B | 1W/3W | COB LED | Aluminium — 1W@350mA / 3W@700mA

LED BUILT IN · 80 CRI · DIMMABLE · QUICK FIX · IP20 · ADJUSTABLE · CE · 2 YEAR





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
11103B/W/W	White	Warm white	3000K	1W/3W	200lm@3W	40°	350mA/700mA	III	40cm	45mm	60mm	100	Requires 350mA/700mA driver
11103B/B/W	Black	Warm white	3000K	1W/3W	200lm@3W	40°	350mA/700mA	III	40cm	45mm	60mm	100	Requires 350mA/700mA driver
11103B/AL/W	Aluminium	Warm white	3000K	1W/3W	200lm@3W	40°	350mA/700mA	III	40cm	45mm	60mm	100	Requires 350mA/700mA driver



The 1W Mini Lighter

Aluminium



11102 | 1W | LED | Aluminium

LED BUILT IN
85 CRI
DIMMABLE
QUICK FIX
IP20
ADJUSTABLE
2 YEAR





Suitable for 89004 driver.





11101D | 1W | LED | Natural aluminium

LED BUILT IN
DIMMABLE
QUICK FIX
ADJUSTABLE
DARK LIGHT
IP20
2 YEAR





Suitable for 89004 driver.



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
11102/W/W	White	Warm white	3000K	1W	60lm	50°	350mA	III	40cm	45mm	30mm	100	Requires 350mA driver
11101D/D/15	Aluminium	Daylight	6000K	1W	60lm	15°	350mA	III	40cm	53mm	40mm	100	Requires 350mA driver



The 1W Mini Series
Aluminium

11101B | 1W | LED | Aluminium



A-A++

LED BUILT IN · DIMMABLE · QUICK FIX · ADJUSTABLE · IP20 · offer · CE · 2 YEAR





Suitable for 89004 driver.



51101W | 1W | LED | Aluminium



A-A++

LED BUILT IN · DIMMABLE · QUICK FIX · ADJUSTABLE · IP20 · offer · CE · 2 YEAR





Suitable for 89004 driver.



51101B | 1W | LED | Aluminium



A-A++

LED BUILT IN · DIMMABLE · QUICK FIX · ADJUSTABLE · IP20 · offer · CE · 2 YEAR





Suitable for 89004 driver.



51101AL | 1W | LED | Aluminium



A-A++

LED BUILT IN · DIMMABLE · QUICK FIX · ADJUSTABLE · IP20 · offer · CE · 2 YEAR





Suitable for 89004 driver.



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
11101B/D/15	Black	Daylight	6000K	1W	60lm	15°	350mA	III	40cm	45mm	40mm	100	Requires 350mA driver
11101B/D/35	Black	Daylight	6000K	1W	60lm	35°	350mA	III	40cm	45mm	40mm	100	Requires 350mA driver
51101W/D/35	White	Daylight	6000K	1W	60lm	35°	350mA	III	40cm	53mm	40mm	100	Requires 350mA driver
51101B/D/35	Black	Daylight	6000K	1W	60lm	35°	350mA	III	40cm	53mm	40mm	100	Requires 350mA driver
51101AL/D/15	Aluminium	Daylight	6000K	1W	60lm	15°	350mA	III	40cm	53mm	40mm	100	Requires 350mA driver
51101AL/W/15	Aluminium	Warm white	3000K	1W	45lm	15°	350mA	III	40cm	53mm	40mm	100	Requires 350mA driver
51101AL/BL/15	Aluminium	Blue	-	1W	-	15°	350mA	III	40cm	53mm	40mm	100	Requires 350mA driver



The 1W Mini Square

Natural aluminium



A-A++

51201AL | 2x1W | LED | Natural aluminium

LED BUILT IN
DIMMABLE
QUICK FIX
ADJUSTABLE
IP20
offer
2 YEAR







A-A++

51301AL | 3x1W | LED | Natural aluminium

LED BUILT IN
DIMMABLE
QUICK FIX
ADJUSTABLE
IP20
offer
2 YEAR







A-A++

51401AL | 4x1W | LED | Natural aluminium

LED BUILT IN
DIMMABLE
QUICK FIX
ADJUSTABLE
IP20
offer
2 YEAR





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
51201AL/D/15	Aluminium	Daylight	6000K	2x1W	2x60lm	15°	350mA		40cm	105x53mm	40mm	50	Requires 350mA driver
51201AL/D/35	Aluminium	Daylight	6000K	2x1W	2x60lm	35°	350mA		40cm	105x53mm	40mm	50	Requires 350mA driver
51301AL/D/15	Aluminium	Daylight	6000K	3x1W	3x60lm	15°	350mA		40cm	155x53mm	40mm	50	Requires 350mA driver
51301AL/D/35	Aluminium	Daylight	6000K	3x1W	3x60lm	35°	350mA		40cm	155x53mm	40mm	50	Requires 350mA driver
51301AL/W/15	Aluminium	Warm white	3000K	3x1W	3x45lm	15°	350mA		40cm	155x53mm	40mm	50	Requires 350mA driver
51301AL/W/35	Aluminium	Warm white	3000K	3x1W	3x45lm	35°	350mA		40cm	155x53mm	40mm	50	Requires 350mA driver
51401AL/D/15	Aluminium	Daylight	6000K	4x1W	4x60lm	15°	350mA		40cm	105x105mm	40mm	50	Requires 350mA driver
51401AL/D/35	Aluminium	Daylight	6000K	4x1W	4x60lm	35°	350mA		40cm	105x105mm	40mm	50	Requires 350mA driver
51401AL/W/15	Aluminium	Warm white	3000K	4x1W	4x45lm	15°	350mA		40cm	105x105mm	40mm	50	Requires 350mA driver
51401AL/W/35	Aluminium	Warm white	3000K	4x1W	4x45lm	35°	350mA		40cm	105x105mm	40mm	50	Requires 350mA driver

The 3W Mini Series
Aluminium





A-A++

11103LC | 3W | LED | Aluminium

LED BUILT IN
DIMMABLE
QUICK FIX
ADJUSTABLE
IP20
offer
2 YEAR





Suitable for 89004A driver.





A-A++

51103LC | 3W | LED | Natural aluminium

LED BUILT IN
DIMMABLE
QUICK FIX
ADJUSTABLE
IP20
offer
2 YEAR





Suitable for 89004A driver.



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
11103LC/B/D/15	Black	Daylight	6000K	3W	120lm	15°	700mA		40cm	45mm	56mm	100	Requires 700mA driver
11103LC/B/D/35	Black	Daylight	6000K	3W	120lm	35°	700mA		40cm	45mm	56mm	100	Requires 700mA driver
51103LC/AL/D/35	Aluminium	Daylight	6000K	3W	120lm	35°	700mA		40cm	53mm	55mm	100	Requires 700mA driver



The 3x1W Glass Lens Spots



A-A++ 11103N/W/D/35

11103N | 3x1W | LED | Natural aluminium

LED BUILT IN
DIMMABLE QUICK FIX ADJUSTABLE
IP20 offer
2 YEAR





Suitable for 89004 driver.





A-A++ 11103N/B/D/35

11103N | 3x1W | LED | Natural aluminium

LED BUILT IN
DIMMABLE QUICK FIX ADJUSTABLE
IP20 offer
2 YEAR





Suitable for 89004 driver.





A-A++ 11103N/AL/D/35

11103N | 3x1W | LED | Natural aluminium

LED BUILT IN
DIMMABLE QUICK FIX ADJUSTABLE
IP20 offer
2 YEAR





Suitable for 89004 driver.



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
									40cm	70mm	50mm	100	
11103N/W/D/35	White	Daylight	6000K	3x1W	180lm	35°	350mA	III	40cm	70mm	50mm	100	Requires 350mA driver
11103N/B/D/35	Black	Daylight	6000K	3x1W	180lm	35°	350mA	III	40cm	70mm	50mm	100	Requires 350mA driver
11103N/B/W/35	Black	Warm white	3000K	3x1W	135lm	35°	350mA	III	40cm	70mm	50mm	100	Requires 350mA driver
11103N/AL/D/35	Aluminium	Daylight	6000K	3x1W	180lm	35°	350mA	III	40cm	70mm	50mm	100	Requires 350mA driver
11103N/AL/W/35	Aluminium	Warm white	3000K	3x1W	135lm	35°	350mA	III	40cm	70mm	50mm	100	Requires 350mA driver



The 3xLED Round Spots

Aluminium



11103L | 3x1W | LED | Natural aluminium

LED BUILT IN · DIMMABLE · QUICK FIX · ADJUSTABLE · IP20 · offer · 2 YEAR





Suitable for 89004 driver.





11103LW | 3x1W | LED | Natural aluminium

LED BUILT IN · DIMMABLE · QUICK FIX · ADJUSTABLE · IP20 · offer · 2 YEAR





Suitable for 89004 driver.





11103LB | 3x1W | LED | Aluminium

LED BUILT IN · DIMMABLE · QUICK FIX · ADJUSTABLE · IP20 · offer · 2 YEAR





Suitable for 89004 driver.





11303L | 3x3W | LED | Natural aluminium

LED BUILT IN · DIMMABLE · QUICK FIX · ADJUSTABLE · IP20 · offer · 2 YEAR





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
11103L/D/15	Aluminium	Daylight	6000K	3x1W	180lm	15°	350mA	III	40cm	70mm	50mm	100	Requires 350mA driver
11103L/W/15	Aluminium	Warm white	3000K	3x1W	135lm	15°	350mA	III	40cm	70mm	50mm	100	Requires 350mA driver
11103LW/D/35	White	Daylight	6000K	3x1W	180lm	35°	350mA	III	40cm	70mm	50mm	100	Requires 350mA driver
11103LB/D/35	Black	Daylight	6000K	3x1W	180lm	35°	350mA	III	40cm	70mm	50mm	100	Requires 350mA driver
11103LB/W/35	Black	Warm white	3000K	3x1W	135lm	35°	350mA	III	40cm	70mm	50mm	100	Requires 350mA driver
11303L/AL/D/35	Aluminium	Daylight	6000K	3x3W	360lm	35°	700mA	III	40cm	70mm	100mm	30	Requires 700mA driver



The 3x1W Square Spots

Aluminium



A-A++ 51103L/D/15

51103L | 3x1W | LED | Natural aluminium

LED BUILT IN

DIMMABLE QUICK FIX ADJUSTABLE

IP20

offer

2 YEAR

offer



51103L/W/15



Suitable for 89004 driver.





A-A++

51103LW | 3x1W | LED | Natural aluminium

LED BUILT IN

DIMMABLE QUICK FIX ADJUSTABLE

IP20

offer

2 YEAR





Suitable for 89004 driver.





A-A++ 51103LB/D/35

51103LB | 3x1W | LED | Natural aluminium

LED BUILT IN

DIMMABLE QUICK FIX ADJUSTABLE

IP20

offer

2 YEAR

offer



51103LB/W/35



Suitable for 89004 driver.



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
51103L/D/15	Aluminium	Daylight	6000K	3x1W	180lm	15°	350mA	III	40cm	70mm	50mm	60	Requires 350mA driver
51103L/D/35	Aluminium	Daylight	6000K	3x1W	180lm	35°	350mA	III	40cm	70mm	50mm	60	Requires 350mA driver
51103L/W/15	Aluminium	Warm white	3000K	3x1W	135lm	15°	350mA	III	40cm	70mm	50mm	60	Requires 350mA driver
51103LW/D/35	White	Daylight	6000K	3x1W	180lm	35°	350mA	III	40cm	70mm	50mm	60	Requires 350mA driver
51103LB/D/35	Black	Daylight	6000K	3x1W	180lm	35°	350mA	III	40cm	70mm	50mm	60	Requires 350mA driver
51103LB/W/35	Black	Warm white	3000K	3x1W	135lm	35°	350mA	III	40cm	70mm	50mm	60	Requires 350mA driver



The 7W COB Range



A-A++

11107B | 7W | COB LED | Die cast

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · IP20 · 3 YEAR







A-A++ 51107/W/W

51107 | 7W | COB LED | Aluminium

LED BUILT IN · 80 CRI · DIMMABLE · QUICK FIX · ADJUSTABLE · CE · 2 YEAR · IP20







A-A++ 51107/AL/W

51107 | 7W | COB LED | Aluminium

LED BUILT IN · 80 CRI · DIMMABLE · QUICK FIX · ADJUSTABLE · CE · 2 YEAR · IP20





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
11107B/W/W	White	Warm white	3000K	7W	560lm	60°	230V		-	75mm	75mm	50	Complete with 300mA driver
51107/W/W	White	Warm white	3000K	7W	513lm	30°	700mA		40cm	70mm	90mm	30	Requires 700mA driver
51107/AL/W	Aluminium	Warm white	3000K	7W	513lm	30°	700mA		40cm	70mm	90mm	30	Requires 700mA driver



The Super Narrow 4° Beam



A-A++ 11106DB/W/W

11106DB | 6W | COB LED | Super narrow beam | Die cast









A-A++ 11106DB/B/W

11106DB | 6W | COB LED | Super narrow beam | Die cast







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class	S				Notes
11106DB/W/W	White	Warm white	3000K	6W	540lm	4°	500mA	III	20cm	68mm	110mm	30	Requires 500mA driver
11106DB/B/W	Black	Warm white	3000K	6W	540lm	4°	500mA	III	20cm	68mm	110mm	30	Requires 500mA driver



The 12W COB Range



A-A++ 11112/W/W

11112 | 12W | COB LED | Die cast

LED BUILT IN · 80 CRI · DIMMABLE · QUICK FIX · IP20 · ADJUSTABLE · CE · 2 YEAR







A-A++ 11112/AL/W

11112 | 12W | COB LED | Natural aluminium

LED BUILT IN · 80 CRI · DIMMABLE · QUICK FIX · IP20 · ADJUSTABLE · CE · 2 YEAR







A-A++

51112 | 12W | COB LED | Aluminium

LED BUILT IN · 80 CRI · DIMMABLE · QUICK FIX · IP20 · ADJUSTABLE · CE · 2 YEAR





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
11112/W/C	White	Cool white	4000K	12W	1100lm	38°	700mA	III	40cm	78mm	90mm	50	Requires 700mA driver
11112/W/W	White	Warm white	3000K	12W	1100lm	38°	700mA	III	40cm	78mm	90mm	50	Requires 700mA driver
11112/AL/W	Aluminium	Warm white	3000K	12W	1100lm	38°	700mA	III	40cm	78mm	90mm	50	Requires 700mA driver
51112/AL/W	Aluminium	Warm white	3000K	12W	880lm	38°	700mA	III	40cm	80mm	90mm	50	Requires 700mA driver

The Compact Spots



11109KD/W/W



11106K/W + White ring



A-A++

11106K | 6W | LED | Plastic

LED BUILT IN
80 CRI
ADJUSTABLE
CE
2 YEAR
IP20



Complete with White/Black/Grey rings.





A-A++

11106KD | 6,3W | LED | Plastic

LED BUILT IN
80 CRI
TRIAC
DIMMABLE
ADJUSTABLE
CE
2 YEAR
IP20



Complete with White/Black/Grey rings.





A-A++

11109KD | 9,2W | COB LED | Aluminium

LED BUILT IN
80 CRI
TRIAC
DIMMABLE
ADJUSTABLE
CE
2 YEAR
IP20





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
11106K/W	White/Black/Grey	Warm white	3000K	6W	345lm	38°	100-240V		67mm	90mm	48	Complete with driver
11106KD/W	White/Black/Grey	Warm white	3000K	6,3W	345lm	38°	230V		67mm	90mm	48	Complete with dimmable driver
11109KD/W/W	White	Warm white	3000K	9,2W	620lm	38°	230V		67mm	90mm	48	Complete with dimmable driver



The COB Round Spots
Aluminium



A-A++ 11106A/AL/C

11106A | 6W | LED | Aluminium

LED BUILT IN
80 CRI
QUICK FIX
ADJUSTABLE
IP20
offer
CE
2 YEAR



11106A/AL/W

offer





A-A++

11110A | 10W | LED | Aluminium

LED BUILT IN
80 CRI
QUICK FIX
ADJUSTABLE
IP20
CE
2 YEAR





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
11106A/AL/C	Aluminium	Cool white	4000K	6W	485lm	36°	100-240V	☐	80mm	80mm	20	Complete with 500mA driver
11106A/AL/W	Aluminium	Warm white	3000K	6W	475lm	36°	100-240V	☐	80mm	80mm	20	Complete with 500mA driver
11110A/W/C	White	Cool white	4000K	10W	840lm	36°	100-240V	☐	100mm	100mm	20	Complete with 250mA driver



The COB Square Spots

Aluminium



A-A++ 51106A/W/C

51106A | 6W | LED | Aluminium





51106A/AL/W

offer





A-A++ 51110A/W/W

51110A | 10W | LED | Aluminium





51110A/AL/C

offer



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
51106A/W/C	White	Warm white	3000K	6W	485lm	36°	100-240V	☐	80mm	80mm	20	Complete with 500mA driver
51106A/AL/W	Aluminium	Warm white	3000K	6W	475lm	36°	100-240V	☐	80mm	80mm	20	Complete with 500mA driver
51110A/W/C	White	Cool white	4000K	10W	840lm	36°	100-240V	☐	100mm	100mm	20	Complete with 250mA driver
51110A/W/W	White	Warm white	3000K	10W	825lm	36°	100-240V	☐	100mm	100mm	20	Complete with 250mA driver
51110A/AL/C	Aluminium	Cool white	4000K	10W	840lm	36°	100-240V	☐	100mm	100mm	20	Complete with 250mA driver
51110A/AL/W	Aluminium	Warm white	3000K	10W	825lm	36°	100-240V	☐	100mm	100mm	20	Complete with 250mA driver



The Interchanging Rings Range

Aluminium



A-A++ 11112H/W/W+050086/B

11112H | 12W | COB LED | Aluminium

Ring must be ordered separately.

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · IP20 · 3 YEAR



11112H/B/W+050086/W





050086/W White



050086/B Black



050086/G Grey



050086/BS Dark brass



050086A/W White



A-A++ 51112H/W/W+050088/B

51112H | 12W | COB LED | Aluminium

Ring must be ordered separately.

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · IP20 · 3 YEAR



51112H/B/W+050088/BS





050088/W White



050088/B Black



050088/G Grey



050088/BS Dark brass



050088A/W White

Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
11112H/W/W	White	Warm white	3000K	12W	940lm	60°	100-240V		90mm	120mm	30	Complete with 300mA driver
11112H/B/W	Black	Warm white	3000K	12W	940lm	60°	100-240V		90mm	120mm	30	Complete with 300mA driver
51112H/W/W	White	Warm white	3000K	12W	940lm	60°	100-240V		95x95mm	120mm	30	Complete with 300mA driver
51112H/B/W	Black	Warm white	3000K	12W	940lm	60°	100-240V		95x95mm	120mm	30	Complete with 300mA driver



11104K/B/W + 050100/B

11104K/W/W + 050100/BS

11107K/B/W + 050102/CU

The Interchanging Rings Range

Aluminium



A-A++ 11104K/W/W + 050100/B

11104K | 3W/5W | COB LED | Aluminium

3W@350mA/5W@500mA | Ring must be ordered separately.

LED BUILT IN · 80 CRI · DIMMABLE · QUICK FIX · DARK LIGHT · IP20 · ADJUSTABLE · CE · 3 YEAR



11104K/B/W + 050100/BS





050100/W White | 050100/B Black | 050100/C Chrome | 050100/BS Brass | 050100/CU Copper



A-A++ 11107K/W/W + 050102/B

11107K | 7W | COB LED | Aluminium

Ring must be ordered separately.

LED BUILT IN · 80 CRI · DIMMABLE · QUICK FIX · DARK LIGHT · IP20 · ADJUSTABLE · CE · 3 YEAR



11107K/B/W + 050102/BS





050102/W White | 050102/B Black | 050102/C Chrome | 050102/BS Brass | 050102/CU Copper

Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
11104K/W/W	White	Warm white	3000K	3W/5W	400lm@5W	35°	350mA/500mA	III	40cm	60mm	80mm	50	Requires 350mA/500mA driver
11104K/B/W	Black	Warm white	3000K	3W/5W	400lm@5W	35°	350mA/500mA	III	40cm	60mm	80mm	50	Requires 350mA/500mA driver
11107K/W/W	White	Warm white	3000K	7W	550lm	35°	700mA	III	40cm	76mm	100mm	30	Requires 700mA driver
11107K/B/W	Black	Warm white	3000K	7W	550lm	35°	700mA	III	40cm	76mm	100mm	30	Requires 700mA driver





A-A++

11103E | 3W | COB LED | Aluminium

LED BUILT IN · 90 CRI · DIMMABLE · QUICK FIX · DARK LIGHT · IP20 · ADJUSTABLE · CE · 3 YEAR







A-A++

11112D | 12W | COB LED | Aluminium

LED BUILT IN · 80 CRI · DIMMABLE · QUICK FIX · DARK LIGHT · IP20 · ADJUSTABLE · CE · 2 YEAR







A-A++ 11103D/W/C

11103D | 3x1W | LED | Semi trimless | Aluminium

LED BUILT IN · DARK LIGHT · IP20 · DIMMABLE · QUICK FIX · ADJUSTABLE · offer · CE · 2 YEAR



11103D/G/W

offer



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
11103E/W/W	White	Warm white	3000K	3W	250lm	24°	350mA	III	40cm	40mm	60mm	100	Requires 350mA driver
11112D/W/W	White	Warm white	3000K	12W	650lm	38°	700mA	III	40cm	79mm	110mm	24	Requires 700mA driver
11103D/W/C	White	Cool white	4000K	3x1W	160lm	45°	350mA	III	40cm	90mm	90mm	50	Requires 350mA driver
11103D/G/C	Grey	Cool white	4000K	3x1W	160lm	45°	350mA	III	40cm	90mm	90mm	50	Requires 350mA driver
11103D/G/W	Grey	Warm white	3000K	3x1W	135lm	45°	350mA	III	40cm	90mm	90mm	50	Requires 350mA driver



11112TA/W/W

51112TA/W/W

11112DL/B/W

The 12W COB Dark Light



11112TA | 12W | COB LED | Die cast

LED BUILT IN
80 CRI
DIMMABLE
QUICK FIX
DARK LIGHT
IP20
ADJUSTABLE
2 YEAR







51112TA | 12W | COB LED | Die cast

LED BUILT IN
80 CRI
DIMMABLE
QUICK FIX
DARK LIGHT
IP20
ADJUSTABLE
2 YEAR







11112DL | 12W | COB LED | Aluminium

LED BUILT IN
80 CRI
DIMMABLE
QUICK FIX
DARK LIGHT
IP20
ADJUSTABLE
2 YEAR





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
11112TA/W/W	White	Warm white	3000K	12W	1100lm	40°	700mA	III	40cm	90mm	125mm	50	Requires 700mA driver
51112TA/W/W	White	Warm white	3000K	12W	1100lm	40°	700mA	III	40cm	90mm	125mm	50	Requires 700mA driver
11112DL/B/W	Black	Warm white	3000K	12W	900lm	24°	700mA	III	40cm	75mm	140mm	50	Requires 700mA driver



The COB Dark Light Range



11103BD | 3W | COB LED | Aluminium

LED BUILT IN · 90 CRI · DIMMABLE · QUICK FIX · DARK LIGHT · IP20 · ADJUSTABLE · CE · 3 YEAR







11107DA/W/W

11107DA | 7W | COB LED | Aluminium

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · DARK LIGHT · IP20 · 3 YEAR



11107DA/B/W





11107FD/W/W

11107FD | 7W | COB LED | Die cast

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · DARK LIGHT · IP20 · 2 YEAR



11107FD/B/W



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
11103BD/W/W	White	Warm white	3000K	3W	220lm	36°	350mA		40cm	44mm	50mm	100	Requires 350mA driver
11107DA/W/W	White	Warm white	3000K	7W	600lm	36°	230V		-	70mm	80mm	50	Complete with 500mA driver
11107DA/B/W	Black	Warm white	3000K	7W	600lm	36°	230V		-	70mm	80mm	50	Complete with 500mA driver
11107FD/W/C	White	Cool white	4000K	7W	560lm	60°	230V		-	80mm	110mm	50	Complete with 300mA driver
11107FD/W/W	White	Warm white	3000K	7W	560lm	60°	230V		-	80mm	110mm	50	Complete with 300mA driver
11107FD/W/EW	White	Extra warm white	2700K	7W	560lm	60°	230V		-	80mm	110mm	50	Complete with 300mA driver
11107FD/B/W	Black	Warm white	3000K	7W	560lm	60°	230V		-	80mm	110mm	50	Complete with 300mA driver

The COB Shop & Hotel Range

11107DL | 7W | COB LED | Aluminium



A-A++ 11107DL/W/W

LED BUILT IN · 80 CRI · DIMMABLE · QUICK FIX · DARK LIGHT · IP20 · ADJUSTABLE · CE · 3 YEAR



11107DL/B/W



11112E | 12W | COB LED | Die cast



A-A++

LED BUILT IN · 80 CRI · DIMMABLE · QUICK FIX · DARK LIGHT · IP20 · ADJUSTABLE · CE · 2 YEAR





51112E | 12W | COB LED | Die cast



A-A++

LED BUILT IN · 80 CRI · DIMMABLE · QUICK FIX · DARK LIGHT · IP20 · ADJUSTABLE · CE · 2 YEAR





51212E | 2x12W | COB LED | Die cast



A-A++

LED BUILT IN · 80 CRI · DIMMABLE · QUICK FIX · DARK LIGHT · IP20 · ADJUSTABLE · CE · 2 YEAR





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
11107DL/W/W	White	Warm white	3000K	7W	450lm	38°	700mA		40cm	60mm	100mm	50	Requires 700mA driver
11107DL/B/W	Black	Warm white	3000K	7W	450lm	38°	700mA		40cm	60mm	100mm	50	Requires 700mA driver
11112E/W/C	White	Cool white	4000K	12W	1100lm	40°	700mA		40cm	87mm	95mm	50	Requires 700mA driver
11112E/W/W	White	Warm white	3000K	12W	1100lm	40°	700mA		40cm	87mm	95mm	50	Requires 700mA driver
11112E/W/EW	White	Extra warm white	2700K	12W	1100lm	40°	700mA		40cm	87mm	95mm	50	Requires 700mA driver
51112E/W/C	White	Cool white	4000K	12W	1100lm	40°	700mA		40cm	90x90mm	95mm	50	Requires 700mA driver
51112E/W/W	White	Warm white	3000K	12W	1100lm	40°	700mA		40cm	90x90mm	95mm	50	Requires 700mA driver
51112E/W/EW	White	Extra warm white	2700K	12W	1100lm	40°	700mA		40cm	90x90mm	95mm	50	Requires 700mA driver
51212E/W/C	White	Cool white	4000K	2x12W	2x1100lm	40°	700mA		40cm	175x90mm	95mm	24	Requires 700mA drivers
51212E/W/W	White	Warm white	3000K	2x12W	2x1100lm	40°	700mA		40cm	175x90mm	95mm	24	Requires 700mA drivers

The 7W Dark Light Shop Range

Aluminium



11107H | 7W | COB LED | Aluminium







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
11107H/W/C	White	Cool white	4000K	7W	350lm	36°	700mA	III	40cm	80mm	90mm	50	Requires 700mA driver
11107H/W/W	White	Warm white	3000K	7W	350lm	36°	700mA	III	40cm	80mm	90mm	50	Requires 700mA driver



Extractable 12W Range



11113E | 12W | COB LED | Aluminium

LED BUILT IN · 90 CRI · DIMMABLE · QUICK FIX · ADJUSTABLE · CE · 3 YEAR · IP20







51113E | 12W | COB LED | Aluminium

LED BUILT IN · 90 CRI · DIMMABLE · QUICK FIX · ADJUSTABLE · CE · 3 YEAR · IP20





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
11113E/W/W	White	Warm white	3000K	12W	1100lm	36°	350mA	III	40cm	80mm	120mm	36	Requires 350mA driver
51113E/W/W	White	Warm white	3000K	12W	1100lm	36°	350mA	III	40cm	80x80mm	120mm	36	Requires 350mA driver



The IP44 & IP54 COB Outdoor/Bathroom Range

Aluminium



11103P | 3W | COB LED | Aluminium

LED BUILT IN · 80 CRI · DIMMABLE · QUICK FIX · IP44 · ADJUSTABLE · CE · 3 YEAR







11107WD | 7W | COB LED | Aluminium

LED BUILT IN · 90 CRI · DIMMABLE · QUICK FIX · DARK LIGHT · IP54 · ADJUSTABLE · CE · 3 YEAR







11207WD | 2x7W | COB LED | Aluminium

LED BUILT IN · 90 CRI · DIMMABLE · QUICK FIX · DARK LIGHT · IP54 · ADJUSTABLE · CE · 3 YEAR





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class	S				Notes
11103P/W/W	White	Warm white	3000K	3W	240lm	36°	350mA	III	40cm	47mm	60mm	100	Requires 350mA driver
11107WD/W/W	White	Warm white	3000K	7W	500lm	36°	700mA	III	40cm	83mm	100mm	36	Requires 700mA driver
11207WD/W/W	White	Warm white	3000K	2x7W	2x500lm	36°	700mA	III	40cm	160x83mm	100mm	16	Requires 700mA drivers



The IP54 COB Outdoor/Bathroom Range

Die cast



11107P | 7W | COB LED | Die cast









11107D | 7W | COB LED | Die cast







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
11107P/W/W	White	Warm white	3000K	7W	530lm	36°	700mA	III	40cm	70mm	70mm	60	Requires 700mA driver
11107D/W/W	White	Warm white	3000K	7W	500lm	36°	700mA	III	40cm	92mm	90mm	30	Requires 700mA driver



Swivel Range

Die cast



A-A++ 11108LA/W/W

11108LA | 8W | COB LED | Die cast

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · IP20 · 3 YEAR









A-A++ 11108LA/B/W

11108LA | 8W | COB LED | Die cast

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · IP20 · 3 YEAR







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
11108LA/W/W	White	Warm white	3000K	8W	600lm	25°	230V	⧈	68mm	50mm	24	Complete with 200mA driver
11108LA/B/W	Black	Warm white	3000K	8W	600lm	25°	230V	⧈	68mm	50mm	24	Complete with 200mA driver



Moving Inner Cylinder Range



11103M | 3W | COB LED | Aluminium

LED BUILT IN · 90 CRI · DIMMABLE · QUICK FIX · ADJUSTABLE · CE · 3 YEAR · DARK LIGHT · IP20









11108M | 7W | COB LED | Die cast

LED BUILT IN · 80 CRI · DIMMABLE · QUICK FIX · ADJUSTABLE · CE · 3 YEAR · IP20









11110B | 10W | COB LED | Die cast

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · 3 YEAR · DARK LIGHT · IP20







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
11103M/W/W	White	Warm white	3000K	3W	280lm	36°	350mA	III	40cm	44mm	35mm	100	Requires 350mA driver
11108M/W/W	White	Warm white	3000K	7W	635lm	40°	700mA	III	40cm	95mm	100mm	30	Requires 700mA driver
11110B/W/C	White	Cool white	4000K	10W	750lm	40°	230V	II	-	120mm	90mm	12	Complete with 250mA driver
11110B/W/W	White	Warm white	3000K	10W	750lm	40°	230V	II	-	120mm	90mm	12	Complete with 250mA driver



11207M/W/W



11107F/W/W

The COB Pop Up Range



11107F | 7W | COB LED | Aluminium

LED BUILT IN
80 CRI
DIMMABLE
QUICK FIX
ADJUSTABLE
3 YEAR
IP20









11207M | 2x7W | COB LED | Aluminium

LED BUILT IN
80 CRI
DIMMABLE
QUICK FIX
ADJUSTABLE
3 YEAR
IP20







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
11107F/W/W	White	Warm white	3000K	7W	560lm	35°	700mA	III	40cm	95mm	50mm	30	Requires 700mA driver
11207M/W/W	White	Warm white	3000K	2x7W	2x464lm	35°	700mA	III	40cm	2x100mm	50mm	20	Requires 700mA drivers



11107RA | 7W | COB LED | Aluminium



A-A++ 11107RA/W/W

LED BUILT IN · 90 CRI · DIMMABLE · QUICK FIX · ADJUSTABLE · CE · 3 YEAR · DARK LIGHT · IP20



11107RA/B/W





11112RA | 12W | COB LED | Aluminium



A-A++ 11112RA/W/W

LED BUILT IN · 90 CRI · DIMMABLE · QUICK FIX · ADJUSTABLE · CE · 3 YEAR · DARK LIGHT · IP20



11112RA/B/W





11112RB | 12W | COB LED | Aluminium



A-A++ 11112RB/W/W

LED BUILT IN · 90 CRI · DIMMABLE · QUICK FIX · ADJUSTABLE · CE · 3 YEAR · DARK LIGHT · IP20



11112RB/B/W





Order Code	Colour	Reflector	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class	S				Notes
11107RA/W/W	White	Black	Warm white	3000K	7W	500lm	36°	700mA	III	40cm	45mm	40mm	36	Requires 700mA driver
11107RA/B/W	Black	Brass	Warm white	3000K	7W	500lm	36°	700mA	III	40cm	45mm	40mm	36	Requires 700mA driver
11112RA/W/W	White	Black	Warm white	3000K	12W	1020lm	36°	350mA	III	40cm	55mm	50mm	20	Requires 350mA driver
11112RA/B/W	Black	Brass	Warm white	3000K	12W	1020lm	36°	350mA	III	40cm	55mm	50mm	20	Requires 350mA driver
11112RB/W/W	White	Black	Warm white	3000K	12W	1020lm	36°	350mA	III	40cm	55mm	50mm	18	Requires 350mA driver
11112RB/B/W	Black	Brass	Warm white	3000K	12W	1020lm	36°	350mA	III	40cm	55mm	50mm	18	Requires 350mA driver



Recessed COB Cylinders



A-A++ 11111C/W/W

11111C | 11W | COB LED | Die cast

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · DARK LIGHT · IP20 · 3 YEAR



11111C/B/W



Complete with Black & Brass reflectors.





A-A++ 51111C/W/W

51111C | 11W | COB LED | Die cast

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · DARK LIGHT · IP20 · 3 YEAR



51111C/B/W



Complete with Black & Brass reflectors.





A-A++ 51211C/W/W

51211C | 2x11W | COB LED | Die cast

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · DARK LIGHT · IP20 · 3 YEAR



51211C/B/W



Complete with Black & Brass reflectors.



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
11111C/W/W	White	Warm white	3000K	11W	820lm	38°	230V		85mm	110mm	20	Complete with 250mA driver
11111C/B/W	Black	Warm white	3000K	11W	820lm	38°	230V		85mm	110mm	20	Complete with 250mA driver
51111C/W/W	White	Warm white	3000K	11W	820lm	38°	230V		85x85mm	110mm	20	Complete with 250mA driver
51111C/B/W	Black	Warm white	3000K	11W	820lm	38°	230V		85x85mm	110mm	20	Complete with 250mA driver
51211C/W/W	White	Warm white	3000K	2x11W	2x820lm	38°	230V		165x85mm	110mm	20	Complete with 250mA drivers
51211C/B/W	Black	Warm white	3000K	2x11W	2x820lm	38°	230V		165x85mm	110mm	20	Complete with 250mA drivers





A-A++ 11107C/W/W

11107C | 7W | COB LED | Die cast





11107C/B/W







A-A++ 11207C/W/W

11207C | 2x7W | COB LED | Die cast





11207C/B/W





Order Code	Colour	Reflector	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
11107C/W/W	White	Black	Warm white	3000K	7W	520lm	36°	700mA	III	40cm	83mm	80mm	36	Requires 700mA driver
11107C/B/W	Black	Brass	Warm white	3000K	7W	520lm	36°	700mA	III	40cm	83mm	80mm	36	Requires 700mA drive
11207C/W/W	White	Black	Warm white	3000K	2x7W	2x520lm	36°	700mA	III	40cm	2x83mm	90mm	24	Requires 700mA drivers
11207C/B/W	Black	Brass	Warm white	3000K	2x7W	2x520lm	36°	700mA	III	40cm	2x83mm	90mm	24	Requires 700mA drivers

The COB Fire Rated Range



11106PF/C



050044/MC



050044/B



050044/C



050044/W



A-A++

11106PF | 6W | COB LED | Fire rated | Die cast

Ring must be ordered separately.

LED BUILT IN 80 CRI

FIRE RATED · DIMMABLE · QUICK FIX

IP20 · ADJUSTABLE · CE · 3 YEAR



Dimensions are complete with the ring.





050044/W White



050044/B Black



050044/C Chrome



050044/MC Brushed chrome

Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
11106PF/C	-	Cool white	4000K	6W	530lm	40°	350mA	III	40cm	75mm	90mm	20	Requires 350mA driver
11106PF/W	-	Warm white	3000K	6W	500lm	40°	350mA	III	40cm	75mm	90mm	20	Requires 350mA driver

Trimless COB Spot

Die cast



A-A++

11107BT | 7W | COB LED | Trimless | Die cast

LED BUILT IN

80 CRI

DIMMABLE

QUICK FIX

DARK LIGHT

IP54

ADJUSTABLE

3 YEAR





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
11107BT/W/W	White	Warm white	3000K	7W	500lm	38°	700mA	III	40cm	96mm	95mm	30	Requires 700mA driver





05

Downlights Fixed

Pages 137-142

GX53 | E27

Die cast | Natural aluminium | Steel | Metal | Gypsum | Trimless

IP20

QUICK FIX

5 YEAR







B-A++ 10007/W

10007 | 9W | GX53 | Steel

IP20

offer



Suitable for GX53 LED lamp.





B-A++ 10007/MC

10007 | 9W | GX53 | Steel

IP20

offer



Suitable for GX53 LED lamp.



Order Code	Colour	Watts	Input	Class				Notes
10007/W	White	9W	100-240V		110mm	60mm	50	-
10007/MC	Brushed chrome	9W	100-240V		110mm	60mm	50	-

The GX53 Downlight





B-A++

10004 | 9W | GX53 | Natural aluminium

IP20

offer



Suitable for GX53 LED lamp.



Order Code	Colour	Watts	Input	Class				Notes
10004/AL	Aluminium	9W	100-240V		86mm	35mm	50	-



E27 Budget Downlights

Metal

10115BF | 15W | E27 | Metal



B-A++

IP20

offer



Suitable for E27 LED lamp.



10220BF | 2x20W | E27 | Metal



B-A++

IP20

offer





50115BF | 15W | E27 | Metal



B-A++ 50115BF/W

IP20

offer



50115BF/MC

offer



50220BF | 2x20W | E27 | Metal



B-A++ 50220BF/W

IP20

offer



50220BF/MC

offer



Order Code	Colour	Watts	Input	Class				Notes
10115BF/MC	Brushed chrome	15W	100-240V		130mm	150mm	12	Use E27 LED lamp
10220BF/MC	Brushed chrome	2x20W	100-240V		210mm	150mm	12	Use E27 LED lamp
50115BF/W	White	15W	100-240V		110x110mm	110mm	16	Use E27 LED lamp
50115BF/MC	Brushed chrome	15W	100-240V		110x110mm	110mm	16	Use E27 LED lamp
50220BF/W	White	2x20W	100-240V		195x195mm	140mm	8	Use E27 LED lamp
50220BF/MC	Brushed chrome	2x20W	100-240V		195x195mm	140mm	8	Use E27 LED lamp



E27 Budget Downlights

Metal

10215D | 2x15W | E27 | Metal



B-A++

IP20

offer



Suitable for E27 LED lamp.



10220D | 2x20W | E27 | Metal



B-A++ 10220D/W

IP20

offer



10220D/MC

offer



10220E | 2x20W | E27 | Metal



B-A++

IP20

offer



Suitable for E27 LED lamps.



10220CF | 2x20W | E27 | Metal



B-A++ 10220CF/W

IP20

offer



10220CF/MC

offer



Order Code	Colour	Watts	Input	Class				Notes
10215D/MC	Brushed chrome	2x15W	100-240V		175mm	150mm	18	Use E27 LED lamp
10220D/W	White	2x20W	100-240V		210mm	150mm	12	Use E27 LED lamp
10220D/MC	Brushed chrome	2x20W	100-240V		210mm	150mm	12	Use E27 LED lamp
10220E/W	White	2x20W	100-240V		210mm	110mm	12	Use E27 LED lamp
10220CF/W	White	2x20W	100-240V		210mm	150mm	12	Use E27 LED lamp
10220CF/MC	Brushed chrome	2x20W	100-240V		210mm	150mm	12	Use E27 LED lamp



E27 Trimless Downlights

Die cast



B-A++

10220T | 2x20W | E27 | Trimless | Die cast

IP20

offer







B-A++

50220T | 2x20W | E27 | Trimless | Die cast

IP20

offer





Order Code	Colour	Watts	Input	Class				Notes
10220T	White	2x20W	100-240V	⏚	203mm	140mm	12	Use E27 LED lamps
50220T	White	2x20W	100-240V	⏚	190x190mm	140mm	12	Use E27 LED lamps

E27 Trimless Downlights

Gypsum



50220GT1



10220GT1



10220GT1 | 2x20W | E27 | Gypsum

IP20







50220GT1 | 2x20W | E27 | Gypsum

IP20





Order Code	Colour	Watts	Input	Class				Notes
10220GT1	White	2x20W	100-240V		262mm	180mm	4	Use E27 LED lamps
50220GT1	White	2x20W	100-240V		242x242mm	180mm	4	Use E27 LED lamps





06

Downlights Fixed LED

Pages 145-186

COB LED | SMD LED | LED

Die cast | Aluminium

IP20 IP40 IP44 IP54 IP65

DIMMABLE DARK LIGHT QUICK FIX UGR19 80 CRI 90 CRI 2 YEAR 3 YEAR 5 YEAR



Round Recessed Panels

Die cast



10108F/G/D



10112F/W/EW

10120F/G/W



A-A++

10108F | 8W | SMD LED | Die cast

LED BUILT IN

80 CRI

IP40

offer







A-A++

10112F | 12W | SMD LED | Die cast

Driver can not pass through the cutout hole.

LED BUILT IN

80 CRI

IP40

offer







A-A++

10120F | 30W | SMD LED | Die cast

Optional dimmable driver code 040060.

LED BUILT IN

80 CRI

IP40

offer





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
10108F/G/D	Grey	Daylight	6000K	8W	537lm	120°	100-240V		108mm	40mm	40	Complete with 500mA driver
10112F/W/EW	White	Extra warm white	2700K	12W	745lm	120°	100-240V		165mm	40mm	20	Complete with 500mA driver
10120F/G/D	Grey	Daylight	6000K	30W	1997lm	120°	100-240V		285mm	40mm	10	Complete with 1000mA driver
10120F/G/W	Grey	Warm white	3000K	30W	1797lm	120°	100-240V		285mm	40mm	10	Complete with 1000mA driver



10103FA/W/D

Round Recessed Panels 3-12W

Die cast



A-A++

10103FA | 3W | SMD LED | Die cast

LED BUILT IN

80 CRI

IP40



super slim!





A-A++ 10108FA/W/W

10108FA | 8W | SMD LED | Die cast

Optional dimmable driver code 89008CT.

LED BUILT IN

80 CRI

IP40



10108FA/B/W





A-A++ 10112FA/W/W

10112FA | 12W | SMD LED | Die cast

Optional dimmable driver code 89012BT.

LED BUILT IN

80 CRI

IP40



10112FA/B/W



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
10103FA/W/D	White	Daylight	6000K	3W	210lm	120°	230V	☐	70mm	50mm	60	Complete with 300mA driver
10103FA/W/C	White	Cool white	4000K	3W	210lm	120°	230V	☐	70mm	50mm	60	Complete with 300mA driver
10103FA/W/W	White	Warm white	3000K	3W	180lm	120°	230V	☐	70mm	50mm	60	Complete with 300mA driver
10108FA/W/D	White	Daylight	6000K	8W	560lm	120°	230V	☐	108mm	50mm	40	Complete with 320mA driver
10108FA/W/C	White	Cool white	4000K	8W	560lm	120°	230V	☐	108mm	50mm	40	Complete with 320mA driver
10108FA/W/W	White	Warm white	3000K	8W	480lm	120°	230V	☐	108mm	50mm	40	Complete with 320mA driver
10108FA/B/C	Black	Cool white	4000K	8W	560lm	120°	230V	☐	108mm	50mm	40	Complete with 320mA driver
10108FA/B/W	Black	Warm white	3000K	8W	480lm	120°	230V	☐	108mm	50mm	40	Complete with 320mA driver
10112FA/W/C	White	Cool white	4000K	12W	840lm	120°	230V	☐	155mm	50mm	30	Complete with 250mA driver
10112FA/W/W	White	Warm white	3000K	12W	720lm	120°	230V	☐	155mm	50mm	30	Complete with 250mA driver
10112FA/B/C	Black	Cool white	4000K	12W	840lm	120°	230V	☐	155mm	50mm	30	Complete with 250mA driver
10112FA/B/W	Black	Warm white	3000K	12W	720lm	120°	230V	☐	155mm	50mm	30	Complete with 250mA driver



Round Recessed Panels 18-40W

Die cast

10118FA | 18W | SMD LED | Die cast

Optional dimmable driver code 89018DT.



A-A++ 10118FA/W/W

LED BUILT IN · 80 CRI · CE · 2 YEAR · IP40



10118FA/B/W



10118FA/G/W



10130FA | 30W | SMD LED | Die cast

Optional dimmable driver code 89030AT.



A-A++ 10130FA/W/C

LED BUILT IN · 80 CRI · CE · 2 YEAR · IP40



10130FA/G/C



10140F | 40W | SMD LED | Die cast



A-A++

LED BUILT IN · 80 CRI · CE · 2 YEAR · IP40





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
10118FA/W/D	White	Daylight	6000K	18W	1260lm	120°	230V	☐	210mm	50mm	20	Complete with 450mA driver
10118FA/W/C	White	Cool white	4000K	18W	1260lm	120°	230V	☐	210mm	50mm	20	Complete with 450mA driver
10118FA/W/W	White	Warm white	3000K	18W	1080lm	120°	230V	☐	210mm	50mm	20	Complete with 450mA driver
10118FA/B/C	Black	Cool white	4000K	18W	1260lm	120°	230V	☐	210mm	50mm	20	Complete with 450mA driver
10118FA/B/W	Black	Warm white	3000K	18W	1080lm	120°	230V	☐	210mm	50mm	20	Complete with 450mA driver
10118FA/G/W	Grey	Warm white	3000K	18W	1080lm	120°	230V	☐	210mm	50mm	20	Complete with 450mA driver
10130FA/W/D	White	Daylight	6000K	30W	2100lm	120°	230V	☐	285mm	50mm	15	Complete with 700mA driver
10130FA/W/C	White	Cool white	4000K	30W	2100lm	120°	230V	☐	285mm	50mm	15	Complete with 700mA driver
10130FA/W/W	White	Warm white	3000K	30W	1800lm	120°	230V	☐	285mm	50mm	15	Complete with 700mA driver
10130FA/G/C	Grey	Cool white	4000K	30W	2100lm	120°	230V	☐	285mm	50mm	15	Complete with 700mA driver
10140F/W/D	White	Daylight	6000K	40W	2800lm	120°	230V	☐	408mm	40mm	5	Complete with 1000mA driver
10140F/W/C	White	Cool white	4000K	40W	2800lm	120°	230V	☐	408mm	40mm	5	Complete with 1000mA driver
10140F/W/W	White	Warm white	3000K	40W	2520lm	120°	230V	☐	408mm	40mm	5	Complete with 1000mA driver



Round Recessed Panel 48W

Die cast



10148PE | 48W | SMD 2835 | 600mm | Die cast

Driver must be ordered separately.

LED BUILT IN

80 CRI

DIMMABLE

2 YEAR

IP20





Optional non-dimmable driver. Order code 89048.



Optional TRIAC dimmable driver. Order code 89048T.



Optional DALI & Push to DIM driver. Order code 89050L.



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
10148PE/W/C	White	Cool white	4000K	48W	4000lm	120°	1200mA	III	585mm	80mm	4	Requires 1200mA driver
10148PE/W/W	White	Warm white	3000K	48W	3500lm	120°	1200mA	III	585mm	80mm	4	Requires 1200mA driver



Square Recessed Panels

Die cast



A-A++ 50108F/W/D

50108F | 8W | SMD LED | Die cast

LED BUILT IN

80 CRI

2 YEAR

IP40



50108F/G/D

offer





A-A++

50116F | 16W | SMD LED | Die cast

LED BUILT IN

80 CRI

2 YEAR

IP40

offer





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
50108F/W/D	White	Daylight	6000K	8W	461lm	120°	100-240V	⧈	96x96mm	40mm	40	Complete with 500mA driver
50108F/G/D	Grey	Daylight	6000K	8W	461lm	120°	100-240V	⧈	96x96mm	40mm	40	Complete with 500mA driver
50116F/G/D	Grey	Daylight	6000K	16W	982lm	120°	100-240V	⧈	152x152mm	40mm	20	Complete with 500mA driver



Square Recessed Panels

Die cast

50122F | 22W | SMD LED | Die cast



A-A++

LED BUILT IN

80 CRI

IP40





50130F | 30W | SMD LED | Die cast

Optional dimmable driver code 040060.



A-A++ 50130F/G/C

LED BUILT IN

80 CRI

IP40

offer



50130F/G/D



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
50122F/G/W	Grey	Warm white	3000K	22W	1490lm	120°	100-240V		204x204mm	40mm	10	Complete with 700mA driver
50130F/G/D	Grey	Daylight	6000K	30W	2174lm	120°	100-240V		284x284mm	40mm	10	Complete with 1000mA driver
50130F/G/C	Grey	Cool white	4000K	30W	2174lm	120°	100-240V		284x284mm	40mm	10	Complete with 1000mA driver

Square Recessed Panels

Die cast



50108FA/W/C

50116FA/W/C



50122FA/W/C

50108FA | 8W | SMD LED | Die cast

Optional dimmable driver code 89008CT.



A-A++ 50108FA/W/W

LED BUILT IN

80 CRI

IP40



50108FA/G/W



50116FA | 16W | SMD LED | Die cast

Optional dimmable driver code 89016T.



A-A++ 50116FA/W/W

LED BUILT IN

80 CRI

IP40



50116FA/G/W



50122FA | 22W | SMD LED | Die cast

Optional dimmable driver code 89022ET.



A-A++

LED BUILT IN

80 CRI

IP40





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
50108FA/W/C	White	Cool white	4000K	8W	560lm	120°	230V		105x105mm	50mm	40	Complete with 320mA driver
50108FA/W/W	White	Warm white	3000K	8W	480lm	120°	230V		105x105mm	50mm	40	Complete with 320mA driver
50108FA/G/W	Grey	Warm white	3000K	8W	480lm	120°	230V		105x105mm	50mm	40	Complete with 320mA driver
50116FA/W/C	White	Cool white	4000K	16W	1120lm	120°	230V		155x155mm	50mm	30	Complete with 350mA driver
50116FA/W/W	White	Warm white	3000K	16W	960lm	120°	230V		155x155mm	50mm	30	Complete with 350mA driver
50116FA/G/W	Grey	Warm white	3000K	16W	960lm	120°	230V		155x155mm	50mm	30	Complete with 350mA driver
50122FA/W/C	White	Cool white	4000K	22W	1540lm	120°	230V		210x210mm	50mm	20	Complete with 550mA driver
50122FA/W/W	White	Warm white	3000K	22W	1320lm	120°	230V		210x210mm	50mm	20	Complete with 550mA driver



Square Recessed Panels

Die cast



A-A++ 50130FA/W/W

50130FA | 30W | SMD LED | Die cast

Optional dimmable driver code 89030AT.

LED BUILT IN

80 CRI

CE

2 YEAR

IP40



50130FA/G/W





A-A++

50148PE | 48W | SMD 2835 | 600x600mm | Die cast

Driver must be ordered separately.

LED BUILT IN

80 CRI

DIMMABLE

CE

2 YEAR

IP20





Optional non-dimmable driver. Order code 89048.



Optional TRIAC dimmable driver. Order code 89048T.



Optional DALI & Push to DIM driver. Order code 89050L.



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
50130FA/W/D	White	Daylight	6000K	30W	2100lm	120°	230V		280x280mm	50mm	15	Complete with 700mA driver
50130FA/W/C	White	Cool white	4000K	30W	2100lm	120°	230V		280x280mm	50mm	15	Complete with 700mA driver
50130FA/W/W	White	Warm white	3000K	30W	1800lm	120°	230V		280x280mm	50mm	15	Complete with 700mA driver
50130FA/G/D	Grey	Daylight	6000K	30W	2100lm	120°	230V		280x280mm	50mm	15	Complete with 700mA driver
50130FA/G/C	Grey	Cool white	4000K	30W	2100lm	120°	230V		280x280mm	50mm	15	Complete with 700mA driver
50130FA/G/W	Grey	Warm white	3000K	30W	1800lm	120°	230V		280x280mm	50mm	15	Complete with 700mA driver
50148PE/W/C	White	Cool white	4000K	48W	4100lm	120°	1200mA		585x585mm	80mm	4	Requires 1200mA driver
50148PE/W/W	White	Warm white	3000K	48W	3900lm	120°	1200mA		585x585mm	80mm	4	Requires 1200mA driver



The 40W Square Panels
Aluminium



A-A++

50140E | 40W | SMD 4014 | 595x595mm | Aluminium

LED BUILT IN

80 CRI

CE

2 YEAR

IP20



Optional suspension kit.
Order code 050017.



Optional DALI & Push to DIM driver.
Order code 89050L.





A-A++

Germany / Austria

D A

50140AE | 40W | SMD 4014 | 620x620mm | Aluminium

LED BUILT IN

80 CRI

DIMMABLE

CE

2 YEAR

IP20



Optional suspension kit.
Order code 050017.



Optional recessed kit (4pcs).
Order code 050108.



Optional DALI & Push to DIM driver.
Order code 89050L.



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class			Notes
50140E/W/D	White	Daylight	6000K	40W	3400lm	230V	⧈	50mm	6	Complete with 1000mA driver
50140E/W/C	White	Cool white	4000K	40W	3400lm	230V	⧈	50mm	6	Complete with 1000mA driver
50140E/W/W	White	Warm white	3000K	40W	3100lm	230V	⧈	50mm	6	Complete with 1000mA driver
50140AE/W/C	White	Cool white	4000K	40W	3400lm	230V	⧈	50mm	6	Complete with 1000mA driver



The 48W Square Panels

Aluminium



A-A++

50148E | 48W | SMD 2835 | 595x595mm | Aluminium

Driver must be ordered separately.

LED BUILT IN · 80 CRI · DIMMABLE · CE · 2 YEAR · IP20



Optional suspension kit. Order code 050017.



Optional recessed kit (4pcs). Order code 050108.



Optional non-dimmable driver. Order code 89048.



Optional TRIAC dimmable driver. Order code 89048T.



Optional DALI & Push to DIM driver. Order code 89050L.



A-A++

50143F | 48W | SMD 2835 | 595x595mm | Aluminium

Complete with driver.

LED BUILT IN · 80 CRI · CE · 2 YEAR · IP20



Optional suspension kit. Order code 050017.



Optional recessed kit (4pcs). Order code 050108.



Optional TRIAC dimmable driver. Order code 89048T.



Optional DALI & Push to DIM driver. Order code 89050L.



A-A++

Germany / Austria D A

50148AE | 48W | SMD 2835 | 620x620mm | Aluminium

Driver must be ordered separately.

LED BUILT IN · 80 CRI · DIMMABLE · CE · 2 YEAR · IP20



Optional suspension kit. Order code 050017.



Optional recessed kit (4pcs). Order code 050108.



Optional non-dimmable driver. Order code 89048.



Optional TRIAC dimmable driver. Order code 89048T.



Optional DALI & Push to DIM driver. Order code 89050L.

Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class			Notes
50148E/W/C	White	Cool white	4000K	48W	4300lm	1200mA	III	50mm	6	Requires 1200mA driver
50148E/W/W	White	Warm white	3000K	48W	4000lm	1200mA	III	50mm	6	Requires 1200mA driver
50143F/W/D	White	Daylight	6000K	48W	3800lm	230V	□	50mm	4	Complete 1200mA with driver
50148AE/W/C	White	Cool white	4000K	48W	4300lm	1200mA	III	50mm	6	Requires 1200mA driver



Square UGR17 & UGR19 Office Panels

Aluminium



50140U | 40W | SMD 4014 | Aluminium

LED BUILT IN · 80 CRI · CE · 2 YEAR · IP20 · UGR17



Optional suspension kit. Order code 050017.



Optional DALI & Push to DIM driver. Order code 89050L.





50140AU | 40W | SMD 4014 | Aluminium

LED BUILT IN · 80 CRI · CE · 2 YEAR · IP20 · UGR17



Optional suspension kit. Order code 050017.



Optional DALI & Push to DIM driver. Order code 89050L.





50148U | 48W | SMD 2835 | 595x595mm | Aluminium

Driver must be ordered separately.

LED BUILT IN · 80 CRI · DIMMABLE · CE · 2 YEAR · IP20 · UGR19 · 120°



Optional suspension kit. Order code 050017.



Optional recessed kit (4pcs). Order code 050108.



Optional non-dimmable driver. Order code 89048.



Optional TRIAC dimmable driver. Order code 89048T.



Optional DALI & Push to DIM driver. Order code 89050L.



50148AU | 48W | SMD 2835 | 620x620mm | Aluminium

Driver must be ordered separately.

LED BUILT IN · 80 CRI · DIMMABLE · CE · 2 YEAR · IP20 · UGR19 · 120°



Optional suspension kit. Order code 050017.



Optional recessed kit (4pcs). Order code 050108.



Optional non-dimmable driver. Order code 89048.



Optional TRIAC dimmable driver. Order code 89048T.



Optional DALI & Push to DIM driver. Order code 89050L.

Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class			Notes
50140U/W/C	White	Cool white	4000K	40W	3400lm	120°	230V		55mm	6	Complete with 1000mA driver
50140AU/W/C	White	Cool white	4000K	40W	3400lm	120°	230V		55mm	6	Complete with 1000mA driver
50140AU/W/W	White	Warm white	3000K	40W	3100lm	120°	230V		55mm	6	Complete with 1000mA driver
50148U/W/D	White	Daylight	6000K	48W	4100lm	120°	1200mA		55mm	4	Requires 1200mA driver
50148U/W/C	White	Cool white	4000K	48W	4300lm	120°	1200mA		55mm	6	Requires 1200mA driver
50148AU/W/C	White	Cool white	4000K	48W	4300lm	120°	1200mA		55mm	6	Requires 1200mA driver
50148AU/W/W	White	Warm white	3000K	48W	4000lm	120°	1200mA		55mm	6	Requires 1200mA driver



Square IP65 Panels

Aluminium



A-A++

50140W | 40W | SMD 4014 | Aluminium

LED BUILT IN

80 CRI

CE

2 YEAR

IP65



Optional recessed kit (4pcs).
Order code 050108.





A-A++

Germany / Austria

D A

50140AW | 40W | SMD 2835 | Aluminium

LED BUILT IN

80 CRI

CE

2 YEAR

IP65



Optional suspension kit.
Order code 050017.



Optional recessed kit (4pcs).
Order code 050108.



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class			Notes
50140W/W/D	White	Daylight	6000K	40W	3600lm	120°	100-240V		55mm	4	Complete with 900mA driver
50140W/W/C	White	Cool white	4000K	40W	3600lm	120°	100-240V		55mm	4	Complete with 900mA driver
50140AW/W/C	White	Cool white	4000K	40W	3200lm	120°	100-240V		55mm	4	Complete with 1000mA driver



Square UGR19 Pro Panel



50136P | 36W | SMD 2835 | Metal

LED BUILT IN

80 CRI

CE

2 YEAR

IP40

UGR19



Optional recessed kit (4pcs).
Order code 050108A.



Optional DALI & Push
to DIM driver.
Order code 89050L.



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class			Notes
50136P/W/C	White	Cool white	4000K	36W	4320lm	230V		60mm	4	Complete with 900mA driver

Rectangular UGR19 Panel



50136RP | 36W | SMD 4014 | 1200x145mm | Aluminium

LED BUILT IN

80 CRI

CE

2 YEAR

IP40

UGR19



Optional suspension kit.
Order code 050150.



Optional recessed kit (4pcs).
Order code 050108B.



Optional DALI & Push to DIM driver.
Order code 89050L.

Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class				Notes
50136RP/W/C	White	Cool white	4000K	36W	2900lm	230V		1100x125mm	50mm	4	Complete with 900mA driver
50136RP/W/W	White	Warm white	3000K	36W	2900lm	230V		1100x125mm	50mm	4	Complete with 900mA driver



The Rectangular Panels

Aluminium



A-A++

50148RE | 48W | SMD 2835 | 1195x295mm | Aluminium

Driver must be ordered separately.

LED BUILT IN · 80 CRI · DIMMABLE · CE · IP20 · 2 YEAR



Optional suspension kit. Order code 050017.

Requires 2 sets.



Optional recessed kit (4pcs). Order code 050108.



Optional non-dimmable driver. Order code 89048.



Optional TRIAC dimmable driver. Order code 89048T.



Optional DALI & Push to DIM driver. Order code 89050L.



A-A++

50160E | 60W | SMD 4014 | 1195x595mm | Aluminium

Driver must be ordered separately.

LED BUILT IN · 80 CRI · DIMMABLE · CE · IP20 · 2 YEAR



Optional suspension kit. Order code 050017.

Requires 2 sets.



Optional recessed kit (4pcs). Order code 050108.



Non-dimmable driver. Order code 89060.



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class			Notes
50148RE/W/D	White	Daylight	6000K	48W	4100lm	1200mA	III	50mm	4	Requires 1200mA driver
50148RE/W/C	White	Cool white	4000K	48W	4100lm	1200mA	III	50mm	4	Requires 1200mA driver
50148RE/W/W	White	Warm white	3000K	48W	3900lm	1200mA	III	50mm	4	Requires 1200mA driver
50160E/W/D	White	Daylight	6000K	60W	4900lm	1300mA	III	50mm	2	Requires 1300mA driver
50160E/W/C	White	Cool white	4000K	60W	5400lm	1300mA	III	50mm	2	Requires 1300mA driver
50160E/W/W	White	Warm white	3000K	60W	5100lm	1300mA	III	50mm	2	Requires 1300mA driver



10122FD/W/C



10116FD/W/C



10108FD/W/C

The Dark Light Dome Reflector

Die cast



A-A++

10108FD | 8W | SMD 2835 | Die cast

LED BUILT IN

80 CRI

2 YEAR

DARK LIGHT

IP20







A-A++

10116FD | 16W | SMD 2835 | Die cast

LED BUILT IN

80 CRI

2 YEAR

DARK LIGHT

IP20







A-A++

10122FD | 22W | SMD 2835 | Die cast

LED BUILT IN

80 CRI

2 YEAR

DARK LIGHT

IP20





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class				Notes
10108FD/W/C	White	Cool white	4000K	8W	560lm	230V	☐	94mm	60mm	45	Complete with 300mA driver
10108FD/W/W	White	Warm white	3000K	8W	560lm	230V	☐	94mm	60mm	45	Complete with 300mA driver
10116FD/W/C	White	Cool white	4000K	16W	1150lm	230V	☐	155mm	80mm	20	Complete with 300mA driver
10116FD/W/W	White	Warm white	3000K	16W	1150lm	230V	☐	155mm	80mm	20	Complete with 300mA driver
10122FD/W/C	White	Cool white	4000K	22W	1550lm	230V	☐	210mm	90mm	20	Complete with 600mA driver
10122FD/W/W	White	Warm white	3000K	22W	1550lm	230V	☐	210mm	90mm	20	Complete with 600mA driver



The Budget Downlight Range

Aluminium



A-A++

10103T | 3W | SMD 2835 | Aluminium

LED BUILT IN

80 CRI

CE

2 YEAR

IP20







A-A++

10107T | 7W | SMD 2835 | Aluminium

LED BUILT IN

80 CRI

CE

2 YEAR

IP20







A-A++

10115T | 15W | SMD 2835 | Aluminium

LED BUILT IN

80 CRI

CE

2 YEAR

IP20





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
10103T/W/C	White	Cool white	4000K	3W	220lm	120°	230V		68mm	50mm	100	Complete with 280mA driver
10103T/W/W	White	Warm white	3000K	3W	210lm	120°	230V		68mm	50mm	100	Complete with 280mA driver
10107T/W/C	White	Cool white	4000K	7W	520lm	120°	230V		85mm	60mm	60	Complete with 280mA driver
10107T/W/W	White	Warm white	3000K	7W	490lm	120°	230V		85mm	60mm	60	Complete with 280mA driver
10115T/W/C	White	Cool white	4000K	15W	1100lm	120°	230V		130mm	60mm	30	Complete with 280mA driver
10115T/W/W	White	Warm white	3000K	15W	1050lm	120°	230V		130mm	60mm	30	Complete with 280mA driver

The Budget Downlight Range

Aluminium





10124T | 24W | SMD 2835 | Aluminium

LED BUILT IN
80 CRI
2 YEAR
IP20







10130T | 30W | SMD 2835 | Aluminium

LED BUILT IN
80 CRI
2 YEAR
IP20





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
10124T/W/C	White	Cool white	4000K	24W	1800lm	120°	230V	⧈	210mm	75mm	20	Complete with 600mA driver
10124T/W/W	White	Warm white	3000K	24W	1700lm	120°	230V	⧈	210mm	75mm	20	Complete with 600mA driver
10130T/W/C	White	Cool white	4000K	30W	2250lm	120°	230V	⧈	210mm	75mm	20	Complete with 700mA driver
10130T/W/W	White	Warm white	3000K	30W	2100lm	120°	230V	⧈	210mm	75mm	20	Complete with 700mA driver



The Chrome Bezel Range

Aluminium



A-A++ 10115/W/C

10115 | 15W | SMD 2835 | Aluminium

LED BUILT IN

80 CRI

CE

2 YEAR

IP44



10115/G/C





A-A++ 10124/W/C

10124 | 24W | SMD 2835 | Aluminium

LED BUILT IN

80 CRI

CE

2 YEAR

IP44



10124/G/C



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
10115/W/C	White	Cool white	4000K	15W	1050lm	120°	230V		160mm	150mm	8	Complete with 300mA driver
10115/W/W	White	Warm white	3000K	15W	1000lm	120°	230V		160mm	150mm	8	Complete with 300mA driver
10115/G/C	Grey	Cool white	4000K	15W	1050lm	120°	230V		160mm	150mm	8	Complete with 300mA driver
10124/W/C	White	Cool white	4000K	24W	1550lm	120°	230V		210mm	160mm	8	Complete with 600mA driver
10124/G/C	Grey	Cool white	4000K	24W	1550lm	120°	230V		210mm	160mm	8	Complete with 600mA driver
10124/G/W	Grey	Warm white	3000K	24W	1450lm	120°	230V		210mm	160mm	8	Complete with 600mA driver



The COB Downlight Range

Aluminium

10110C | 10W | COB LED | Aluminium



A-A++

LED BUILT IN
80 CRI
2 YEAR
IP20





10120C | 20W | COB LED | Aluminium



A-A++ 10120C/W/W

LED BUILT IN
80 CRI
2 YEAR
IP20



10120C/G/W



10130C | 30W | COB LED | Aluminium



A-A++ 10130C/W/W

LED BUILT IN
80 CRI
2 YEAR
IP20



10130C/G/W



10130CR | 30W | COB LED | Aluminium

90CRI.



A-A++

LED BUILT IN
90 CRI
2 YEAR
IP20





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
10110C/G/W	Grey	Warm white	3000K	10W	700lm	80°	230V	☐	95mm	90mm	40	Complete with 260mA driver
10120C/W/W	White	Warm white	3000K	20W	1400lm	80°	230V	☐	160mm	100mm	18	Complete with 500mA driver
10120C/G/C	Grey	Cool white	4000K	20W	1400lm	80°	230V	☐	160mm	100mm	18	Complete with 500mA driver
10120C/G/W	Grey	Warm white	3000K	20W	1400lm	80°	230V	☐	160mm	100mm	18	Complete with 500mA driver
10130C/W/W	White	Warm white	3000K	30W	2200lm	80°	230V	☐	210mm	120mm	9	Complete with 850mA driver
10130C/G/C	Grey	Cool white	4000K	30W	2200lm	80°	230V	☐	210mm	120mm	9	Complete with 850mA driver
10130C/G/W	Grey	Warm white	3000K	30W	2200lm	80°	230V	☐	210mm	120mm	9	Complete with 850mA driver
10130CR/W/W	White	Warm white	3000K	30W	2200lm	80°	230V	☐	210mm	120mm	9	Complete with 850mA driver

The COB Downlight Range

Die cast



10107CA | 7W | COB LED | Die cast



A-A++

LED BUILT IN
80 CRI
CE
2 YEAR
IP20





10110CA | 10W | COB LED | Die cast



A-A++

LED BUILT IN
80 CRI
CE
2 YEAR
IP20





10115CA | 15W | COB LED | Die cast



A-A++

LED BUILT IN
80 CRI
CE
2 YEAR
IP20





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
10107CA/W/C	White	Cool white	4000K	7W	560lm	60°	230V		75mm	70mm	50	Complete with 300mA driver
10107CA/W/W	White	Warm white	3000K	7W	560lm	60°	230V		75mm	70mm	50	Complete with 300mA driver
10110CA/W/C	White	Cool white	4000K	10W	850lm	60°	230V		95mm	100mm	50	Complete with 300mA driver
10110CA/W/W	White	Warm white	3000K	10W	850lm	60°	230V		95mm	100mm	50	Complete with 300mA driver
10115CA/W/C	White	Cool white	4000K	15W	1275lm	60°	230V		125mm	100mm	30	Complete with 350mA driver
10115CA/W/W	White	Warm white	3000K	15W	1275lm	60°	230V		125mm	100mm	30	Complete with 350mA driver



The COB Downlight Range

Die cast



10120CA | 20W | COB LED | Die cast

LED BUILT IN · 80 CRI · CE · 2 YEAR · IP20 · A-A++







10130CA | 30W | COB LED | Die cast

LED BUILT IN · 80 CRI · CE · 2 YEAR · IP20 · A-A++







10160CA | 60W | COB LED | Die cast

LED BUILT IN · 80 CRI · CE · 2 YEAR · IP20 · A-A++





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
10120CA/W/C	White	Cool white	4000K	20W	1800lm	60°	230V	☐	145mm	100mm	20	Complete with 500mA driver
10120CA/W/W	White	Warm white	3000K	20W	1800lm	60°	230V	☐	145mm	100mm	20	Complete with 500mA driver
10130CA/W/C	White	Cool white	4000K	30W	2700lm	60°	230V	☐	210mm	140mm	10	Complete with 750mA driver
10130CA/W/W	White	Warm white	3000K	30W	2700lm	60°	230V	☐	210mm	140mm	10	Complete with 750mA driver
10160CA/W/C	White	Cool white	4000K	60W	5400lm	60°	230V	☐	210mm	160mm	10	Complete with 1500mA driver
10160CA/W/W	White	Warm white	3000K	60W	5400lm	60°	230V	☐	210mm	160mm	10	Complete with 1500mA driver

The Semi Dark Light COB Pro Range

Die cast



10130CD/W/C



10115CD/W/C



10107CD/W/C



A-A++

10107CD | 7W | COB LED | Die cast

LED BUILT IN

80 CRI

2 YEAR

IP20





110mm



60mm



120°



A-A++

10115CD | 15W | COB LED | Die cast

LED BUILT IN

80 CRI

2 YEAR

IP20





170mm



75mm



120°

Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
10107CD/W/C	White	Cool white	4000K	7W	560lm	120°	230V	☐	100mm	70mm	30	Complete with 300mA driver
10107CD/W/W	White	Warm white	3000K	7W	511lm	120°	230V	☐	100mm	70mm	30	Complete with 300mA driver
10115CD/W/C	White	Cool white	4000K	15W	1200lm	120°	230V	☐	160mm	90mm	18	Complete with 400mA driver
10115CD/W/W	White	Warm white	3000K	15W	1095lm	120°	230V	☐	160mm	90mm	18	Complete with 400mA driver



The Semi Dark Light COB Pro Range

Die cast

10130CD | 30W | COB LED | Die cast



LED BUILT IN

80 CRI

IP20









10140CD | 40W | COB LED | Die cast



LED BUILT IN

80 CRI

IP20









Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
10130CD/W/C	White	Cool white	4000K	30W	2400lm	120°	230V	☐	215mm	100mm	6	Complete with 700mA driver
10130CD/W/W	White	Warm white	3000K	30W	2190lm	120°	230V	☐	215mm	100mm	6	Complete with 700mA driver
10140CD/W/C	White	Cool white	4000K	40W	3200lm	120°	230V	☐	245mm	100mm	6	Complete with 1000mA driver



Dark light Pro Range

Aluminium



A-A++ 10108ED/W/B/W

10108ED | 8W | SMD 2835 | Aluminium

LED BUILT IN · 80 CRI · CE · 2 YEAR · DARK LIGHT · IP20







A-A++ 10112ED/W/B/W

10112ED | 12W | SMD 2835 | Aluminium

LED BUILT IN · 80 CRI · CE · 2 YEAR · DARK LIGHT · IP20







A-A++ 10130ED/W/B/W

10130ED | 30W | SMD 2835 | Aluminium

LED BUILT IN · 80 CRI · CE · 2 YEAR · DARK LIGHT · IP20





Order Code	Colour	Reflector	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
10108ED/W/B/W	White	Black	Warm white	3000K	8W	480lm	60°	230V	☐	75mm	80mm	50	Complete with 300mA driver
10112ED/W/B/W	White	Black	Warm white	3000K	12W	720lm	60°	230V	☐	92mm	95mm	50	Complete with 300mA driver
10130ED/W/B/W	White	Black	Warm white	3000K	30W	1800lm	60°	230V	☐	145mm	130mm	20	Complete with 750mA driver



Dark light Pro Range

Aluminium



A-A++ 10108ED/W/BS/W

10108ED | 8W | SMD 2835 | Aluminium







A-A++ 10112ED/W/BS/W

10112ED | 12W | SMD 2835 | Aluminium







A-A++ 10130ED/W/BS/W

10130ED | 30W | SMD 2835 | Aluminium





Order Code	Colour	Reflector	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
10108ED/W/BS/W	White	Brass	Warm white	3000K	8W	560lm	60°	230V		75mm	80mm	50	Complete with 300mA driver
10112ED/W/BS/W	White	Brass	Warm white	3000K	12W	840lm	60°	230V		92mm	95mm	50	Complete with 300mA driver
10130ED/W/BS/W	White	Brass	Warm white	3000K	30W	2100lm	60°	230V		145mm	130mm	20	Complete with 750mA driver



The COB Project Round Range

10105K | 5W | COB LED | Die cast



A-A++ 10105K/W/W

LED BUILT IN

80 CRI

CE

2 YEAR

IP53



10105K/G/W





10110K | 10W | COB LED | Die cast



A-A++ 10110K/W/W

LED BUILT IN

80 CRI

TRIAC DIMMABLE

CE

2 YEAR

IP53



10110K/G/W





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
10105K/W/C	White	Cool white	4000K	5W	410lm	100°	230V		107mm	130mm	24	Complete with 120mA dimmable driver
10105K/W/W	White	Warm white	3000K	5W	350lm	100°	230V		107mm	130mm	24	Complete with 120mA dimmable driver
10105K/G/C	Grey	Cool white	4000K	5W	410lm	100°	230V		107mm	130mm	24	Complete with 120mA dimmable driver
10105K/G/W	Grey	Warm white	3000K	5W	350lm	100°	230V		107mm	130mm	24	Complete with 400mA driver
10110K/W/W	White	Warm white	3000K	10W	600lm	100°	230V		122mm	150mm	24	Complete with 250mA dimmable driver
10110K/G/W	Grey	Warm white	3000K	10W	600lm	100°	230V		122mm	150mm	24	Complete with 250mA dimmable driver



The COB Project Round Range

Dimmable



10120K | 20W | COB LED | Die cast

LED BUILT IN · 80 CRI · TRIAC DIMMABLE · CE · IP53 · 2 YEAR







10130K | 30W | COB LED | Die cast

LED BUILT IN · 80 CRI · TRIAC DIMMABLE · CE · IP53 · 2 YEAR







10130KA/G/W

10130KA | 30W | COB LED | Die cast

LED BUILT IN · 80 CRI · TRIAC DIMMABLE · CE · IP53 · 2 YEAR



10130KA/W/W





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
10120K/G/W	Grey	Warm white	3000K	20W	1500lm	100°	230V	⧈	150mm	170mm	24	Complete with 500mA dimmable driver
10130K/G/W	Grey	Warm white	3000K	30W	2000lm	100°	230V	⧈	175mm	195mm	12	Complete with 700mA dimmable driver
10130KA/W/W	White	Warm white	3000K	30W	2000lm	100°	230V	⧈	210mm	210mm	12	Complete with 700mA dimmable driver
10130KA/G/W	Grey	Warm white	3000K	30W	2000lm	100°	230V	⧈	210mm	210mm	12	Complete with 700mA dimmable driver



The COB Project Square Range

Die cast

50105K | 5W | COB LED | Die cast



A-A++ 50105K/W/W

LED BUILT IN
80 CRI
CE
2 YEAR
IP53



50105K/G/C



50120K | 20W | COB LED | Die cast



A-A++ 50120K/W/C

LED BUILT IN
80 CRI
CE
2 YEAR
IP53



50120K/G/C



50130K | 30W | COB LED | Die cast



A-A++ 50130K/W/C

LED BUILT IN
80 CRI
CE
2 YEAR
IP53



50130K/G/C



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
50105K/W/W	White	Warm white	3000K	5W	240lm	100°	230V		85x85mm	115mm	24	Complete with 400mA driver
50105K/G/C	Grey	Cool white	4000K	5W	310lm	100°	230V		85x85mm	115mm	24	Complete with 400mA driver
50120K/W/C	White	Cool white	4000K	20W	1060lm	100°	230V		147x147mm	160mm	12	Complete with 700mA driver
50120K/G/C	Grey	Cool white	4000K	20W	1060lm	100°	230V		147x147mm	160mm	12	Complete with 700mA driver
50120K/G/W	Grey	Warm white	3000K	20W	930lm	100°	230V		147x147mm	160mm	12	Complete with 700mA driver
50130K/G/C	Grey	Cool white	4000K	30W	1770lm	100°	230V		147x147mm	160mm	12	Complete with 1100mA driver
50130K/G/W	Grey	Warm white	3000K	30W	1350lm	100°	230V		147x147mm	160mm	12	Complete with 1100mA driver



10120 | 20W | LED | Aluminium

Ring must be ordered separately.



A-A++ 10120/W+10100/W

LED BUILT IN

75 CRI

CE

2 YEAR

IP44



10120/W+10100/AL





10142 | 42W | COB LED | Aluminium

Ring must be ordered separately.



A-A++ 10142/W+10100/W

LED BUILT IN

80 CRI

CE

2 YEAR

IP20



10142/W+10100/AL





10100 | Rings for 10120 & 10142



CE

10100/AL Aluminium
10100/W White
10100/G Grey

50



10140P | 40W | COB LED | Aluminium



A-A++

LED BUILT IN

80 CRI

CE

2 YEAR

DARK LIGHT

IP20



Optional black ring.
Order code 050097/B.



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
10120/C	-	Cool white	4000K	20W	1800lm	110°	230V	☐	180mm	70mm	10	Complete with 320mA driver
10120/W	-	Warm white	3000K	20W	1800lm	110°	230V	☐	180mm	70mm	10	Complete with 320mA driver
10142/W	-	Warm white	3000K	42W	3225lm	60°	100-240V	☐	180mm	170mm	4	Complete with 1000mA driver
10140P/W/C	White	Cool white	4000K	40W	3400lm	60°	230V	☐	190mm	150mm	12	Complete with 1000mA driver
10140P/W/W	White	Warm white	3000K	40W	3200lm	60°	230V	☐	190mm	150mm	12	Complete with 1000mA driver



10112/G/D



10128/G/D

Architectural Downlights

Die cast



A-A++

10112/G/D | 9W | LED | Die cast

LED BUILT IN
80 CRI
IP20
offer







A-A++

10112/G/W | 12W | LED | Die cast

LED BUILT IN
80 CRI
IP20
offer







A-A++

10128 | 28W | LED | Die cast

LED BUILT IN
80 CRI
IP20
offer





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
10112/G/D	Grey	Daylight	6000K	9W	400lm	90°	230V	⧈	89mm	110mm	10	Complete with driver
10112/G/W	Grey	Warm white	3000K	12W	400lm	90°	230V	⧈	89mm	110mm	10	Complete with driver
10128/G/D	Grey	Daylight	6000K	28W	1400lm	90°	230V	⧈	169mm	110mm	10	Complete with driver
10128/G/W	Grey	Warm white	3000K	28W	1150lm	90°	230V	⧈	169mm	110mm	10	Complete with driver



10112KD/W/C

10107KD/W/W

The SMD Dark Light Range

Plastic



A-A++

10107KD | 7W | SMD LED | Plastic

LED BUILT IN
80 CRI
DIMMABLE
QUICK FIX
DARK LIGHT
IP20
2 YEAR







A-A++

10112KD | 12W | SMD LED | Plastic

LED BUILT IN
80 CRI
DIMMABLE
QUICK FIX
DARK LIGHT
IP20
2 YEAR





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
10107KD/W/W	White	Warm white	3000K	7W	500lm	100°	350mA	III	30cm	113mm	125mm	24	Requires 350mA driver
10112KD/W/C	White	Cool white	4000K	12W	900lm	100°	350mA	III	30cm	168mm	160mm	12	Requires 350mA driver

Dark Light Downlights

Aluminium



10105E | 5W | LED | Natural aluminium



A-A++

DARK LIGHT · IP40 · offer · LED BUILT IN · DIMMABLE · QUICK FIX · CE · 3 YEAR





10115E | 15W | LED | Semi trimless | Natural aluminium



A-A++

DARK LIGHT · IP40 · offer · LED BUILT IN · DIMMABLE · QUICK FIX · CE · 3 YEAR





10130A | 30W | SMD LED | Aluminium



A-A++ 10130A/AL/W

DARK LIGHT · IP20 · offer · LED BUILT IN · 80 CRI · CE · 2 YEAR



10130A/W/W

offer



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class	S				Notes
10105E/AL/C	Aluminium	Cool white	4000K	5W	375lm	-	500mA	III	40cm	85mm	110mm	20	Requires 500mA driver
10105E/AL/W	Aluminium	Warm white	3000K	5W	360lm	-	500mA	III	40cm	85mm	110mm	20	Requires 500mA driver
10115E/AL/C	Aluminium	Cool white	4000K	15W	1125lm	-	700mA	III	40cm	125mm	150mm	20	Requires 700mA driver
10115E/AL/W	Aluminium	Warm white	3000K	15W	1050lm	-	700mA	III	40cm	125mm	150mm	20	Requires 700mA driver
10130A/AL/W	Aluminium	Warm white	3000K	30W	2300lm	80°	100-240V	□	-	210mm	170mm	5	Complete with 350mA driver
10130A/W/W	White	Warm white	3000K	30W	2300lm	80°	100-240V	□	-	210mm	170mm	5	Complete with 350mA driver



The COB Dark Light Range



10113A | 15W | COB LED | Aluminium

LED BUILT IN
80 CRI
3 YEAR
DARK LIGHT
IP20







10150T | 38W/50W | COB LED | Trimless | Die cast

38W@1050mA / 50w@1400mA

LED BUILT IN
90 CRI
DIMMABLE
QUICK FIX
DARK LIGHT
IP20
3 YEAR



Optional non-dimmable driver. Order code 89048.



Optional TRIAC dimmable driver. Order code 89048T.



Optional DALI & Push to DIM driver. Order code 89050L.



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class	S				Notes
10113A/W/W	White	Warm white	3000K	15W	1000lm	50°	100-240V		-	95mm	130mm	20	Complete with 350mA driver
10150T/W/C	White	Cool white	4000K	38W/50W	2700lm/3750lm	24°	1050mA/1400mA		50cm	170mm	160mm	6	Requires 1050mA/1400mA driver
10150T/W/W	White	Warm white	3000K	38W/50W	2500lm/3500lm	24°	1050mA/1400mA		50cm	170mm	160mm	6	Requires 1050mA/1400mA driver



Shop Square Boxes

50120B | 20W | COB LED | Aluminium + metal



LED BUILT IN
80 CRI
3 YEAR
new
IP20





50220B | 2x20W | COB LED | Aluminium + metal



LED BUILT IN
80 CRI
3 YEAR
new
IP20





50130B | 30W | COB LED | Aluminium + metal



LED BUILT IN
80 CRI
3 YEAR
new
IP20





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
50120B/W/C	White	Cool white	4000K	20W	1800lm	30°	230V	☐	105x105mm	120mm	20	Complete with 500mA driver
50120B/W/W	White	Warm white	3000K	20W	1700lm	30°	230V	☐	105x105mm	120mm	20	Complete with 500mA driver
50120B/B/W	Black	Warm white	3000K	20W	1700lm	30°	230V	☐	105x105mm	120mm	20	Complete with 500mA driver
50220B/W/C	White	Cool white	4000K	2x20W	2x1800lm	30°	230V	☐	190x110mm	120mm	10	Complete with 500mA drivers
50220B/W/W	White	Warm white	3000K	2x20W	2x1700lm	30°	230V	☐	190x110mm	120mm	10	Complete with 500mA drivers
50220B/B/W	Black	Warm white	3000K	2x20W	2x1700lm	30°	230V	☐	190x110mm	120mm	10	Complete with 500mA drivers
50130B/W/C	White	Cool white	4000K	30W	2700lm	30°	230V	☐	130x130mm	120mm	16	Complete with 750mA driver
50130B/W/W	White	Warm white	3000K	30W	2600lm	30°	230V	☐	130x130mm	120mm	16	Complete with 750mA driver
50130B/B/W	Black	Warm white	3000K	30W	2600lm	30°	230V	☐	130x130mm	120mm	16	Complete with 750mA driver



The SMD Dark Light Range

10109D | 9W | SMD 2835 | Die cast



A-A++ 10109D/W/W

new
DARK LIGHT
IP20

LED BUILT IN
80 CRI
CE
2 YEAR



10109D/B/W



10122D | 22W | SMD 2835 | Die cast



A-A++ 10122D/W/W

new
DARK LIGHT
IP20

LED BUILT IN
80 CRI
CE
2 YEAR



10122D/B/W



50122D | 22W | SMD 2835 | Die cast



A-A++ 50122D/W/W

new
DARK LIGHT
IP20

LED BUILT IN
80 CRI
CE
2 YEAR



50122D/W/C



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
10109D/W/C	White	Cool white	4000K	9W	765lm	100°	230V		110mm	70mm	50	Complete with 300mA driver
10109D/W/W	White	Warm white	3000K	9W	720lm	100°	230V		110mm	70mm	50	Complete with 300mA driver
10109D/B/C	Black	Cool white	4000K	9W	765lm	100°	230V		110mm	70mm	50	Complete with 300mA driver
10109D/B/W	Black	Warm white	3000K	9W	720lm	100°	230V		110mm	70mm	50	Complete with 300mA driver
10122D/W/C	White	Cool white	4000K	22W	1870lm	100°	230V		165mm	75mm	20	Complete with 500mA driver
10122D/W/W	White	Warm white	3000K	22W	1760lm	100°	230V		165mm	75mm	20	Complete with 500mA driver
10122D/B/C	Black	Cool white	4000K	22W	1870lm	100°	230V		165mm	75mm	20	Complete with 500mA driver
10122D/B/W	Black	Warm white	3000K	22W	1760lm	100°	230V		165mm	75mm	20	Complete with 500mA driver
50122D/W/C	White	Cool white	4000K	22W	1870lm	100°	230V		160x160mm	75mm	20	Complete with 500mA driver
50122D/W/W	White	Warm white	3000K	22W	1760lm	100°	230V		160x160mm	75mm	20	Complete with 500mA driver



The IP54 Dark Light Bathroom Downlights

Die cast



A-A++

10109FD | 9W | SMD 2835 | Die cast

LED BUILT IN

80 CRI

2 YEAR

DARK LIGHT

IP54







A-A++

10120FD | 20W | SMD 2835 | Die cast

LED BUILT IN

80 CRI

2 YEAR

DARK LIGHT

IP54





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
10109FD/W/C	White	Cool white	4000K	9W	765lm	100°	230V	⧈	111mm	70mm	40	Complete with 300mA driver
10109FD/W/W	White	Warm white	3000K	9W	765lm	100°	230V	⧈	111mm	70mm	40	Complete with 300mA driver
10120FD/W/C	White	Cool white	4000K	20W	1700lm	100°	230V	⧈	166mm	70mm	20	Complete with 300mA driver
10120FD/W/W	White	Warm white	3000K	20W	1700lm	100°	230V	⧈	166mm	70mm	20	Complete with 300mA driver



The IP54 Bathroom Downlights

10107B | 7W | SMD 2835 | Die cast



A-A++

LED BUILT IN · 80 CRI · CE · 2 YEAR · IP54





10113B | 13W | SMD 2835 | Die cast



A-A++

LED BUILT IN · 80 CRI · CE · 2 YEAR · IP54





10118B | 18W | SMD 2835 | Die cast



A-A++

LED BUILT IN · 80 CRI · CE · 2 YEAR · IP54





10125B | 25W | SMD 2835 | Die cast



A-A++

LED BUILT IN · 80 CRI · CE · 2 YEAR · IP54





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
10107B/W/C	White	Cool white	4000K	7W	540lm	90°	100-240V	☐	65mm	70mm	50	Complete with 260mA driver
10107B/W/W	White	Warm white	3000K	7W	500lm	90°	100-240V	☐	65mm	70mm	50	Complete with 260mA driver
10113B/W/C	White	Cool white	4000K	13W	950lm	90°	100-240V	☐	95mm	70mm	24	Complete with 380mA driver
10113B/W/W	White	Warm white	3000K	13W	925lm	90°	100-240V	☐	95mm	70mm	24	Complete with 380mA driver
10118B/W/C	White	Cool white	4000K	18W	1400lm	90°	100-240V	☐	140mm	70mm	30	Complete with 500mA driver
10118B/W/W	White	Warm white	3000K	18W	1300lm	90°	100-240V	☐	140mm	70mm	30	Complete with 500mA driver
10125B/W/C	White	Cool white	4000K	25W	2000lm	90°	100-240V	☐	210mm	80mm	10	Complete with 700mA driver
10125B/W/W	White	Warm white	3000K	25W	1875lm	90°	100-240V	☐	210mm	80mm	10	Complete with 700mA driver



The Outdoor/Bathroom IP65 Range

Die cast



10110G | 10W | COB LED | Die cast

LED BUILT IN

80 CRI

3 YEAR

IP65







10115G | 15W | COB LED | Die cast

LED BUILT IN

80 CRI

3 YEAR

IP65





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
10110G/W/C	White	Cool white	4000K	10W	800lm	60°	230V	☐	200cm	82mm	90mm	30	Complete with 250mA driver
10110G/W/W	White	Warm white	3000K	10W	750lm	60°	230V	☐	200cm	82mm	90mm	30	Complete with 250mA driver
10115G/W/C	White	Cool white	4000K	15W	1200lm	60°	230V	☐	200cm	100mm	95mm	20	Complete with 350mA driver
10115G/W/W	White	Warm white	3000K	15W	1125lm	60°	230V	☐	200cm	100mm	95mm	20	Complete with 350mA driver



The Outdoor/Bathroom IP65 Range

Die cast



10120G | 20W | COB LED | Die cast

LED BUILT IN · 80 CRI · CE · 3 YEAR · IP65 · A-A++







10130G | 30W | COB LED | Die cast

LED BUILT IN · 80 CRI · CE · 3 YEAR · IP65 · A-A++







10150G | 50W | COB LED | Die cast

LED BUILT IN · 80 CRI · CE · 3 YEAR · IP65 · A-A++





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
10120G/W/C	White	Cool white	4000K	20W	1600lm	60°	230V	☐	200cm	120mm	105mm	10	Complete with 500mA driver
10120G/W/W	White	Warm white	3000K	20W	1500lm	60°	230V	☐	200cm	120mm	105mm	10	Complete with 500mA driver
10130G/W/C	White	Cool white	4000K	30W	2600lm	60°	230V	☐	200cm	160mm	120mm	8	Complete with 750mA driver
10130G/W/W	White	Warm white	3000K	30W	2500lm	60°	230V	☐	200cm	160mm	120mm	8	Complete with 750mA driver
10150G/W/C	White	Cool white	4000K	50W	4100lm	60°	230V	☐	200cm	210mm	140mm	4	Complete with 1200mA driver
10150G/W/W	White	Warm white	3000K	50W	4000lm	60°	230V	☐	200cm	210mm	140mm	4	Complete with 1200mA driver



The Frameless IP65 Range

Die cast + PC



A-A++

10106CF | 6W | SMD 4014 | Die cast + PC

LED BUILT IN

80 CRI

IK08

CE

2 YEAR

IP65



Frameless





A-A++

10108CF | 8W | SMD 4014 | Die cast + PC

LED BUILT IN

80 CRI

IK08

CE

2 YEAR

IP65



Frameless



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
10106CF/C	White	Cool white	4000K	6W	400lm	120°	230V	☐	55mm	40mm	40	Complete with 250mA driver
10106CF/W	White	Warm white	3000K	6W	400lm	120°	230V	☐	55mm	40mm	40	Complete with 250mA driver
10108CF/C	White	Cool white	4000K	8W	550lm	120°	230V	☐	80mm	50mm	40	Complete with 500mA driver
10108CF/W	White	Warm white	3000K	8W	550lm	120°	230V	☐	80mm	50mm	40	Complete with 500mA driver



The Frameless IP65 Range



10115CF | 15W | SMD 4014 | Die cast + PC

LED BUILT IN · 80 CRI · IK08 · CE · 2 YEAR · IP65



Frameless





050146/W White

050146 | Surface base for 10115CF | Die cast

CE · 5 YEAR · IP40



050146/B Black

20





10130CF | 30W | SMD 4014 | Die cast + PC

LED BUILT IN · 80 CRI · IK08 · CE · 2 YEAR · IP65



Frameless





050148/W White

050148 | Surface base for 10130CF | Die cast

CE · 5 YEAR · IP40



050148/B Black

20



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
10115CF/C	White	Cool white	4000K	15W	1200lm	120°	230V	☐	135mm	50mm	20	Complete with 500mA driver
10115CF/W	White	Warm white	3000K	15W	1200lm	120°	230V	☐	135mm	50mm	20	Complete with 500mA driver
10130CF/C	White	Cool white	4000K	30W	2400lm	120°	230V	☐	195mm	50mm	20	Complete with 1050mA driver
10130CF/W	White	Warm white	3000K	30W	2400lm	120°	230V	☐	195mm	50mm	20	Complete with 1050mA driver





07

Downlights Adjustable

Pages 189-202

R111 | PAR30 | HQI | E27 | G53 | G12

Die cast | Natural aluminium | Metal | Gypsum | Trimless

IP20





Adjustable Round

Die cast



11110D | 75W | R111 | GU10 | Die cast

ADJUSTABLE

5 YEAR

IP20



Suitable for R111 LED lamp.





11070RD | 75W | PAR30 | E27 | Die cast

ADJUSTABLE

QUICK FIX

5 YEAR

IP20

offer



Suitable for PAR30 LED lamp.





Order Code	Colour	Watts	Input	Class					Notes
11110D/W	White	75W	100-240V		15cm	155mm	80mm	36	-
11070RD/G	Grey	75W	100-240V		30cm	155mm	180mm	12	-



Adjustable R111 Shop Range

Aluminium



E-A++

11110N | 75W | R111 | G53 | Aluminium

ADJUSTABLE

5 YEAR

IP20



Suitable for R111 LED lamp.





E-A++

51110N | 75W | R111 | G53 | Aluminium

ADJUSTABLE

5 YEAR

IP20



Suitable for R111 LED lamp.





E-A++

51210N | 2x75W | R111 | G53 | Aluminium

ADJUSTABLE

5 YEAR

IP20



Suitable for R111 LED lamps.





E-A++

51310N | 3x75W | R111 | G53 | Aluminium

ADJUSTABLE

5 YEAR

IP20



Suitable for R111 LED lamps.



Order Code	Colour	Watts	Input	Class					Notes
11110N/W	White	75W	12V		30cm	165mm	160mm	30	-
51110N/W	White	75W	12V		30cm	165x165mm	160mm	30	-
51210N/W	White	2x75W	12V		30cm	315x165mm	160mm	15	-
51310N/W	White	3x75W	12V		30cm	460x165mm	160mm	10	-



Adjustable R111 Range

Die cast



11110U | 75W | R111 | G53 | Die cast







51110 | 50W | R111 | G53 | Die cast





Order Code	Colour	Watts	Input	Class					Notes
11110U/G	Grey	75W	12V		30cm	152mm	180mm	18	-
51110/W	White	50W	12V		15cm	180x180mm	120mm	8	-
51110/G	Grey	50W	12V		15cm	180x180mm	120mm	8	-



Aluminium R111 Round



E-A++ 11110AB/W

11110AB | 75W | R111 | G53 | Aluminium

ADJUSTABLE

5 YEAR

IP20



Suitable for R111 LED lamp.





E-A++ 11110AB/B

11110AB | 75W | R111 | G53 | Aluminium

ADJUSTABLE

5 YEAR

IP20

offer



Suitable for R111 LED lamp.





E-A++ 11110AB/AL

11110AB | 75W | R111 | G53 | Natural aluminium

ADJUSTABLE

5 YEAR

IP20



Suitable for R111 LED lamp.



Order Code	Colour	Watts	Input	Class					Notes
11110AB/W	White	75W	12V	III	40cm	150mm	75mm	20	-
11110AB/B	Black	75W	12V	III	40cm	150mm	75mm	20	-
11110AB/AL	Aluminium	75W	12V	III	40cm	150mm	75mm	20	-





E-A++ 51110AB/W

51110AB | 75W | R111 | G53 | Aluminium

ADJUSTABLE

5 YEAR

IP20



Suitable for R111 LED lamp.





E-A++ 51110AB/B

51110AB | 75W | R111 | G53 | Natural aluminium

ADJUSTABLE

5 YEAR

IP20



Suitable for R111 LED lamp.



Order Code	Colour	Watts	Input	Class					Notes
51110AB/W	White	75W	12V	III	40cm	150mm	75mm	20	-
51110AB/B	Black	75W	12V	III	40cm	150mm	75mm	20	-



51110AB/B



51210AB/AL

Aluminium R111 Square



E-A++ 51210AB/W

51210AB | 2x75W | R111 | G53 | Aluminium

ADJUSTABLE

5 YEAR

IP20



Suitable for R111 LED lamps.





E-A++ 51210AB/AL

51210AB | 2x75W | R111 | G53 | Aluminium

ADJUSTABLE

5 YEAR

IP20



Suitable for R111 LED lamps.





E-A++

51310AB | 3x75W | R111 | G53 | Natural aluminium

ADJUSTABLE

5 YEAR

IP20



Suitable for R111 LED lamps.



Order Code	Colour	Watts	Input	Class					Notes
51210AB/W	White	2x75W	12V	III	40cm	320x150mm	75mm	10	-
51210AB/AL	Aluminium	2x75W	12V	III	40cm	320x150mm	75mm	10	-
51310AB/AL	Aluminium	3x75W	12V	III	40cm	495x150mm	75mm	10	-



The R111 Dark Light Shop Range

Die cast



E-A++

11110AD | 75W | R111 | GU10 | Die cast

ADJUSTABLE

5 YEAR

DARK LIGHT

IP20







E-A++

51110AD | 75W | R111 | GU10 | Die cast

ADJUSTABLE

5 YEAR

DARK LIGHT

IP20





Order Code	Colour	Watts	Input	Class					Notes
11110AD/B	Black	75W	100-240V	⏚	20cm	155mm	150mm	20	-
51110AD/B	Black	75W	100-240V	⏚	20cm	155x155mm	150mm	20	-



51110ATR/B



11110ATR/W



11110AD/B

The R111 Trimless Shop Range

Die cast



E-A++ 11110ATR/B

11110ATR | 75W | R111 | GU10 | Trimless | Die cast

ADJUSTABLE

5 YEAR

IP20



11110ATR/W





E-A++ 51110ATR/B

51110ATR | 75W | R111 | GU10 | Trimless | Die cast

ADJUSTABLE

5 YEAR

IP20



51110ATR/W



Order Code	Colour	Watts	Input	Class					Notes
11110ATR/W	White	75W	100-240V	⏚	20cm	170mm	150mm	10	-
11110ATR/B	Black	75W	100-240V	⏚	20cm	170mm	150mm	10	-
51110ATR/W	White	75W	100-240V	⏚	20cm	170x170mm	150mm	10	-
51110ATR/B	Black	75W	100-240V	⏚	20cm	170x170mm	150mm	10	-



Gypsum R111



11110GT1 | 75W | R111 | G53 | Gypsum

ADJUSTABLE

5 YEAR

IP20



Suitable for R111 LED lamp.





51110GT1 | 75W | R111 | G53 | Gypsum

ADJUSTABLE

5 YEAR

IP20



Suitable for R111 LED lamp.



Order Code	Colour	Watts	Input	Class					Notes
11110GT1	White	75W	12V	III	25cm	212mm	170mm	6	-
51110GT1	White	75W	12V	III	25cm	212x212mm	170mm	6	-

Extractable R111

Die cast



E-A++

11110H | 75W | R111 | GU10 | Die cast

ADJUSTABLE

IP20

offer



Suitable for R111 LED lamp.



Order Code	Colour	Watts	Input	Class					Notes
11110H/W	White	75W	100-240V		20cm	185mm	110mm	8	-

Multi System Metal Bases

For Modules on page 200



51100R | Metal



offer



11100R | Metal



offer



51200R | Metal



offer



51200AR | Metal



offer



51300R | Metal



offer



51300AR | Metal



offer



51400R | Metal



offer



51400AR | Metal



offer



51401R | Metal



offer

Order Code	Colour			Notes
51100R/W	White	150mm	24	-
51100R/G	Grey	150mm	24	-
51200R/W	White	330x150mm	20	-
51200R/G	Grey	330x150mm	20	-
51300R/G	Grey	470x150mm	20	-
51400R/W	White	330x330mm	10	-
51400R/G	Grey	330x330mm	10	-
51401R/W	White	630x150mm	20	-
51401R/G	Grey	630x150mm	20	-

Order Code	Colour			Notes
11100R/W	White	150mm	24	-
11100R/G	Grey	150mm	24	-
51200AR/W	White	330x150mm	20	-
51200AR/G	Grey	330x150mm	20	-
51300AR/G	Grey	470x150mm	20	-
51400AR/W	White	330x330mm	10	-
51400AR/G	Grey	330x330mm	10	-



Multi System Modules

For Bases on page 199

11110R | 75W | R111 | G53 | Die cast

Base must be ordered separately on page199.



E-A++ 11110R/W

ADJUSTABLE

5 YEAR

IP20

offer



11110R/G



11070R | 70W | PAR30 E27 | Die cast

Base must be ordered separately on page199.



E-A++

ADJUSTABLE

5 YEAR

IP20

offer



Suitable for PAR30 LED lamp.



11106R | 20W | E27 | Die cast

Base must be ordered separately on page199.



E-A++ 11106R/W/1

ADJUSTABLE

5 YEAR

IP20

offer

offer



11106R/G/1



Suitable for E27 LED lamp.



Order Code	Colour	Watts	Input	Class				Notes
11110R/W	White	75W	12V		25cm	80mm	45	-
11110R/G	Grey	75W	12V		25cm	80mm	45	-
11070R/G	Grey	70W	100-240V		40cm	160mm	20	-
11106R/W/1	White	20W	100-240V		-	180mm	20	Use E27 LED lamp
11106R/G/1	Grey	20W	100-240V		-	180mm	20	Use E27 LED lamp



Trimless Multi System Boxes

For Modules on page 202



51100TR | Trimless box | Metal







51200TR | Trimless box | Metal





Order Code	Colour	Watts	Input	Class				Notes
51100TR/W	White	-	-	-	164x164mm	200mm	8	-
51100TR/B	Black	-	-	-	164x164mm	200mm	8	-
51200TR/W	White	-	-	-	312x164m	200mm	6	-
51200TR/B	Black	-	-	-	312x164m	200mm	6	



51200TR/B + 11110TR/B

51100TR/B + 11150TR/B/38

Trimless Multi System Modules

For Bases on page 201



E-A++

11110TR/W | 75W | R111 | G53 | Die cast

Base must be ordered separately on page 201.

ADJUSTABLE CE 5 YEAR IP20



Suitable for R111 LED lamp.





E-A++

11110TR/B | 75W | R111 | GU10 | Die cast

Base must be ordered separately on page 201.

ADJUSTABLE CE 5 YEAR IP20



Suitable for R111 LED lamp.





B-A++ 11150TR/W/38

11150TR | 70W | HQI | G12 | Die cast

Base must be ordered separately on page 201.

ADJUSTABLE QUICK FIX CE 5 YEAR IP20



11150TR/B/38



Suitable for 8010L LED lamp (Direct 230V).





E-A++

11070TR | 70W | PAR30 E27 | Die cast

Base must be ordered separately on page 201.

ADJUSTABLE QUICK FIX CE 5 YEAR IP20



Suitable for PAR30 LED lamp.



Order Code	Colour	Watts	Input	Class			Notes
11110TR/W	White	75W	12V		10cm	2	-
11110TR/B	Black	75W	100-240V		10cm	2	-
11150TR/W/38	White	70W	230V		30cm	36	Requires ballast
11150TR/B/38	Black	70W	230V		30cm	36	Requires ballast
11070TR/W	White	70W	100-240V		30cm	36	-





08

Downlights Adjustable LED

Pages 205-222

COB LED | SMD LED | LED

Die cast | Natural aluminium | Trimless

IP20

ADJUSTABLE ADJUSTABLE DIMMABLE DARK LIGHT QUICK FIX 80 CRI 85 CRI 2 YEAR 3 YEAR



COB Trimless LED

Aluminium



A-A++

11130BT | 30W | COB LED | Trimlesss | Aluminium

LED BUILT IN

80 CRI

DIMMABLE

QUICK FIX

IP20

ADJUSTABLE

3 YEAR





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
11130BT/W/C	White	Cool white	4000K	30W	2200lm	38°	700mA	III	40cm	110mm	160mm	12	Requires 700mA driver
11130BT/W/W	White	Warm white	3000K	30W	2200lm	38°	700mA	III	40cm	110mm	160mm	12	Requires 700mA driver



Adjustable Multi LED

Aluminium

11106LB | 6x1W | LED | Aluminium



A-A++

LED BUILT IN · DIMMABLE · QUICK FIX · ADJUSTABLE · IP20 · offer · CE · 2 YEAR





11109L | 9x1W | LED | Natural aluminium



A-A++

LED BUILT IN · DIMMABLE · QUICK FIX · ADJUSTABLE · IP20 · offer · CE · 2 YEAR





11112L | 12x1W | LED | Natural aluminium



A-A++

LED BUILT IN · DIMMABLE · QUICK FIX · ADJUSTABLE · IP20 · offer · CE · 2 YEAR





11118L | 18x1W | LED | Natural aluminium



A-A++

LED BUILT IN · DIMMABLE · QUICK FIX · ADJUSTABLE · IP20 · offer · CE · 2 YEAR





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
11106LB/D/35	Black	Daylight	6000K	6x1W	360lm	35°	350mA		40cm	90mm	50mm	50	Requires 350mA driver
11106LB/W/35	Black	Warm white	3000K	6x1W	270lm	35°	350mA		40cm	90mm	50mm	50	Requires 350mA driver
11109L/D/35	Aluminium	Daylight	6000K	9x1W	540lm	35°	350mA		40cm	110mm	80mm	30	Requires 350mA driver
11109L/W/35	Aluminium	Warm white	3000K	9x1W	405lm	35°	350mA		40cm	110mm	80mm	30	Requires 350mA driver
11112L/D/15	Aluminium	Daylight	6000K	12x1W	720lm	15°	350mA		40cm	140mm	80mm	30	Requires 350mA driver
11112L/D/35	Aluminium	Daylight	6000K	12x1W	720lm	35°	350mA		40cm	140mm	80mm	30	Requires 350mA driver
11112L/W/15	Aluminium	Warm white	3000K	12x1W	540lm	15°	350mA		40cm	140mm	80mm	30	Requires 350mA driver
11112L/W/35	Aluminium	Warm white	3000K	12x1W	540lm	35°	350mA		40cm	140mm	80mm	30	Requires 350mA driver
11118L/D/35	Aluminium	Daylight	6000K	18x1W	1080lm	35°	350mA		40cm	155mm	90mm	30	Requires 350mA driver
11118L/W/35	Aluminium	Warm white	3000K	18x1W	810lm	35°	350mA		40cm	155mm	90mm	30	Requires 350mA driver



The COB Shop Range
Die cast

11138 | 38W | COB LED | Die cast



A-A++ 11138/W/W

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · 2 YEAR · IP20



11138/G/C



51125 | 25W | COB LED | Die cast



A-A++

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · 2 YEAR · IP20





51138 | 38W | COB LED | Die cast



A-A++ 51138/W/C

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · 2 YEAR · IP20



51138/G/C



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
11138/W/C	White	Cool white	4000K	38W	2450lm	38°	100-240V	⧈	150mm	160mm	12	Complete with 900mA driver
11138/W/W	White	Warm white	3000K	38W	2450lm	38°	100-240V	⧈	150mm	160mm	12	Complete with 900mA driver
11138/G/C	Grey	Cool white	4000K	38W	2450lm	38°	100-240V	⧈	150mm	160mm	12	Complete with 900mA driver
51125/G/C	Grey	Cool white	4000K	25W	1750lm	38°	100-240V	⧈	130x130mm	160mm	12	Complete with 600mA driver
51138/W/C	White	Cool white	4000K	38W	2450lm	38°	100-240V	⧈	170x170mm	200mm	8	Complete with 900mA driver
51138/G/C	Grey	Cool white	4000K	38W	2450lm	38°	100-240V	⧈	170x170mm	200mm	8	Complete with 900mA driver

The COB Box Type Shop Range



A-A++ 51120/W/W

51120 | 20W | COB LED | Aluminium

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · 2 YEAR · IP20



51120/G/W







A-A++ 51220/W/C

51220 | 2x20W | COB LED | Aluminium

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · 2 YEAR · IP20



51220/G/C







A-A++

51130 | 30W | COB LED | Aluminium + metal

new · LED BUILT IN · 80 CRI · ADJUSTABLE · CE · 2 YEAR · IP20







A-A++

51230 | 2x30W | COB LED | Aluminium + metal

new · LED BUILT IN · 80 CRI · ADJUSTABLE · CE · 2 YEAR · IP20





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
51120/W/W	White	Warm white	3000K	20W	1400lm	36°	230V	□	165x165mm	140mm	12	Complete with 500mA driver
51120/G/C	Grey	Cool white	4000K	20W	1400lm	36°	230V	□	165x165mm	140mm	12	Complete with 500mA driver
51120/G/W	Grey	Warm white	3000K	20W	1400lm	36°	230V	□	165x165mm	140mm	12	Complete with 500mA driver
51220/W/C	White	Cool white	4000K	2x20W	2x1400lm	36°	230V	□	330x165mm	140mm	8	Complete with 500mA drivers
51220/G/C	Grey	Cool white	4000K	2x20W	2x1400lm	36°	230V	□	330x165mm	140mm	8	Complete with 500mA drivers
51220/G/W	Grey	Warm white	3000K	2x20W	2x1400lm	36°	230V	□	330x165mm	140mm	8	Complete with 500mA drivers
51130/B/C	Black	Cool white	4000K	30W	2700lm	38°	230V	□	160x160mm	125mm	12	Complete with 750mA driver
51130/B/W	Black	Warm white	3000K	30W	2600lm	38°	230V	□	160x160mm	125mm	12	Complete with 750mA driver
51230/B/C	Black	Cool white	4000K	2x30W	2x2700lm	38°	230V	□	320x160mm	125mm	6	Complete with 750mA drivers
51230/B/W	Black	Warm white	3000K	2x30W	2x2600lm	38°	230V	□	320x160mm	125mm	6	Complete with 750mA drivers



The COB Shop Downlights Pro

Die cast



11150A | 50W | COB LED | Die cast

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · 2 YEAR · IP20







51125A | 25W | COB LED | Die cast

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · 2 YEAR · IP20







11125B | 25W | COB LED | Die cast

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · 2 YEAR · IP20





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
11150A/W/C	White	Cool white	4000K	50W	4450lm	40°	100-240V	⧈	165mm	160mm	8	Complete with 1200mA driver
11150A/W/W	White	Warm white	3000K	50W	3950lm	40°	100-240V	⧈	165mm	160mm	8	Complete with 1200mA driver
51125A/W/W	White	Warm white	3000K	25W	2300lm	40°	100-240V	⧈	165x165mm	130mm	8	Complete with 700mA driver
11125B/W/C	White	Cool white	4000K	25W	2450lm	35°	100-240V	⧈	190mm	120mm	8	Complete with 700mA driver



The COB Round Downlights

Die cast



11120B | 20W | COB LED | Die cast

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · 3 YEAR · IP20







11140B | 40W | COB LED | Die cast

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · 3 YEAR · IP20







11150B | 50W | COB LED | Die cast

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · 3 YEAR · IP20





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
11120B/W/C	White	Cool white	4000K	20W	1600lm	36°	230V	☐	120mm	125mm	18	Complete with 700mA driver
11120B/W/W	White	Warm white	3000K	20W	1500lm	36°	230V	☐	120mm	125mm	18	Complete with 700mA driver
11140B/W/C	White	Cool white	4000K	40W	3300lm	36°	230V	☐	180mm	165mm	8	Complete with 1000mA driver
11150B/W/C	White	Cool white	4000K	50W	3850lm	40°	230V	☐	120mm	250mm	12	Complete with 1200mA driver
11150B/W/W	White	Warm white	3000K	50W	3750lm	40°	230V	☐	120mm	250mm	12	Complete with 1200mA driver



51120B/W/C

51140B/W/C

The COB Square Downlights

Die cast

51109B | 10W | COB LED | Die cast



A-A++

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · 3 YEAR · IP20





51120B | 20W | COB LED | Die cast



A-A++

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · 3 YEAR · IP20





51140B | 40W | COB LED | Die cast



A-A++

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · 3 YEAR · IP20





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
51109B/W/W	White	Warm white	3000K	10W	700lm	36°	230V	☐	90x90mm	120mm	27	Complete with 200mA driver
51120B/W/C	White	Cool white	4000K	20W	1600lm	36°	230V	☐	125x125mm	160mm	12	Complete with 500mA driver
51120B/W/W	White	Warm white	3000K	20W	1500lm	36°	230V	☐	125x125mm	160mm	12	Complete with 500mA driver
51140B/W/C	White	Cool white	4000K	40W	3300lm	36°	230V	☐	170x170mm	160mm	8	Complete with 1000mA driver
51140B/W/W	White	Warm white	3000K	40W	3200lm	36°	230V	☐	170x170mm	160mm	8	Complete with 1000mA driver



The COB Square Downlights

Die cast



A-A++

51209B | 2x10W | COB LED | Die cast

LED BUILT IN

80 CRI

ADJUSTABLE

CE

3 YEAR

IP20







A-A++

51240B | 2x40W | COB LED | Die cast

LED BUILT IN

80 CRI

ADJUSTABLE

CE

3 YEAR

IP20





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
51209B/W/W	White	Warm white	3000K	2x10W	2x700lm	36°	230V	□	180x90mm	130mm	18	Complete with 200mA drivers
51240B/W/W	White	Warm white	3000K	2x40W	2x3200lm	36°	230V	□	320x165mm	170mm	4	Complete with 1000mA drivers



11118TR/W/C



11118TR/G/C



11112TR/W/W

The COB Semi Trimless Range



A-A++

11112TR | 12W | COB LED | Aluminium | Semi trimless

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · DARK LIGHT · IP20 · 2 YEAR







A-A++ 11118TR/W/C

11118TR | 18W | COB LED | Aluminium | Semi trimless

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · DARK LIGHT · IP20 · 2 YEAR



11118TR/G/C





A-A++

11140TR | 40W | COB LED | Die cast

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · IP20 · 3 YEAR





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
11112TR/W/W	White	Warm white	3000K	12W	890lm	35°	100-240V	☐	105mm	110mm	20	Complete with 300mA driver
11118TR/W/C	White	Cool white	4000K	18W	1300lm	35°	100-240V	☐	135mm	200mm	12	Complete with 450mA driver
11118TR/G/C	Grey	Cool white	4000K	18W	1300lm	35°	100-240V	☐	135mm	200mm	20	Complete with 450mA driver
11118TR/G/W	Grey	Warm white	3000K	18W	1120lm	35°	100-240V	☐	135mm	200mm	20	Complete with 450mA driver
11140TR/W/W	White	Warm white	3000K	40W	3200lm	36°	230V	☐	165mm	170mm	8	Complete with 1000mA driver



The COB Semi Trimless Square

51115TR | 15W | COB LED | Die cast



A-A++

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · 3 YEAR · IP20





51120TR | 20W | COB LED | Die cast



A-A++

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · 3 YEAR · IP20





51140TR | 40W | COB LED | Die cast



A-A++

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · 3 YEAR · IP20





51220TR | 2x20W | COB LED | Die cast



A-A++

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · 3 YEAR · IP20





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
51115TR/W/W	White	Warm white	3000K	15W	1000lm	36°	230V	⧈	95x95mm	120mm	27	Complete with 500mA driver
51120TR/W/W	White	Warm white	3000K	20W	1500lm	36°	230V	⧈	120x120mm	150mm	12	Complete with 700mA driver
51140TR/W/W	White	Warm white	3000K	40W	3200lm	36°	230V	⧈	160x160mm	180mm	8	Complete with 1000mA driver
51220TR/W/W	White	Warm white	3000K	2x20W	2x1500lm	36°	230V	⧈	230x120mm	150mm	6	Complete with 700mA drivers

The COB Retro Downlights

Aluminium



11115C | 15W | COB LED | Aluminium



LED BUILT IN · 80 CRI · ADJUSTABLE · CE · IP20 · 2 YEAR





11120C | 20W | COB LED | Aluminium



LED BUILT IN · 80 CRI · ADJUSTABLE · CE · IP20 · 2 YEAR





11130C | 30W | COB LED | Aluminium



LED BUILT IN · 80 CRI · ADJUSTABLE · CE · IP20 · 2 YEAR





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
11115C/W/C	White	Cool white	4000K	15W	1200lm	38°	230V	⧈	95mm	100mm	30	Complete with 350mA driver
11120C/W/C	White	Cool white	4000K	20W	1600lm	38°	230V	⧈	125mm	100mm	30	Complete with 500mA driver
11120C/W/W	White	Warm white	3000K	20W	1500lm	38°	230V	⧈	125mm	100mm	30	Complete with 500mA driver
11130C/W/C	White	Cool white	4000K	30W	2200lm	38°	230V	⧈	145mm	110mm	18	Complete with 700mA driver
11130C/W/W	White	Warm white	3000K	30W	2100lm	38°	230V	⧈	145mm	110mm	18	Complete with 700mA driver

The Shop Classic Rectangle

Die cast



51140 | 40W | COB LED | Aluminium



A-A++ 51140/B/C

new

IP20

LED BUILT IN

80 CRI

ADJUSTABLE

CE

2 YEAR



51140/B/W





51145 | 45W | SMD LED | Die cast



A-A++ 51145/W/C

IP20

LED BUILT IN

80 CRI

ADJUSTABLE

CE

2 YEAR



51145/W/W



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
51140/B/C	Black	Cool white	4000K	40W	3500lm	70°	230V	☐	220x130mm	140mm	9	Complete with 1050mA driver
51140/B/W	Black	Warm white	3000K	40W	3400lm	70°	230V	☐	220x130mm	140mm	9	Complete with 1050mA driver
51145/W/C	White	Cool white	4000K	45W	3500lm	95°	230V	☐	210x130mm	150mm	4	Complete with 1200mA driver
51145/W/W	White	Warm white	3000K	45W	3500lm	95°	230V	☐	210x130mm	150mm	4	Complete with 1200mA driver



11115E/W/W

The COB Pop Up Range

Die cast



11115E | 15W | COB LED | Die cast

LED BUILT IN

80 CRI

DIMMABLE

QUICK FIX

ADJUSTABLE

3 YEAR

IP20





150mm

53mm



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
11115E/W/W	White	Warm white	3000K	15W	1114lm	38°	350mA		30cm	135mm	65mm	25	Requires 350mA driver



The COB Pop Out Range

Aluminium



A-A++

11107R | 7W | COB LED | Aluminium

LED BUILT IN · 80 CRI · DIMMABLE · QUICK FIX · ADJUSTABLE · CE · 3 YEAR · IP20









A-A++

11114R | 14W | COB LED | Aluminium

LED BUILT IN · 80 CRI · DIMMABLE · QUICK FIX · ADJUSTABLE · CE · 3 YEAR · IP20









A-A++

11125R | 25W | COB LED | Aluminium

LED BUILT IN · 80 CRI · DIMMABLE · QUICK FIX · ADJUSTABLE · CE · 3 YEAR · IP20







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
11107R/W/C	White	Cool white	4000K	7W	600lm	38°	350mA	III	40cm	100mm	70mm	12	Requires 350mA driver
11114R/W/C	White	Cool white	4000K	14W	1100lm	36°	700mA	III	40cm	130mm	85mm	12	Requires 700mA driver
11114R/W/W	White	Warm white	3000K	14W	1037lm	36°	700mA	III	40cm	130mm	85mm	12	Requires 700mA driver
11125R/W/C	White	Cool white	4000K	25W	2200lm	40°	700mA	III	40cm	160mm	85mm	8	Requires 700mA driver
11125R/W/W	White	Warm white	3000K	25W	2070lm	40°	700mA	III	40cm	160mm	85mm	8	Requires 700mA driver



The COB Extractable Range

11118H | 18W | COB LED | Aluminium



A-A++ 11118H/W/C

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · 2 YEAR · IP20



11118H/G/C



11115F | 15W | COB LED | Die cast



A-A++

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · 2 YEAR · IP20





11125F | 25W | COB LED | Die cast



A-A++

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · 2 YEAR · IP20





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
11118H/W/C	White	Cool white	4000K	18W	1300lm	35°	100-240V	⊡	120mm	110mm	20	Complete with 500mA driver
11118H/G/C	Grey	Cool white	4000K	18W	1300lm	35°	100-240V	⊡	120mm	110mm	20	Complete with 500mA driver
11118H/G/W	Grey	Warm white	3000K	18W	1120lm	35°	100-240V	⊡	120mm	110mm	20	Complete with 500mA driver
11115F/W/C	White	Cool white	4000K	15W	1100lm	60°	230V	⊡	145mm	155mm	18	Complete with 350mA driver
11125F/W/C	White	Cool white	4000K	25W	1900lm	60°	230V	⊡	172mm	170mm	12	Complete with 650mA driver



11110F/W/W

11120F/W/W

The COB Extractable Range



A-A++

11110F | 10W | COB LED | Die cast

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · IP20 · 3 YEAR







A-A++

11112F | 12W | COB LED | Die cast

LED BUILT IN · 80 CRI · DIMMABLE · QUICK FIX · ADJUSTABLE · CE · IP20 · 2 YEAR







A-A++

11120F | 20W | COB LED | Die cast

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · IP20 · 3 YEAR





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class	S				Notes
11110F/W/C	White	Cool white	4000K	10W	800lm	36°	230V		-	90mm	105mm	36	Complete with 200mA driver
11110F/W/W	White	Warm white	3000K	10W	770lm	36°	230V		-	90mm	105mm	36	Complete with 200mA driver
11112F/W/C	White	Cool white	4000K	12W	1100lm	50°	700mA		40cm	102mm	120mm	36	Requires 700mA driver
11112F/W/W	White	Warm white	3000K	12W	1100lm	50°	700mA		40cm	102mm	120mm	36	Requires 700mA driver
11120F/W/W	White	Warm white	3000K	20W	1500lm	36°	230V		-	125mm	130mm	18	Complete with 500mA driver



The COB Recessed Range

Die cast



A-A++

11135L | 35W | COB LED | Die cast

Matching design with 65624T.

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · 3 YEAR · IP20









A-A++

11130B | 30W | COB LED | Die cast

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · 3 YEAR · IP20



15° Reflector for 11130B.
Order code 0736/15.







A-A++

11140L | 40W | COB LED | Die cast

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · 3 YEAR · IP20







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
11135L/W/C	White	Cool white	4000K	35W	3050lm	45°	230V		145mm	110mm	18	Complete with 900mA driver
11130B/W/W	White	Warm white	3000K	30W	2200lm	36°	230V		100mm	70mm	9	Complete with 700mA driver
11140L/W/C	White	Cool white	4000K	40W	3200lm	36°	230V		100mm	70mm	12	Complete with 1000mA driver
11140L/W/W	White	Warm white	3000K	40W	3100lm	36°	230V		100mm	70mm	12	Complete with 1000mA driver



11125RA/W/C

11115RA/W/C

The COB Pop Out Range



11115RA | 15W | COB LED | Die cast

LED BUILT IN
80 CRI
ADJUSTABLE
CE
DARK LIGHT
IP20
3 YEAR









11125RA | 25W | COB LED | Die cast

LED BUILT IN
80 CRI
ADJUSTABLE
CE
DARK LIGHT
IP20
3 YEAR







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
11115RA/W/C	White	Cool white	4000K	15W	1100lm	36°	230V	☐	90mm	70mm	24	Complete with 500mA driver
11125RA/W/C	White	Cool white	4000K	25W	1900lm	36°	230V	☐	120mm	80mm	12	Complete with 700mA driver
11125RA/W/W	White	Warm white	3000K	25W	1800lm	36°	230V	☐	120mm	80mm	12	Complete with 700mA driver





09

LED Strips & Profiles

Pages 225-266

SMD LED | LED

12V DC | 24V DC

IP20 IP54 IP65 IP67 IP68

DIMMABLE QUICK FIX 75 CRI 80 CRI 85 CRI 95 CRI 2 YEAR 3 YEAR 5 YEAR







7821 | 4,8W/m | SMD 3528 | 60LEDs/m

3M Double face adhesive.

LED BUILT IN · 75 CRI · DIMMABLE · IP20 · 5 YEAR



Supplied in 5m roll.



Dimming remote control.
Order code 20030.





7831 | 14,4W/m | SMD 5050 | 60LEDs/m

3M Double face adhesive.

LED BUILT IN · 75 CRI · DIMMABLE · IP20 · 5 YEAR



Supplied in 5m roll.



Dimming remote control.
Order code 20030.





Accessories for 7821 & 7831

III · 50cm

7821

7824 Power supply cable
7822 Connector

7831

7834 Power supply cable
7832 Connector

Order Code	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
7821/D	Daylight	6000K	4,8W/m	360lm/m	12V DC	III	40	Requires 12V DC driver
7831/C	Cool white	4000K	14,4W/m	1050lm/m	12V DC	III	40	Requires 12V DC driver



7833/W

The Ultra Slim Range 24V



A-A++ Ultra slim

7823 | 9,6W/m | SMD 2216 | 140LEDs/m | Ultra slim

3M Double face adhesive.

LED BUILT IN · 90 CRI · DIMMABLE · IP20 · CE · 5 YEAR



Supplied in 5m roll.



Dimming remote control.
Order code 20030.





A-A++ Ultra slim

7833 | 14,4W/m | SMD 2110 | 196LEDs/m

3M Double face adhesive.

LED BUILT IN · 90 CRI · DIMMABLE · IP20 · CE · 5 YEAR



Supplied in 5m roll.



Dimming remote control.
Order code 20030.



Order Code	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
7823/C	Cool white	4000K	9,6W/m	960lm/m	24V DC	III	40	Requires 24V DC driver
7823/W	Warm white	3000K	9,6W/m	864lm/m	24V DC	III	40	Requires 24V DC driver
7823/EW	Extra warm white	2700K	9,6W/m	768lm/m	24V DC	III	40	Requires 24V DC driver
7833/C	Cool white	4000K	14,4W/m	1300lm/m	24V DC	III	40	Requires 24V DC driver
7833/W	Warm white	3000K	14,4W/m	1200lm/m	24V DC	III	40	Requires 24V DC driver
7833/EW	Extra warm white	2700K	14,4W/m	1160lm/m	24V DC	III	40	Requires 24V DC driver



The 4,8W/m Indoor 24V



7820 | 4,8W/m | SMD 2216 | 70LEDs/m

3M Double face adhesive.

LED BUILT IN · 90 CRI · DIMMABLE · CE · 5 YEAR



Supplied in 5m roll.



Dimming remote control.
Order code 20030.





Accessories for 7820

III · 50cm · CE

7824 Power supply cable
7822 Connector

Order Code	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
7820/D	Daylight	6000K	4,8W/m	480lm/m	24V DC	III	40	Requires 24V DC driver
7820/C	Cool white	4000K	4,8W/m	480lm/m	24V DC	III	40	Requires 24V DC driver
7820/W	Warm white	3000K	4,8W/m	432lm/m	24V DC	III	40	Requires 24V DC driver
7820/EW	Extra warm white	2700K	4,8W/m	384lm/m	24V DC	III	40	Requires 24V DC driver
7820/UW	Ultra warm white	2200K	4,8W/m	384lm/m	24V DC	III	40	Requires 24V DC driver



The 4,8W/m Outdoor 24V



7820W | 4,8W/m | SMD 2216 | 70LEDs/m | Silicone

3M Double face adhesive.

IP68

LED BUILT IN · 90 CRI · DIMMABLE · CE · 3 YEAR



Supplied in 5m roll.



Dimming remote control.
Order code 20030.





7820AW | 4,8W/m | SMD 3528 | 60LEDs/m | Silicone

NO adhesive.

IP68 offer

LED BUILT IN · 80 CRI · DIMMABLE · CE · 3 YEAR



Supplied in 5m roll.



Dimming remote control.
Order code 20030.





Accessories for 7820W & 7820AW

CE

7826 Mounting clip
7828 End cup

Order Code	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
7820W/D	Daylight	6000K	4,8W/m	432lm/m	24V DC	III	40	Requires 24V DC driver / Avoid direct sunlight
7820W/C	Cool white	4000K	4,8W/m	432lm/m	24V DC	III	40	Requires 24V DC driver / Avoid direct sunlight
7820W/W	Warm white	3000K	4,8W/m	390lm/m	24V DC	III	40	Requires 24V DC driver / Avoid direct sunlight
7820W/EW	Extra warm white	2700K	4,8W/m	346lm/m	24V DC	III	40	Requires 24V DC driver / Avoid direct sunlight
7820AW/W	Warm white	3000K	4,8W/m	280lm/m	24V DC	III	40	Requires 24V DC driver / Avoid direct sunlight

The 9,6W/m 24V

SMD 2216 140LEDs/m



7829 | 9,6W/m | SMD 2216 | 140LEDs/m

3M Double face adhesive.

LED BUILT IN · 90 CRI · DIMMABLE · 5 YEAR



Supplied in 5m roll.



Dimming remote control.
Order code 20030.



Order Code	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
7829/C	Cool white	4000K	9,6W/m	960lm/m	24V DC	III	40	Requires 24V DC driver
7829/W	Warm white	3000K	9,6W/m	864lm/m	24V DC	III	40	Requires 24V DC driver
7829/EW	Extra warm white	2700K	9,6W/m	768lm/m	24V DC	III	40	Requires 24V DC driver



The 14,4W/m CRI97 Indoor 24V

Full spectrum



7835C | 14,4W/m | SMD 2835 | 70LEDs/m

3M Double face adhesive.

LED BUILT IN · 97 CRI · DIMMABLE · 5 YEAR



Supplied in 5m roll.



Dimming remote control.
Order code 20030.





Accessories for 7835C

III · 50cm

7835P Power supply cable

7837 Connector

Order Code	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
7835C/C	Cool white	4000K	14,4W/m	1008lm/m	24V DC	III	40	Requires 24V DC driver
7835C/W	Warm white	3000K	14,4W/m	864m/m	24V DC	III	40	Requires 24V DC driver



The 14,4W/m Indoor 24V



7830 | 14,4W/m | SMD 5050 | 60LEDs/m

3M Double face adhesive.

LED BUILT IN | 80 CRI | DIMMABLE | CE | 5 YEAR



Supplied in 5m roll.



Dimming remote control.
Order code 20030.





7835 | 14,4W/m | SMD 2835 | 70LEDs/m

3M Double face adhesive.

LED BUILT IN | 90 CRI | DIMMABLE | CE | 5 YEAR



Supplied in 5m roll.



Dimming remote control.
Order code 20030.





Accessories for 7830 & 7835

III | 50cm | CE

7830

7834 Power supply cable
7832 Connector

7835

7835P Power supply cable
7837 Connector

Order Code	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
7830/EW	Extra warm white	2700K	14,4W/m	980lm/m	24V DC	III	40	Requires 24V DC driver
7835/D	Daylight	6000K	14,4W/m	1300lm/m	24V DC	III	40	Requires 24V DC driver
7835/C	Cool white	4000K	14,4W/m	1300lm/m	24V DC	III	40	Requires 24V DC driver
7835/W	Warm white	3000K	14,4W/m	1152lm/m	24V DC	III	40	Requires 24V DC driver
7835/EW	Extra warm white	2700K	14,4W/m	1008lm/m	24V DC	III	40	Requires 24V DC driver



The 14,4W/m Outdoor 24V



7835W | 14,4W/m | SMD 2835 | 70LEDs/m | Silicone

3M Double face adhesive.

LED BUILT IN | 90 CRI | DIMMABLE | CE | 3 YEAR



Supplied in 5m roll.



Dimming remote control.
Order code 20030.





7827 | Mounting clip for 7835W

CE

Order Code	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
7835W/D	Daylight	6000K	14,4W/m	1170lm/m	24V DC	III	40	Requires 24V DC driver / Avoid direct sunlight
7835W/C	Cool white	4000K	14,4W/m	1170lm/m	24V DC	III	40	Requires 24V DC driver / Avoid direct sunlight
7835W/W	Warm white	3000K	14,4W/m	1040lm/m	24V DC	III	40	Requires 24V DC driver / Avoid direct sunlight
7835W/EW	Extra warm white	2700K	14,4W/m	910lm/m	24V DC	III	40	Requires 24V DC driver / Avoid direct sunlight



Connect In One Length Range 24V



7813L | 3W/m | SMD 2835 | 60LEDs/m

Can be connected in 30m full length / 3M Double face adhesive.

LED BUILT IN · 80 CRI · DIMMABLE · IP20 · 5 YEAR



Supplied in 30m roll.







7820L | 4,8W/m | SMD 2216 | 60LEDs/m

Can be connected in 15m full length / 3M Double face adhesive.

LED BUILT IN · 90 CRI · DIMMABLE · IP20 · 5 YEAR



Supplied in 15m roll.



Dimming remote control.
Order code 20030.





7820WL | 4,8W/m | SMD 2216 | 60LEDs/m | Silicone

Can be connected in 15m full length / 3M Double face adhesive.

LED BUILT IN · 90 CRI · DIMMABLE · IP68 · 3 YEAR



Supplied in 15m roll.



Dimming remote control.
Order code 20030.





Accessories for 7820WL

7826 Mounting clip
7828 End cup

Order Code	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
7813L/W	Warm white	3000K	3W/m	240lm/m	24V DC	III	20	Requires 24V DC driver
7820L/C	Cool white	4000K	4,8W/m	384lm/m	24V DC	III	40	Requires 24V DC driver
7820L/W	Warm white	3000K	4,8W/m	336lm/m	24V DC	III	40	Requires 24V DC driver
7820L/EW	Extra warm white	2700K	4,8W/m	312lm/m	24V DC	III	40	Requires 24V DC driver
7820WL/W	Warm white	3000K	4,8W/m	302lm/m	24V DC	III	20	Requires 24V DC driver / Avoid direct sunlight



The Vertical Light Range 24V



7820V | 4,8W/m | SMD 3014 | 60LEDs/m | Vertical light

3M Double face adhesive.

LED BUILT IN · 90 CRI · DIMMABLE · IP20 · 5 YEAR



Supplied in 5m roll.



Dimming remote control.
Order code 20030.





7835V | 14,4W/m | SMD 3014 | 120LEDs/m | Vertical light

3M Double face adhesive.

LED BUILT IN · 90 CRI · DIMMABLE · IP20 · 5 YEAR



Supplied in 5m roll.



Dimming remote control.
Order code 20030.





Accessories for 7820V & 7835V

III · 50cm · CE

7824 Power supply cable
7822 Connector

Order Code	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
7820V/C	Cool white	4000K	4,8W/m	500lm/m	24V DC	III	40	Requires 24V DC driver
7820V/W	Warm white	3000K	4,8W/m	450lm/m	24V DC	III	40	Requires 24V DC driver
7835V/C	Cool white	4000K	14,4W/m	1300lm/m	24V DC	III	40	Requires 24V DC driver
7835V/W	Warm white	3000K	14,4W/m	1152lm/m	24V DC	III	40	Requires 24V DC driver

The 19,2W/m Indoor 24V



7825 | 19,2W/m | SMD 2835 | 140LEDs/m

3M Double face adhesive.

IP20 | LED BUILT IN | 90 CRI | DIMMABLE | 5 YEAR



Supplied in 5m roll.

Cut every 5cm
(7-LED segment)

10mm



7870/C | 19,2W/m | SMD 3528 | 240LEDs/m

No shadow / 3M Double face adhesive.

IP20 | LED BUILT IN | 80 CRI | DIMMABLE | 5 YEAR



Supplied in 5m roll.

Cut every 2,5cm
(6-LED segment)

10mm



7870 | 19,2W/m | SMD 2216 | 238LEDs/m

No shadow / 3M Double face adhesive.

IP20 | LED BUILT IN | 90 CRI | DIMMABLE | 5 YEAR



Supplied in 5m roll.

Cut every 2,95cm
(7-LED segment)

10mm



7875/D | 19,2W/m | SMD 3528 | 240LEDs/m

3M Double face adhesive.

IP20 | LED BUILT IN | 80 CRI | DIMMABLE | 5 YEAR



Supplied in 5m roll.

Cut every 5cm
(12-LED segment)

16mm



7875 | 19,2W/m | SMD 2216 | 240LEDs/m

3M Double face adhesive.

IP20 | LED BUILT IN | 90 CRI | DIMMABLE | 5 YEAR



Supplied in 5m roll.

Cut every 5cm
(12-LED segment)

16mm

Order Code	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
7825/C	Cool white	4000K	19,2W/m	1728lm/m	24V DC		40	Requires 24V DC driver
7825/W	Warm white	3000K	19,2W/m	1536lm/m	24V DC		40	Requires 24V DC driver
7825/EW	Extra warm white	2700K	19,2W/m	1344lm/m	24V DC		40	Requires 24V DC driver
7870/C	Cool white	4000K	19,2lm/m	1300lm/m	24V DC		40	Requires 24V DC driver
7870/D	Daylight	6000K	19,2lm/m	1920lm/m	24V DC		40	Requires 24V DC driver
7870/W	Warm white	3000K	19,2lm/m	1728lm/m	24V DC		40	Requires 24V DC driver
7875/D	Daylight	6000K	19,2lm/m	1400lm/m	24V DC		40	Requires 24V DC driver
7875/C	Cool white	4000K	19,2lm/m	1536lm/m	24V DC		40	Requires 24V DC driver
7875/W	Warm white	3000K	19,2lm/m	1344lm/m	24V DC		40	Requires 24V DC driver

The 24W/m Indoor 24V





7845 | 24W/m | SMD 2216 | 300LEDs/m

No shadow / 3M Double face adhesive.

IP20

LED BUILT IN · 90 CRI · DIMMABLE · 5 YEAR



Supplied in 5m roll.

Cut every 2cm
(6-LED segment)

10mm



7887 | 24W/m | SMD 2110 | 700LEDs/m

3M Double face adhesive.

IP20

LED BUILT IN · 90 CRI · DIMMABLE · 5 YEAR



Supplied in 5m roll.

Cut every 1cm
(7-LED segment)

12mm

Order Code	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
7845/C	Cool white	4000K	24W/m	1900lm/m	24V DC	III	40	Requires 24V DC driver
7845/W	Warm white	3000K	24W/m	1800lm/m	24V DC	III	40	Requires 24V DC driver
7845/EW	Extra warm white	2700K	24W/m	1750lm/m	24V DC	III	40	Requires 24V DC driver
7887/W	Warm white	3000K	24W/m	2050lm/m	24V DC	III	40	Requires 24V DC driver



7885/C

The High Power Strips 24V



7880 | 28,8W/m | SMD 2835 | 120LEDs/m

3M Double face adhesive.

A-A++ | IP20 | LED BUILT IN | 90 CRI | DIMMABLE | CE | 5 YEAR



Supplied in 5m roll.







7882 | 42W/m | SMD 2835 | 240LEDs/m

3M Double face adhesive.

A-A++ | IP20 | LED BUILT IN | 80 CRI | DIMMABLE | CE | 5 YEAR



Supplied in 2m roll.







7885 | 48W/m | SMD 2835 | 294LEDs/m

3M Double face adhesive.

A-A++ | IP20 | LED BUILT IN | 90 CRI | DIMMABLE | CE | 5 YEAR



Supplied in 2m roll.





Order Code	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
7880/D	Daylight	6000K	28,8W/m	2304lm/m	24V DC	III	40	Requires 24V DC driver
7880/C	Cool white	4000K	28,8W/m	2304lm/m	24V DC	III	40	Requires 24V DC driver
7880/W	Warm white	3000K	28,8W/m	2016lm/m	24V DC	III	40	Requires 24V DC driver
7882/W	Warm white	3000K	42W/m	6100lm/m	24V DC	III	40	Requires 24V DC driver
7885/C	Cool white	4000K	48W/m	4800lm/m	24V DC	III	20	Requires 24V DC driver
7885/W	Warm white	3000K	48W/m	4320lm/m	24V DC	III	20	Requires 24V DC driver





7835/DEW | 20W/m | SMD 2835 | 120LEDs/m

3M Double face adhesive.

LED BUILT IN · 90 CRI · DIMMABLE · 5 YEAR



Supplied in 5m roll.



Variable colour temperature.





20032 | 12-24V DC | Variable colour temperature controller & dimmer | 2 channels x 3A

DIMMABLE

Remote controller for changing colour temperature from extra warm white to daylight. Suitable for use with LED strips 7835/DEW. 50 meters range, includes dimmer control and programme mode.



Order Code	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
7835/DEW	Extra warm white - Daylight	2700K - 6500K	20W/m	600lm/m (EW) + 800lm/m (D)	24V DC	III	40	Requires 12-24V DC driver



The Blue LED Strips 24V



7820/BL | 4,8W/m | SMD 3528 | 60LEDs/m

3M Double face adhesive.

IP20

LED BUILT IN · DIMMABLE · CE · 5 YEAR



Supplied in 5m roll.



Dimming remote control.
Order code 20030.

Cut every 10cm
(6-LED segment)

8mm



7820W/BL | 4,8W/m | SMD 3528 | 60LEDs/m | Silicone

3M Double face adhesive.

IP68

LED BUILT IN · DIMMABLE · CE · 3 YEAR



Supplied in 5m roll.



Dimming remote control.
Order code 20030.

Cut every 10cm
(6-LED segment)

12mm

Order Code	Light Colour	Input	Input	Class		Notes
7820/BL	Blue	4,8W/m	24V DC	III	40	Requires 24V DC driver
7820W/BL	Blue	4,8W/m	24V DC	III	40	Requires 24V DC driver / Avoid direct sunlight



LED Strips Complete Sets



A-A++ RGB

7820A/RGB | 2W/m/color | SMD 5050 | 30LEDs/m

LED BUILT IN · DIMMABLE · CE · 3 YEAR

IP20



Supplied in 5m roll.

10mm



A-A++ RGB+W

7830A/RGBW | 3W/m/color | SMD 5050 | 30LEDs/m

3M Double face adhesive.

LED BUILT IN · 80 CRI · DIMMABLE · CE · 3 YEAR

IP20



Supplied in 5m roll.

12mm



A-A++

7820C/A | 2,16W/m | SMD 3528 | Sensor

3M Double face adhesive.

CE · 3 YEAR

IP20



- Night time bed light.
- Set of 2x1,2m pcs.
- Switches ON when you step out of bed.

Order Code	Light Colour	CCT (K)	Watts	Input	Class		Notes
7820A/RGB	RGB	-	2W/m/color	230V / 12V DC	⧈	12	Set of LED strip + remote
7830A/RGBW	RGB + Warm white	RGB + 3000K	3W/m/color	100-240V / 12V DC	⧈	12	Set of LED strip + remote
7820C/A	Amber	1700K	2,16W/m	100-240V / 12V DC	⧈	20	Set of LED strips + sensors



The RGB & RGBW Strips 24V



A-A++ RGB

IP20

7830/RGB | 14,4W/m | SMD 5050 | 60LEDs/m

3M Double face adhesive.

LED BUILT IN · DIMMABLE · CE · 5 YEAR



Supplied in 5m roll.



Dimming remote control.
Order code 20034.

Cut every 10cm (6-LED segment)

10mm



Accessories for 7830/RGB

III · 50cm · CE

7834/RGB Power supply cable
7832/RGB Connector



A-A++ RGB+W

IP20

7830/RGBW | 19,2W/m | SMD 5050 | 60LEDs/m

3M Double face adhesive.

LED BUILT IN · DIMMABLE · CE · 5 YEAR



Supplied in 5m roll.



Dimming remote control.
Order code 20036.

Cut every 10cm (6-LED segment)

12mm

Order Code	Light Colour	CCT (K)	Watts	Input	Class		Notes
7830/RGB	RGB	-	14,4W/m	24V DC	III	40	Requires 24V DC driver
7830/RGBW	RGB + Warm white	RGB + 3000K	RGB 14,4W/m + WW 4,8W/m	24V DC	III	40	Requires 24V DC driver



The Outdoor RGB Strip 24V



A-A++ RGB

7830W/RGB | 14,4W/m | SMD 5050 | 60LEDs/m | Silicone

3M Double face adhesive.

LED BUILT IN · DIMMABLE · 3 YEAR · IP68



Supplied in 5m roll.



Dimming remote control.
Order code 20034.





7827 | Mounting clip for 7830W

Order Code	Light Colour	CCT (K)	Watts	Input	Class		Notes
7830W/RGB	RGB	-	14,4W/m	24V DC	III	40	Requires 24V DC driver / Avoid direct sunlight

Surface Slim Profiles



7901/AL | 2m Surface profile + PC opal diffuser | Aluminium | Suitable for 7823 & 7833 LED Strips 5mm

4



Complete with 2 pairs end cups & 6pcs metal fixing clips.





7836/W | 2m Square profile | Aluminium
Suitable for 7820, 7821, 7825, 7829, 7830, 7831, 7835, 7835C, 7844 & 7870 LED Strips 12mm



2m Diffuser.
Order code 7836A/P Opal.



Complete with 4 pairs end cups, 4 connectors & 6pcs fixing clips.





7836/G | 2m Square profile | Aluminium
Suitable for 7820, 7821, 7825, 7829, 7830, 7831, 7835, 7844 & 7870 LED Strips 12mm



2m Diffuser.
Order code 7836A/P Opal.



Complete with 4 pairs end cups, 4 connectors & 6pcs fixing clips.





7902/W | 2m Surface profile + PC opal diffuser | Aluminium | Suitable for 7820 & 7821 LED Strips 12mm



Complete with 2 pairs end cups & 6pcs fixing clips.





7902/B | 2m Surface profile + PC opal diffuser | Aluminium | Suitable for 7820 & 7821 LED Strips 12mm



Complete with 2 pairs end cups & 6pcs fixing clips.





7902/AL | 2m Surface profile + PC opal diffuser | Aluminium | Suitable for 7820 & 7821 LED Strips 12mm



Complete with 2 pairs end cups & 6pcs fixing clips.



Surface Profiles





7904/W

7904 | 2m Surface profile + PC opal diffuser | Aluminium

Suitable for 7820, 7821, 7825, 7829, 7830, 7831, 7835, 7844 & 7870 LED Strips 12mm



7904/B



7904/AL



Complete with 2 pairs end cups & 6pcs fixing clips.





7905/W

7905 | 2m Surface profile + PC opal diffuser | Aluminium

Suitable for 7825, 7830, 7835, 7844, 7845, 7870 & 7875 LED Strips 16mm

80

new



7905/B



7905/AL



Complete with 2 pairs end cups & 6pcs fixing clips.





Surface /Suspended Wide Profiles

External driver



7912/B | 2m Surface/Suspended profile + PC opal diffuser | Aluminium

Suitable for 7825, 7845, 7870, 7875, 7880, 7882 & 7887 LED Strips 25mm



Complete with 2 pairs end cups.



Optional Trimless kit (10pcs). Order code 7838M.



Optional suspension wire (1pc). Order code 7900P.



Optional 180° connector. Order code 7900C.



Optional 90° connector. Order code 7900R.





7912/AL | 2m Surface / Suspended profile + PC opal diffuser | Aluminium

Suitable for 7825, 7845, 7870, 7875, 7880, 7882 & 7887 LED Strips 25mm



Complete with 2 pairs end cups.



Optional Trimless kit (10pcs). Order code 7838M.



Optional suspension wire (1pc). Order code 7900P.



Optional 180° connector. Order code 7900C.



Optional 90° connector. Order code 7900R.





7912A/AL | 2m Surface / Suspended profile + PC opal diffuser | Aluminium | Suitable for 7880 & 7885 LED Strips 40mm



Complete with 2 pairs end cups.



Optional Trimless kit (10pcs). Order code 7838M.



Optional suspension wire (1pc). Order code 7900P.



Optional 180° connector. Order code 7900C.



Optional 90° connector. Order code 7900R.

6





050122 | Profile power supply base | With power cable | Aluminium

IP20



050122/B Black



050122/G Grey

050122/W White

30





Surface/Suspended Wide Profiles

Internal driver



7910/AL | 2m Surface / Suspended profile + PC opal diffuser | Aluminium

Suitable for 7825, 7845, 7870, 7875, 7880, 7882 & 7887 LED Strips 25mm | Use drivers on pages 635 & 636



Complete with 2 pairs end cups.



Optional Trimless kit (10pcs). Order code 7838M.



Optional suspension wire (1pc). Order code 7900P.



Optional 180° connector. Order code 7900C.



Optional 90° connector. Order code 7900R.





7910A/B | 2m Surface / Suspended profile + PC opal diffuser | Aluminium

Suitable for 7885 LED Strips 45mm | Use drivers on pages 635 & 636



Complete with 2 pairs end cups.



Optional suspension wire (1pc). Order code 7900P.



Optional 180° connector. Order code 7900C.



Optional 90° connector. Order code 7900R.

6





7910A/AL | 2m Surface / Suspended profile + PC opal diffuser | Aluminium

Suitable for 7885 LED Strips 45mm | Use drivers on pages 635 & 636



Complete with 2 pairs end cups.



Optional suspension wire (1pc). Order code 7900P.



Optional 180° connector. Order code 7900C.



Optional 90° connector. Order code 7900R.

6





050122/W White

050122 | Profile power supply base | With power cable | Aluminium

IP20



050122/B Black



050122/G Grey

30





Triangular Profiles



7908A/AL | 2m Triangle profile + PC opal diffuser | Aluminium
Suitable for 7820, 7821, 7829, 7830, 7835, 7835C & 7844 LED Strips 10mm

60



Complete with 2 pairs end cups & 6pcs surface mounting clips.





7908/AL | 2m Triangle profile + PC opal diffuser | Aluminium | Suitable for 7820, 7821, 7825, 7829, 7830, 7831, 7835, 7835C, 7844, 7870 & 7875 LED Strips 16mm



Complete with 2 pairs end cups & 1pc 180° connector.





7937T/AL | 2m Surface profile + PC semi-opal diffuser | Aluminium
Suitable for 7820, 7821, 7829, 7830, 7835, 7835C & 7844 LED Strips 12mm

40



Complete with 2 pairs end cups.



Shelf illumination



7906D/AL

7906B/AL

Side Light Surface & Suspended Profiles



7906/AL | 2m Surface profile + PMMA opal square diffuser | Aluminium
Suitable for 7820, 7821, 7825, 7829, 7830, 7831, 7835 & 7844 LED Strips 15mm



Complete with 2 pairs end cups.





7906A/AL | 2m Surface / Suspended profile + PC opal diffuser | Aluminium
Suitable for 7820, 7821, 7825, 7830, 7835, 7844, 7845, 7875, 7870 & 7887 LED Strips 16mm

12



Complete with 2 pairs end cups & 6pcs surface mounting clips.



Optional suspension wire (1pc). Order code 7900P.



Optional 180° connector. Order code 7900C.





7906B/AL | 2m Surface / Suspended profile + PC opal diffuser | Aluminium
Suitable for 7845, 7882, 7875, 7880 & 7887 LED Strips 30mm

16



Complete with 2 pairs end cups & 6pcs surface mounting clips.



Optional suspension wire (1pc). Order code 7900P.





7906C/AL | 2m Surface / Suspended profile + PC opal diffuser | Aluminium
Suitable for 7882, 7845, 7875, 7880 & 7887 LED Strips 30mm | Use drivers on pages 635 & 636

8



Complete with 2 pairs end cups.



Optional suspension wire (1pc). Order code 7900P.





7906D/AL | 2m Surface / Suspended profile + PC opal diffuser | Aluminium
Suitable for 7885 & 7880 LED Strips 40mm | Use drivers on pages 635 & 636

6



Complete with 2 pairs end cups.



Optional suspension wire (1pc). Order code 7900P.



Up/Down Light Wall Profile



7916/AL | 2m Wall mounted profile + PC opal diffuser | Aluminium | Suitable for 7820, 7821, 7825, 7829, 7830, 7835, 7844, 7845, 7870, 7875, 7880 & 7887 LED Strips | Use drivers on pages 635 & 636



Complete with 2 pairs end cups & 5pcs fixing clips.



Recessed Profiles



7901R/AL | 2m Recessed profile + PC opal diffuser | Aluminium | Suitable for 7823 & 7833 LED Strips 5mm

120



Complete with
2 pairs end cups.

8x2000mm

13mm





7902R/W | 2m Recessed profile + PC opal diffuser | Aluminium | Suitable for 7820 & 7821 LED Strips 12mm



Complete with
2 pairs end cups.

18x2000mm

10mm





7902R/B | 2m Recessed profile + PC opal diffuser | Aluminium | Suitable for 7820 & 7821 LED Strips 12mm



Complete with
2 pairs end cups.

18x2000mm

10mm





7902R/AL | 2m Recessed profile + PC opal diffuser | Aluminium | Suitable for 7820 & 7821 LED Strips 12mm



Complete with
2 pairs end cups.

18x2000mm

10mm





7904R/W | 2m Recessed profile + PC opal diffuser | Aluminium | Suitable for 7820, 7821, 7825, 7829 7830, 7831, 7835, 7844 & 7870 LED Strips 12mm



Complete with
2 pairs end cups.

18x2000mm

16mm





7904R/AL | 2m Recessed profile + PC opal diffuser | Aluminium | Suitable for 7820, 7821, 7825, 7829 7830, 7831, 7835, 7844 & 7870 LED Strips 12mm



Complete with
2 pairs end cups.

18x2000mm

16mm





Recessed Profiles



7906R/W | 2m Recessed profile + PC opal diffuser | Aluminium
Suitable for 7820, 7821, 7829, 7830, 7831, 7835 & 7844 LED Strips 20mm

60



Complete with 2 pairs end cups.

25x2000mm

12mm





7906R/AL | 2m Recessed profile + PC opal diffuser | Aluminium
Suitable for 7820, 7821, 7829, 7830, 7831, 7835 & 7844 LED Strips 20mm

60



Complete with 2 pairs end cups.

25x2000mm

12mm





7912R/B | 2m Recessed profile + PC opal diffuser | Aluminium
Suitable for 7825, 7829, 7830, 7831, 7835, 7844, 7845, 7870, 7875, 7880 & 7887 LED Strips 20mm



Complete with 2 pairs end cups & 6pcs fixing clips.

25x2000mm

30mm





7912R/AL | 2m Recessed profile + PC opal diffuser | Aluminium
Suitable for 7825, 7829, 7830, 7831, 7835, 7844, 7845, 7870, 7875, 7880 & 7887 LED Strips 20mm



Complete with 2 pairs end cups & 6pcs fixing clips.

25x2000mm

30mm





Recessed Profiles



7910R/B | 2m Recessed profile + PC opal diffuser | Aluminium | Suitable for 7825, 7845, 7870, 7875, 7880, 7882 & 7887 LED Strips 25mm



Complete with 2 pairs end cups & 4pcs fixing clips with screws.

40x2000mm

40mm





7910R/AL | 2m Recessed profile + PC opal diffuser | Aluminium | Suitable for 7825, 7845, 7870, 7875, 7880, 7882 & 7887 LED Strips 25mm



Complete with 2 pairs end cups & 4pcs fixing clips with screws.

40x2000mm

40mm





7910AR/AL | 2m Recessed profile + PC opal diffuser | Aluminium | Suitable for 7875, 7880 & 7885 LED Strips 40mm

6



Complete with 2 pairs end cups & 4pcs metal fixing clips.

52x2000mm

35mm





Trimless Recessed Profiles



7900TR/AL | 2m Trimless profile + PC opal diffuser | Aluminium
Suitable for 7823 & 7833 LED Strips 5mm

40

new



Complete with 2 pairs end cups.

9x2000mm





7901TR/AL | 2m Trimless profile + PC opal diffuser | Aluminium
Suitable for 7820, 7821,7823, 7829 & 7833 LED Strips 10mm

2



Complete with 2 pairs end cups.

13x2000mm





7904TR/AL | 2m Trimless profile + PC opal diffuser | Aluminium
Suitable for 7820, 7821, 7825, 7829, 7830, 7835, 7844, 7870 & 7875 LED Strips 20mm

2



Complete with 2 pairs end cups.

30x2000mm





7906TR/AL | 2m Trimless profile + PC opal diffuser | Aluminium | Suitable for 7875 & 7880 LED Strips 37mm

12



Complete with 2 pairs end cups.

50x2000mm





7904ATR/AL | 2m Trimless profile + PC opal diffuser | Aluminium | Suitable for 7820, 7821, 7825, 7829, 7830, 7835, 7844, 7845, 7870, 7875 & 7887 LED Strips 20mm

12



Complete with 2 pairs end cups.

26x2000mm





IP67 & IP68 Profiles



7918/W | 2m White profile + PMMA opal diffuser | Plastic | Suitable for 7820, 7821 & 7829 LED Strips 8mm

IP68



Complete with 2 pairs end cups & 6pcs fixing clips.





7914R/AL | 2m Inground profile + 3mm PC opal diffuser | Aluminium | Suitable for 7820, 7821 & 7829 LED Strips 8mm

20

IP67



Complete with 2 pairs end cups.

23x2000mm

12mm





7915R/AL | 2m Inground profile + 3mm PC opal diffuser | Aluminium | Suitable for 7820, 7821 & 7829 LED Strips 10mm

80

new

IP67



Complete with 2 pairs end cups.

22x2000mm

14mm





LED Modules



7840 | 0,72W (3LEDs x 0,24W)

Double face adhesive.

LED BUILT IN · DIMMABLE · CE · IP65 · 3 YEAR



Supplied in 10pcs chain.
Total length 1,7m.





7842 | 1,44W (4LEDs x 0,36W)

Double face adhesive.

LED BUILT IN · DIMMABLE · CE · IP65 · 3 YEAR



Supplied in 10pcs chain.
Total length 1,25m.



Order Code	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
7840/Y	Yellow	-	0,72W	-	12V DC	III	100	Requires 12V DC driver
7842/D	Daylight	6000K	1,44W	64lm	12V DC	III	100	Requires 12V DC driver
7842/BL	Blue	-	1,44W	-	12V DC	III	100	Requires 12V DC driver
7842/GR	Green	-	1,44W	-	12V DC	III	100	Requires 12V DC driver
7842/Y	Yellow	-	1,44W	-	12V DC	III	100	Requires 12V DC driver



The 230V Solid LED Strip

Plastic



A-A++

38104B | 4W | SMD 2835 | Plastic

Connect 25 fittings maximum.

LED BUILT IN

80 CRI

QUICK FIX

CE

IP20

2 YEAR







A-A++

38108B | 8W | SMD 2835 | Plastic

Connect 12 fittings maximum.

LED BUILT IN

80 CRI

QUICK FIX

CE

IP20

2 YEAR







A-A++

38114B | 14W | SMD 2835 | Plastic

Connect 7 fittings maximum.

LED BUILT IN

80 CRI

QUICK FIX

CE

IP20

2 YEAR





Order Code	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
38104B/C	Cool white	4000K	4W	320lm	230V	☐	30	Complete with driver
38104B/W	Warm white	3000K	4W	320lm	230V	☐	30	Complete with driver
38108B/C	Cool white	4000K	8W	640lm	230V	☐	30	Complete with driver
38108B/W	Warm white	3000K	8W	640lm	230V	☐	30	Complete with driver
38114B/C	Cool white	4000K	14W	1120lm	230V	☐	30	Complete with driver
38114B/W	Warm white	3000K	14W	1120lm	230V	☐	30	Complete with driver



The 230V Solid LED Strip

Aluminium + PC



38104L | 4W | LED | Aluminium + PC

Connect maximum 5pcs at 110V / Connect maximum 10pcs at 230V.

LED BUILT IN

75 CRI

QUICK FIX

CE

2 YEAR

IP20







38115L | 15W | LED | Aluminium + PC

Connect maximum 5pcs at 110V / Connect maximum 10pcs at 230V.

LED BUILT IN

75 CRI

QUICK FIX

CE

2 YEAR

IP20





Order Code	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
38104L/D	Daylight	6000K	4W	305lm	100-240V		50	Includes power supply cable, corner cable, connector
38104L/W	Warm white	3000K	4W	280lm	100-240V		50	Includes power supply cable, corner cable, connector
38115L/C	Cool white	4000K	15W	1095lm	100-240V		30	Includes power supply cable, corner cable, connector



The 230V Solid Double LED Strip

Aluminium + PC



38207L | 7W | LED | Aluminium + PC

Connect maximum 5pcs at 110V / Connect maximum 10pcs at 230V.





38215L | 15W | LED | Aluminium + PC

Connect maximum 5pcs at 110V / Connect maximum 10pcs at 230V.





38230L | 30W | LED | Aluminium + PC

Connect maximum 5pcs at 110V / Connect maximum 10pcs at 230V.



Order Code	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
38207L/D	Daylight	6000K	7W	530lm	100-240V		30	Includes power supply cable, corner cable, connector
38207L/C	Cool white	4000K	7W	510lm	100-240V		30	Includes power supply cable, corner cable, connector
38207L/W	Warm white	3000K	7W	490lm	100-240V		30	Includes power supply cable, corner cable, connector
38215L/D	Daylight	6000K	15W	1140lm	100-240V		25	Includes power supply cable, corner cable, connector
38215L/W	Warm white	3000K	15W	1050lm	100-240V		25	Includes power supply cable, corner cable, connector
38230L/D	Daylight	6000K	30W	2280lm	100-240V		20	Includes power supply cable, corner cable, connector
38230L/W	Warm white	3000K	30W	2100lm	100-240V		20	Includes power supply cable, corner cable, connector



The LED Shelf System

Aluminium + PC



38103 | 3W | SMD 3014 | Aluminium + PC

LED BUILT IN · 80 CRI · DIMMABLE · QUICK FIX · IP20 · 2 YEAR



2m maximum each line.





38105 | 5W | SMD 3014 | Aluminium + PC

LED BUILT IN · 80 CRI · DIMMABLE · QUICK FIX · IP20 · 2 YEAR



2m maximum each line.





38110 | 10W | SMD 3014 | Aluminium + PC

LED BUILT IN · 80 CRI · DIMMABLE · QUICK FIX · IP20 · 2 YEAR



2m maximum each line.





12122 | 3W | SMD 3528 | Aluminium + PC

Can be fixed with double face adhesive or screws.

LED BUILT IN · 80 CRI · DIMMABLE · QUICK FIX · IP20 · 2 YEAR



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
38103/W	-	Warm white	3000K	3W	225lm	24V DC		100	Requires 24V DC driver / Includes mounting clips (2pcs), screws (2pcs)
38105/W	-	Warm white	3000K	5W	375lm	24V DC		50	Requires 24V DC driver / Includes mounting clips (2pcs), screws (2pcs)
38110/W	-	Warm white	3000K	10W	750lm	24V DC		25	Requires 24V DC driver / Includes mounting clips (3pcs), screws (3pcs)
12122/G/W	Grey	Warm white	3000K	3W	180lm	24V DC		100	Requires 24V DC driver

The LED Shelf System Accessories



38102A | Touch ON/OFF and dimmer | Max. 60W | 24V DC









38102B | Wave hand | Door ON/OFF | Max. 60W | 24V DC









38102C | PIR Sensor | Max. 60W | 24V DC

Adjustable 1min / 5min.







38101A | Connector for 38103, 38105 & 38110





38101B | Corner for 38103, 38105 & 38110





38101C | Power supply cable connector for 38103, 38105 & 38110

100cm



38101D | 8 - Way connection box | 24V DC

100cm





The 230V IP65 Range



7850 | 6W/m | SMD 2835 | 60LEDs/m | PVC

Cut every 1m.

LED BUILT IN · 80 CRI · DIMMABLE · QUICK FIX · IP65 · CE · 2 YEAR



Supplied in 100m roll.

11mm



7850C Connector



7850P
230V Power supply
for 50m



7850F Fixing clip



7850L Corner



7850E End cup



7860 | 9W/m | SMD 5050 | 60LEDs/m | PVC

Cut every 1m.

LED BUILT IN · 80 CRI · DIMMABLE · QUICK FIX · IP65 · CE · 2 YEAR



Supplied in 50m roll.

15mm



7860C Connector



7860P
230V Power supply
for 50m



7860F Fixing clip



7860L Corner



7860E End cup



7860R
Shrinking sleeve

Order Code	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
7850/D	Daylight	6000K	6W/m	320lm/m	230V	☐	100m roll	Requires 7850P power supply
7850/C	Cool white	4000K	6W/m	400lm/m	230V	☐	100m roll	Requires 7850P power supply
7850/W	Warm white	3000K	6W/m	400lm/m	230V	☐	100m roll	Requires 7850P power supply
7850/BL	Blue	-	6W/m	-	230V	☐	100m roll	Requires 7850P power supply
7860/D	Daylight	6000K	9W/m	750lm/m	230V	☐	50m roll	Requires 7860P power supply
7860/C	Cool white	4000K	9W/m	750lm/m	230V	☐	50m roll	Requires 7860P power supply
7860/W	Warm white	3000K	9W/m	750lm/m	230V	☐	50m roll	Requires 7860P power supply

The 230V IP65 Range



7862 | 13W/m | SMD 5630 | 120LEDs/m | PVC

Cut every 1m.

LED BUILT IN · 80 CRI · CE · IP65 · 2 YEAR



18mm



7862C Connector



7862P
230V Power supply
for 30m



7862F Fixing clip



7862E End cup



7862L Corner connector



7862R Shrinking sleeve

Order Code	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
7862/C	Cool white	4000K	13W/m	1050lm/m	230V		30m roll	Requires 7862P power supply
7862/W	Warm white	3000K	13W/m	1000lm/m	230V		30m roll	Requires 7862P power supply

24V Linkable Modules

Aluminium



38001A | 1W | LED | Aluminium

IP20 offer

LED BUILT IN · DIMMABLE · QUICK FIX · CE · 3 YEAR







38002A | 3W | LED | Aluminium

IP20 offer

LED BUILT IN · DIMMABLE · QUICK FIX · CE · 3 YEAR







38005A | 6W | LED | Aluminium

IP20 offer

LED BUILT IN · DIMMABLE · QUICK FIX · CE · 3 YEAR







38006 & 38007 | Power supply cable and corner cable for 38001A, 38002A & 38005A

III · QUICK FIX · CE

Power supply cable
38006A For DL and WW
38006B For BL
38006C For RGB

Corner cable
38007A For DL and WW
38007B For BL
38007C For RGB



Order Code	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
38001A/D	Daylight	6000K	1W	64lm	24V DC	III	100	Requires 24V DC driver
38001A/W	Warm white	3000K	1W	60lm	24V DC	III	100	Requires 24V DC driver
38001A/BL	Blue	-	1W	-	24V DC	III	100	Requires 24V DC driver
38001A/RGB	RGB	-	1W	-	24V DC	III	100	Requires 24V DC driver
38002A/D	Daylight	6000K	3W	144lm	24V DC	III	100	Requires 24V DC driver
38002A/W	Warm white	3000K	3W	135lm	24V DC	III	100	Requires 24V DC driver
38002A/BL	Blue	-	3W	-	24V DC	III	100	Requires 24V DC driver
38002A/RGB	RGB	-	3W	-	24V DC	III	100	Requires 24V DC driver
38005A/D	Daylight	6000K	6W	384lm	24V DC	III	100	Requires 24V DC driver
38005A/W	Warm white	3000K	6W	360lm	24V DC	III	100	Requires 24V DC driver
38005A/BL	Blue	-	6W	-	24V DC	III	100	Requires 24V DC driver

IP67 Flex Lightline



7811 | 10W/m | SMD 2216 | 192 LEDs | Silicone





Supplied in 5m roll.







Accessories for 7811

7811F	Fixing clip
7811E	End cup

Order Code	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
7811/C	Cool white	4000K	10W/m	550lm/m	24V DC	III	40	Requires 24V DC driver
7811/W	Warm white	3000K	10W/m	550lm/m	24V DC	III	40	Requires 24V DC driver



Flex Lightline



7810 | 4,8W/m | LED | Silicone

IP54







7810 | 4,8W/m | LED | Silicone

IP54







7810 | 4,8W/m | LED | Silicone

IP54







7810 | 4,8W/m | LED | Silicone

IP54







7810 | 4,8W/m | LED | Silicone

IP54
offer





Order Code	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
7810/D	Daylight	6000K	4,8W/m	180lm/m	230V		50m roll	Requires 7814 power supply
7810/BL	Blue	-	4,8W/m	-	230V		50m roll	Requires 7814 power supply
7810/R	Red	-	4,8W/m	-	230V		50m roll	Requires 7814 power supply
7810/P	Pink	-	4,8W/m	-	230V		50m roll	Requires 7814 power supply
7810/RBL	Red + Blue	-	4,8W/m	-	230V		50m roll	Requires 7818 controller RBL

Flex Lightline Accessories



7814 | Power supply for 7810

Connect maximum 50m.



7818 | RBL Controller for 7810/RBL

Connect maximum 30m.

offer



Accessories for 7810

400
25

7812 Connector
7817 End cup



7815 | 2m Profile for 7810 | Aluminium



10



7815/W White
7815/G Grey



7815B | Housing box for 7814, 7818 & 7819



8



7815B/W White
7815B/G Grey

Order Code	Colour	Input	Class			Notes
7814	White	230V		150cm	100	-
7818	White	230V		80cm	48	-





10

Track Spots

Pages 269-300

COB LED | SMD LED | LED | GU10 | Rx7s | HQI | PAR30 | E27 | CDM-R

Die cast | Natural aluminium

IP20

ADJUSTABLE DARK LIGHT 80 CRI 2 YEAR 3 YEAR 5 YEAR



Cylindrical Track Spot



A-A++ 65608T/G/D

65608T | 3x1W | LED | Die cast

IP20

offer

LED BUILT IN

ADJUSTABLE

2 YEAR









A-A++ 65608T/G/W

65608T | 3x1W | LED | Die cast

IP20

offer

LED BUILT IN

ADJUSTABLE

2 YEAR







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
65608T/G/D	Grey	Daylight	6000K	3x1W	217lm	60°	230V	⏚	30	Complete with driver
65608T/G/W	Grey	Warm white	3000K	3x1W	205lm	60°	230V	⏚	30	Complete with driver



The COB Dark Light Range



65610AT/W/C

65610AT | 10W | COB LED | Aluminium

DARK LIGHT
IP20

LED BUILT IN
80 CRI
ADJUSTABLE
2 YEAR



65610AT/B/W







65620AT/W/C

65620AT | 20W | COB LED | Aluminium

DARK LIGHT
IP20

LED BUILT IN
80 CRI
ADJUSTABLE
2 YEAR



65620AT/B/W





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
65610AT/W/C	White	Cool white	4000K	10W	800lm	38°	230V	⏚	20	Complete with 300mA driver
65610AT/W/W	White	Warm white	3000K	10W	800lm	38°	230V	⏚	20	Complete with 300mA driver
65610AT/B/W	Black	Warm white	3000K	10W	800lm	38°	230V	⏚	20	Complete with 300mA driver
65620AT/W/C	White	Cool white	4000K	20W	1500lm	38°	230V	⏚	10	Complete with 500mA driver
65620AT/W/W	White	Warm white	3000K	20W	1500lm	38°	230V	⏚	10	Complete with 500mA driver
65620AT/B/W	Black	Warm white	3000K	20W	1500lm	38°	230V	⏚	10	Complete with 500mA driver



The COB Track Spot Range

Aluminium



65611T | 15W | COB LED | Aluminium

LED BUILT IN
80 CRI
ADJUSTABLE
2 YEAR
IP20









65612T/G/C

65612T | 30W | COB LED | Aluminium

LED BUILT IN
80 CRI
ADJUSTABLE
2 YEAR
IP20



65612T/W/W





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
65611T/G/W	Grey	Warm white	3000K	15W	1100lm	36°	230V		12	Complete with 350mA driver
65612T/W/W	White	Warm white	3000K	30W	2300lm	36°	230V		9	Complete with 700mA driver
65612T/G/C	Grey	Cool white	4000K	30W	2400lm	36°	230V		9	Complete with 700mA driver





The COB Track Spot Range

Aluminium



65614T | 45W | COB LED | Aluminium

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · 2 YEAR · IP20









65616T/B/C

65616T | 50W | COB LED | Aluminium

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · 2 YEAR · IP20



65616T/B/W





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
65614T/W/W	White	Warm white	3000K	45W	3500lm	36°	230V		9	Complete with 1000mA driver
65616T/B/C	Black	Cool white	4000K	50W	4200lm	38°	230V		6	Complete with 1200mA driver
65616T/B/W	Black	Warm white	3000K	50W	4000lm	38°	230V		6	Complete with 1200mA driver





The COB Track Spot Range

Aluminium



65611NT | 15W | COB LED | Aluminium

LED BUILT IN
80 CRI
ADJUSTABLE
CE
2 YEAR
IP20









65612NT | 30W | COB LED | Aluminium

LED BUILT IN
80 CRI
ADJUSTABLE
CE
2 YEAR
IP20









65614NT | 42W | COB LED | Aluminium

LED BUILT IN
80 CRI
ADJUSTABLE
CE
2 YEAR
IP20







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
65611NT/W/C	White	Cool white	4000K	15W	1300lm	38°	230V		10	Complete with 400mA driver
65611NT/W/W	White	Warm white	3000K	15W	1200lm	38°	230V		10	Complete with 400mA driver
65612NT/W/C	White	Cool white	4000K	30W	2500lm	38°	230V		10	Complete with 750mA driver
65612NT/W/W	White	Warm white	3000K	30W	2400lm	38°	230V		10	Complete with 750mA driver
65614NT/W/C	White	Cool white	4000K	42W	3500lm	38°	230V		10	Complete with 1050mA driver
65614NT/W/W	White	Warm white	3000K	42W	3400lm	38°	230V		10	Complete with 1050mA driver



The COB Track Spot Range

Aluminium



65611NT | 15W | COB LED | Aluminium

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · 2 YEAR · IP20









65612NT | 30W | COB LED | Aluminium

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · 2 YEAR · IP20









65614NT | 42W | COB LED | Aluminium

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · 2 YEAR · IP20







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
65611NT/B/C	Black	Cool white	4000K	15W	1300lm	38°	230V		10	Complete with 400mA driver
65611NT/B/W	Black	Warm white	3000K	15W	1200lm	38°	230V		10	Complete with 400mA driver
65612NT/B/C	Black	Cool white	4000K	30W	2500lm	38°	230V		10	Complete with 750mA driver
65612NT/B/W	Black	Warm white	3000K	30W	2400lm	38°	230V		10	Complete with 750mA driver
65614NT/B/C	Black	Cool white	4000K	42W	3500lm	38°	230V		10	Complete with 1050mA driver
65614NT/B/W	Black	Warm white	3000K	42W	3400lm	38°	230V		10	Complete with 1050mA driver



The COB Cylinder Track Spot



65642AT | 10W | COB LED | Aluminium

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · 2 YEAR · IP20









65642BT | 20W | COB LED | Aluminium

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · 2 YEAR · IP20









65642CT | 30W | COB LED | Aluminium

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · 2 YEAR · IP20







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
65642AT/W/C	White	Cool white	4000K	10W	850lm	38°	230V		24	Complete with 250mA driver
65642AT/W/W	White	Warm white	3000K	10W	800lm	38°	230V		24	Complete with 250mAdriver
65642BT/W/C	White	Cool white	4000K	20W	1700lm	38°	230V		18	Complete with 500mA driver
65642BT/W/W	White	Warm white	3000K	20W	1600lm	38°	230V		18	Complete with 500mA driver
65642CT/W/C	White	Cool white	4000K	30W	2600lm	38°	230V		15	Complete with 750mA driver
65642CT/W/W	White	Warm white	3000K	30W	2400lm	38°	230V		15	Complete with 750mA driver



65642BT/B/C



65642CT/B/C

The COB Cylinder Track Spot



65642AT | 10W | COB LED | Aluminium

LED BUILT IN
80 CRI
ADJUSTABLE
CE
2 YEAR
IP20









65642BT | 20W | COB LED | Aluminium

LED BUILT IN
80 CRI
ADJUSTABLE
CE
2 YEAR
IP20









65642CT | 30W | COB LED | Aluminium

LED BUILT IN
80 CRI
ADJUSTABLE
CE
2 YEAR
IP20







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
65642AT/B/C	Black	Cool white	4000K	10W	850lm	38°	230V		24	Complete with 250mA driver
65642AT/B/W	Black	Warm white	3000K	10W	800lm	38°	230V		24	Complete with 250mAdriver
65642BT/B/C	Black	Cool white	4000K	20W	1700lm	38°	230V		18	Complete with 500mA driver
65642BT/B/W	Black	Warm white	3000K	20W	1600lm	38°	230V		18	Complete with 500mA driver
65642CT/B/C	Black	Cool white	4000K	30W	2600lm	38°	230V		15	Complete with 750mA driver
65642CT/B/W	Black	Warm white	3000K	30W	2400lm	38°	230V		15	Complete with 750mA driver

The COB Cylinder Range



65646T | 8W | COB LED | Aluminium

new

IP20

LED BUILT IN · 80 CRI · TRIAC DIMMABLE · ADJUSTABLE · CE · 2 YEAR







65108T | 8W | COB LED | Aluminium

IP20

LED BUILT IN · 90 CRI · TRIAC DIMMABLE · ADJUSTABLE · CE · 2 YEAR







65632T | 35W | COB LED | Aluminium

IP20

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · 2 YEAR









65632CT | 50W | COB LED | Die cast

IP20

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · 2 YEAR







Order Code	Colour	Reflector	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
65646T/W/W	White	-	Warm white	3000K	8W	650lm	36°	230V		24	AC LED
65646T/B/W	Black	-	Warm white	3000K	8W	650lm	36°	230V		24	AC LED
65108T/W/W	White	Black	Warm white	3000K	8W	560lm	36°	230V		24	Complete with 350mA driver
65108T/B/W	Black	Brass	Warm white	3000K	8W	560lm	36°	230V		24	Complete with 350mA driver
65632T/W/C	White	-	Cool white	4000K	35W	3300lm	36°	230V		9	Complete with 900mA driver
65632T/W/W	White	-	Warm white	3000K	35W	3200lm	36°	230V		9	Complete with 900mA driver
65632CT/W/C	White	-	Cool white	4000K	50W	4000lm	36°	230V		6	Complete with 1250mA driver
65632CT/W/W	White	-	Warm white	3000K	50W	3750lm	36°	230V		6	Complete with 1250mA driver
65632CT/B/W	Black	-	Warm white	3000K	50W	3750lm	36°	230V		6	Complete with 1250mA driver



The COB Dark Light Cylinder Range

Die cast



65640AT | 10W | COB LED | Die cast

LED BUILT IN
80 CRI
ADJUSTABLE
CE
DARK LIGHT
IP20
2 YEAR









65640BT | 36W | COB LED | Die cast

LED BUILT IN
80 CRI
ADJUSTABLE
CE
DARK LIGHT
IP20
2 YEAR



15° Reflector for 65640BT.
Order code 0740/15.





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
65640AT/W/W	White	Warm white	3000K	10W	730lm	36°	230V	⏚	24	Complete with 500mA driver
65640BT/W/C	White	Cool white	4000K	36W	2500lm	36°	230V	⏚	16	Complete with 900mA driver
65640BT/W/W	White	Warm white	3000K	36W	2400lm	36°	230V	⏚	16	Complete with 900mA driver



65620T2/W/C



65620TA/W/C

The COB Side Box Range



A-A++ 65620TA/W/C

65620TA | 15W | COB LED | Die cast

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · 2 YEAR · IP20



65620TA/W/W







A-A++

65620T | 20W | COB LED | Aluminium

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · 2 YEAR · IP20









A-A++

65620T2 | 2x15W | COB LED | Aluminium

Ideal for corridors, left & right shelves illumination.

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · 2 YEAR · IP20







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
65620TA/W/C	White	Cool white	4000K	15W	1200lm	45°	230V		12	Complete with 400mA driver
65620TA/W/W	White	Warm white	3000K	15W	1095lm	45°	230V		12	Complete with 400mA driver
65620T/W/W	White	Warm white	3000K	20W	1460lm	45°	230V		12	Complete with 500mA driver
65620T2/W/C	White	Cool white	4000K	2x15W	2x1200lm	45°	230V		6	Complete with 700mA driver



The COB Track Spots



A-A++ 65628T/W/C

65628T | 15W | COB LED | Aluminium

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · 2 YEAR · IP20



65628T/B/C







A-A++ 65630T/W/C

65630T | 25W | COB LED | Die cast

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · 2 YEAR · IP20



65630T/W/W







A-A++ 65626T/W/C

65626T | 25W | COB LED | Die cast

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · 2 YEAR · IP20



65626T/W/W





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
65628T/W/C	White	Cool white	4000K	15W	1200lm	45°	230V		12	Complete with 400mA driver
65628T/W/W	White	Warm white	3000K	15W	1095lm	45°	230V		12	Complete with 400mA driver
65628T/B/C	Black	Cool white	4000K	15W	1200lm	45°	230V		12	Complete with 400mA driver
65628T/B/W	Black	Warm white	3000K	15W	1095lm	45°	230V		12	Complete with 400mA driver
65630T/W/C	White	Cool white	4000K	25W	1900lm	45°	100-240V		12	Complete with 580mA driver
65630T/W/W	White	Warm white	3000K	25W	1800lm	45°	100-240V		12	Complete with 580mA driver
65626T/W/C	White	Cool white	4000K	25W	2000lm	45°	100-240V		12	Complete with 580mA driver
65626T/W/W	White	Warm white	3000K	25W	1900lm	45°	100-240V		12	Complete with 580mA driver



The COB Top Box Range



65618T/W/C

65618T | 35W | COB LED | Die cast

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · 3 YEAR · IP20



65618T/G/C





65619T/W/C

65619T | 38W | COB LED | Aluminium

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · 3 YEAR · IP20



65619T/B/C



15° Reflector for 65619T.
Order code 0742/15.





65624T | 35W | COB LED | Die cast

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · 3 YEAR · IP20







65638T | 50W | COB LED | Die cast

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · 3 YEAR · IP20





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
65618T/W/C	White	Cool white	4000K	35W	3350lm	45°	230V		12	Complete with 900mA driver
65618T/W/W	White	Warm white	3000K	35W	3200lm	45°	230V		12	Complete with 900mA driver
65618T/G/C	Grey	Cool white	4000K	35W	3350lm	45°	230V		12	Complete with 900mA driver
65619T/W/C	White	Cool white	4000K	38W	3200lm	36°	230V		16	Complete with 900mA driver
65619T/W/W	White	Warm white	3000K	38W	3000lm	36°	230V		16	Complete with 900mA driver
65619T/B/C	Black	Cool white	4000K	38W	3200lm	36°	230V		16	Complete with 900mA driver
65619T/B/W	Black	Warm white	3000K	38W	3000lm	36°	230V		16	Complete with 900mA driver
65624T/W/C	White	Cool white	4000K	35W	3050lm	45°	230V		12	Complete with 900mA driver
65624T/W/W	White	Warm white	3000K	35W	2950lm	45°	230V		12	Complete with 900mA driver
65638T/W/C	White	Cool white	4000K	50W	3700lm	36°	230V		12	Complete with 1200mA driver



The COB Side Box Range

Die cast



65226T | 26W | COB LED | Die cast

LED BUILT IN
80 CRI
ADJUSTABLE
3 YEAR
IP20









65622T | 34W | COB LED | Die cast

LED BUILT IN
80 CRI
ADJUSTABLE
3 YEAR
IP20



Optional 18° reflector.
Order code 0730/18.





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
65226T/W/W	White	Warm white	3000K	26W	1960lm	30°	100-240V	⏚	8	Complete with driver
65622T/W/C	White	Cool white	4000K	34W	3550lm	42°	230V	⏚	12	Complete with 900mA driver
65622T/W/W	White	Warm white	3000K	34W	3350lm	42°	230V	⏚	12	Complete with 900mA driver



65652T/W/W

65644T/W/W

The Honeycomb Range



A-A++ 65644T/W/W

65644T | 8W | COB LED | Dimmable | Aluminium

Complete with honeycomb.

new

IP20

LED BUILT IN · 80 CRI · TRIAC DIMMABLE · ADJUSTABLE · CE · 2 YEAR



65644T/B/W







A-A++ 65652T/W/W

65652T | 30W | COB LED | Die cast

Complete with honeycomb.

new

IP20

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · 2 YEAR



65652T/B/W





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
65644T/W/W	White	Warm white	3000K	8W	600lm	36°	230V		24	AC LED
65644T/B/W	Black	Warm white	3000K	8W	600lm	36°	230V		24	AC LED
65652T/W/C	White	Cool white	4000K	30W	1800lm	24°	230V		12	Complete with 700mA driver
65652T/W/W	White	Warm white	3000K	30W	1700lm	24°	230V		12	Complete with 700mA driver
65652T/B/C	Black	Cool white	4000K	30W	1800lm	24°	230V		12	Complete with 700mA driver
65652T/B/W	Black	Warm white	3000K	30W	1700lm	24°	230V		12	Complete with 700mA driver



The Zoomable Range



A-A++ 65650T/W/C

65650T | 30W | COB LED | Adjustable beam 20°-60° | Aluminium

new

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · IP20 · 2 YEAR



65650T/B/C







A-A++ 65648T/B/C

65648T | 30W | COB LED | Adjustable beam 12°-60° | Aluminium

new

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · IP20 · 2 YEAR



65648T/B/W





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
65650T/W/C	White	Cool white	4000K	30W	2400lm	20°-60°	230V		15	Complete with 750mA driver
65650T/W/W	White	Warm white	3000K	30W	2300lm	20°-60°	230V		15	Complete with 750mA driver
65650T/B/C	Black	Cool white	4000K	30W	2400lm	20°-60°	230V		15	Complete with 750mA driver
65650T/B/W	Black	Warm white	3000K	30W	2300lm	20°-60°	230V		15	Complete with 750mA driver
65648T/B/C	Black	Cool white	4000K	30W	2550lm	12°-60°	120-240V		12	Complete with 700mA driver
65648T/B/W	Black	Warm white	3000K	30W	2550lm	12°-60°	120-240V		12	Complete with 700mA driver



LED Linear Track Light

65018T | 16W | SMD 2835 | Linear light | Aluminium + PC



65018T/W/W

new

IP20

LED BUILT IN

80 CRI

2 YEAR



65018T/B/W



65025T | 25W | SMD 2835 | Linear light | Aluminium + PC



65025T/W/W

new

IP20

LED BUILT IN

80 CRI

2 YEAR



65025T/B/W



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
65018T/W/C	White	Cool white	4000K	16W	1600lm	110°	100-240V		12	Complete with 400mA driver
65018T/W/W	White	Warm white	3000K	16W	1600lm	110°	100-240V		12	Complete with 400mA driver
65018T/B/C	Black	Cool white	4000K	16W	1600lm	110°	100-240V		12	Complete with 400mA driver
65018T/B/W	Black	Warm white	3000K	16W	1600lm	110°	100-240V		12	Complete with 400mA driver
65025T/W/C	White	Cool white	4000K	25W	2500lm	110°	100-240V		12	Complete with 600mA driver
65025T/W/W	White	Warm white	3000K	25W	2500lm	110°	100-240V		12	Complete with 600mA driver
65025T/B/C	Black	Cool white	4000K	25W	2500lm	110°	100-240V		12	Complete with 600mA driver
65025T/B/W	Black	Warm white	3000K	25W	2500lm	110°	100-240V		12	Complete with 600mA driver



Adjustable LED Linear Track Light



A-A++ 65024T/W/C

65024T | 10x5W | COB LED | Linear track light | Aluminium + plastic

LED BUILT IN

80 CRI

±45° ADJUSTABLE

CE

2 YEAR

IP20



65024T/B/C







A-A++ 65026T/W/C

65026T | 40W | SMD 2835 | Linear track light | Aluminium + plastic

LED BUILT IN

80 CRI

±45° ADJUSTABLE

CE

2 YEAR

IP20



65026T/B/C





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
65024T/W/C	White	Cool white	4000K	10x5W	10x425lm	30°	230V		10	Complete with 500mA driver
65024T/W/W	White	Warm white	3000K	10x5W	10x400lm	30°	230V		10	Complete with 500mA driver
65024T/B/C	Black	Cool white	4000K	10x5W	10x425lm	30°	230V		10	Complete with 500mA driver
65024T/B/W	Black	Warm white	3000K	10x5W	10x400lm	30°	230V		10	Complete with 500mA driver
65026T/W/C	White	Cool white	4000K	40W	3400lm	100°	230V		10	Complete with 450mA driver
65026T/W/W	White	Warm white	3000K	40W	3200lm	100°	230V		10	Complete with 450mA driver
65026T/B/C	Black	Cool white	4000K	40W	3400lm	100°	230V		10	Complete with 450mA driver
65026T/B/W	Black	Warm white	3000K	40W	3200lm	100°	230V		10	Complete with 450mA driver



65042T/B/C



65510T/B



65020T/B/W

The Track Floodlight Range

Die cast



A-A++ 65020T/W/C

65020T | 20W | SMD 3030 | Die cast

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · 2 YEAR · IP20



65020T/B/C







A-A++ 65042T/W/W

65042T | 42W | SMD 2835 | Die cast

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · 2 YEAR · IP20



65042T/B/W







B-A+ 65510T/W

65510T | 70W | HQI | Rx7s | Die cast

ADJUSTABLE · CE · 2 YEAR · IP20 · offer



65510T/B



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
65020T/W/C	White	Cool white	4000K	20W	1500lm	24°	230V		20	Complete with 600mA driver
65020T/W/W	White	Warm white	3000K	20W	1400lm	24°	230V		20	Complete with 600mA driver
65020T/B/C	Black	Cool white	4000K	20W	1500lm	24°	230V		20	Complete with 600mA driver
65020T/B/W	Black	Warm white	3000K	20W	1400lm	24°	230V		20	Complete with 600mA driver
65042T/W/C	White	Cool white	4000K	42W	3570lm	80°	230V		4	Complete with 1200mA driver
65042T/W/W	White	Warm white	3000K	42W	3150lm	80°	230V		4	Complete with 1200mA driver
65042T/B/C	Black	Cool white	4000K	42W	3570lm	80°	230V		4	Complete with 1200mA driver
65042T/B/W	Black	Warm white	3000K	42W	3150lm	80°	230V		4	Complete with 1200mA driver
65510T/W	White	-	-	70W	-	-	230V		12	Complete with electronic ballast
65510T/B	Black	-	-	70W	-	-	230V		12	Complete with electronic ballast
65510T/G	Grey	-	-	70W	-	-	230V		12	Complete with electronic ballast



The Track Floodlight Range

Die cast



C-A++

65009T | 100W | Halogen | R7s | Die cast

ADJUSTABLE

5 YEAR

IP20

offer



Suitable for 7610L LED lamp (Direct 230V).





B-A+

65010T/G

65010T | 70W | HQI | Rx7s | Die cast

ADJUSTABLE

2 YEAR

IP20

offer



offer

65010T/B





B-A+

65010B | 70W | HQI | Rx7s | Ceiling mounted | Die cast

ADJUSTABLE

2 YEAR

IP20

offer





Order Code	Colour	Watts	Input	Class		Notes
65009T/G	Grey	100W	230V		12	-
65010T/B	Black	70W	230V		12	Complete with electronic ballast
65010T/G	Grey	70W	230V		12	Complete with electronic ballast
65010B/G	Grey	70W	230V		12	Complete with electronic ballast



The Oval Track Spots

Die cast



65112T | 50W | MR16 | GU5,3 | Die cast

ADJUSTABLE

IP20

offer







65114T | 50W | R111 | G53 | Die cast

ADJUSTABLE

IP20

offer





Order Code	Colour	Watts	Input	Class		Notes
65112T/G	Grey	50W	230V / 12V		16	Complete with transformer
65114T/G	Grey	50W	230V / 12V		12	Complete with transformer



The Cone Series Track Spots

Die cast



65736T | 35W | HQI | G12 | Die cast

ADJUSTABLE

IP20

offer

2 YEAR









65719T/B

65719T | 75W | R111 | GU10 | Die cast

ADJUSTABLE

IP20

offer

5 YEAR



Suitable for R111 LED lamp.







65719T/G

65719T | 75W | R111 | GU10 | Die cast

ADJUSTABLE

IP20

offer

5 YEAR



Suitable for R111 LED lamp.





Order Code	Colour	Watts	Input	Beam Angle	Class		Notes
65736T/G	Grey	35W	230V	67°	⏚	12	Complete with electronic ballast
65719T/B	Black	75W	100-240V	-	⏚	12	-
65719T/G	Grey	75W	100-240V	-	⏚	12	-



65835T/G



65835T/B

The Square Head Range

Die cast



B-A+ 65835T/W

65835T | 35W | HQI | G8,5 | Die cast

IP20

offer

ADJUSTABLE

2 YEAR



offer 65835T/B



offer 65835T/G





B-A+ 65834T/W

65834T | 70W | HQI | G8,5 | Die cast

IP20

offer

ADJUSTABLE

2 YEAR



65834T/G offer



Order Code	Colour	Watts	Input	Beam Angle	Class		Notes
65835T/W	White	35W	230V	53°		12	Complete with electronic ballast
65835T/B	Black	35W	230V	53°		12	Complete with electronic ballast
65835T/G	Grey	35W	230V	53°		12	Complete with electronic ballast
65834T/W	White	70W	230V	53°		12	Complete with electronic ballast
65834T/G	Grey	70W	230V	53°		12	Complete with electronic ballast





65935T | 35W | HQI | G8,5 | Die cast

ADJUSTABLE

IP20

offer









65934T | 70W | HQI | G8,5 | Die cast

ADJUSTABLE

IP20

offer







Order Code	Colour	Watts	Input	Beam Angle	Class		Notes
65935T/G	Grey	35W	230V	53°		18	Complete with electronic ballast
65934T/G	Grey	70W	230V	53°		18	Complete with electronic ballast



Box Series Track Spots

Die cast



65012T | 50W | MR16 | GU5,3 | Die cast

ADJUSTABLE

2 YEAR

IP20

offer









65019T/G

65019T | 50W | MR16 | GU10 | Die cast

ADJUSTABLE

5 YEAR

IP20



65019T/W







65011T | 75W | PAR30 | E27 | Die cast

ADJUSTABLE

5 YEAR

IP20

offer



Suitable for PAR30 LED lamp.







65016T/G

65016T | 70W | CDM-R | E27 | Die cast

ADJUSTABLE

2 YEAR

IP20

offer



offer

65016T/B





Order Code	Colour	Watts	Input	Class		Notes
65012T/G	Grey	50W	230V / 12V		20	Complete with transformer
65019T/W	White	50W	100-240V		16	-
65019T/G	Grey	50W	100-240V		16	-
65011T/G	Grey	75W	100-240V		8	-
65016T/B	Black	70W	230V		8	Complete with electronic ballast
65016T/G	Grey	70W	230V		8	Complete with electronic ballast



π Series Track Spots

Die cast



65008T/G/D/24

65008T | 10W | LED | Die cast

LED BUILT IN

70 CRI 6000K

80 CRI 3000K

ADJUSTABLE

IP20

offer

2 YEAR



65008T/G/W/24

offer







65013T | 70W | CDM-R111 | GX8,5 | Die cast

ADJUSTABLE

IP20

offer

2 YEAR



offer





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
65008T/G/D/24	Grey	Daylight	6000K	10W	600lm	24°	230V	⏚	12	Complete with driver
65008T/G/W/24	Grey	Warm white	3000K	10W	600lm	24°	230V	⏚	12	Complete with driver
65013T/G	Grey	-	-	70W	-	-	230V	⏚	8	Complete with electronic ballast



65514T/G



65534T/W

The Side Box Range

Die cast



65534T | 70W | HQI | G8,5 | Die cast









65514T | 75W | R111 | GU10 | Die cast



Suitable for R111 LED lamp.





Order Code	Colour	Watts	Input	Beam Angle	Class		Notes
65534T/W	White	70W	230V	53°		16	Complete with electronic ballast
65514T/G	Grey	75W	100-240V	-		12	-



The Side Box Range HQI

Die cast



B-A+ 65235T/W

65235T | 35W | HQI | G8,5 | Die cast





65235T/G







B-A+ 65234T/W

65234T | 70W | HQI | G8,5 | Die cast





65234T/G





Order Code	Colour	Watts	Input	Beam Angle	Class		Notes
65235T/W	White	35W	230V	50°		1	Complete with electronic ballast
65235T/G	Grey	35W	230V	50°		1	Complete with electronic ballast
65234T/W	White	70W	230V	50°		1	Complete with electronic ballast
65234T/G	Grey	70W	230V	50°		1	Complete with electronic ballast



The GU10 Track Spots

Aluminium



B-A++ 65520T/W

65520T | 20W | MR16 | GU10 | Aluminium

ADJUSTABLE

5 YEAR

IP20



65520T/B



Suitable for GU10 LED lamp.





B-A++ 65519T/W

65519T | 20W | MR16 | GU10 | Aluminium

ADJUSTABLE

5 YEAR

IP20



65519T/B



65519T/G





C-A++ 65518T/W

65518T | 50W | R111 | GU10 | Aluminium

ADJUSTABLE

5 YEAR

IP20



65518T/B



65518T/G



Order Code	Colour	Watts	Input	Class		Notes
65520T/W	White	20W	100-240V		20	-
65520T/B	Black	20W	100-240V		20	-
65519T/W	White	20W	100-240V		12	-
65519T/B	Black	20W	100-240V		12	-
65519T/G	Grey	20W	100-240V		12	-
65518T/W	White	50W	100-240V		12	-
65518T/B	Black	50W	100-240V		12	-
65518T/G	Grey	50W	100-240V		12	-



65105NAT/B



65105NT/B

The Dark Light GU10 Range



A-A++ 65522T/B

65522T | 10W | MR16 | GU10 | Aluminium

ADJUSTABLE

DARK LIGHT

IP20

5 YEAR



65522T/W



Removable honeycomb.





A-A++ 65105NT/B

65105NT | 10W | MR16 | GU10 | Aluminium

ADJUSTABLE

DARK LIGHT

IP20

5 YEAR



65105NT/W



Suitable for GU10 LED lamp.





A-A++ 65105NAT/B

65105NAT | 10W | MR16 | GU10 | Aluminium

ADJUSTABLE

new

DARK LIGHT

IP20

5 YEAR



65105NAT/W



Suitable for GU10 LED lamp.



Order Code	Colour	Reflector	Watts	Input	Class		Notes
65522T/W	White	-	10W	100-240V		24	-
65522T/B	Black	-	10W	100-240V		24	-
65105NT/W	White	Black	10W	100-240V		24	-
65105NT/B	Black	Brass	10W	100-240V		24	-
65105NAT/W	White	Black	10W	100-240V		24	-
65105NAT/B	Black	Brass	10W	100-240V		24	-



The E27 Track Spot

Die cast



C-A++ 65111AT/W

65111AT | 75W | PAR30 | E27 | Die cast

ADJUSTABLE

5 YEAR

IP20



Suitable for PAR30 LED lamp.







C-A++ 65111AT/B

65111AT | 75W | PAR30 | E27 | Die cast

ADJUSTABLE

5 YEAR

IP20



Suitable for PAR30 LED lamp.







C-A++ 65111AT/G

65111AT | 75W | PAR30 | E27 | Die cast

ADJUSTABLE

5 YEAR

IP20



Suitable for PAR30 LED lamp.





Order Code	Colour	Watts	Input	Class		Notes
65111AT/W	White	75W	100-240V		40	-
65111AT/B	Black	75W	100-240V		40	-
65111AT/G	Grey	75W	100-240V		40	-


65111AT/W


65618AT/W

The E27 Track Spot

Die cast


C-A++ 65118AT/W

65118AT | 50W | R111 | GU10 | Die cast

ADJUSTABLE

5 YEAR

IP20


Suitable for R111 LED lamp.




C-A++ 65118AT/B

65118AT | 50W | R111 | GU10 | Die cast

ADJUSTABLE

5 YEAR

IP20


Suitable for R111 LED lamp.




C-A++ 65118AT/G

65118AT | 50W | R111 | GU10 | Die cast

ADJUSTABLE

5 YEAR

IP20


Suitable for R111 LED lamp.



Order Code	Colour	Watts	Input	Class		Notes
65118AT/W	White	50W	100-240V		40	-
65118AT/B	Black	50W	100-240V		40	-
65118AT/G	Grey	50W	100-240V		40	-





11

Tracks

Pages 303-308

16A | 6A

Die cast | Aluminium | Plastic

IP20

5 YEAR





40003A/W

Square Track Surface



40003A/W

40003A | 16A | 3m Square track | 3-phase | Aluminium



40003A/B



40003A/G





41002A/W

41002A | 6A | Track adaptor | Plastic



41002A/B



41002A/G





41030/W

41030 | 6A | Surface mount base for track spots | Plastic

IP20



41030/B



41030/G



Order Code	Colour	Input	Ampere	Class		Notes
40003A/W	White	100-240V	16A		10	-
40003A/B	Black	100-240V	16A		10	-
40003A/G	Grey	100-240V	16A		10	-
41002A/W	White	100-240V	6A		50	-
41002A/B	Black	100-240V	6A		50	-
41002A/G	Grey	100-240V	6A		50	-
41030/W	White	100-240V	6A		40	-
41030/B	Black	100-240V	6A		40	-
41030/G	Grey	100-240V	6A		40	-

Square Track Accessories



65100/BASE | Surface mounting base for spots | Die cast



41020 | Heavy items mechanical adaptor for 40003A | Die cast

41020/W



41020/B



41020/G

50





41004A | 16A | Live end for 40003A | Plastic

41004A/W/..



41004A/B/..



41004A/G/..





41010A | 16A | Live connector for 40003A | Plastic

41010A/W



41010A/B



41010A/G





41008A | 16A | Connector for 40003A | Plastic

41008A/W



41008A/B



41008A/G



Order Code	Colour	Direction	Input	Ampere	Class		Notes
41004A/W/L	White	Left	100-240V	16A		50	-
41004A/W/R	White	Right	100-240V	16A		50	-
41004A/B/L	Black	Left	100-240V	16A		50	-
41004A/B/R	Black	Right	100-240V	16A		50	-
41004A/G/L	Grey	Left	100-240V	16A		50	-
41004A/G/R	Grey	Right	100-240V	16A		50	-
41010A/W	White	-	100-240V	16A		50	-
41010A/B	Black	-	100-240V	16A		50	-
41010A/G	Grey	-	100-240V	16A		50	-
41008A/W	White	-	100-240V	16A		100	-
41008A/B	Black	-	100-240V	16A		100	-
41008A/G	Grey	-	100-240V	16A		100	-

Square Track Accessories



41012A/W/..

41012A | 16A | Corner for 40003A | Plastic



41012A/B/..



41012A/G/..





41016A/W

41016A | 16A | T connector for 40003A | Plastic



41016A/B



41016A/G





41024A/W

41024A | 16A | Flexible connector for 40003A | Plastic



41024A/B



41024A/G





41022A/W

41022A | End cup for 40003A | Plastic



41022A/B



41022A/G

200



Order Code	Colour	Direction	Input	Ampere	Class		Notes
41012A/W/L	White	Left	100-240V	16A		25	-
41012A/W/R	White	Right	100-240V	16A		25	-
41012A/B/L	Black	Left	100-240V	16A		25	-
41012A/B/R	Black	Right	100-240V	16A		25	-
41012A/G/L	Grey	Left	100-240V	16A		25	-
41012A/G/R	Grey	Right	100-240V	16A		25	-
41016A/W	White	-	100-240V	16A		25	-
41016A/B	Black	-	100-240V	16A		25	-
41016A/G	Grey	-	100-240V	16A		25	-
41024A/W	White	-	100-240V	16A		10	-
41024A/B	Black	-	100-240V	16A		10	-
41024A/G	Grey	-	100-240V	16A		10	-



Adjustable Track Suspension



41026R/W | Adjustable wire 2m for 40003A | Metal



100



41032/W

41032 | Connector for suspending 40003A track

new



41032/B

100



Rounded Track & Accessories



40003/G

40003 | 16A | 3m track | 3-phase | Aluminium



40003/W





41002/G

41002 | 16A | Track adaptor | Plastic



41002/W



41002/B





41004/G/L

41004 | 16A | Live end for 40003 | Plastic



41004/W/L





41010/G

41010 | 16A | Live connector for 40003 | Plastic



41010/W





41008/G

41008 | 16A | Connector for 40003 | Plastic



41008/W



41008/B



Order Code	Colour	Direction	Input	Ampere	Class		Notes
40003/W	White	-	100-240V	16A		10	-
40003/G	Grey	-	100-240V	16A		10	-
41002/W	White	-	100-240V	16A		150	-
41002/B	Black	-	100-240V	16A		150	-
41002/G	Grey	-	100-240V	16A		150	-
41004/W/L	White	Left	100-240V	16A		50	-
41004/G/L	Grey	Left	100-240V	16A		50	-
41010/W	White	-	100-240V	16A		40	-
41010/G	Grey	-	100-240V	16A		40	-
41008/W	White	-	100-240V	16A		50	-
41008/B	Black	-	100-240V	16A		50	-
41008/G	Grey	-	100-240V	16A		50	-

Rounded Track Accessories

41012 | 16A | Corner for 40003 | Plastic



41012/G/..



41012/W/..



41012/B/..



41016 | 16A | T connector for 40003 | Plastic



41016/G



41016/W



41016/B



41018 | 16A | X connector for 40003 | Plastic



41018/G



41018/W



41022 | End cover for 40003 | Plastic



41022/G



41022/W

200



41020 | Heavy items mechanical adaptor for 40003 | Die cast



41020/G



41020/W



41020/B

50



Order Code	Colour	Direction	Input	Ampere	Class		Notes
41012/W/L	White	Left	100-240V	16A		20	-
41012/W/R	White	Right	100-240V	16A		20	-
41012/B/L	Black	Left	100-240V	16A		20	-
41012/B/R	Black	Right	100-240V	16A		20	-
41012/G/L	Grey	Left	100-240V	16A		20	-
41012/G/R	Grey	Right	100-240V	16A		20	-
41016/W	White	-	100-240V	16A		10	-
41016/B	Black	-	100-240V	16A		10	-
41016/G	Grey	-	100-240V	16A		10	-
41018/W	White	-	100-240V	16A		10	-
41018/G	Grey	-	100-240V	16A		10	-





12

Office & Kitchen

Pages 311-318

T5 | T8 | SMD LED

Die cast | Aluminium | Steel | Plastic

IP20

DARK LIGHT

QUICK FIX

80 CRI

2 YEAR

3 YEAR



T5 Linkable
Plastic

38135A | 35W | T5 | Diffuser | Plastic







Order Code	Colour	Light Colour	CCT (K)	Watts	Input	Class		Notes
38135A/W	White	Warm white	3000K	35W	230V		30	Includes warm white lamp, power supply cable, corner cable, connector

The LED T8 Linear Fittings



A-A++ 38236D/W

38236D | 2xT8 LED 120cm | Steel

Diffuser / louver must be ordered separately

LED BUILT IN

5 YEAR

IP20



38236D/G





A-A++

38258D | 2xT8 LED 150cm | Steel

Diffuser / louver must be ordered separately

LED BUILT IN

5 YEAR

IP20







38236DL | Louver for 38236D & 38258D | 30cm | Plastic



For 38236D order 4pcs

For 38258D order 5pcs



38236DF | Diffuser for 38236D | 120cm





38258DF | Diffuser for 38258D | 150cm



Order Code	Colour	Input	Class		Notes
38236D/W	White	100-240V	⏚	6	Only suitable for T8 LED tubes
38236D/G	Grey	100-240V	⏚	6	Only suitable for T8 LED tubes
38258D/G	Grey	100-240V	⏚	6	Only suitable for T8 LED tubes





38225M | 25W | SMD 2835 | Aluminium + Plastic

LED BUILT IN

80 CRI

CE

2 YEAR

IP20



Optional suspension kit.
Order code 050090.





38248M | 48W | SMD 2835 | Aluminium + Plastic

LED BUILT IN

80 CRI

CE

2 YEAR

IP20



Optional suspension kit.
Order code 050090.



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
38225M/W/C	White	Cool white	4000K	25W	2200lm	230V		8	Complete with driver
38225M/W/W	White	Warm white	3000K	25W	2100lm	230V		8	Complete with driver
38248M/W/C	White	Cool white	4000K	48W	4300lm	230V		8	Complete with driver
38248M/W/W	White	Warm white	3000K	48W	4200lm	230V		8	Complete with driver





The LED Linear Range



38120L | 20W | SMD 2835 | Aluminium + PC

LED BUILT IN
80 CRI
CE
2 YEAR
IP20



Optional suspension kit.
Order code 050090.





38135L | 35W | SMD 2835 | Aluminium + PC

LED BUILT IN
80 CRI
CE
2 YEAR
IP20



Optional suspension kit.
Order code 050090.





38248L | 48W | SMD 2835 | Aluminium + PC

LED BUILT IN
80 CRI
CE
2 YEAR
IP20



Optional suspension kit.
Order code 050090.



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
38120L/W/C	White	Cool white	4000K	20W	1800lm	230V		12	Complete with driver
38120L/W/W	White	Warm white	3000K	20W	1700lm	230V		12	Complete with driver
38135L/W/C	White	Cool white	4000K	35W	3100lm	230V		12	Complete with driver
38135L/W/W	White	Warm white	3000K	35W	3000lm	230V		12	Complete with driver
38248L/W/C	White	Cool white	4000K	48W	4300lm	230V		12	Complete with driver
38248L/W/W	White	Warm white	3000K	48W	4200lm	230V		12	Complete with driver



LED Linear Profiles



38150A/W/C

38150A | 40W | LED | Linear system | Diffuser | Aluminium

LED BUILT IN

80 CRI

3 YEAR

new

IP20

UGR19



38150A/B/C



Complete with 4 Fixing clips & 4 connectors.







38150E/W

38150E | 1m Profile for 38150A, 38150B, 38150BU & 38150C

new

IP20



38150E/B



Complete with 4 Fixing clips & 4 connectors.

12





050170C/W

050170C | Corner for 38150A, 38150B, 38150BU & 38150C

new

IP20



050170C/B

2





050170 | 3m Suspension kit for 38150A, 38150B, 38150BU & 38150C

20

new

Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class			Notes
38150A/W/C	White	Cool white	4000K	40W	3400lm	120°	230V		300cm	12	Complete with 1000mA driver
38150A/W/W	White	Warm white	3000K	40W	3400lm	120°	230V		300cm	12	Complete with 1000mA driver
38150A/B/C	Black	Cool white	4000K	40W	3400lm	120°	230V		300cm	12	Complete with 1000mA driver
38150A/B/W	Black	Warm white	3000K	40W	3400lm	120°	230V		300cm	12	Complete with 1000mA driver





38150B | 40W | 48LEDs | Linear system | Aluminium

new
DARK LIGHT
IP20
LED BUILT IN
80 CRI
CE
3 YEAR
UGR17




Complete with 4 Fixing clips & 4 connectors.





38150C | 40W | 24LEDs + Diffuser | Linear system | Aluminium

new
IP20
LED BUILT IN
80 CRI
CE
3 YEAR
UGR19




Complete with 4 Fixing clips & 4 connectors.



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class			Notes
38150B/W/C	White	Cool white	4000K	40W	3800lm	34°	230V		300cm	12	Complete with 1000mA driver
38150B/W/W	White	Warm white	3000K	40W	3800lm	34°	230V		300cm	12	Complete with 1000mA driver
38150B/B/C	Black	Cool white	4000K	40W	3800lm	34°	230V		300cm	12	Complete with 1000mA driver
38150B/B/W	Black	Warm white	3000K	40W	3800lm	34°	230V		300cm	12	Complete with 1000mA driver
38150C/W/C	White	Cool white	4000K	40W	3400lm	120°	230V		300cm	12	Complete with 1000mA driver
38150C/W/W	White	Warm white	3000K	40W	3400lm	120°	230V		300cm	12	Complete with 1000mA driver
38150C/B/C	Black	Cool white	4000K	40W	3400lm	120°	230V		300cm	12	Complete with 1000mA driver
38150C/B/W	Black	Warm white	3000K	40W	3400lm	120°	230V		300cm	12	Complete with 1000mA driver



LED Linear Profiles



A-A++ 38150BU/W/C

38150BU | 40W + 20W Uplight | 48LEDs + Diffuser | Linear system | Aluminium

new

LED BUILT IN

80 CRI

3 YEAR

DARK LIGHT

IP20

UGR17



38150BU/B/C



Complete with 4 Fixing clips & 4 connectors.





38150E/W

38150E | 1m Profile for 38150A, 38150B, 38150BU & 38150C

new

IP20



38150E/B



Complete with 4 Fixing clips & 4 connectors.

12





050170C/W

050170C | Corner for 38150A, 38150B, 38150BU & 38150C

new

IP20



050170C/B

2





050170 | 3m Suspension kit for 38150A, 38150B, 38150BU & 38150C

new

20

Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class			Notes
38150BU/W/C	White	Cool white	4000K	40W/20W	3800lm/1800lm	34°/120°	230V		300cm	12	Complete with 1000mA + 500mA drivers
38150BU/W/W	White	Warm white	3000K	40W/20W	3800lm/1800lm	34°/120°	230V		300cm	12	Complete with 1000mA + 500mA drivers
38150BU/B/C	Black	Cool white	4000K	40W/20W	3800lm/1800lm	34°/120°	230V		300cm	12	Complete with 1000mA + 500mA drivers
38150BU/B/W	Black	Warm white	3000K	40W/20W	3800lm/1800lm	34°/120°	230V		300cm	12	Complete with 1000mA + 500mA drivers



T5 Suspended Linear



38154A | 54W | T5 | Aluminium

IP20

offer

2 YEAR







38154M | 54W | T5 | Aluminium

DARK LIGHT

IP20

offer

2 YEAR





Order Code	Colour	Watts	Input	Class		Notes
38154A/G	Grey	54W	230V	⏚	6	Complete with electronic ballast
38154M/G	Grey	54W	230V	⏚	6	Complete with electronic ballast





13

Wall & Ceiling

Pages 321-358

R111 | MR16 | PAR30 | GU10 | G9 | GX53 | E27

Die cast | Natural aluminium | Gypsum | Stainless steel

IP20 IP44 IP54

ADJUSTABLE ADJUSTABLE DARK LIGHT 2 YEAR 3 YEAR 5 YEAR





62210B/B



62110B/W

The R111 GU10 Spots

Aluminium



E-A++ 62110B/W

62110B | 75W | R111 | GU10 | Aluminium

ADJUSTABLE

5 YEAR

IP20



Suitable for R111 LED lamp.





E-A++ 62110B/B

62110B | 75W | R111 | GU10 | Aluminium

ADJUSTABLE

5 YEAR

IP20



Suitable for R111 LED lamp.





E-A++ 62210B/W

62210B | 2x75W | R111 | GU10 | Aluminium

ADJUSTABLE

5 YEAR

IP20



Suitable for R111 LED lamps.





E-A++ 62210B/B

62210B | 2x75W | R111 | GU10 | Aluminium

ADJUSTABLE

5 YEAR

IP20



Suitable for R111 LED lamps.



Order Code	Colour	Watts	Input	Class		Notes
62110B/W	White	75W	100-240V		20	-
62110B/B	Black	75W	100-240V		20	-
62210B/W	White	2x75W	100-240V		20	-
62210B/B	Black	2x75W	100-240V		20	-



The R111 GU10 Spots

Natural aluminium



E-A++

62110 | 75W | R111 | GU10 | Natural aluminium

ADJUSTABLE

3 YEAR

IP20

offer



Suitable for R111 LED lamp.





E-A++

62110A | 75W | R111 | GU10 | Natural aluminium

ADJUSTABLE

3 YEAR

IP20



Suitable for R111 LED lamp.





E-A++

62210A | 2x75W | R111 | GU10 | Natural aluminium

ADJUSTABLE

3 YEAR

IP20



Suitable for R111 LED lamps.





E-A++

62310A | 3x75W | R111 | GU10 | Natural aluminium

ADJUSTABLE

3 YEAR

IP20



Suitable for R111 LED lamps.



Order Code	Colour	Watts	Input	Class		Notes
62110/AL	Aluminium	75W	100-240V		12	-
62110A/AL	Aluminium	75W	100-240V		10	-
62210A/AL	Aluminium	2x75W	100-240V		6	-
62310A/AL	Aluminium	3x75W	100-240V		4	-

one

Indirect Wall Light

Natural aluminium

38108J | 8W | T5 | Natural aluminium







Order Code	Colour	Watts	Input	Class		Notes
38108J/AL	Aluminium	8W	230V		12	Complete with electronic ballast



The Decorative Wall Lights

Gypsum



60038 | 20W | E27 | Gypsum

IP20



Suitable for E27 LED lamp.





60040 | 40W | G9 | Gypsum

IP20



Suitable for G9 LED lamp.





60042 | 40W | G9 | Gypsum

IP20



Suitable for G9 LED lamp.





60054 | 2x35W | MR16 | GU10 | Gypsum

IP20



Suitable for GU10 LED lamps.



Order Code	Colour	Watts	Input	Class		Notes
60038	White	20W	100-240V		6	-
60040	White	40W	100-240V		18	-
60042	White	40W	100-240V		9	-
60054	White	2x35W	100-240V		9	-

The Chill Out Cylinder

GU10





A-A++ 12105M/B + 050112/BS

12105M | 10W | MR16 | GU10 | Aluminium body + plastic reflector

Reflector must be ordered separately.

DARK LIGHT

IP20



12105M/W + 050112/B





050112/W White



050112/B Black



050112/G Grey



050112/BS Brass



new

050112/ABS Antique brass



050112/GL Gold



050112/CU Copper



new

050112/DC Dark chrome

Order Code	Colour	Watts	Input	Class		Notes
12105M/W	White	10W	100-240V		20	-
12105M/B	Black	10W	100-240V		20	-



GU10 Dark Light

Aluminium



A-A++ 12105N/W

12105N | 10W | MR16 | GU10 | Aluminium

DARK LIGHT

IP20



12105N/B





A-A++ 12105NA/W

12105NA | 10W | MR16 | GU10 | Aluminium

DARK LIGHT

IP20



12105NA/B





A-A++ 12205NA/W

12205NA | 2x10W | MR16 | GU10 | Aluminium

DARK LIGHT

IP20



12205NA/B



Order Code	Colour	Reflector	Watts	Input	Class		Notes
12105N/W	White	Black	10W	100-240V		36	-
12105N/B	Black	Brass	10W	100-240V		36	-
12105NA/W	White	Black	10W	100-240V		36	-
12105NA/B	Black	Brass	10W	100-240V		36	-
12205NA/W	White	Black	2x10W	100-240V		24	-
12205NA/B	Black	Brass	2x10W	100-240V		24	-



GU10 Ceiling Cylinders

Aluminium



B-A++ 12105E/W

12105E | 20W | MR16 | GU10 | Aluminium

DARK LIGHT

IP20



12105E/B





B-A++

12105D | 20W | MR16 | GU10 | Aluminium

IP20





Order Code	Colour	Watts	Input	Class		Notes
12105E/W	White	20W	100-240V		20	-
12105E/B	Black	20W	100-240V		20	-
12105D/W	White	20W	100-240V		20	-



The Dark Light Cylinders

Aluminium



A-A++ 12105AL/W/B

12105AL | 10W | MR16 | GU10 | Aluminium

new
DARK LIGHT
IP20
5 YEAR



12105AL/W/GL







A-A++ 12105AL/B/B

12105AL | 10W | MR16 | GU10 | Aluminium

new
DARK LIGHT
IP20
5 YEAR



12105AL/B/GL





Order Code	Colour	Reflector	Watts	Input	Class		Notes
12105AL/W/B	White	Black	10W	100-240V	⏚	20	-
12105AL/W/GL	White	Gold	10W	100-240V	⏚	20	-
12105AL/B/B	Black	Black	10W	100-240V	⏚	20	-
12105AL/B/GL	Black	Gold	10W	100-240V	⏚	20	-



GU10 Decorative Cylinders

Aluminium

12105T | 10W | MR16 | GU10 | Aluminium



A-A++ 12105T/W

new

IP20



12105T/B



12205T | 2x10W | MR16 | GU10 | Aluminium



A-A++ 12205T/W

new

IP20



12205T/B



Order Code	Colour	Reflector	Watts	Input	Class		Notes
12105T/W	White	Brass	10W	100-240V		25	-
12105T/B	Black	Brass	10W	100-240V		25	-
12205T/W	White	Brass	2x10W	100-240V		10	-
12205T/B	Black	Brass	2x10W	100-240V		10	-



GU10 Decorative Square Cylinders

Aluminium



A-A++ 12105TA/W

12105TA | 10W | MR16 | GU10 | Aluminium

new

IP20



12105TA/B





A-A++ 12205TA/W

12205TA | 2x10W | MR16 | GU10 | Aluminium

new

IP20



12205TA/B



Order Code	Colour	Reflector	Watts	Input	Class		Notes
12105TA/W	White	Brass	10W	100-240V	⏚	25	-
12105TA/B	Black	Brass	10W	100-240V	⏚	25	-
12205TA/W	White	Brass	2x10W	100-240V	⏚	10	-
12205TA/B	Black	Brass	2x10W	100-240V	⏚	10	-



GU10 Adjustable Cylinders
Aluminium



A-A++ 12105Y/B

12105Y | 10W | MR16 | GU10 | Aluminium

new

IP20

ADJUSTABLE

5 YEAR



12105Y/W





A-A++ 12205Y/B

12205Y | 2x10W | MR16 | GU10 | Aluminium

new

IP20

ADJUSTABLE

5 YEAR



12205Y/W



Order Code	Colour	Watts	Input	Class		Notes
12105Y/W	White	10W	100-240V	⏚	25	-
12105Y/B	Black	10W	100-240V	⏚	25	-
12205Y/W	White	2x10W	100-240V	⏚	5	-
12205Y/B	Black	2x10W	100-240V	⏚	5	-



GU10 Adjustable Square Cylinders

Aluminium



A-A++ 12105YA/B

12105YA | 10W | MR16 | GU10 | Aluminium



new

IP20



12105YA/W





A-A++ 12205YA/B

12205YA | 2x10W | MR16 | GU10 | Aluminium



new

IP20



12205YA/W



Order Code	Colour	Watts	Input	Class		Notes
12105YA/W	White	10W	100-240V	⏚	25	-
12105YA/B	Black	10W	100-240V	⏚	25	-
12205YA/W	White	2x10W	100-240V	⏚	10	-
12205YA/B	Black	2x10W	100-240V	⏚	10	-



12140/G

12138G/B

Adjustable Ceiling Lights



E-A++

12140 | 75W | PAR30 | E27 | Die cast

ADJUSTABLE

5 YEAR

IP20



Suitable for PAR30 LED lamp.





E-A++

12140G | 75W | R111 | GU10 | Die cast

ADJUSTABLE

5 YEAR

IP20



Suitable for R111 LED lamp.





E-A++

12142 | 75W | R111 | GU10 | Aluminium

ADJUSTABLE

5 YEAR

IP20



Suitable for R111 LED lamp.





E-A++ 12138G/W

12138G | 75W | R111 | GU10 | Die cast

ADJUSTABLE

5 YEAR

IP20



12138G/B



12138G/G



Order Code	Colour	Watts	Input	Class		Notes
12140/G	Grey	75W	100-240V		18	-
12140G/G	Grey	75W	100-240V		18	-
12142/W	White	75W	100-240V		20	-
12138G/W	White	75W	100-240V		32	-
12138G/B	Black	75W	100-240V		32	-
12138G/G	Grey	75W	100-240V		32	-



R111 GU10 Ceiling Lights

12144 | 15W | R111 | GU10 | Aluminium



B-A++ 12144/B

new

IP20

5 YEAR



12144/W





12144A | 15W | R111 | GU10 | Aluminium



B-A++ 12144A/B

new

IP20

5 YEAR



12144A/W





Order Code	Colour	Watts	Input	Class		Notes
12144/W	White	15W	100-240V		10	-
12144/B	Black	15W	100-240V		10	-
12144A/W	White	15W	100-240V		10	-
12144A/B	Black	15W	100-240V		10	-



Square Ceiling Lights

Natural aluminium



E-A++

12105B | 35W | MR16 | GU10 | Natural aluminium

ADJUSTABLE

3 YEAR

IP20



Suitable for GU10 LED lamp.





E-A++

12205B | 2x35W | MR16 | GU10 | Natural aluminium

ADJUSTABLE

3 YEAR

IP20



Suitable for GU10 LED lamps.



Order Code	Colour	Watts	Input	Class		Notes
12105B/AL	Aluminium	35W	100-240V		20	-
12205B/AL	Aluminium	2x35W	100-240V		20	-



The GU10 Ceiling Lights

Aluminium



12105AB/W

12105AB | 10W | MR16 | GU10 | Aluminium





12105AB/B



12105AB/AL





12105AC/W

12105AC | 10W | MR16 | GU10 | Aluminium





12105AC/B



12105AC/AL



Order Code	Colour	Watts	Input	Class		Notes
12105AB/W	White	10W	100-240V		20	-
12105AB/B	Black	10W	100-240V		20	-
12105AB/AL	Aluminium	10W	100-240V		20	-
12105AC/W	White	10W	100-240V		10	-
12105AC/B	Black	10W	100-240V		10	-
12105AC/AL	Aluminium	10W	100-240V		10	-

The GU10 & G9 Ceiling Lights



12132 | 50W | MR16 | GU10 | Natural aluminium

IP20 offer



Suitable for GU10 LED lamp.





12126 | 50W | MR16 | GU10 | Natural aluminium

IP20 offer



Suitable for GU10 LED lamp.





12124 | 35W | MR16 | GU10 | Natural aluminium

IP20 offer



Suitable for GU10 LED lamp.





12134/AL

12134 | 50W | MR16 | GU10 | Natural aluminium

IP20



12134/B





12120 | 25W | G9 | Natural aluminium

IP20 offer



Suitable for G9 LED lamp.



Order Code	Colour	Watts	Input	Class		Notes
12132/AL	Aluminium	50W	100-240V		50	-
12126/AL	Aluminium	50W	100-240V		20	-
12124/AL	Aluminium	35W	100-240V		12	-
12134/B	Black	50W	100-240V		20	-
12134/AL	Aluminium	50W	100-240V		20	-
12120/AL	Aluminium	25W	100-240V		4	-



The GU10 Indoor/Outdoor Spots



E-A++

67300 | 35W | MR16 | GU10 | Natural aluminium

ADJUSTABLE

3 YEAR

IP54



Suitable for GU10 LED lamp.





E-A++ 67164/AL

67164 | 35W | MR16 | GU10 | Aluminium

ADJUSTABLE

3 YEAR

IP54



67164/G



67164/BR





E-A++ 67162/AL

67162 | 35W | MR16 | GU10 | Aluminium

ADJUSTABLE

3 YEAR

IP54



67162/G



67162/BR



Order Code	Colour	Watts	Input	Class		Notes
67300/AL	Aluminium	35W	100-240V		10	-
67164/G	Grey	35W	100-240V		20	-
67164/AL	Aluminium	35W	100-240V		10	-
67164/BR	Rust brown	35W	100-240V		20	-
67162/G	Grey	35W	100-240V		20	-
67162/AL	Aluminium	35W	100-240V		10	-
67162/BR	Rust brown	35W	100-240V		20	-



G9 Decorative Wall Lights

Aluminium



60056 | 30W | G9 | Aluminium

IP20







6017 | 30W | G9 | Aluminium

IP20







6017A | 30W | G9 | Aluminium

IP20







6030 | 30W | G9 | Mirror reflector | Aluminium

IP20





Order Code	Colour	Watts	Input	Class		Notes
60056/W	White	30W	100-240V		20	-
60056/B	Black	30W	100-240V		20	-
6017/W	White	30W	100-240V		20	-
6017/B	Black	30W	100-240V		20	-
6017A/W	White	30W	100-240V		20	-
6017A/B	Black	30W	100-240V		20	-
6030/W	White	30W	100-240V		20	-
6030/B	Black	30W	100-240V		20	-



The GU10 & G9 Wall Lights



E-A++

6017G | 40W | G9 | Natural aluminium

IP20



Suitable for G9 LED lamp.





E-A++

6012 | 40W | G9 | Natural aluminium

IP20



Suitable for G9 LED lamp.





E-A++

6022 | 2x50W | MR16 | GU10 | Natural aluminium

IP20

offer



Suitable for GU10 LED lamps.





E-A++

6005 | 50W | MR16 | GU10 | Die cast

IP20

offer



Suitable for GU10 LED lamp.



Order Code	Colour	Watts	Input	Class		Notes
6017G/AL	Aluminium	40W	100-240V		20	-
6012/AL	Aluminium	40W	100-240V		10	-
6022/AL	Aluminium	2x50W	100-240V		25	-
6005/G	Grey	50W	100-240V		20	-



67302A/AL

67302/AL

The GX53 Range

Natural aluminium



B-A++

67302 | 9W | GX53 | Natural aluminium

IP54



Suitable for GX53 LED lamp.





B-A++

67302A | 2x9W | GX53 | Natural aluminium

IP54



Suitable for GX53 LED lamps.





B-A++

67228 | 9W | GX53 | Natural aluminium

IP54



Suitable for GX53 LED lamp.



Order Code	Colour	Watts	Input	Class		Notes
67302/AL	Aluminium	9W	100-240V		20	-
67302A/AL	Aluminium	2x9W	100-240V		10	-
67228/AL	Aluminium	9W	100-240V		20	-



Indoor/Outdoor Wall Lights

Natural aluminium



67160 | 2x35W | MR16 | GU10 | Natural aluminium

IP54



Suitable for GU10 LED lamps.





67163 | 2x35W | MR16 | GU10 | Natural aluminium

IP54



Suitable for GU10 LED lamps.



Order Code	Colour	Watts	Input	Class		Notes
67160/AL	Aluminium	2x35W	100-240V		10	-
67163/AL	Aluminium	2x35W	100-240V		10	-



The GU10 Outdoor Wall Lights

Die cast



E-A++ 67400A/W

67400A | 35W | MR16 | GU10 | Die cast

3 YEAR

IP54



67400A/AN



67400A/B



67400A/G





E-A++ 67400B/W

67400B | 2x35W | MR16 | GU10 | Die cast

3 YEAR

IP54



67400B/AN



67400B/B



67400B/G



Order Code	Colour	Watts	Input	Class		Notes
67400A/W	White	35W	100-240V		12	-
67400A/AN	Anthracite	35W	100-240V		12	-
67400A/B	Black	35W	100-240V		12	-
67400A/G	Grey	35W	100-240V		12	-
67400B/W	White	2x35W	100-240V		12	-
67400B/AN	Anthracite	2x35W	100-240V		12	-
67400B/B	Black	2x35W	100-240V		12	-
67400B/G	Grey	2x35W	100-240V		12	-



The PAR30 Outdoor Wall Lights

Die cast



67400D | 20W | PAR30 | E27 | Die cast

IK06

3 YEAR

IP65


67400D/W


67400D/B


67400D/G





67400E | 2x20W | PAR30 | E27 | Die cast

IK06

3 YEAR

IP65


67400E/W


67400E/B


67400E/G



Order Code	Colour	Watts	Input	Class		Notes
67400D/W	White	20W	100-240V		6	-
67400D/AN	Anthracite	20W	100-240V		6	-
67400D/B	Black	20W	100-240V		6	-
67400D/G	Grey	20W	100-240V		6	-
67400E/W	White	2x20W	100-240V		6	-
67400E/AN	Anthracite	2x20W	100-240V		6	-
67400E/B	Black	2x20W	100-240V		6	-
67400E/G	Grey	2x20W	100-240V		6	-



The GU10 Outdoor Cube Lights

Die cast



A-A++ 67426/AN

67426 | 7W | MR16 | GU10 | Die cast

3 YEAR

IP65



67426/W



67426/B



67426/G





A-A++ 67426A/AN

67426A | 2x7W | MR16 | GU10 | Die cast

3 YEAR

IP65



67426A/W



67426A/B



67426A/G



Order Code	Colour	Watts	Input	Class		Notes
67426/W	White	7W	100-240V		18	-
67426/AN	Anthracite	7W	100-240V		18	-
67426/B	Black	7W	100-240V		18	-
67426/G	Grey	7W	100-240V		18	-
67426A/W	White	2x7W	100-240V		12	-
67426A/AN	Anthracite	2x7W	100-240V		12	-
67426A/B	Black	2x7W	100-240V		12	-
67426A/G	Grey	2x7W	100-240V		12	-



The GU10 Dark Light Outdoor

Aluminium



E-A++ 67130CD/AN

67130CD | 35W | MR16 | GU10 | Aluminium

DARK LIGHT

IP54

3 YEAR



67130CD/W



67130CD/B





E-A++ 67130DD/AN

67130DD | 35W | MR16 | GU10 | Aluminium

DARK LIGHT

IP54

3 YEAR



67130DD/W



67130DD/B



Order Code	Colour	Watts	Input	Class		Notes
67130CD/W	White	35W	100-240V		18	-
67130CD/AN	Anthracite	35W	100-240V		18	-
67130CD/B	Black	35W	100-240V		18	-
67130DD/W	White	35W	100-240V		18	-
67130DD/AN	Anthracite	35W	100-240V		18	-
67130DD/B	Black	35W	100-240V		18	-



67130A/W



67130E/BR



67130D/G



67130C/W

GU10 Outdoor Cylinders

Die cast



E-A++ 67130C/AN

67130C | 35W | MR16 | GU10 | Die cast

IP54



67130C/W



67130C/B



67130C/G



67130C/BR





E-A++ 67130E/AN

67130E | 35W | MR16 | GU10 | Die cast

IP54



67130E/W



67130E/B



67130E/G



67130E/BR





E-A++ 67130/AN

67130 | 2x35W | MR16 | GU10 | Die cast

IP54



67130/W



67130/B



67130/G



67130/BR



Order Code	Colour	Watts	Input	Class		Notes
67130C/W	White	35W	100-240V		30	-
67130C/AN	Anthracite	35W	100-240V		30	-
67130C/B	Black	35W	100-240V		30	-
67130C/G	Grey	35W	100-240V		30	-
67130C/BR	Rust brown	35W	100-240V		30	-
67130E/W	White	35W	100-240V		18	-
67130E/AN	Anthracite	35W	100-240V		18	-
67130E/B	Black	35W	100-240V		18	-
67130E/G	Grey	35W	100-240V		18	-
67130E/BR	Rust brown	35W	100-240V		18	-
67130/W	White	2x35W	100-240V		18	-
67130/AN	Anthracite	2x35W	100-240V		18	-
67130/B	Black	2x35W	100-240V		18	-
67130/G	Grey	2x35W	100-240V		18	-
67130/BR	Rust brown	2x35W	100-240V		18	-



GU10 Outdoor Cubes

Die cast



E-A++ 67130D/AN

67130D | 35W | MR16 | GU10 | Die cast

IP54



67130D/W



67130D/B



67130D/G



67130D/BR





E-A++ 67130F/AN

67130F | 35W | MR16 | GU10 | Die cast

IP54



67130F/W



67130F/B



67130F/G



67130F/BR





E-A++ 67130A/AN

67130A | 2x35W | MR16 | GU10 | Die cast

IP54



67130A/W



67130A/B



67130A/G



67130A/BR



Order Code	Colour	Watts	Input	Class		Notes
67130D/W	White	35W	100-240V		20	-
67130D/AN	Anthracite	35W	100-240V		20	-
67130D/B	Black	35W	100-240V		20	-
67130D/G	Grey	35W	100-240V		20	-
67130D/BR	Rust brown	35W	100-240V		20	-
67130F/W	White	35W	100-240V		20	-
67130F/AN	Anthracite	35W	100-240V		20	-
67130F/B	Black	35W	100-240V		20	-
67130F/G	Grey	35W	100-240V		20	-
67130F/BR	Rust brown	35W	100-240V		20	-
67130A/W	White	2x35W	100-240V		20	-
67130A/AN	Anthracite	2x35W	100-240V		20	-
67130A/B	Black	2x35W	100-240V		20	-
67130A/G	Grey	2x35W	100-240V		20	-
67130A/BR	Rust brown	2x35W	100-240V		20	-



67132E/G



67132C/BR



67132D/G



67132A/W

PAR30 Outdoor Cylinders

Die cast



E-A++ 67132C/AN

67132C | 75W | PAR30 | E27 | Die cast

IP54



67132C/W



67132C/B



67132C/G



67132C/BR





E-A++ 67132E/AN

67132E | 75W | PAR30 | E27 | Die cast

IP54



67132E/G



67132E/BR





E-A++ 67132/AN

67132 | 2x75W | PAR30 | E27 | Die cast

IP54



67132/W



67132/G



67132/BR



Order Code	Colour	Watts	Input	Class		Notes
67132C/W	White	75W	100-240V		18	-
67132C/AN	Anthracite	75W	100-240V		18	-
67132C/B	Black	75W	100-240V		18	-
67132C/G	Grey	75W	100-240V		18	-
67132C/BR	Rust brown	75W	100-240V		18	-
67132E/AN	Anthracite	75W	100-240V		12	-
67132E/G	Grey	75W	100-240V		12	-
67132E/BR	Rust brown	75W	100-240V		12	-
67132/W	White	2x75W	100-240V		12	-
67132/AN	Anthracite	2x75W	100-240V		12	-
67132/G	Grey	2x75W	100-240V		12	-
67132/BR	Rust brown	2x75W	100-240V		12	-



PAR30 Outdoor Cubes

Die cast



E-A++ 67132D/AN

67132D | 75W | PAR30 | E27 | Die cast

3 YEAR

IP54



67132D/W



67132D/B



67132D/G





E-A++ 67132F/AN

67132F | 75W | PAR30 | E27 | Die cast

3 YEAR

IP54



67132F/B



67132F/G





E-A++ 67132A/AN

67132A | 2x75W | PAR30 | E27 | Die cast

3 YEAR

IP54



67132A/W



67132A/B



67132A/G



Order Code	Colour	Watts	Input	Class		Notes
67132D/W	White	75W	100-240V		18	-
67132D/AN	Anthracite	75W	100-240V		18	-
67132D/B	Black	75W	100-240V		18	-
67132D/G	Grey	75W	100-240V		18	-
67132F/AN	Anthracite	75W	100-240V		12	-
67132F/B	Black	75W	100-240V		12	-
67132F/G	Grey	75W	100-240V		12	-
67132A/W	White	2x75W	100-240V		12	-
67132A/AN	Anthracite	2x75W	100-240V		12	-
67132A/B	Black	2x75W	100-240V		12	-
67132A/G	Grey	2x75W	100-240V		12	-



The Round E27 Outdoor Plafo

Die cast

67204B | 2x20W | E27 | Die cast



B-A++ 67204B/AN

IP54



67204B/W



67204B/B



67204B/G



67204 | 20W | E27 | Die cast



B-A++ 67204/AN

IP54



67204/W



67204/B



67204/G



67206 | 3x20W | E27 | Die cast



B-A++

IP54





Order Code	Colour	Watts	Input	Class		Notes
67204B/W	White	2x20W	100-240V		10	-
67204B/AN	Anthracite	2x20W	100-240V		10	-
67204B/B	Black	2x20W	100-240V		10	-
67204B/G	Grey	2x20W	100-240V		10	-
67204/W	White	20W	100-240V		6	-
67204/AN	Anthracite	20W	100-240V		6	-
67204/B	Black	20W	100-240V		6	-
67204/G	Grey	20W	100-240V		6	-
67206/G	Grey	3x20W	100-240V		3	-



The Square E27 Outdoor Plafo

Die cast



B-A++ 67208B/AN

67208B | 2x20W | E27 | Die cast

IP54



67208B/W



67208B/B



67208B/G





B-A++ 67208/AN

67208 | 20W | E27 | Die cast

IP54



67208/W



67208/B



67208/G





B-A++ 67210/AN

67210 | 2x20W | E27 | Die cast

IP54



67210/W



67210/B



67210/G



Order Code	Colour	Watts	Input	Class		Notes
67208B/W	White	2x20W	100-240V		10	-
67208B/B	Black	2x20W	100-240V		10	-
67208B/G	Grey	2x20W	100-240V		10	-
67208B/AN	Anthracite	2x20W	100-240V		10	-
67208/W	White	20W	100-240V		8	-
67208/B	Black	20W	100-240V		8	-
67208/G	Grey	20W	100-240V		8	-
67208/AN	Anthracite	20W	100-240V		8	-
67210/W	White	2x20W	100-240V		6	-
67210/B	Black	2x20W	100-240V		6	-
67210/G	Grey	2x20W	100-240V		6	-
67210/AN	Anthracite	2x20W	100-240V		6	-



The GX53 Outdoor Range

Die cast



B-A++

67104P | 9W | GX53 | Die cast

IP54



Suitable for GX53 LED lamp.







B-A++

67106P | 9W | GX53 | Die cast

IP54



Suitable for GX53 LED lamp.







B-A++

67134E | 9W | GX53 | Die cast

IP54



Suitable for GX53 LED lamp.







B-A++

67134A | 2x9W | GX53 | Die cast

IP54



Suitable for GX53 LED lamps.





Order Code	Colour	Watts	Input	Class		Notes
67104P/G	Grey	9W	100-240V		30	-
67106P/G	Grey	9W	100-240V		30	-
67134E/G	Grey	9W	100-240V		12	-
67134A/W	White	2x9W	100-240V		8	-

Outdoor Plafo

Die cast



67216 | 2x20W | E27 | Die cast

IP54



Suitable for E27 LED lamps.

300x300mm

95mm



67214 | 2x20W | E27 | Die cast

IP54



Suitable for E27 LED lamps.

300mm

95mm

Order Code	Colour	Watts	Input	Class		Notes
67216/G	Grey	2x20W	100-240V		6	-
67214/G	Grey	2x20W	100-240V		6	-



Outdoor E27 Square

Die cast



B-A++ 67328/G

67328 | 20W | E27 | Die cast + PC

3 YEAR

IP54



67328/AN





B-A++

67328A | 20W | E27 | Die cast + PC

3 YEAR

IP54



Suitable for E27 LED lamp.





B-A++

67292 | 2x15W | E27 | Die cast + glass

3 YEAR

IP54





Order Code	Colour	Watts	Input	Class		Notes
67328/AN	Anthracite	20W	100-240V		8	-
67328/G	Grey	20W	100-240V		8	-
67328A/G	Grey	20W	100-240V		8	-
67292/G	Grey	2x15W	100-240V		4	-



Outdoor E27 Square

Die cast



B-A++ 67420/W

67420 | 15W | E27 | Die cast + frosted glass

3 YEAR

IP54



67420/AN



67420/G





B-A++ 67420A/W

67420A | 15W | E27 | Die cast + frosted glass

3 YEAR

IP54



67420A/AN



67420A/G





B-A++ 67420B/W

67420B | 2x12W | E27 | Die cast + frosted glass

3 YEAR

IP54



67420B/AN



67420B/G



Order Code	Colour	Watts	Input	Class		Notes
67420/W	White	15W	100-240V		6	-
67420/AN	Anthracite	15W	100-240V		6	-
67420/B	Black	15W	100-240V		6	-
67420/G	Grey	15W	100-240V		6	-
67420A/W	White	15W	100-240V		6	-
67420A/AN	Anthracite	15W	100-240V		6	-
67420A/G	Grey	15W	100-240V		6	-
67420B/W	White	2x12W	100-240V		4	-
67420B/AN	Anthracite	2x12W	100-240V		4	-
67420B/B	Black	2x12W	100-240V		4	-
67420B/G	Grey	2x12W	100-240V		4	-

Outdoor Wall & Ceiling Spot

Stainless steel



67032 | 35W | MR16 | GU10 | Stainless steel 304

ADJUSTABLE

2 YEAR

IP44



Suitable for GU10 LED lamp.



Order Code	Colour	Watts	Input	Class		Notes
67032	Stainless steel	35W	100-240V	⏚	12	-

Outdoor Wall Spot

Stainless steel



67030 | 2x35W | MR16 | GU10 | Stainless steel 304

2 YEAR

IP44



Suitable for GU10 LED lamp.



Order Code	Colour	Watts	Input	Class		Notes
67030	Stainless steel	2x35W	100-240V	⏚	12	-





14

Wall & Ceiling LED

Pages 361-424

COB LED | SMD LED | LED

Die cast | Natural aluminium | Gypsum | ABS + PC

IP20 IP40 IP54 IP65

ADJUSTABLE ADJUSTABLE DIMMABLE DARK LIGHT QUICK FIX 80 CRI 85 CRI 2 YEAR





Window Frame Illumination



67454 | 6W | LED | Die cast

Window frame illumination.

LED BUILT IN · 80 CRI · IK08 · IP65 · CE · 2 YEAR







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
67454/AN/W	Anthracite	Warm white	3000K	6W	330lm	270°	100-240V		18	Complete with 500mA driver



62401AL/D/15



60008/AL/D



60008A/AL/BL

Indoor Mini Series

Natural aluminium



A-A++

60008A | 1W | LED | Natural aluminium

LED BUILT IN

2 YEAR

IP20 offer







A-A++

60008 | 2x1W | LED | Natural aluminium

LED BUILT IN

2 YEAR

IP20 offer







A-A++

65102 | 1W | LED | Natural aluminium

LED BUILT IN

ADJUSTABLE

2 YEAR

IP20 offer







A-A++

62401AL | 4x1W | LED | Natural aluminium

LED BUILT IN

ADJUSTABLE

2 YEAR

IP20 offer





Order Code	Colour	Light Colour	CCT (K)	Watts	Input	Class		Notes
60008A/AL/BL	Aluminium	Blue	-	1W	100-240V		50	Complete with driver
60008/AL/D	Aluminium	Daylight	6000K	2x1W	100-240V		50	Complete with driver
60008/AL/BL	Aluminium	Blue	-	2x1W	100-240V		50	Complete with driver
65102/D	Aluminium	Daylight	6000K	1W	100-240V		20	Complete with driver
65102/W	Aluminium	Warm white	3000K	1W	100-240V		20	Complete with driver
62401AL/D/15	Aluminium	Daylight	6000K	4x1W	100-240V		20	Complete with driver
62401AL/W/15	Aluminium	Warm white	3000K	4x1W	100-240V		20	Complete with driver



Reading Spots

Aluminium

65746 | 3W | LED | Aluminium

With ON/OFF Switch.



A-A++ 65746/W/W

new IP20

LED BUILT IN | 80 CRI | ADJUSTABLE | CE | 2 YEAR



65746/B/W



65746/C/W



65746A | 3W | LED | USB | Aluminium

With USB charger and ON/OFF Switch.



A-A++ 65746A/W/W

new IP20

LED BUILT IN | 80 CRI | ADJUSTABLE | CE | 2 YEAR



65746A/B/W



65742 | 3W | COB LED | Aluminium

With USB charger and ON/OFF Switch.



A-A++ 65742/W/W

IP20

LED BUILT IN | 85 CRI | ADJUSTABLE | CE | 2 YEAR



65742/B/W



USB charging socket.



65746R | 3W | LED | Wall recessed | Aluminium

With ON/OFF Switch.



A-A++ 65746R/W/W

new IP20

LED BUILT IN | 80 CRI | ADJUSTABLE | CE | 2 YEAR



65746R/B/W



Order Code	Colour	Reflector	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
65746/W/W	White	-	Warm white	3000K	3W	150lm	36°	100-240V		-	-	24	Complete with 700mA driver
65746/B/W	Black	-	Warm white	3000K	3W	150lm	36°	100-240V		-	-	24	Complete with 700mA driver
65746/C/W	Chrome	-	Warm white	3000K	3W	150lm	36°	100-240V		-	-	24	Complete with 700mA driver
65746A/W/W	White	-	Warm white	3000K	3W	150lm	36°	100-240V		-	-	24	Complete with 700mA driver
65746A/B/W	Black	-	Warm white	3000K	3W	150lm	36°	100-240V		-	-	24	Complete with 700mA driver
65742/W/W	White	Black	Warm white	3000K	3W	150lm	36°	100-240V		-	-	12	Complete with 700mA driver
65742/B/W	Black	Brass	Warm white	3000K	3W	150lm	36°	100-240V		-	-	12	Complete with 700mA driver
65746R/W/W	White	-	Warm white	3000K	3W	150lm	36°	100-240V		115x50mm	50mm	24	Complete with 700mA driver
65746R/B/W	Black	-	Warm white	3000K	3W	150lm	36°	100-240V		115x50mm	50mm	24	Complete with 700mA driver



Reading Spots
Aluminium



A-A++

65746B | 3W+5W Back light | LED | Aluminium

With 2 x ON/OFF Switches.

LED BUILT IN | 80 CRI | ADJUSTABLE | CE | 2 YEAR | new | IP20







A-A++ 65738/W/W

65738 | 3W | LED | Aluminium

With ON/OFF Switch.

LED BUILT IN | 85 CRI | ADJUSTABLE | CE | 2 YEAR | IP20



65738/AL/W





A-A++ 65738A/W/W

65738A | 3W | LED | Aluminium

With ON/OFF Switch.

LED BUILT IN | 85 CRI | ADJUSTABLE | CE | 2 YEAR | IP20



65738A/B/W





A-A++ 65744/W/W

65744 | 3W | COB LED | Aluminium

With USB charger and ON/OFF Switch.

LED BUILT IN | 85 CRI | ADJUSTABLE | CE | 2 YEAR | IP20



65744/B/W



USB charging socket.



Order Code	Colour	Reflector	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
65746B/W/W	White	-	Warm white	3000K	3W+5W	150lm	36°	230V		24	Complete with 700mA + 350mA drivers
65738/W/W	White	Black	Warm white	3000K	3W	160lm	36°	100-240V		24	Complete with 700mA driver
65738/AL/W	Aluminium	Black	Warm white	3000K	3W	160lm	36°	100-240V		24	Complete with 700mA driver
65738A/W/W	White	-	Warm white	3000K	3W	160lm	36°	100-240V		24	Complete with 700mA driver
65738A/B/W	Black	-	Warm white	3000K	3W	160lm	36°	100-240V		24	Complete with 700mA driver
65744/W/W	White	Black	Warm white	3000K	3W	150lm	36°	100-240V		12	Complete with 700mA driver
65744/B/W	Black	Brass	Warm white	3000K	3W	150lm	36°	100-240V		12	Complete with 700mA driver



The COB Moving Heads Spots

Die cast



65110A | 10W | COB LED | Die cast

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · 2 YEAR · IP20







65110C | 2x10W | COB LED | Die cast

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · 2 YEAR · IP20







65110D | 4x10W | COB LED | Die cast

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · 2 YEAR · IP20







65110B | 10W | COB LED | Die cast

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · 2 YEAR · IP20





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
65110A/W/W	White	Warm white	3000K	10W	900lm	60°	230V		12	Complete with 250mA driver
65110C/W/W	White	Warm white	3000K	2x10W	2x900lm	60°	230V		10	Complete with 500mA driver
65110D/W/W	White	Warm white	3000K	4x10W	4x900lm	60°	230V		4	Complete with 1000mA driver
65110B/W/W	White	Warm white	3000K	10W	900lm	60°	230V		10	Complete with 250mA driver



The COB Moving Heads Spots

Die cast



A-A++

65110E | 3x10W | COB LED | Die cast

LED BUILT IN

80 CRI

ADJUSTABLE

CE

2 YEAR

IP20









A-A++

65110F | 4x10W | COB LED | Die cast

LED BUILT IN

80 CRI

ADJUSTABLE

CE

2 YEAR

IP20







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
65110E/W/W	White	Warm white	3000K	3x10W	3x900lm	60°	230V		4	Complete with 700mA driver
65110F/W/W	White	Warm white	3000K	4x10W	4x900lm	60°	230V		4	Complete with 1000mA driver

Adjustable Display Spots





12109LA | 9W | COB LED | Die cast

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · 2 YEAR · IP20 · A-A++









12108LA | 8W | COB LED | Aluminium

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · 2 YEAR · IP20 · A-A++ 12108LA/W/W



12108LA/B/W







12208LA | 2x8W | COB LED | Aluminium

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · 2 YEAR · IP20 · A-A++ 12208LA/W/W



12208LA/B/W





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
12109LA/W/W	White	Warm white	3000K	9W	700lm	25°	230V		24	Complete with 250mA driver
12108LA/W/W	White	Warm white	3000K	8W	600lm	25°	230V		24	Complete with 200mA driver
12108LA/B/W	Black	Warm white	3000K	8W	600lm	25°	230V		24	Complete with 200mA driver
12208LA/W/W	White	Warm white	3000K	2x8W	2x600lm	25°	230V		18	Complete with 200mA drivers
12208LA/B/W	Black	Warm white	3000K	2x8W	2x600lm	25°	230V		18	Complete with 200mA drivers



12109LA/W/W



65107/W/W

The COB Adjustable Decorative Spot



A-A++

12107F | 7W | COB LED | Aluminium

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · 2 YEAR · IP20









A-A++

12112LA | 12W | COB LED | Aluminium

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · 2 YEAR · IP20









A-A++

65107 | 7W | COB LED | Aluminium

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · 2 YEAR · IP20







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
12107F/W/W	White	Warm white	3000K	7W	565lm	35°	100-240V		12	Complete with 700mA driver
12112LA/W/W	White	Warm white	3000K	12W	740lm	30°	230V		20	Complete with 300mA driver
65107/W/W	White	Warm white	3000K	7W	594lm	35°	100-240V		12	Complete with 700mA driver



Decorative Indoor Wall Lights

Aluminium



6028 | 6W | LED | Aluminium

LED BUILT IN · 2 YEAR · IP20







60032 | 3x1W | LED | Natural aluminium

LED BUILT IN · ADJUSTABLE · 2 YEAR · IP20







60034 | 3x1W | LED | Natural aluminium

LED BUILT IN · ADJUSTABLE · 2 YEAR · IP20







67434 | 8W | SMD 2835 | Aluminium

LED BUILT IN · 80 CRI · ADJUSTABLE · 2 YEAR · IP20





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
6028/AL/W	Aluminium	Warm white	3000K	6W	475lm	100-240V		20	Complete with driver
60032/AL/W	Aluminium	Warm white	3000K	3x1W	-	100-240V		20	Complete with driver
60034/AL/W	Aluminium	Warm white	3000K	3x1W	-	100-240V		10	Complete with driver
67434/W/W	White	Warm white	3000K	8W	500lm	230V		12	Complete with 300mA driver



Decorative Wall & Ceiling

Natural aluminium



12101 | 6x0,2W | LED | Natural aluminium + PC

LED BUILT IN · CE · 2 YEAR · IP20 · offer







60004 | 6x0,2W | LED | Natural aluminium + PC

LED BUILT IN · CE · 2 YEAR · IP20 · offer



offer





60001 | 3x0,2W | LED | Natural aluminium

LED BUILT IN · CE · 2 YEAR · IP20 · offer







60010 | 1W | LED | Natural aluminium

LED BUILT IN · CE · 2 YEAR · IP20 · offer





Order Code	Colour	Light Colour	CCT (K)	Watts	Input	Class		Notes
12101/AL/W	Aluminium	Warm white	3000K	6x0,2W	230V	⏚	24	Complete with driver
60004/AL/GR	Aluminium	Green	-	6x0,2W	230V	⏚	20	Complete with driver
60004/AL/R	Aluminium	Red	-	6x0,2W	230V	⏚	20	Complete with driver
60001/AL/D	Aluminium	Daylight	6000K	6x0,2W	230V	⏚	100	Complete with driver
Other available colours: **60001/AL/BL** Blue **60001/AL/GR** Green **60001/AL/R** Red **60001/AL/Y** Yellow								
60010/AL/BL	Aluminium	Blue	-	1W	100-240V	⏚	100	Complete with driver



The Retro Opal Range

Die cast + PC



67424 | 9W | SMD 3528 | Die cast + PC

LED BUILT IN · 80 CRI · CE · 2 YEAR · IP54 · A-A++









67424A | 9W | SMD 3528 | Die cast + PC

LED BUILT IN · 80 CRI · CE · 2 YEAR · IP54 · A-A++









67424B | 20W | SMD 3528 | Die cast + PC

LED BUILT IN · 80 CRI · CE · 2 YEAR · IP54 · A-A++









67364 | 8W | SMD LED | Die cast + PC

LED BUILT IN · 80 CRI · CE · 2 YEAR · IP54 · A-A++



Automatic day/night operation.



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
67424/W/W	White	Warm white	3000K	9W	600lm	230V		12	Complete with 350mA driver
67424A/W/W	White	Warm white	3000K	9W	600lm	230V		12	Complete with 350mA driver
67424B/W/W	White	Warm white	3000K	20W	1100lm	230V		6	Complete with 500mA driver
67364/G/W	Grey	Warm white	3000K	8W	450lm	230V		8	Photocell



The Classic Outdoor Range

Die cast



A-A++ 67444C/W/W

67444C | 10W | SMD 2835 | Die cast

LED BUILT IN · 80 CRI · CE · 2 YEAR · IP54



67444C/B/W





A-A++ 67442B/W/W

67442B | 10W | SMD 2835 | Die cast

LED BUILT IN · 80 CRI · CE · 2 YEAR · IP54



67442B/B/W





A-A++ 67442C/W/W

67442C | 10W | SMD 2835 | Die cast

LED BUILT IN · 80 CRI · CE · 2 YEAR · IP54



67442C/B/W





A-A++ 67442/W/W

67442 | 10W | SMD 2835 | Die cast

LED BUILT IN · 80 CRI · CE · 2 YEAR · IP54



67442/B/W



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
67444C/W/W	White	Warm white	3000K	10W	600lm	230V	⏚	12	AC LED
67444C/B/W	Black	Warm white	3000K	10W	600lm	230V	⏚	12	AC LED
67442B/W/W	White	Warm white	3000K	10W	600lm	230V	⏚	12	AC LED
67442B/B/W	Black	Warm white	3000K	10W	600lm	230V	⏚	12	AC LED
67442C/W/W	White	Warm white	3000K	10W	600lm	230V	⏚	12	AC LED
67442C/B/W	Black	Warm white	3000K	10W	600lm	230V	⏚	12	AC LED
67442/W/W	White	Warm white	3000K	10W	600lm	230V	⏚	12	AC LED
67442/B/W	Black	Warm white	3000K	10W	600lm	230V	⏚	12	AC LED

Sign Illumination Spot

7046P | 8W | COB LED | Die cast







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
7046P/AN/W	Anthracite	Warm white	3000K	8W	600lm	50°	230V		6	Complete with 350mA driver



Outdoor Wall Washers

Die cast



A-A++ 67346/W/W

67346 | 12W | SMD 2835 | Die cast

LED BUILT IN
80 CRI
ADJUSTABLE
CE
2 YEAR
IP65







A-A++ 67346/AN/W

67346 | 12W | SMD 2835 | Die cast

LED BUILT IN
80 CRI
ADJUSTABLE
CE
2 YEAR
IP65







A-A++

67346A | 30W | SMD 2835 | Die cast

LED BUILT IN
80 CRI
ADJUSTABLE
CE
2 YEAR
IP65





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
67346/W/W	White	Warm white	3000K	12W	840lm	230V		8	Complete with 250mA driver
67346/AN/W	Anthracite	Warm white	3000K	12W	840lm	230V		8	Complete with 250mA driver
67346A/AN/W	Anthracite	Warm white	3000K	30W	2800lm	230V		4	Complete with 700mA driver



12106C/W/W

12110D/W/W

The COB Indoor Round Cylinders



A-A++

12106C | 6W | COB LED | Aluminium

LED BUILT IN

80 CRI

ADJUSTABLE

CE

2 YEAR

IP20









A-A++

12110D | 10W | COB LED | Die cast

LED BUILT IN

85 CRI

ADJUSTABLE

CE

2 YEAR

IP20









A-A++

12104M | 4,5W | COB LED | Cement + black reflector

LED BUILT IN

90 CRI

CE

2 YEAR

DARK LIGHT

IP20









A-A++ 12208LA/W/W

12115A | 15W | COB LED | Aluminium

LED BUILT IN

90 CRI

CE

2 YEAR

DARK LIGHT

IP20



12208LA/B/W





Order Code	Colour	Reflector	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
12106C/W/W	White	-	Warm white	3000K	6W	480lm	36°	230V		10	Complete with 700mA driver
12110D/W/W	White	-	Warm white	3000K	10W	800lm	36°	100-240V		18	Complete with 500mA driver
12104M/W	Stone	-	Warm white	3000K	4,5W	350lm	40°	100-240V		18	Complete with 350mA driver
12115A/W/W	White	Black	Warm white	3000K	15W	1100lm	36°	230V		30	Complete with 350mA driver
12115A/B/W	Black	Brass	Warm white	3000K	15W	1100lm	36°	230V		30	Complete with 350mA driver



12107KA/W/W + 050106/B

12107K/B/W + 050106/BS

12107K/W/W + 050106/W

The Chill Out LED Cylinders



A-A++ 12107K/B/W + 050106/BS

12107K | 7W | COB LED | Aluminium

Ring must be ordered separately.

LED BUILT IN

80 CRI

2 YEAR

IP20



12107K/W/W + 050106/B







A-A++ 12107KA/B/W + 050106/BS

12107KA | 7W | COB LED | Aluminium

Ring must be ordered separately.

LED BUILT IN

80 CRI

2 YEAR

IP20



12107KA/W/W + 050106/B







050106/W White



050106/B Black



050106/BS Brass

Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
12107K/W/W	White	Warm white	3000K	7W	500lm	35°	230V		30	AC LED
12107K/B/W	Black	Warm white	3000K	7W	500lm	35°	230V		30	AC LED
12107KA/W/W	White	Warm white	3000K	7W	500lm	35°	230V		30	AC LED
12107KA/B/W	Black	Warm white	3000K	7W	500lm	35°	230V		30	AC LED



LED Decorative Cylinders



A-A++ 12115D/B/W

12115D | 15W | COB LED | Aluminium + plastic

LED BUILT IN

80 CRI

CE

2 YEAR

IP20



12115DW/W







A-A++ 12124D/B/W

12124D | 24W | COB LED | Aluminium + plastic

LED BUILT IN

80 CRI

CE

2 YEAR

IP20



12124DW/W





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
12115D/W/W	White	Warm white	3000K	15W	1200lm	45°	230V	⏚	24	Complete with 350mA driver
12115D/B/W	Black	Warm white	3000K	15W	1200lm	45°	230V	⏚	24	Complete with 350mA driver
12124D/W/W	White	Warm white	3000K	24W	2000lm	45°	230V	⏚	18	Complete with 600mA driver
12124D/B/W	Black	Warm white	3000K	24W	2000lm	45°	230V	⏚	18	Complete with 600mA driver





A-A++ 12108C/B/W

12108C | 8W | COB LED | Die cast

LED BUILT IN

80 CRI

IP20



12108C/W/W







A-A++ 12122C/B/W

12122C | 22W | COB LED | Die cast

LED BUILT IN

80 CRI

IP20



12122C/W/W





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
12108C/W/W	White	Warm white	3000K	8W	520lm	38°	230V		50	Complete with 650mA driver
12108C/B/W	Black	Warm white	3000K	8W	520lm	38°	230V		50	Complete with 650mA driver
12122C/W/W	White	Warm white	3000K	22W	1500lm	38°	230V		20	Complete with 500mA driver
12122C/B/W	Black	Warm white	3000K	22W	1500lm	38°	230V		20	Complete with 500mA driver



The COB Indoor Square Cylinders



A-A++

12106CA | 6W | COB LED | Aluminium

LED BUILT IN
80 CRI
ADJUSTABLE
CE
2 YEAR
IP20









A-A++

12107AL | 7W | COB LED | Aluminium

LED BUILT IN
80 CRI
ADJUSTABLE
TRIAC
DIMMABLE
CE
2 YEAR
IP20









A-A++

12211L | 2x11W | COB LED | Metal

LED BUILT IN
80 CRI
ADJUSTABLE
CE
2 YEAR
IP20







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
12106CA/W/W	White	Warm white	3000K	6W	480lm	36°	230V		10	Complete with 700mA driver
12107AL/AL/W	Aluminium	Warm white	3000K	7W	480lm	38°	230V		20	Complete with dimmable driver
12211L/W/W	White	Warm white	3000K	2x11W	2x830lm	40°	230V		8	Complete with 500mA drivers



Surface Shop Square Boxes

Aluminium



12107B | 7W | COB LED | Aluminium

new

IP20









12207B | 2x7W | COB LED | Aluminium

IP20









12307B | 3x7W | COB LED | Aluminium

IP20







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
12107B/W/W	White	Warm white	3000K	7W	550lm	36°	230V		36	Complete with 350mA driver
12207B/W/W	White	Warm white	3000K	2x7W	1100lm	36°	100-240V		24	Complete with 350mA driver
12307B/W/W	White	Warm white	3000K	3x7W	1650lm	36°	100-240V		12	Complete with 350mA driver



The SMD Cylinders

Aluminium



A-A++ 12115L/W/W

12115L | 15W | SMD LED | Aluminium

LED BUILT IN

80 CRI

CE

2 YEAR

IP40



12115L/B/W







A-A++

12125L | 25W | SMD LED | Aluminium

LED BUILT IN

80 CRI

CE

2 YEAR

IP40









A-A++

12135L | 35W | SMD LED | Aluminium

LED BUILT IN

80 CRI

CE

2 YEAR

IP40







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
12115L/W/W	White	Warm white	3000K	15W	1280lm	230V		36	Complete with 350mA driver
12115L/B/W	Black	Warm white	3000K	15W	1280lm	230V		36	Complete with 350mA driver
12125L/W/W	White	Warm white	3000K	25W	2050lm	230V		36	Complete with 600mA driver
12135L/W/W	White	Warm white	3000K	35W	3000lm	230V		12	Complete with 800mA driver



12115L/B/W

12125L/W/W

12125LD/W/W

The SMD Cylinders

Aluminium



A-A++

12107LD | 7W | SMD 2835 | Aluminium

new

DARK LIGHT

IP20

LED BUILT IN

80 CRI

CE

2 YEAR









A-A++

12115LD | 15W | SMD 2835 | Aluminium

new

DARK LIGHT

IP20

LED BUILT IN

80 CRI

CE

2 YEAR









A-A++

12125LD | 25W | SMD 2835 | Aluminium

new

DARK LIGHT

IP20

LED BUILT IN

80 CRI

CE

2 YEAR







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
12107LD/W/W	White	Warm white	3000K	7W	600lm	90°	230V		48	Complete with 150mA driver
12115LD/W/W	White	Warm white	3000K	15W	1280lm	90°	230V		18	Complete with 350mA driver
12125LD/W/W	White	Warm white	3000K	25W	2050lm	90°	230V		18	Complete with 600mA driver



The Hidden Light Cylinders Range



12108FD | 8W | SMD 2835 | Die cast

LED BUILT IN
80 CRI
2 YEAR
DARK LIGHT
IP20







12116FD | 16W | SMD 2835 | Die cast

LED BUILT IN
80 CRI
2 YEAR
DARK LIGHT
IP20





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
12108FD/W/W	White	Warm white	3000K	8W	560lm	230V		36	Complete with 300mA driver
12116FD/W/W	White	Warm white	3000K	16W	1100lm	230V		20	Complete with 300mA driver



The COB LED Indoor Cylinders

Aluminium

12115LA | 15W | COB LED | Aluminium



LED BUILT IN
80 CRI
CE
2 YEAR
IP20







12125LA | 25W | COB LED | Aluminium



LED BUILT IN
80 CRI
CE
2 YEAR
IP20







12130LA | 30W | COB LED | Aluminium



LED BUILT IN
80 CRI
CE
2 YEAR
IP20







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
12115LA/W/W	White	Warm white	3000K	15W	1300lm	50°	230V		36	Complete with 350mA driver
12125LA/W/W	White	Warm white	3000K	25W	2100lm	50°	230V		18	Complete with 600mA driver
12130LA/W/W	White	Warm white	3000K	30W	2500lm	50°	230V		12	Complete with 700mA driver





A-A++ 12112Z/B/W

12112Z | 12W | COB LED | Die cast + Plastic

LED BUILT IN · 80 CRI · CE · 2 YEAR · DARK LIGHT · IP20



12112Z/W/W



Complete with Black & Brass reflectors.





A-A++ 12120Z/B/W

12120Z | 20W | COB LED | Die cast + Plastic

LED BUILT IN · 80 CRI · CE · 2 YEAR · DARK LIGHT · IP20



12120Z/W/W



Complete with Black & Brass reflectors.





A-A++ 12130Z/B/W

12130Z | 30W | COB LED | Die cast + Plastic

LED BUILT IN · 80 CRI · CE · 2 YEAR · DARK LIGHT · IP20



12130Z/W/W



Complete with Black & Brass reflectors.



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
12112Z/W/W	White	Warm white	3000K	12W	960lm	45°	230V		30	Complete with 300mA driver
12112Z/B/W	Black	Warm white	3000K	12W	960lm	45°	230V		30	Complete with 300mA driver
12120Z/W/W	White	Warm white	3000K	20W	1600lm	45°	230V		24	Complete with 500mA driver
12120Z/B/W	Black	Warm white	3000K	20W	1600lm	45°	230V		24	Complete with 500mA driver
12130Z/W/W	White	Warm white	3000K	30W	2400lm	45°	230V		12	Complete with 750mA driver
12130Z/B/W	Black	Warm white	3000K	30W	2400lm	45°	230V		12	Complete with 750mA driver



The Retro Dark Light Square Cylinders



A-A++ 12112ZA/B/W

12112ZA | 12W | COB LED | Die cast + Plastic

LED BUILT IN · 80 CRI · CE · 2 YEAR · DARK LIGHT · IP20



12112ZA/W/W



Complete with Black & Brass reflectors.







A-A++ 12120ZA/B/W

12120ZA | 20W | COB LED | Die cast + Plastic

LED BUILT IN · 80 CRI · CE · 2 YEAR · DARK LIGHT · IP20



12120ZA/W/W



Complete with Black & Brass reflectors.





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
12112ZA/W/W	White	Warm white	3000K	12W	960lm	45°	230V	⏚	30	Complete with 300mA driver
12112ZA/B/W	Black	Warm white	3000K	12W	960lm	45°	230V	⏚	30	Complete with 300mA driver
12120ZA/W/W	White	Warm white	3000K	20W	1600lm	45°	230V	⏚	24	Complete with 500mA driver
12120ZA/B/W	Black	Warm white	3000K	20W	1600lm	45°	230V	⏚	24	Complete with 500mA driver



12110HA/W/W

12115HA/W/W

Dark Light Pro Square Cylinders



A-A++

12110HA | 10W | COB LED | Aluminium

new

DARK LIGHT

IP20

LED BUILT IN

80 CRI

2 YEAR



80x80mm

104mm

60°



A-A++

12115HA | 15W | COB LED | Aluminium

new

DARK LIGHT

IP20

LED BUILT IN

80 CRI

2 YEAR



100x100mm

120mm

60°

Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
12110HA/W/W	White	Warm white	3000K	10W	800lm	60°	230V		48	Complete with 250mA driver
12115HA/W/W	White	Warm white	3000K	15W	1200lm	60°	230V		48	Complete with 350mA driver



COB Outdoor Ceiling Cylinders



A-A++

67380 | 10W | COB LED | Aluminium

LED BUILT IN

80 CRI

CE

2 YEAR

IP54









A-A++

67380A | 25W | COB LED | Die cast

LED BUILT IN

80 CRI

CE

2 YEAR

IP54







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
67380/W/W	White	Warm white	3000K	10W	700lm	60°	100-240V	⏚	24	Complete with 250mA driver
67380A/W/W	White	Warm white	3000K	25W	1800lm	60°	100-240V	⏚	12	Complete with 600mA driver



Outdoor Ceiling Cylinders

Die cast



A-A++ 67138C/G/D

67138C | 6x1W | LED | Die cast

LED BUILT IN

IP54 offer



67138C/G/W







A-A++ 67138D/G/D

67138D | 6x1W | LED | Die cast

LED BUILT IN

IP54 offer







Order Code	Colour	Light Colour	CCT (K)	Watts	Input	Class		Notes
67138C/G/D	Grey	Daylight	6000K	6x1W	230V		12	Complete with driver
67138C/G/W	Grey	Warm white	3000K	6x1W	230V		12	Complete with driver
67138D/G/D	Grey	Daylight	6000K	6x1W	230V		12	Complete with driver



Outdoor Ceiling Cylinders

Die cast



67138C/AN/W

67138C | 6W | COB LED | Die cast

LED BUILT IN

80 CRI

CE

2 YEAR

IP54



67138C/W/W



67138C/B/W





67138D/AN/W

67138D | 6W | COB LED | Die cast

LED BUILT IN

80 CRI

CE

2 YEAR

IP54



67138D/W/W



67138D/B/W



67138D/G/W



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
67138C/W/W	White	Warm white	3000K	6W	440lm	35°	100-240V		18	Complete with 500mA driver
67138C/AN/W	Anthracite	Warm white	3000K	6W	440lm	35°	100-240V		18	Complete with 500mA driver
67138C/B/W	Black	Warm white	3000K	6W	440lm	35°	100-240V		18	Complete with 500mA driver
67138D/W/W	White	Warm white	3000K	6W	440lm	35°	100-240V		18	Complete with 500mA driver
67138D/AN/W	Anthracite	Warm white	3000K	6W	440lm	35°	100-240V		18	Complete with 500mA driver
67138D/B/W	Black	Warm white	3000K	6W	440lm	35°	100-240V		18	Complete with 500mA driver
67138D/G/W	Grey	Warm white	3000K	6W	440lm	35°	100-240V		18	Complete with 500mA driver



Outdoor Wall Cylinders



A-A++ 67138E/W/W

67138E | 6W | COB LED | Die cast

LED BUILT IN
80 CRI
CE
2 YEAR
IP54









A-A++ 67138E/AN/W

67138E | 6W | COB LED | Die cast

LED BUILT IN
80 CRI
CE
2 YEAR
IP54









A-A++ 67138E/B/W

67138E | 6W | COB LED | Die cast

LED BUILT IN
80 CRI
CE
2 YEAR
IP54









A-A++ 67138E/G/W

67138E | 6W | COB LED | Die cast

LED BUILT IN
80 CRI
CE
2 YEAR
IP54







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
67138E/W/W	White	Warm white	3000K	6W	440lm	35°	100-240V		12	Complete with 500mA driver
67138E/AN/W	Anthracite	Warm white	3000K	6W	440lm	35°	100-240V		12	Complete with 500mA driver
67138E/B/W	Black	Warm white	3000K	6W	440lm	35°	100-240V		12	Complete with 500mA driver
67138E/G/W	Grey	Warm white	3000K	6W	440lm	35°	100-240V		12	Complete with 500mA driver

Outdoor Wall Cylinders





67138F | 6W | COB LED | Die cast

LED BUILT IN
80 CRI
2 YEAR
IP54









67138F | 6W | COB LED | Die cast

LED BUILT IN
80 CRI
2 YEAR
IP54









67138F | 6W | COB LED | Die cast

LED BUILT IN
80 CRI
2 YEAR
IP54









67138F | 6W | COB LED | Die cast

LED BUILT IN
80 CRI
2 YEAR
IP54







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
67138F/W/W	White	Warm white	3000K	6W	440lm	35°	100-240V		12	Complete with 500mA driver
67138F/AN/W	Anthracite	Warm white	3000K	6W	440lm	35°	100-240V		12	Complete with 500mA driver
67138F/B/W	Black	Warm white	3000K	6W	440lm	35°	100-240V		12	Complete with 500mA driver
67138F/G/W	Grey	Warm white	3000K	6W	440lm	35°	100-240V		12	Complete with 500mA driver



Outdoor Wall Cylinders

Up & down beam



A-A++ 67138/AN/W

67138 | 2x6W | COB LED | Die cast

LED BUILT IN

80 CRI

CE

2 YEAR

IP54



67138/W/W



67138/B/W



67138/G/W





A-A++ 67138A/AN/W

67138A | 2x6W | COB LED | Die cast

LED BUILT IN

80 CRI

CE

2 YEAR

IP54



67138A/W/W



67138A/B/W



67138A/G/W



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
67138/W/W	White	Warm white	3000K	2x6W	2x440lm	35°	230V		12	Complete with 500mA driver
67138/AN/W	Anthracite	Warm white	3000K	2x6W	2x440lm	35°	230V		12	Complete with 500mA driver
67138/B/W	Black	Warm white	3000K	2x6W	2x440lm	35°	230V		12	Complete with 500mA driver
67138/G/W	Grey	Warm white	3000K	2x6W	2x440lm	35°	230V		12	Complete with 500mA driver
67138A/W/W	White	Warm white	3000K	2x6W	2x440lm	35°	230V		12	Complete with 500mA driver
67138A/AN/W	Anthracite	Warm white	3000K	2x6W	2x440lm	35°	230V		12	Complete with 500mA driver
67138A/B/W	Black	Warm white	3000K	2x6W	2x440lm	35°	230V		12	Complete with 500mA driver
67138A/G/W	Grey	Warm white	3000K	2x6W	2x440lm	35°	230V		12	Complete with 500mA driver



Outdoor Wall Cylinders High Power



A-A++ 67138EL/AN/C

67138EL | 20W | COB LED | Die cast

new

IP65

LED BUILT IN

80 CRI

TRIAC DIMMABLE

CE

2 YEAR



67138EL/AN/W







A-A++ 67138L/AN/C

67138L | 2x20W | COB LED | Die cast

new

IP65

LED BUILT IN

80 CRI

TRIAC DIMMABLE

CE

2 YEAR



67138L/AN/W





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
67138EL/AN/C	Anthracite	Cool white	4000K	20W	1400lm	35°	230V		4	AC LED
67138EL/AN/W	Anthracite	Warm white	3000K	20W	1400lm	35°	230V		4	AC LED
67138L/AN/C	Anthracite	Cool white	4000K	2x20W	2x1400lm	35°	230V		2	AC LED
67138L/AN/W	Anthracite	Warm white	3000K	2x20W	2x1400lm	35°	230V		2	AC LED



The Cage Wall Lights



67420AL/AN/W

67420L | 7W | SMD 2835 | Die cast + frosted glass

LED BUILT IN
80 CRI
2 YEAR
IP54



67420L/W/W



67420L/G/W





67420AL | 7W | SMD 2835 | Die cast + frosted glass

LED BUILT IN
80 CRI
2 YEAR
IP54





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
67420L/W/W	White	Warm white	3000K	7W	500lm	230V		6	Complete with 350mA driver
67420L/AN/W	Anthracite	Warm white	3000K	7W	500lm	230V		6	Complete with 350mA driver
67420L/G/W	Grey	Warm white	3000K	7W	500lm	230V		6	Complete with 350mA driver
67420AL/AN/W	Anthracite	Warm white	3000K	7W	300lm	230V		6	Complete with 350mA driver



The Cage Ceiling Lights



A-A++ 67420BL/W/W

67420BL | 13W | SMD 2835 | Die cast + frosted glass

LED BUILT IN

80 CRI

CE

2 YEAR

IP54







A-A++ 67420BL/AN/W

67420BL | 13W | SMD 2835 | Die cast + frosted glass

LED BUILT IN

80 CRI

CE

2 YEAR

IP54







A-A++ 67420BL/G/W

67420BL | 13W | SMD 2835 | Die cast + frosted glass

LED BUILT IN

80 CRI

CE

2 YEAR

IP54





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
67420BL/W/W	White	Warm white	3000K	13W	800lm	230V	⏚	4	Complete with 300mA driver
67420BL/AN/W	Anthracite	Warm white	3000K	13W	800lm	230V	⏚	4	Complete with 300mA driver
67420BL/G/W	Grey	Warm white	3000K	13W	800lm	230V	⏚	4	Complete with 300mA driver



Wall Adjustable Beams



A-A++ 67440/AN/W

67440 | 9W | SMD 2835 | Adjustable beam | Die cast

LED BUILT IN

80 CRI

CE

2 YEAR

IP54



67440/W/W







A-A++

67440A | 11W | SMD 2835 | Adjustable beam | Die cast

LED BUILT IN

80 CRI

CE

2 YEAR

IP54







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
67440/W/W	White	Warm white	3000K	9W	600lm	230V	⏚	8	Complete with 350mA driver
67440/AN/W	Anthracite	Warm white	3000K	9W	600lm	230V	⏚	8	Complete with 350mA driver
67440A/AN/W	Anthracite	Warm white	3000K	11W	700lm	230V	⏚	8	Complete with 350mA driver



67076A/B/W

67076/W/W

The Glass Face Wall Lights



A-A++ 67076/W/W

67076 | 4W | SMD LED | Glass + metal

new

DARK LIGHT

IP65

LED BUILT IN

80 CRI

CE

2 YEAR



67076/B/W





A-A++ 67076A/W/W

67076A | 5W | SMD LED | Glass + metal

new

DARK LIGHT

IP65

LED BUILT IN

80 CRI

CE

2 YEAR



67076A/B/W



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
67076/W/W	White	Warm white	3000K	4W	300lm	230V	⏚	12	AC LED
67076/B/W	Black	Warm white	3000K	4W	300lm	230V	⏚	12	AC LED
67076A/W/W	White	Warm white	3000K	5W	350lm	230V	⏚	12	AC LED
67076A/B/W	Black	Warm white	3000K	5W	350lm	230V	⏚	12	AC LED



Outdoor Wall Up & Down Lights

Die cast



67356 | 5W | LED | Die cast

LED BUILT IN

85 CRI

2 YEAR

IP54







67342 | 4x3W | LED | Die cast

LED BUILT IN

80 CRI

2 YEAR

IP54







67374 | 2x3W | SMD 5630 | Die cast

LED BUILT IN

80 CRI

2 YEAR

IP54







67374A | 2x6W | SMD 2835 | Die cast

LED BUILT IN

80 CRI

2 YEAR

IP54





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
67356/W/W	White	Warm white	3000K	5W	170lm	230V		18	AC LED
67356/G/W	Grey	Warm white	3000K	5W	170lm	230V		18	AC LED
67342/G/W	Grey	Warm white	3000K	4x3W	350lm	230V		12	Complete with 700mA driver
67374/W/W	White	Warm white	3000K	2x3W	2x210lm	230V		24	Complete with 350mA driver
67374/AN/W	Anthracite	Warm white	3000K	2x3W	2x210lm	230V		24	Complete with 350mA driver
67374A/W/W	White	Warm white	3000K	2x6W	2x420lm	230V		12	Complete with 300mA driver
67374A/AN/W	Anthracite	Warm white	3000K	2x6W	2x420lm	230V		12	Complete with 300mA driver



Outdoor Wall Up & Down Lights



A-A++ 67362B/AN/W

67362B | 9W | SMD LED | Die cast

LED BUILT IN

80 CRI

CE

2 YEAR

IP54



67362B/W/W





A-A++ 67362C/AN/W

67362C | 2x4,5W | SMD 3014 | Die cast

LED BUILT IN

80 CRI

CE

2 YEAR

IP54



67362C/W/W





A-A++ 67392/AN/W

67392 | 7W | SMD 2835 | ABS + PC

LED BUILT IN

80 CRI

CE

2 YEAR

IP65



67392/W/W



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
67362B/W/W	White	Warm white	3000K	9W	600lm	230V		12	Complete with 350mA driver
67362B/AN/W	Anthracite	Warm white	3000K	9W	600lm	230V		12	Complete with 350mA driver
67362C/W/W	White	Warm white	3000K	2x4,5W	2x315lm	230V		12	Complete with 350mA driver
67362C/AN/W	Anthracite	Warm white	3000K	2x4,5W	2x315lm	230V		12	Complete with 350mA driver
67392/W/W	White	Warm white	3000K	7W	400lm	230V		20	Complete with 500mA driver
67392/AN/W	Anthracite	Warm white	3000K	7W	400lm	230V		20	Complete with 500mA driver



Outdoor Slim Oval Range

Up & down beam



A-A++ 67378/AN/W

67378 | 2x3W | SMD 5630 | Die cast

LED BUILT IN

80 CRI

CE

2 YEAR

IP54



67378/W/W





A-A++ 67378A/AN/W

67378A | 2x6W | SMD 2835 | Die cast

LED BUILT IN

80 CRI

CE

2 YEAR

IP54



67378A/W/W



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
67378/W/W	White	Warm white	3000K	2x3W	2x210lm	230V		24	Complete with 350mA driver
67378/AN/W	Anthracite	Warm white	3000K	2x3W	2x210lm	230V		24	Complete with 350mA driver
67378A/W/W	White	Warm white	3000K	2x6W	2x420lm	230V		12	Complete with 300mA driver
67378A/AN/W	Anthracite	Warm white	3000K	2x6W	2x420lm	230V		12	Complete with 300mA driver



Outdoor Slim Range

Up & down beam



67376 | 2x3W | SMD 2835 | Die cast

LED BUILT IN
80 CRI
CE
2 YEAR
IP54







67376A | 2x6W | SMD 2835 | Die cast

LED BUILT IN
80 CRI
CE
2 YEAR
IP54







67412 | 2x6W | COB LED | Adjustable beam | Die cast

LED BUILT IN
80 CRI
CE
2 YEAR
IP54





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
67376/W/W	White	Warm white	3000K	2x3W	2x210lm	230V		24	Complete with 350mA driver
67376/AN/W	Anthracite	Warm white	3000K	2x3W	2x210lm	230V		24	Complete with 350mA driver
67376A/W/W	White	Warm white	3000K	2x6W	2x420lm	230V		12	Complete with 300mA driver
67376A/AN/W	Anthracite	Warm white	3000K	2x6W	2x420lm	230V		12	Complete with 300mA driver
67412/W/W	White	Warm white	3000K	2x6W	2x400lm	230V		12	Complete with 500mA driver
67412/AN/W	Anthracite	Warm white	3000K	2x6W	2x400lm	230V		12	Complete with 500mA driver





Indoor/Outdoor Wall Lines

Natural aluminium



67298 | 3x3W | LED | Natural aluminium

LED BUILT IN

2 YEAR

IP54









67274 | 4W | LED | Natural aluminium

LED BUILT IN

2 YEAR

IP54









67274A | 2x1W | LED | Natural aluminium

LED BUILT IN

2 YEAR

IP54







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
67298/AL/W	Aluminium	Warm white	3000K	3x3W	450lm	100-240V		20	Complete with driver
67274/AL/W	Aluminium	Warm white	3000K	4W	150lm	100-240V		20	Complete with driver
67274A/AL/BL	Aluminium	Blue	-	2x1W	-	100-240V		12	Complete with driver



Indoor/Outdoor Wall Lines

Natural aluminium



67274B | 4x1,5W | LED | Natural aluminium

LED BUILT IN

2 YEAR

IP54







67274C | 6x1W | LED | Natural aluminium

LED BUILT IN

2 YEAR

IP54





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
67274B/AL/W	Aluminium	Warm white	3000K	4x1,5W	200lm	100-240V		12	Complete with driver
67274C/AL/W	Aluminium	Warm white	3000K	6x1W	300lm	230V		20	Complete with driver



Indoor/Outdoor Adjustable Beams

67340A | 2x3W | LED | Adjustable beam | Die cast



LED BUILT IN
80 CRI
2 YEAR
IP54





67340A | 2x3W | LED | Adjustable beam | Die cast



LED BUILT IN
80 CRI
2 YEAR
IP54





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
67340A/W/W	White	Warm white	3000K	2x3W	2x210lm	230V	⏚	8	Complete with 700mA driver
67340A/AN/W	Anthracite	Warm white	3000K	2x3W	2x210lm	230V	⏚	8	Complete with 700mA driver
67340A/G/W	Grey	Warm white	3000K	2x3W	2x210lm	230V	⏚	8	Complete with 700mA driver



Outdoor Wall Dark Lights

Die cast



A-A++ 67398/AN/W

67398 | 3W | SMD 1208 | Die cast

LED BUILT IN · 80 CRI · CE · 2 YEAR · DARK LIGHT · IP54



67398/W/W





A-A++ 67398A/AN/W

67398A | 2x3W | LED | Die cast

LED BUILT IN · 80 CRI · CE · 2 YEAR · DARK LIGHT · IP54



67398A/W/W



67398A/B/W





A-A++ 67398C/AN/W

67398C | 2x3W | LED | Die cast

LED BUILT IN · 80 CRI · CE · 2 YEAR · DARK LIGHT · IP54



67398C/W/W



67398C/B/W



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
67398/W/W	White	Warm white	3000K	3W	200lm	100-240V		24	Complete with 350mA driver
67398/AN/W	Anthracite	Warm white	3000K	3W	200lm	100-240V		24	Complete with 350mA driver
67398A/W/W	White	Warm white	3000K	2x3W	2x200lm	100-240V		12	Complete with 350mA driver
67398A/AN/W	Anthracite	Warm white	3000K	2x3W	2x200lm	100-240V		12	Complete with 350mA driver
67398A/B/W	Black	Warm white	3000K	2x3W	2x200lm	100-240V		12	Complete with 350mA driver
67398C/W/W	White	Warm white	3000K	2x3W	2x200lm	100-240V		18	Complete with 350mA driver
67398C/AN/W	Anthracite	Warm white	3000K	2x3W	2x200lm	100-240V		18	Complete with 350mA driver
67398C/B/W	Black	Warm white	3000K	2x3W	2x200lm	100-240V		18	Complete with 350mA driver

Outdoor Wall Lights

Die cast



67304/G/W



67124/G/W



A-A++

67468 | 10W | LED | Dimmable | Die cast + glass

new

IP65

LED BUILT IN

80 CRI

TRIAC DIMMABLE

2 YEAR







A-A++ 67124/G/W

67124 | 2x1W | LED | Die cast

IP54

offer

LED BUILT IN

2 YEAR



67124/G/BL

offer





A-A++

67304 | 2x1W | LED | Die cast

IP54

LED BUILT IN

2 YEAR





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
67468/W/W	White	Warm white	3000K	10W	600lm	230V		6	AC LED
67124/G/W	Grey	Warm white	3000K	2x1W	-	230V		18	Complete with driver
67124/G/BL	Grey	Blue	-	2x1W	-	230V		18	Complete with driver
67304/G/W	Grey	Warm white	3000K	2x1W	-	100-240V		12	Complete with driver



Down Illumination Wall Lights

ABS + PC



A-A++ 67386A/W/W

67386A | 1,5W | SMD 2835 | ABS + PC

LED BUILT IN

80 CRI

DARK LIGHT

IP65



67386A/AN/W





A-A++ 67386C/W/W

67386C | 4W | SMD 2835 | ABS + PC

LED BUILT IN

80 CRI

DARK LIGHT

IP65



67386C/AN/W





A-A++ 67396/W/W

67396 | 6W | SMD 2835 | ABS + PC

LED BUILT IN

80 CRI

IP65



67396/AN/W





A-A++ 67396A/W/W

67396A | 6W | SMD 2835 | Sensor | ABS + PC

LED BUILT IN

80 CRI

IP65



67396A/AN/W



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
67386A/W/W	White	Warm white	3000K	1,5W	80lm	230V		40	AC LED
67386A/AN/W	Anthracite	Warm white	3000K	1,5W	80lm	230V		40	AC LED
67386C/W/W	White	Warm white	3000K	4W	220lm	230V		20	AC LED
67386C/AN/W	Anthracite	Warm white	3000K	4W	220lm	230V		20	AC LED
67396/W/W	White	Warm white	3000K	6W	300lm	230V		20	AC LED
67396/AN/W	Anthracite	Warm white	3000K	6W	300lm	230V		20	AC LED
67396A/W/W	White	Warm white	3000K	6W	300lm	230V		20	AC LED
67396A/AN/W	Anthracite	Warm white	3000K	6W	300lm	230V		20	AC LED





A-A++ 67394B/W/W

67394B | 3,5W | SMD 2835 | ABS + PC

LED BUILT IN · 80 CRI · IK08 · CE · 2 YEAR · IP65



67394B/AN/W





A-A++ 67394A/W/W

67394A | 3,5W | SMD 2835 | ABS + PC

LED BUILT IN · 80 CRI · IK08 · CE · 2 YEAR · IP65



67394A/AN/W





A-A++ 67394/W/W

67394 | 3,5W | SMD 2835 | ABS + PC

LED BUILT IN · 80 CRI · IK08 · CE · 2 YEAR · IP65



67394/AN/W



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
67394B/W/W	White	Warm white	3000K	3,5W	250lm	230V	☐	40	AC LED
67394B/AN/W	Anthracite	Warm white	3000K	3,5W	250lm	230V	☐	40	AC LED
67394A/W/W	White	Warm white	3000K	3,5W	250lm	230V	☐	40	AC LED
67394A/AN/W	Anthracite	Warm white	3000K	3,5W	250lm	230V	☐	40	AC LED
67394/W/W	White	Warm white	3000K	3,5W	250lm	230V	☐	24	AC LED
67394/AN/W	Anthracite	Warm white	3000K	3,5W	250lm	230V	☐	24	AC LED



67388A/W/W

67388B/AN/W

Outdoor Dark Lights

ABS + PC



A-A++ 67388A/W/W

67388A | 2W | SMD 2835 | ABS + PC

LED BUILT IN · 80 CRI · IK08 · CE · 2 YEAR · DARK LIGHT · IP65



67388A/AN/W





A-A++ 67388B/W/W

67388B | 2W | SMD 2835 | ABS + PC

LED BUILT IN · 80 CRI · IK08 · CE · 2 YEAR · DARK LIGHT · IP65



67388B/AN/W





A-A++ 67388C/W/W

67388C | 2W | SMD 2835 | ABS + PC

LED BUILT IN · 80 CRI · IK08 · CE · 2 YEAR · DARK LIGHT · IP65



67388C/AN/W



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
67388A/W/W	White	Warm white	3000K	2W	65lm	230V	☐	40	AC LED
67388A/AN/W	Anthracite	Warm white	3000K	2W	65lm	230V	☐	40	AC LED
67388B/W/W	White	Warm white	3000K	2W	60lm	230V	☐	40	AC LED
67388B/AN/W	Anthracite	Warm white	3000K	2W	60lm	230V	☐	40	AC LED
67388C/W/W	White	Warm white	3000K	2W	75lm	230V	☐	24	AC LED
67388C/AN/W	Anthracite	Warm white	3000K	2W	75lm	230V	☐	24	AC LED



Round Indoor/Outdoor Wall Dark Lights

Die cast



A-A++ 67359/AN/W

67359 | 3W | SMD 5630 | Die cast

LED BUILT IN

80 CRI

2 YEAR

DARK LIGHT

IP54



67359/W/W





A-A++ 67360/AN/W

67360 | 9W | SMD 5630 | Die cast

LED BUILT IN

80 CRI

2 YEAR

DARK LIGHT

IP54



67360/W/W



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
67359/W/W	White	Warm white	3000K	3W	200lm	100-240V		30	Complete with 350mA driver
67359/AN/W	Anthracite	Warm white	3000K	3W	200lm	100-240V		30	Complete with 350mA driver
67360/W/W	White	Warm white	3000K	9W	350lm	230V		12	Complete with 700mA driver
67360/AN/W	Anthracite	Warm white	3000K	9W	350lm	230V		12	Complete with 700mA driver



Square Indoor/Outdoor Wall Dark Lights

Die cast



A-A++ 67359A/AN/W

67359A | 3W | SMD 5630 | Die cast

LED BUILT IN

80 CRI

2 YEAR

DARK LIGHT

IP54



67359A/W/W





A-A++ 67360A/AN/W

67360A | 9W | SMD 5630 | Die cast

LED BUILT IN

80 CRI

2 YEAR

DARK LIGHT

IP54



67360A/W/W





A-A++ 67359B/AN/W

67359B | 6W | SMD 2835 | Die cast

LED BUILT IN

80 CRI

2 YEAR

DARK LIGHT

IP54



67359B/W/W



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
67359A/W/W	White	Warm white	3000K	3W	200lm	100-240V		30	Complete with 350mA driver
67359A/AN/W	Anthracite	Warm white	3000K	3W	200lm	100-240V		30	Complete with 350mA driver
67360A/W/W	White	Warm white	3000K	9W	350lm	230V		12	Complete with 700mA driver
67360A/AN/W	Anthracite	Warm white	3000K	9W	350lm	230V		12	Complete with 700mA driver
67359B/W/W	White	Warm white	3000K	6W	400lm	230V		24	Complete with 350mA driver
67359B/AN/W	Anthracite	Warm white	3000K	6W	400lm	230V		24	Complete with 350mA driver



Outdoor Dark Lights



A-A++ 67430B/AN/W

67430B | 8W | SMD 2835 | ABS + PC

LED BUILT IN

80 CRI

CE

2 YEAR

DARK LIGHT

IP65



67430B/W/W





A-A++ 67360A/AN/W

67430A | 8W | SMD 2835 | ABS + PC

LED BUILT IN

80 CRI

CE

2 YEAR

DARK LIGHT

IP65



67360A/W/W



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
67430B/W/W	White	Warm white	3000K	8W	350lm	230V		20	Complete with 300mA driver
67430B/AN/W	Anthracite	Warm white	3000K	8W	350lm	230V		20	Complete with 300mA driver
67430A/W/W	White	Warm white	3000K	8W	350lm	230V		20	Complete with 300mA driver
67430A/AN/W	Anthracite	Warm white	3000K	8W	350lm	230V		20	Complete with 300mA driver

Outdoor Dark Lights



67416/W/W



67418/AN/W



67414/AN/W



A-A++ 67414/AN/W

67414 | 3W | SMD 2835 | ABS + PC

LED BUILT IN

80 CRI

CE

2 YEAR

DARK LIGHT

IP65



67414/W/W





A-A++ 67416/AN/W

67416 | 3W | SMD 2835 | ABS + PC

LED BUILT IN

80 CRI

CE

2 YEAR

DARK LIGHT

IP65



67416/W/W





A-A++ 67418/AN/W

67418 | 3W | SMD 2835 | ABS + PC

LED BUILT IN

80 CRI

CE

2 YEAR

DARK LIGHT

IP65



67418/W/W



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
67414/W/W	White	Warm white	3000K	3W	100lm	230V		40	AC LED
67414/AN/W	Anthracite	Warm white	3000K	3W	100lm	230V		40	AC LED
67416/W/W	White	Warm white	3000K	3W	100lm	230V		40	AC LED
67416/AN/W	Anthracite	Warm white	3000K	3W	100lm	230V		40	AC LED
67418/W/W	White	Warm white	3000K	3W	100lm	230V		40	AC LED
67418/AN/W	Anthracite	Warm white	3000K	3W	100lm	230V		40	AC LED



Indoor/Outdoor Wall Lines

Die cast



67170 | 3W | LED | Die cast

LED BUILT IN

2 YEAR

IP54 offer







67172 | 2x3W | LED | Die cast

LED BUILT IN

2 YEAR

IP54 offer





Order Code	Colour	Light Colour	Watts	Input	Class		Notes
67170/G/BL	Grey	Blue	3W	100-240V		40	Complete with driver
67172/G/BL	Grey	Blue	2x3W	100-240V		20	Complete with driver



Indoor/Outdoor Wall Lines

Die cast



A-A++

67354 | 2x3W | LED | Die cast

LED BUILT IN

80 CRI

2 YEAR

IP54



Use provided accessories to change to narrow beam.







A-A++

67308 | 2x4W | LED | Die cast

LED BUILT IN

80 CRI

2 YEAR

DARK LIGHT

IP54







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
67354/G/W	Grey	Warm white	3000K	2x3W	182lm	100-240V	⏚	12	Complete with driver
67308/G/W	Grey	Warm white	3000K	2x4W	-	100-240V	⏚	12	Complete with driver



The Roof Tile Range

Die cast



67422/W/W

67422 | 6W | COB LED | Die cast

LED BUILT IN

80 CRI

CE

2 YEAR

IP54



67422/AN/W





67422A/W/W

67422A | 2x6W | COB LED | Die cast

LED BUILT IN

80 CRI

CE

2 YEAR

IP54



67422A/AN/W



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
67422/W/W	White	Warm white	3000K	6W	400lm	230V		24	Complete with 500mA driver
67422/AN/W	Anthracite	Warm white	3000K	6W	400lm	230V		24	Complete with 500mA driver
67422A/W/W	White	Warm white	3000K	2x6W	2x400lm	230V		12	Complete with 500mA driver
67422A/AN/W	Anthracite	Warm white	3000K	2x6W	2x400lm	230V		12	Complete with 500mA driver



Outdoor Wall Lights

Die cast



67174/G/D

67174 | 3W | LED | Die cast

LED BUILT IN

80 CRI

CE

2 YEAR

IP54



67174/W/D





67176/G/W

67176 | 3W | LED | Die cast

LED BUILT IN

80 CRI

CE

2 YEAR

IP54



67176/W/D



Order Code	Colour	Light Colour	CCT (K)	Watts	Input	Class		Notes
67174/W/D	White	Daylight	6000K	3W	230V		12	Complete with driver
67174/G/D	Grey	Daylight	6000K	3W	230V		12	Complete with driver
67176/W/D	White	Daylight	6000K	3W	230V		12	Complete with driver
67176/G/W	Grey	Warm white	3000K	3W	230V		12	Complete with driver



Outdoor Surface Round Points

Die cast



67126 | 1,5W | LED | Die cast

LED BUILT IN

2 YEAR

IP54 offer







67128 | 1,5W | LED | Die cast

LED BUILT IN

2 YEAR

IP54 offer





Order Code	Colour	Light Colour	CCT (K)	Watts	Input	Class		Notes
67126/G/BL	Grey	Blue	-	1,5W	230V		30	Complete with driver
67128/G/BL	Grey	Blue	-	1,5W	230V		30	Complete with driver



Outdoor Surface Square Points

Die cast



A-A++

67116 | 1,6W | LED | Die cast

LED BUILT IN

2 YEAR

IP54







67118/G/D

67118 | 1,6W | LED | Die cast

LED BUILT IN

2 YEAR

IP54

offer



67118/G/BL

offer



Order Code	Colour	Light Colour	CCT (K)	Watts	Input	Class		Notes
67116/G/W	Grey	Warm white	3000K	1,6W	230V		30	Complete with driver
67118/G/D	Grey	Daylight	6000K	1,6W	230V		30	Complete with driver
67118/G/BL	Grey	Blue	-	1,6W	230V		30	Complete with driver



Outdoor Mini Series

Die cast

60014C | 2x1W | LED | Die cast



LED BUILT IN

2 YEAR

IP44

offer







60016B | 2x1W | LED | Die cast



60016B/G/BL

LED BUILT IN

2 YEAR

IP44

offer

offer



A-A++ 60016B/G/W





60012A | 1W | LED | Die cast



60012A/G/BL

LED BUILT IN

2 YEAR

IP44

offer

offer



A-A++ 60012A/G/D





60012B | 2x1W | LED | Die cast



LED BUILT IN

2 YEAR

IP44

offer







Order Code	Colour	Light Colour	CCT (K)	Watts	Input	Class		Notes
60014C/G/BL	Grey	Blue	-	2x1W	12V AC		100	Use 12V AC transformer
60016B/G/W	Grey	Warm white	3000K	2x1W	12V AC		50	Use 12V AC transformer
60016B/G/BL	Grey	Blue	-	2x1W	12V AC		50	Use 12V AC transformer
60012A/G/D	Grey	Daylight	6000K	1W	12V AC		50	Use 12V AC transformer
60012A/G/W	Grey	Warm white	3000K	1W	12V AC		50	Use 12V AC transformer
60012A/G/BL	Grey	Blue	-	1W	12V AC		50	Use 12V AC transformer
60012B/G/BL	Grey	Blue	-	2x1W	12V AC		50	Use 12V AC transformer



Indoor/Outdoor Light Points

Natural aluminium



A-A++

67220A | 1W | LED | Natural aluminium + acrylic

LED BUILT IN

2 YEAR

IP54

offer









A-A++

67334 | 1W | LED | Natural aluminium

LED BUILT IN

2 YEAR

IP54









A-A++

67336 | 2x1W | LED | Natural aluminium

LED BUILT IN

2 YEAR

IP54









A-A++

67256 | 3W | LED | Natural aluminium

LED BUILT IN

2 YEAR

DARK LIGHT

IP54

offer







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
67220A/AL/D	Aluminium	Daylight	6000K	1W	-	100-240V		20	Complete with driver
67334/AL/W	Aluminium	Warm white	3000K	1W	65lm	100-240V		20	Complete with driver
67336/AL/W	Aluminium	Warm white	3000K	2x1W	130lm	100-240V		20	Complete with driver
67256/AL/W	Aluminium	Warm white	3000K	3W	-	230V		12	Complete with driver



The Backlight Range



A-A++ 67450/W/W

67450 | 7W | SMD 2835 | ABS + PC

LED BUILT IN

80 CRI

IK08

CE

DARK LIGHT

IP54

2 YEAR



67450/AN/W





A-A++ 67450A/W/W

67450A | 7W | SMD 2835 | ABS + PC

LED BUILT IN

80 CRI

IK08

CE

DARK LIGHT

IP54

2 YEAR



67450A/AN/W



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
67450/W/W	White	Warm white	3000K	7W	600lm	230V	⧈	24	Complete with 300mA driver
67450/AN/W	Anthracite	Warm white	3000K	7W	600lm	230V	⧈	24	Complete with 300mA driver
67450A/W/W	White	Warm white	3000K	7W	600lm	230V	⧈	24	Complete with 300mA driver
67450A/AN/W	Anthracite	Warm white	3000K	7W	600lm	230V	⧈	24	Complete with 300mA driver



The Backlight Wall Range

Aluminium

67466A | 6W | SMD 2835 | Aluminium



A-A++ 67466A/W/W

new

IP20

LED BUILT IN

80 CRI



67466A/B/W



67466B | 6W | SMD 2835 | Aluminium



A-A++ 67466B/W/W

new

IP20

LED BUILT IN

80 CRI



67466B/B/W



67466C | 12W | SMD 2835 | Aluminium



A-A++ 67466C/W/W

new

IP20

LED BUILT IN

80 CRI



67466C/B/W



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
67466A/W/W	White	Warm white	3000K	6W	400lm	230V		12	Complete with 300mA driver
67466A/B/W	Black	Warm white	3000K	6W	400lm	230V		12	Complete with 300mA driver
67466B/W/W	White	Warm white	3000K	6W	400lm	230V		12	Complete with 300mA driver
67466B/B/W	Black	Warm white	3000K	6W	400lm	230V		12	Complete with 300mA driver
67466C/W/W	White	Warm white	3000K	12W	800lm	230V		12	Complete with 300mA driver
67466C/B/W	Black	Warm white	3000K	12W	800lm	230V		12	Complete with 300mA driver





15

Plafo

Pages 427-460

E27 | G9 | SMD LED | LED

Die cast | Steel | Metal | PC

IP20 IP40 IP54 IP65

DIMMABLE DARK LIGHT 80 CRI 2 YEAR 5 YEAR





E27 Plafo
Steel



B-A++ 12220/W

12220 | 2x20W | E27 | Steel

IP20

offer



Suitable for E27 LED lamps.





B-A++ 12220/MC

12220 | 2x20W | E27 | Steel

IP20

offer



Suitable for E27 LED lamps.



Order Code	Colour	Watts	Input	Class		Notes
12220/W	White	2x20W	100-240V		8	-
12220/MC	Brushed chrome	2x20W	100-240V		8	-



Square LED Plafo

Steel



62102 | 17W | SMD LED | Steel

LED BUILT IN

IP20

80 CRI

2 YEAR

offer







62104 | 30W | SMD LED | Steel

LED BUILT IN

IP20

2 YEAR

offer





Order Code	Colour	Light Colour	CCT (K)	Watts	Input	Class		Notes
62102/MC	Brushed chrome	Warm white	3000K	17W	230V	⏚	5	Complete with 700mA driver
62104/MC	Brushed chrome	Warm white	3000K	30W	230V	⏚	4	Complete with 700mA driver



Decorative LED Plafo

Metal + PC



A-A++ 62010/G/F

62010 | 11W | LED | Metal + PC

LED BUILT IN

2 YEAR

IP20









62010/G/BL



62010/G/OR



62010/G/V



A-A++

62010A | 31W | LED | Metal + PC

LED BUILT IN

2 YEAR

IP20







Order Code	Colour	Ring Colour	Light Colour	CCT (K)	Watts	Input	Class		Notes
62010/G/F	Grey	Frosted	Warm white	3000K	11W	230V		5	-
62010/G/BL	Grey	Blue	Warm white	3000K	11W	230V		5	-
62010/G/OR	Grey	Orange	Warm white	3000K	11W	230V		5	-
62010/G/V	Grey	Violet	Warm white	3000K	11W	230V		5	-
62010A/G/V	Grey	Violet	Warm white	3000K	31W	230V		5	-



Decorative LED Plafo

Metal + PC



62014 | 31W | LED | Metal + PC

LED BUILT IN

2 YEAR

IP20









62012 | 16W | LED | Metal + PC

LED BUILT IN

2 YEAR

IP20







Order Code	Colour	Ring Colour	Light Colour	CCT (K)	Watts	Input	Class		Notes
62014/G	Grey	-	Warm white	3000K	31W	230V	⏚	5	-
62012/G/V	Grey	Violet	Warm white	3000K	16W	230V	⏚	5	-

The LED Plafo Range

Round



62024B/W

62024A | 14W | SMD LED | Metal + plastic



A-A++

LED BUILT IN

2 YEAR

IP20







62024B | 18W | SMD LED | Metal + plastic



A-A++

LED BUILT IN

2 YEAR

IP20







62024C | 26W | SMD LED | Metal + plastic



A-A++

LED BUILT IN

2 YEAR

IP20







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
62024A/W	White	Warm white	3000K	14W	850lm	230V	⏚	5	Complete with 350mA driver
62024B/W	White	Warm white	3000K	18W	1100lm	230V	⏚	5	Complete with 450mA driver
62024C/W	White	Warm white	3000K	26W	1600lm	230V	⏚	5	Complete with 700mA driver

The LED Slim Plafo Range

Round



62022B/W/W



A-A++

62022A | 20W | SMD 2835 | PC

LED BUILT IN

2 YEAR

IP20









A-A++

62022B | 25W | SMD 2835 | PC

LED BUILT IN

2 YEAR

IP20









A-A++

62022C | 36W | SMD 2835 | PC

LED BUILT IN

2 YEAR

IP20









A-A++

62022AM | 20W | SMD 2835 | Sensor 30min timer | PC

LED BUILT IN

80 CRI

2 YEAR

IP20







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
62022A/W/W	White	Warm white	3000K	20W	1600lm	230V	☐	5	Complete with 450mA driver
62022B/W/W	White	Warm white	3000K	25W	2000lm	230V	☐	5	Complete with 600mA driver
62022C/W/W	White	Warm white	3000K	36W	2900lm	230V	☐	4	Complete with 900mA driver
62022AM/W/W	White	Warm white	3000K	20W	1600lm	230V	☐	5	Complete with 450mA driver



62018/G



67284LE/W/C

The IP65 Polycarbonate Range



A-A++ 67284LE/W/C

67284LE | 25W/5W | SMD 2835 | Emergency 3Hrs Maintained | PC

LED BUILT IN

80 CRI

CE

2 YEAR

IP65



67284LE/W/W





67284L | Plafo for LED board 67284LA | ABS + PC

CE

2 YEAR

IP65



LED board 67284LA





A-A++

67284LA | 14W | LED board for 67284L/G

LED BUILT IN

CE

2 YEAR



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class	Battery Duration		Notes
67284LE/W/C	White	Cool white	4000K	25W/5W	1900lm	230V		3Hrs	12	Supplied with battery
67284LE/W/W	White	Warm white	3000K	25W/5W	1900lm	230V		3Hrs	12	Supplied with battery
67284LA/D	White	Daylight	6000K	14W	1150lm	100-240V		-	20	LED board for 67284L



LED Circular Plafo

Metal + PC

62018 | 11W | LED | Metal + PC



A-A++

LED BUILT IN

2 YEAR

IP20







62018A | 27W | LED | Metal + PC



A-A++

LED BUILT IN

2 YEAR

IP20







Order Code	Colour	Light Colour	CCT (K)	Watts	Input	Class		Notes
62018/G	Grey	Warm white	3000K	11W	230V		5	-
62018A/W	White	Warm white	3000K	27W	230V		5	-



62115F/W/W

The LED Panel Plafo

Round



62130F/G/C



A-A++ 62115F/W/W

62115F | 16W | SMD LED | Die cast

LED BUILT IN

80 CRI

CE

2 YEAR

IP40



62115F/B/W



62115F/G/C





A-A++ 62130F/W/W

62130F | 30W | SMD LED | Die cast

Optional dimmable driver code 040060.

LED BUILT IN

80 CRI

CE

2 YEAR

IP40



62130F/B/W



62130F/G/C



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
62115F/W/C	White	Cool white	4000K	16W	1118lm	230V	☐	10	Complete with 500mA driver
62115F/W/W	White	Warm white	3000K	16W	1006lm	230V	☐	10	Complete with 500mA driver
62115F/B/C	Black	Cool white	4000K	16W	1118lm	230V	☐	10	Complete with 500mA driver
62115F/B/W	Black	Warm white	3000K	16W	1006lm	230V	☐	10	Complete with 500mA driver
62115F/G/C	Grey	Cool white	4000K	16W	1118lm	230V	☐	10	Complete with 500mA driver
62130F/W/C	White	Cool white	4000K	30W	1997lm	230V	☐	10	Complete with 1000mA driver
62130F/W/W	White	Warm white	3000K	30W	1797lm	230V	☐	10	Complete with 1000mA driver
62130F/B/W	Black	Warm white	3000K	30W	1797lm	230V	☐	10	Complete with 1000mA driver
62130F/G/C	Grey	Cool white	4000K	30W	1997lm	230V	☐	10	Complete with 1000mA driver

The LED Panel Plafo

Square



62122F/W/W

62130AF/W/W



A-A++ 62122F/W/W

62122F | 22W | SMD LED | Die cast

LED BUILT IN

80 CRI

CE

2 YEAR

IP40



62122F/B/W



62122F/G/C





A-A++ 62130AF/W/W

62130AF | 30W | SMD LED | Die cast

Optional dimmable driver code 040060.

LED BUILT IN

80 CRI

CE

2 YEAR

IP40



62130AF/W/C



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
62122F/W/W	White	Warm white	3000K	22W	1490lm	230V		10	Complete with 700mA driver
62122F/B/W	Black	Warm white	3000K	22W	1490lm	230V		10	Complete with 700mA driver
62122F/G/C	Grey	Cool white	4000K	22W	1656lm	230V		10	Complete with 700mA driver
62130AF/W/C	White	Cool white	4000K	30W	2174lm	230V		10	Complete with 1000mA driver
62130AF/W/W	White	Warm white	3000K	30W	1957lm	230V		10	Complete with 1000mA driver





62140AE | 40W | SMD 2835 | Aluminium

LED BUILT IN

80 CRI

2 YEAR

IP40







62140RE | 40W | SMD 2835 | Aluminium

LED BUILT IN

80 CRI

2 YEAR

IP40





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
62140AE/W/C	White	Cool white	4000K	40W	3600lm	230V		4	Complete with 1000mA driver
62140AE/W/W	White	Warm white	3000K	40W	3400lm	230V		4	Complete with 1000mA driver
62140RE/W/C	White	Cool white	4000K	40W	3600lm	230V		4	Complete with 1000mA driver
62140RE/W/W	White	Warm white	3000K	40W	3200lm	230V		4	Complete with 1000mA driver



LED Die Cast Panel Range



62140F | 40W | SMD LED | Die cast

LED BUILT IN

80 CRI

2 YEAR

IP40

A-A++



Suspension kit included.





62140AF | 40W | SMD LED | Die cast

LED BUILT IN

80 CRI

2 YEAR

IP40

A-A++



Suspension kit included.





62140RF | 40W | SMD 2016 | Die cast

LED BUILT IN

80 CRI

2 YEAR

IP40

A-A++



Optional suspension kit.
Order code 050128.



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
62140F/W/D	White	Daylight	6000K	40W	2800lm	230V		5	Complete with 1000mA driver
62140F/W/C	White	Cool white	4000K	40W	2800lm	230V		5	Complete with 1000mA driver
62140F/W/W	White	Warm white	3000K	40W	2520lm	230V		5	Complete with 1000mA driver
62140AF/W/D	White	Daylight	6000K	40W	2850lm	230V		4	Complete with 1000mA driver
62140AF/W/C	White	Cool white	4000K	40W	2850lm	230V		4	Complete with 1000mA driver
62140AF/W/W	White	Warm white	3000K	40W	2560lm	230V		4	Complete with 1000mA driver
62140RF/W/C	White	Cool white	4000K	40W	2700lm	230V		5	Complete with 1000mA driver
62140RF/W/W	White	Warm white	3000K	40W	2700lm	230V		5	Complete with 1000mA driver

The Ultra Slim LED Panel Plafo

Aluminium + PC





A-A++

62018F | 18W | SMD 4014 | Aluminium + PC

LED BUILT IN

80 CRI

CE

2 YEAR

IP40









A-A++

62018AF | 18W | SMD 4014 | Aluminium + PC

LED BUILT IN

80 CRI

CE

2 YEAR

IP40







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
62018F/W/C	White	Cool white	4000K	18W	1450lm	230V	☐	20	Complete with driver
62018F/W/W	White	Warm white	3000K	18W	1400lm	230V	☐	20	Complete with driver
62018AF/W/C	White	Cool white	4000K	18W	1450lm	230V	☐	20	Complete with driver
62018AF/W/W	White	Warm white	3000K	18W	1400lm	230V	☐	20	Complete with driver

one

The Ultra Slim LED Panel Plafo

Aluminium + PC



62018AF/W/C



62030F/W/C



A-A++

62030F | 30W | SMD 4014 | Aluminium + PC

LED BUILT IN

80 CRI

2 YEAR

IP40







A-A++

62038F | 38W | SMD 4014 | Aluminium + PC

LED BUILT IN

80 CRI

2 YEAR

IP40







A-A++

62046F | 46W | SMD 4014 | Aluminium + PC

LED BUILT IN

80 CRI

2 YEAR

IP40





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
62030F/W/C	White	Cool white	4000K	30W	2400lm	230V	⏚	10	Complete with driver
62030F/W/W	White	Warm white	3000K	30W	2300lm	230V	⏚	10	Complete with driver
62038F/W/C	White	Cool white	4000K	38W	3000lm	230V	⏚	5	Complete with driver
62038F/W/W	White	Warm white	3000K	38W	2900lm	230V	⏚	5	Complete with driver
62046F/W/C	White	Cool white	4000K	46W	3600lm	230V	⏚	5	Complete with driver
62046F/W/W	White	Warm white	3000K	46W	3500lm	230V	⏚	5	Complete with driver

The Ultra Slim LED Floating Plafo

Aluminium





A-A++ 62140FB/W/W

62140FB | 40W | SMD 2835 | Aluminium

LED BUILT IN

80 CRI

CE

2 YEAR

IP20



62140FB/B/C







A-A++ 62160FB/W/W

62160FB | 60W | SMD 2835 | Aluminium

LED BUILT IN

80 CRI

CE

2 YEAR

IP20



62160FB/B/C





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
62140FB/W/C	White	Cool white	4000K	40W	3500lm	230V		4	Complete with 1000mA driver
62140FB/W/W	White	Warm white	3000K	40W	3500lm	230V		4	Complete with 1000mA driver
62140FB/B/C	Black	Cool white	4000K	40W	3500lm	230V		4	Complete with 1000mA driver
62160FB/W/C	White	Cool white	4000K	60W	5300lm	230V		3	Complete with 1500mA driver
62160FB/W/W	White	Warm white	3000K	60W	5300lm	230V		3	Complete with 1500mA driver
62160FB/B/C	Black	Cool white	4000K	60W	5300lm	230V		3	Complete with 1500mA driver

LED Indoor Plafo

Aluminium



67438/W/W



67436A/W/W



A-A++

67436 | 20W | SMD 2835 | Aluminium

LED BUILT IN

80 CRI

CE

2 YEAR

IP44









A-A++

67436A | 32W | SMD 2835 | Aluminium

LED BUILT IN

80 CRI

CE

2 YEAR

IP44









A-A++ 67438/B/W

67438 | 40W | SMD 2835 | Aluminium

LED BUILT IN

80 CRI

CE

2 YEAR

IP20



67438/W/W







A-A++ 67438A/B/W

67438A | 45W | SMD 2835 | Aluminium

LED BUILT IN

80 CRI

CE

2 YEAR

IP20



67438A/W/W





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
67436/W/W	White	Warm white	3000K	20W	1400lm	230V		5	Complete with 600mA driver
67436A/W/W	White	Warm white	3000K	32W	2250lm	230V		5	Complete with 500mA driver
67438/W/W	White	Warm white	3000K	40W	2800lm	230V		1	Complete with 500mA driver
67438/B/W	Black	Warm white	3000K	40W	2800lm	230V		1	Complete with 500mA driver
67438A/W/W	White	Warm white	3000K	45W	3150lm	230V		1	Complete with 450mA driver
67438A/B/W	Black	Warm white	3000K	45W	3150lm	230V		1	Complete with 450mA driver



The E27 Plafo Outdoor Range

Round



B-A++ 67280E/B

67280E | 12W | E27 | ABS + PC

IP65 IK08 CE 2 YEAR



67280E/W



67280E/G



67280E/AN





B-A++ 67280EA/B

67280EA | 2x12W | E27 | ABS + PC

IP65 IK08 CE 2 YEAR



67280EA/W



67280EA/G



67280EA/AN



Order Code	Colour	Watts	Input	Class		Notes
67280E/W	White	12W	100-240V	☐	10	-
67280E/AN	Anthracite	12W	100-240V	☐	10	-
67280E/B	Black	12W	100-240V	☐	10	-
67280E/G	Grey	12W	100-240V	☐	10	-
67280EA/W	White	2x12W	100-240V	☐	10	-
67280EA/AN	Anthracite	2x12W	100-240V	☐	10	-
67280EA/B	Black	2x12W	100-240V	☐	10	-
67280EA/G	Grey	2x12W	100-240V	☐	10	-

The E27 Plafo Outdoor Range

Square



B-A++ 67282E/B

67282E | 12W | E27 | ABS + PC

IK08 | CE | 2 YEAR | IP65



67282E/W



67282E/G



67282E/AN





B-A++

67282 | 18W | E27 | PC

CE | 2 YEAR | IP65



Suitable for E27 LED lamp.





B-A++

67282A | 2x18W | E27 | PC

CE | 2 YEAR | IP65



Suitable for E27 LED lamps.





B-A++ 67282EA/B

67282EA | 2x12W | E27 | ABS + PC

IK08 | CE | 2 YEAR | IP65



67282EA/W



67282EA/G



67282EA/AN



Order Code	Colour	Watts	Input	Class		Notes
67282E/W	White	12W	100-240V		10	-
67282E/AN	Anthracite	12W	100-240V		10	-
67282E/B	Black	12W	100-240V		10	-
67282E/G	Grey	12W	100-240V		10	-
67282/W	White	18W	100-240V		12	-
67282A/W	White	2x18W	100-240V		8	-
67282EA/W	White	2x12W	100-240V		10	-
67282EA/AN	Anthracite	2x12W	100-240V		10	-
67282EA/B	Black	2x12W	100-240V		10	-
67282EA/G	Grey	2x12W	100-240V		10	-

The LED Plafo Outdoor Round



67280N/W

67280N | 16W | SMD 2835 | ABS + PC

LED BUILT IN · 80 CRI · IK08 · CE · IP65 · 2 YEAR



67280N/G



67280N/AN





67280AN/W

67280AN | 24W | SMD 2835 | ABS + PC

LED BUILT IN · 80 CRI · IK08 · CE · IP65 · 2 YEAR



67280AN/G



67280AN/AN





67280BN/W

67280BN | 30W | SMD 2835 | ABS + PC

LED BUILT IN · 80 CRI · IK08 · CE · IP65 · 2 YEAR



67280BN/G



67280BN/AN





67280ANE | 15W | SMD 2835 | Emergency 3Hrs Maintained | ABS + PC

LED BUILT IN · 80 CRI · IK08 · CE · IP65 · 2 YEAR





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
67280N/W/C	White	Cool white	4000K	16W	960lm	230V	☐	10	Complete with 500mA driver
67280N/W/W	White	Warm white	3000K	16W	960lm	230V	☐	10	Complete with 500mA driver
67280N/AN/W	Anthracite	Warm white	3000K	16W	960lm	230V	☐	10	Complete with 500mA driver
67280N/G/W	Grey	Warm white	3000K	16W	960lm	230V	☐	10	Complete with 500mA driver
67280AN/W/C	White	Cool white	4000K	24W	1440lm	230V	☐	10	Complete with 600mA driver
67280AN/W/W	White	Warm white	3000K	24W	1440lm	230V	☐	10	Complete with 600mA driver
67280AN/AN/W	Anthracite	Warm white	3000K	24W	1440lm	230V	☐	10	Complete with 600mA driver
67280AN/G/W	Grey	Warm white	3000K	24W	1440lm	230V	☐	10	Complete with 600mA driver
67280BN/W/W	White	Warm white	3000K	30W	1800lm	230V	☐	5	Complete with 700mA driver
67280BN/AN/W	Anthracite	Warm white	3000K	30W	1800lm	230V	☐	5	Complete with 700mA driver
67280BN/G/W	Grey	Warm white	3000K	30W	1800lm	230V	☐	5	Complete with 700mA driver
67280ANE/G/W	Grey	Warm white	3000K	15W	1000lm	230V	☐	10	Emergency 3Hrs Maintained



The LED Plafo Outdoor Square

Plastic



A-A++ 67282N/W

67282N | 16W | SMD 2835 | ABS + PC

LED BUILT IN · 80 CRI · IK08 · CE · IP65 · 2 YEAR



67282N/G



67282N/AN





A-A++ 67282AN/W

67282AN | 24W | SMD 2835 | ABS + PC

LED BUILT IN · 80 CRI · IK08 · CE · IP65 · 2 YEAR



67282AN/G



67282AN/AN





A-A++ 67282BN/W

67282BN | 30W | SMD 2835 | ABS + PC

LED BUILT IN · 80 CRI · IK08 · CE · IP65 · 2 YEAR



67282BN/G



67282BN/AN





A-A++

67282ANE | 16W | SMD 2835 | Emergency 3Hrs Maintained | ABS + PC

LED BUILT IN · 80 CRI · IK08 · CE · IP65 · 2 YEAR





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
67282N/W/W	White	Warm white	3000K	16W	960lm	230V		10	Complete with 500mA driver
67282N/AN/W	Anthracite	Warm white	3000K	16W	960lm	230V		10	Complete with 500mA driver
67282N/G/W	Grey	Warm white	3000K	16W	960lm	230V		10	Complete with 500mA driver
67282AN/W/W	White	Warm white	3000K	24W	1440lm	230V		10	Complete with 600mA driver
67282AN/AN/W	Anthracite	Warm white	3000K	24W	1440lm	230V		10	Complete with 600mA driver
67282AN/G/W	Grey	Warm white	3000K	24W	1440lm	230V		10	Complete with 600mA driver
67282BN/W/W	White	Warm white	3000K	30W	1800lm	230V		4	Complete with 700mA driver
67282BN/AN/W	Anthracite	Warm white	3000K	30W	1800lm	230V		4	Complete with 700mA driver
67282BN/G/W	Grey	Warm white	3000K	30W	1800lm	230V		4	Complete with 700mA driver
67282ANE/G/W	Grey	Warm white	3000K	16W	1280lm	230V		10	Emergency 3Hrs Maintained





67363A/AN/W



67363/W/W

67363A/W/W

Outdoor Slim LED Plafo

Die cast



A-A++ 67362/AN/W

67362 | 25W | SMD LED | Die cast

LED BUILT IN

80 CRI CE 2 YEAR

IP54



67362/W/W





A-A++ 67363/AN/W

67363 | 30W | SMD LED | Die cast

LED BUILT IN

80 CRI CE 2 YEAR

IP54



67363/W/W





A-A++ 67362A/AN/W

67362A | 25W | SMD LED | Die cast

LED BUILT IN

80 CRI CE 2 YEAR

IP54



67362A/W/W





A-A++ 67363A/AN/W

67363A | 30W | SMD LED | Die cast

LED BUILT IN

80 CRI CE 2 YEAR

IP54



67363A/W/W



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
67362/W/W	White	Warm white	3000K	25W	1600lm	230V		8	Complete with 350mA driver
67362/AN/W	Anthracite	Warm white	3000K	25W	1600lm	230V		8	Complete with 350mA driver
67363/W/W	White	Warm white	3000K	30W	2500lm	100-240V		6	Complete with 700mA driver
67363/AN/W	Anthracite	Warm white	3000K	30W	2500lm	100-240V		6	Complete with 700mA driver
67362A/W/W	White	Warm white	3000K	25W	1600lm	230V		8	Complete with 350mA driver
67362A/AN/W	Anthracite	Warm white	3000K	25W	1600lm	230V		8	Complete with 350mA driver
67363A/W/W	White	Warm white	3000K	30W	2500lm	100-240V		6	Complete with 700mA driver
67363A/AN/W	Anthracite	Warm white	3000K	30W	2500lm	100-240V		6	Complete with 700mA driver



Outdoor Project LED Plafo

Die cast



A-A++ 67384/AN/W

67384 | 30W | SMD 3014 | Die cast

LED BUILT IN

80 CRI

CE

2 YEAR

IP54



67384/W/W





A-A++ 67384A/AN/W

67384A | 30W | SMD 3014 | Die cast

LED BUILT IN

80 CRI

CE

2 YEAR

IP54



67384A/W/W



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
67384/W/W	White	Warm white	3000K	30W	2500lm	100-240V		4	Complete with 700mA driver
67384/AN/W	Anthracite	Warm white	3000K	30W	2500lm	100-240V		4	Complete with 700mA driver
67384A/W/W	White	Warm white	3000K	30W	2500lm	100-240V		4	Complete with 700mA driver
67384A/AN/W	Anthracite	Warm white	3000K	30W	2500lm	100-240V		4	Complete with 700mA driver



The LED Slim Plafo Range

Round



A-A++

67366 | 12W | SMD 2835 | PC

LED BUILT IN

80 CRI

CE

2 YEAR

IP54









A-A++

67366E | 12W | SMD 2835 | Emergency 3Hrs Maintained | PC

LED BUILT IN

80 CRI

CE

2 YEAR

IP54









A-A++

67368 | 18W | SMD 2835 | PC

LED BUILT IN

80 CRI

CE

2 YEAR

IP54









A-A++

67368M | 25W | SMD 2835 | Sensor 120sec timer | PC

LED BUILT IN

80 CRI

CE

2 YEAR

IP54







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
67366/W/C	White	Cool white	4000K	12W	960lm	100-240V		20	Complete with 160mA driver
67366/W/W	White	Warm white	3000K	12W	900lm	100-240V		20	Complete with 160mA driver
67366E/W/C	White	Cool white	4000K	12W	960lm	230V		20	Emergency 3Hrs Maintained
67366E/W/W	White	Warm white	3000K	12W	900lm	230V		20	Emergency 3Hrs Maintained
67368/W/C	White	Cool white	4000K	18W	1488lm	100-240V		10	Complete with 225mA driver
67368/W/W	White	Warm white	3000K	18W	1350lm	100-240V		10	Complete with 225mA driver
67368M/W/C	White	Cool white	4000K	25W	2100lm	230V		10	Complete with driver
67368M/W/W	White	Warm white	3000K	25W	2000lm	230V		10	Complete with driver



The LED Slim Plafo Range

PC



A-A++

67370 | 25W | SMD 2835 | PC

LED BUILT IN

80 CRI

CE

2 YEAR

IP54









A-A++

67372 | 25W | SMD 2835 | PC

LED BUILT IN

80 CRI

CE

2 YEAR

IP54







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
67370/W/C	White	Cool white	4000K	25W	2000lm	100-240V		10	Complete with 300mA driver
67370/W/W	White	Warm white	3000K	25W	1875lm	100-240V		10	Complete with 300mA driver
67372/W/C	White	Cool white	4000K	25W	2000lm	100-240V		10	Complete with 300mA driver
67372/W/W	White	Warm white	3000K	25W	1875lm	100-240V		10	Complete with 300mA driver



The IP44 Ceiling Plafo

Steel



E-A++

62100 | 40W | G9 | Steel

IP44

offer

2 YEAR



Suitable for G9 LED lamp.





E-A++

62200 | 60W | E27 | Steel

IP44

2 YEAR



Suitable for E27 LED lamp.





E-A++

62300 | 2x60W | E27 | Steel

IP44

2 YEAR



Suitable for E27 LED lamps.



Order Code	Colour	Watts	Input	Class		Notes
62100/MC	Brushed chrome	40W	100-240V		20	Indoor use only
62200/MC	Brushed chrome	60W	100-240V		6	Indoor use only
62300/MC	Brushed chrome	2x60W	100-240V		5	Indoor use only

Stainless Steel Outdoor Plafo



67316A | 26W | E27 | Stainless steel + glass

2 YEAR

IP54

B-A++



Suitable for E27 LED lamp.



Order Code	Colour	Watts	Input	Class		Notes
67316A	Stainless steel	26W	100-240V	⏚	6	-



64002/G/C



64004/G/C



64006/G/C

Multi LED Slim Plafo

Round



A-A++ 64002/W/C

64002 | 7W | LED | Die cast

DARK LIGHT · IP20 · offer

LED BUILT IN · 2 YEAR







A-A++ 64002/G/C

64002 | 7W | LED | Die cast

DARK LIGHT · IP20 · offer

LED BUILT IN · 2 YEAR







A-A++

64004 | 16W | LED | Die cast

DARK LIGHT · IP20 · offer

LED BUILT IN · 2 YEAR







A-A++

64006 | 24W | LED | Die cast

DARK LIGHT · IP20 · offer

LED BUILT IN · 2 YEAR





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
64002/W/C	White	Cool white	4000K	7W	400lm	230V	☐	10	Complete with driver
64002/G/C	Grey	Cool white	4000K	7W	400lm	230V	☐	10	Complete with driver
64004/G/C	Grey	Cool white	4000K	16W	860lm	230V	☐	10	Complete with driver
64006/G/C	Grey	Cool white	4000K	24W	1500lm	230V	☐	10	Complete with driver



64008/G/C



64010/G/C

Multi LED Slim Plafo

Square



A-A++

64008 | 8W | LED | Die cast

DARK LIGHT

IP20

offer

LED BUILT IN

2 YEAR







A-A++

64010 | 17W | LED | Die cast

DARK LIGHT

IP20

offer

LED BUILT IN

2 YEAR





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
64008/G/C	Grey	Cool white	4000K	8W	500lm	230V	⧈	10	Complete with driver
64010/G/C	Grey	Cool white	4000K	17W	1100lm	230V	⧈	10	Complete with driver

The LED Decorative Plafo

Round



62144N/W/W



62132N/W/W

62130N | 20W | SMD 2835 | Aluminium



A-A++ 62130N/AN/W

LED BUILT IN

80 CRI

CE

2 YEAR

IP20



62130N/W/W





62132N | 32W | SMD 2835 | Aluminium



A-A++ 62132N/AN/W

LED BUILT IN

80 CRI

CE

2 YEAR

IP20



62132N/W/W





62142N | 42W | SMD 2835 | Aluminium



A-A++ 62142N/AN/W

LED BUILT IN

80 CRI

CE

2 YEAR

IP20



62142N/W/W





62144N | 50W | SMD 2835 | Metal



A-A++ 62144N/B/W

LED BUILT IN

80 CRI

CE

2 YEAR

IP20



62144N/W/W





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
62130N/W/W	White	Warm white	3000K	20W	1200lm	120°	230V		1	Complete with 500mA driver
62130N/AN/W	Anthracite	Warm white	3000K	20W	1200lm	120°	230V		1	Complete with 500mA driver
62132N/W/W	White	Warm white	3000K	32W	1920lm	120°	230V		1	Complete with 750mA driver
62132N/AN/W	Anthracite	Warm white	3000K	32W	1920lm	120°	230V		1	Complete with 750mA driver
62142N/W/W	White	Warm white	3000K	42W	2520lm	120°	230V		1	Complete with 1000mA driver
62142N/AN/W	Anthracite	Warm white	3000K	42W	2520lm	120°	230V		1	Complete with 1000mA driver
62144N/W/W	White	Warm white	3000K	50W	2750lm	120°	230V		1	Complete with 1200mA driver
62144N/B/W	Black	Warm white	3000K	50W	2750lm	120°	230V		1	Complete with 1200mA driver



The LED Decorative Plafo

Square

62132NA | 38W | SMD 2835 | Aluminium



A-A++ 62132NA/B/W

LED BUILT IN

80 CRI

CE

2 YEAR

IP20



62132NA/W/W





62142NA | 50W | SMD 2835 | Aluminium



A-A++ 62142NA/B/W

LED BUILT IN

80 CRI

CE

2 YEAR

IP20



62142NA/W/W





62135NA | 35W | SMD 2835 | Metal



A-A++

LED BUILT IN

80 CRI

CE

2 YEAR

IP20







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
62132NA/W/W	White	Warm white	3000K	38W	2280lm	120°	230V		1	Complete with 950mA driver
62132NA/B/W	Black	Warm white	3000K	38W	2280lm	120°	230V		1	Complete with 950mA driver
62142NA/W/W	White	Warm white	3000K	50W	3000lm	120°	230V		1	Complete with 1200mA driver
62142NA/B/W	Black	Warm white	3000K	50W	3000lm	120°	230V		1	Complete with 1200mA driver
62135NA/W/W	White	Warm white	3000K	35W	2100lm	120°	230V		1	Complete with 700mA driver



The LED Slim Line Plafo

62160 | 62W | SMD 2835 | Metal



A-A++ 62160/B/W

LED BUILT IN

80 CRI

CE

2 YEAR

IP20



62160/W/W





62160A | 62W | SMD 2835 | Aluminium



A-A++ 62160A/B/W

LED BUILT IN

80 CRI

CE

2 YEAR

IP20



62160A/W/W





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
62160/W/W	White	Warm white	3000K	62W	3600lm	120°	230V		1	Complete with 1500mA driver
62160/B/W	Black	Warm white	3000K	62W	3600lm	120°	230V		1	Complete with 1500mA driver
62160A/W/W	White	Warm white	3000K	62W	3600lm	120°	230V		1	Complete with 1500mA driver
62160A/B/W	Black	Warm white	3000K	62W	3600lm	120°	230V		1	Complete with 1500mA driver

The LED Project Plafo

Metal



62160/W/W



62125D/W/C



A-A++

62118D | 18W | SMD 2835 | Metal

LED BUILT IN

80 CRI

2 YEAR

IP20









A-A++

62125D | 25W | SMD 2835 | Metal

LED BUILT IN

80 CRI

2 YEAR

IP20









A-A++

62150D | 50W | SMD 2835 | Metal

LED BUILT IN

80 CRI

2 YEAR

IP20







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
62118D/W/W	White	Warm white	3000K	18W	1100lm	120°	230V		1	Complete with 300mA driver
62125D/W/C	White	Cool white	4000K	25W	1600lm	120°	230V		1	Complete with 700mA driver
62125D/W/W	White	Warm white	3000K	25W	1500lm	120°	230V		1	Complete with 700mA driver
62150D/W/C	White	Cool white	4000K	50W	3150lm	120°	230V		1	Complete with 1400mA driver
62150D/W/W	White	Warm white	3000K	50W	3000lm	120°	230V		1	Complete with 1400mA driver



67404M/W/W



67404A/W/C

Indoor LED & Music Plafo



A-A++

67404M | 12W | SMD 2835 | PC

LED BUILT IN · 80 CRI · IK08 · CE · 2 YEAR · IP40









A-A++

67404 | 18W | SMD 2835 | PC

LED BUILT IN · 80 CRI · CE · 2 YEAR · IP40









A-A++

67404A | 25W | SMD 2835 | PC

LED BUILT IN · 80 CRI · IK08 · CE · 2 YEAR · IP40









A-A++

62025 | 24W | SMD LED | Dimmable + RGB + Speaker | ABS + PMMA

Bluetooth speaker plafo.

LED BUILT IN · 80 CRI · DIMMABLE · CE · 2 YEAR · IP20



Application iLight.





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
67404M/W/W	White	Warm white	3000K	12W	1100lm	100-240V	☐	20	Complete with driver
67404/W/C	White	Cool white	4000K	18W	1700lm	100-240V	☐	10	Complete with driver
67404/W/W	White	Warm white	3000K	18W	1650lm	100-240V	☐	10	Complete with driver
67404A/W/C	White	Cool white	4000K	25W	2350lm	100-240V	☐	10	Complete with driver
67404A/W/W	White	Warm white	3000K	25W	2300lm	100-240V	☐	10	Complete with driver
62025	White	Extra warm white - Daylight	2700K - 6500K	24W	1560lm	100-240V	☐	5	Complete with driver



The LED Plafo Range

67402 | 25W | SMD 2835 | Aluminium + PC



A-A++ 67402/W/W

LED BUILT IN

80 CRI

CE

2 YEAR

IP40



67402/B/W



67390 | 21W | SMD 2835 | ABS + PC



A-A++ 67390/W/W

LED BUILT IN

80 CRI

CE

2 YEAR

IP65



67390/AN/C



67448 | 24W | SMD LED | Metal + Plastic



A-A++

LED BUILT IN

85 CRI

CE

2 YEAR

IP20





67448A | 36W | SMD LED | Metal + Plastic



A-A++

LED BUILT IN

85 CRI

CE

2 YEAR

IP20





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
67402/W/W	White	Warm white	3000K	25W	1850lm	100-240V		10	Complete with driver
67402/B/W	Black	Warm white	3000K	25W	1850lm	100-240V		10	Complete with driver
67390/W/W	White	Warm white	3000K	21W	1300lm	230V		10	Complete with 500mA driver
67390/AN/C	Anthracite	Cool white	4000K	21W	1300lm	230V		10	Complete with 500mA driver
67390/AN/W	Anthracite	Warm white	3000K	21W	1300lm	230V		10	Complete with 500mA driver
67448/W/W	White	Warm white	3000K	24W	1800lm	100-240V		5	Complete with 560mA driver
67448A/W/W	White	Warm white	3000K	36W	2700lm	100-240V		5	Complete with 850mA driver





16

Bathroom & Mirror

Pages 463-470

G9 | T5 | T8 | E14 | 2G11 | SMD LED

Die cast + acrylic | Aluminium + PC | Metal + glass

IP44

2 YEAR 3 YEAR





The Mirror LED Round

Aluminium + PC



A-A++

38115C | 15W | SMD 2835 | Aluminium + PC

LED BUILT IN

80 CRI

CE

2 YEAR

IP44









A-A++

38120C | 20W | SMD 2835 | Aluminium + PC

LED BUILT IN

80 CRI

CE

2 YEAR

IP44







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
38115C/C	Chrome	Cool white	4000K	15W	1300lm	230V		10	Complete with 350mA driver
38115C/W	Chrome	Warm white	3000K	15W	1300lm	230V		10	Complete with 350mA driver
38120C/W	Chrome	Cool white	4000K	20W	1700lm	230V		10	Complete with 500mA driver
38120C/C	Chrome	Warm white	3000K	20W	1700lm	230V		10	Complete with 500mA driver



The Mirror LED Range

38114DL | 23W | SMD 2835 | Die cast + acrylic



LED BUILT IN · 80 CRI · CE · 2 YEAR · IP44





38114EL | 23W | SMD 2835 | Die cast + acrylic



LED BUILT IN · 80 CRI · CE · 2 YEAR · IP44





38121EL | 23W | SMD 2835 | Die cast + acrylic



LED BUILT IN · 80 CRI · CE · 2 YEAR · IP44





38114CL | 18W | SMD 2835 | Die cast + acrylic



LED BUILT IN · 80 CRI · CE · 2 YEAR · IP44





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
38114DL/C	Chrome	Cool white	4000K	23W	1650lm	100-240V		8	Complete with 250mA driver
38114DL/W	Chrome	Warm white	3000K	23W	1650lm	100-240V		8	Complete with 250mA driver
38114EL/C	Chrome	Cool white	4000K	23W	1650lm	100-240V		8	Complete with 250mA driver
38114EL/W	Chrome	Warm white	3000K	23W	1650lm	100-240V		8	Complete with 250mA driver
38121EL/C	Chrome	Cool white	4000K	23W	1650lm	100-240V		8	Complete with 250mA driver
38114CL/C	Chrome	Cool white	4000K	18W	1300lm	100-240V		6	Complete with 250mA driver



The Mirror T5 Range

For T5 14W/21W Fluorescent



B-A++

38121D | 21W | T5 | Die cast + acrylic

2 YEAR

IP44







B-A++

38114C | 14W | T5 | Die cast + acrylic

2 YEAR

IP44





Order Code	Colour	Watts	Input	Class		Notes
38121D/C	Chrome	21W	230V		8	Complete with electronic ballast
38114C/C	Chrome	14W	230V		6	Complete with electronic ballast



The Mirror 60cm Range

For T8 LED Tubes



A-A++

38114DE | T8 LED 60cm | Die cast + acrylic

2 YEAR

IP44







A-A++

38114EE | T8 LED 60cm | Die cast + acrylic

2 YEAR

IP44







A-A++

38114GE | T8 LED 60cm | Die cast + acrylic

2 YEAR

IP44







A-A++

38114CE | T8 LED 60cm | Die cast + acrylic

2 YEAR

IP44





Order Code	Colour	Watts	Input	Class		Notes
38114DE/C	Chrome	-	100-240V		6	Only suitable for T8 LED tubes
38114EE/C	Chrome	-	100-240V		6	Only suitable for T8 LED tubes
38114GE/C	Chrome	-	100-240V		6	Only suitable for T8 LED tubes
38114CE/C	Chrome	-	100-240V		6	Only suitable for T8 LED tubes



Mirror Light

Die cast + acrylic



38110BD | 10W | SMD 2835 | PC

Variable colour temperature and dimmable.

LED BUILT IN · 80 CRI · DIMMABLE · CE · 3 YEAR · IP20







38114GL | 23W | SMD 2835 | Die cast + acrylic

LED BUILT IN · 80 CRI · CE · 2 YEAR · IP44







38124 | 24W | 2G11 | Die cast + acrylic

CE · 2 YEAR · IP44





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class			Notes
38110BD	-	Extra warm white - Daylight	2700K - 6500K	10W	700lm	230V		1,5	20	Complete with driver
38114GL/C	Chrome	Cool white	4000K	23W	1650lm	230V		-	10	Complete with driver
38124/C	Chrome	-	-	24W	-	230V		-	6	Complete with electronic ballast



Mirror Side Lights

Metal + glass



A-A++

60204 | 7W | SMD LED | Die cast + Mirror

LED BUILT IN

2 YEAR

IP44







E-A++

60106 | 40W | E14 | Metal + glass

2 YEAR

IP44







E-A++

60106A | 2x40W | E14 | Metal + glass

2 YEAR

IP44





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
60204/C	Chrome	Cool white	4000K	7W	490lm	100-240V		6	Complete with driver
60106/C	Chrome	-	-	40W	-	100-240V		10	-
60106A/C	Chrome	-	-	2x40W	-	100-240V		10	-

The Mirror G9 Decorative Globes

Metal + glass



60107C/C

60107B/C



C-A++

60107A | 28W | G9 | Metal + glass

2 YEAR

IP44



Suitable for G9 LED lamp.





C-A++

60107B | 2x28W | G9 | Metal + glass

2 YEAR

IP44



Suitable for G9 LED lamps.



Order Code	Colour	Watts	Input	Class		Notes
60107A/C	Chrome	28W	100-240V		12	-
60107B/C	Chrome	2x28W	100-240V		8	-



The Mirror G9 Decorative Globes

Metal + glass



C-A++

60107C | 3x28W | G9 | Metal + glass

2 YEAR

IP44



Suitable for G9 LED lamps.





C-A++

60107D | 4x28W | G9 | Metal + glass

2 YEAR

IP44



Suitable for G9 LED lamps.



Order Code	Colour	Watts	Input	Class		Notes
60107C/C	Chrome	3x28W	100-240V	⏚	6	-
60107D/C	Chrome	4x28W	100-240V	⏚	6	-





17

Pendants

Pages 473-484

MR16 | GU10 | E14 | G9 | E27 | COB LED | LED

Die cast | Natural aluminium | Gypsum | Metal

IP20 IP40

ADJUSTABLE 80 CRI 2 YEAR 3 YEAR 5 YEAR





Gypsum Pendants



A-A++

63036 | 10W | MR16 | GU10 | Gypsum

IP20



Suitable for GU10 LED lamp.





B-A++

63038 | 7W | GX53 | Gypsum

IP20



Suitable for GX53 LED lamp.



Order Code	Colour	Watts	Input	Class		Notes
63036	White	10W	100-240V		12	-
63038	White	7W	100-240V		12	-



Cylinder Pendants

63105N | 10W | MR16 | GU10 | Aluminium



A-A++ 63105N/W

DARK LIGHT IP20



63105N/B





63105M | 10W | MR16 | GU10 | Aluminium body + plastic reflector

Reflector must be ordered separately.



A-A++ 63105M/W + 050112/GL

DARK LIGHT IP20



63105M/B + 050112/W







050112/W White | 050112/B Black | 050112/G Grey | 050112/BS Brass | new 050112/ABS Antique brass | 050112/GL Gold | 050112/CU Copper | new 050112/DC Dark chrome

63105L | 35W | MR16 | GU10 | Aluminium



E-A++ 63105L/W

DARK LIGHT IP20



63105L/B





Order Code	Colour	Reflector	Watts	Input	Class		Notes
63105N/W	White	Black	10W	100-240V		24	-
63105N/B	Black	Brass	10W	100-240V		24	-
63105M/W	White	-	10W	100-240V		12	-
63105M/B	Black	-	10W	100-240V		12	-
63105L/W	White	Black	35W	100-240V		20	-
63105L/B	Black	Brass	35W	100-240V		20	-



Mini Pendants LED

Natural aluminium



A-A++

63001 | 3W | LED | Natural aluminium

LED BUILT IN

2 YEAR

IP20









A-A++ 63002/AL/W

63002 | 3W | LED | Recessed base | Natural aluminium

LED BUILT IN

2 YEAR

IP20

offer



63002/AL/BL





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class				Notes
63001/AL/W	Aluminium	Warm white	3000K	3W	100lm	45°	100-240V		-	-	20	Complete with driver
63002/AL/W	Aluminium	Warm white	3000K	3W	130lm	45°	100-240V		70mm	40mm	8	Complete with driver
63002/AL/BL	Aluminium	Blue	-	3W	-	45°	100-240V		70mm	40mm	8	Complete with driver





63108 | 8W | COB LED | Aluminium

LED BUILT IN
90 CRI
TRIAC DIMMABLE
CE
IP20
3 YEAR







63108A/W/W

63108A | 6W | COB LED | Die cast

new
LED BUILT IN
80 CRI
CE
3 YEAR
IP20



63108A/B/W





Order Code	Colour	Reflector	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
63108/W/W	White	Black	Warm white	3000K	8W	510lm	36°	100-240V		10	Complete with 350mA driver
63108A/W/W	White	Black	Warm white	3000K	6W	420lm	30°	230V		12	Complete with 700mA driver
63108A/B/W	Black	Brass	Warm white	3000K	6W	420lm	30°	230V		12	Complete with 700mA driver



Retro Pendants



A-A++

63040 | 12W | E27 | Aluminium

IP20









A-A++

63042 | 12W | E27 | Aluminium

IP20









A-A++

63044 | 12W | E27 | Aluminium

IP20







Order Code	Colour	Reflector	Watts	Input	Class		Notes
63040/B/BS	Black	Brass	12W	100-240V		1	-
63042/B/BS	Black	Brass	12W	100-240V		1	-
63044/B/BS	Black	Brass	12W	100-240V		1	-



Retro Pendants



B-A++ 63020/B/BS

63020 | 20W | E27 | Aluminium

IP20



63020/W/G







A-A++

63026 | 12W | E27 | Aluminium

IP20







Order Code	Colour	Reflector	Watts	Input	Class		Notes
63020/W/G	White	Grey	20W	100-240V		1	-
63020/B/G	Black	Grey	20W	100-240V		1	-
63020/B/BS	Black	Brass	20W	100-240V		1	-
63026/B/BS	Black	Brass	12W	100-240V		1	-



Bowl Shade Pendant Range

63016A | 20W | E27 | Aluminium



B-A++ 63016A/B/BS



63016A/W/G





63022 | 20W | E27 | Aluminium



B-A++ 63022/B/BS



63022/W/BS





63022A | 20W | E27 | Aluminium



B-A++ 63022A/B/BS



63022A/W/BS





63022B | 25W | E27 | Aluminium



B-A++ 63022B/B/BS



63022B/W/BS





Order Code	Colour	Reflector	Watts	Input	Class		Notes
63016A/W/G	White	Grey	20W	100-240V		1	-
63016A/B/G	Black	Grey	20W	100-240V		1	-
63016A/B/BS	Black	Brass	20W	100-240V		1	-
63022/W/BS	White	Brass	20W	100-240V		1	-
63022/B/BS	Black	Brass	20W	100-240V		1	-
63022A/W/BS	White	Brass	20W	100-240V		1	-
63022A/B/BS	Black	Brass	20W	100-240V		1	-
63022B/W/BS	White	Brass	25W	100-240V		1	-
63022B/B/BS	Black	Brass	25W	100-240V		1	-



Decorative E27



E-A++ 0990/B

0990 | 50W | E27

5 YEAR

IP20



Suitable for E27 LED lamp.





E-A++ 0990/BBS

0990 | 50W | E27

5 YEAR

IP20



Suitable for E27 LED lamp.





E-A++

0992 | 50W | E27

5 YEAR

IP20



Suitable for E27 LED lamp.



Order Code	Colour	Lampholder	Watts	Input	Class		Notes
0990/B	Black	E27	50W	100-240V	⏚	36	-
0990/BBS	Brushed brass	E27	50W	100-240V	⏚	36	-
0992/B	Black	E27	50W	100-240V	⏚	36	-



The COB Moving Heads Pendant



65110P | 4x10W | COB LED | Die cast

LED BUILT IN

80 CRI

ADJUSTABLE

2 YEAR

IP20







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
65110P/W/W	White	Warm white	3000K	4x10W	4x900lm	60°	230V	⏚	2	Complete with 1000mA driver



Linear LED Bars



38018 | 6x1W | LED | Metal

LED BUILT IN

2 YEAR

IP20









38016/G/W

38016 | 16W | LED | Die cast

LED BUILT IN

2 YEAR

IP20



38016/W/D





Order Code	Colour	Light Colour	CCT (K)	Watts	Input	Class		Notes
38018/G/W	Grey	Warm white	3000K	6x1W	100-240V		1	Complete with driver
38016/W/D	White	Daylight	6000K	16W	100-240V		1	Complete with driver
38016/W/W	White	Warm white	3000K	16W	100-240V		1	Complete with driver
38016/G/W	Grey	Warm white	3000K	16W	100-240V		1	Complete with driver

Pendant HQI G12



63070D | 70W | HQI | G12 | Aluminium + PC

IP20

offer







63270 | 2x70W | HQI | G12 | Die cast

IP20

offer





Order Code	Colour	Watts	Input	Class		Notes
63070D/G	Grey	70W	230V		6	Complete with electronic ballast
63270/G	Grey	2x70W	230V		4	Complete with electronic ballast





A-A++

63034 | 18W | COB LED | Aluminium

LED BUILT IN

CE 2 YEAR

IP40









A-A++

63025L | 25W | COB LED | Aluminium

LED BUILT IN

85 CRI CE 2 YEAR

IP20



Optional glass included.







A-A++

63030L | 30W | COB LED | Aluminium

LED BUILT IN

85 CRI CE 2 YEAR

IP20







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
63034/W/W	White	Warm white	3000K	18W	1019lm	30°	100-240V		1	Complete with 1400mA driver
63025L/W/W	White	Warm white	3000K	25W	1800lm	42°	230V		1	Complete with 700mA driver
63030L/G/W	Grey	Warm white	3000K	30W	2000lm	76°	230V		1	Complete with 700mA driver





18

Decorative

Pages 487-512

MR16 | GU10 | GU5,3 | G4 | G9 | E27 | E14 | SMD LED | LED

Die cast + crystal | Wood | Metal | Plastic | ABS | PC

IP20 IP44 IP54 IP65

ADJUSTABLE ADJUSTABLE DIMMABLE 80 CRI 2 YEAR 3 YEAR 5 YEAR







10101C4 | 10W | G4 | Die cast + crystal

IP20
offer







10101C5 | 10W | G4 | Die cast + crystal

IP20
offer





Order Code	Colour	Watts	Input	Class					Notes
10101C4/C	Chrome	10W	12V	III	40cm	60mm	30mm	50	-
10101C5/C	Chrome	10W	12V	III	40cm	60mm	30mm	50	-

Crystal Recessed

Die cast + crystal



10105C4 | 50W | MR16 | GU5,3 | Die cast + crystal





Order Code	Colour	Watts	Input	Class					Notes
10105C4/C	Chrome	50W	12V		40cm	72mm	50mm	4	-





61048A | 40W | E27 | Metal | Table lamp

5 YEAR

IP20



Suitable for 9G06F
LED flame lamp.





61048B | 40W | E27 | Metal | Floor lamp

5 YEAR

IP20



Suitable for 9G06F
LED flame lamp.



Order Code	Colour	Watts	Input	Class		Notes
61048A	Antique oriental	40W	100-240V		1	-
61048B	Antique oriental	40W	100-240V		1	-





61050A | 40W | E27 | Metal | Table lamp

IP20



Suitable for 9G06F LED flame lamp.







61050B | 40W | E27 | Metal | Floor lamp

IP20



Suitable for 9G06F LED flame lamp.







63052 | 40W | E27 | Metal | Pendant

IP20



Suitable for 9G06F LED flame lamp.





Order Code	Colour	Watts	Input	Class		Notes
61050A	Antique oriental	40W	100-240V		1	-
61050B	Antique oriental	40W	100-240V		1	-
63052	Antique oriental	40W	100-240V		1	-



The Hotel Range
Metal



C-A++

61046 | 40W | E27 | Metal + white fabric shade

ADJUSTABLE

2 YEAR

IP20



Suitable for E27 LED lamp.





C-A++

61076 | 40W | E27 | Metal + white fabric shade

2 YEAR

IP20



Suitable for E27 LED lamp.





C-A++

61078 | 40W | E27 | Metal + white fabric shade

2 YEAR

IP20



Suitable for E27 LED lamp.



Order Code	Colour	Watts	Input	Class		Notes
61046/MC	Brushed chrome	40W	100-240V		8	With ON/OFF Switch
61076/C	Chrome	40W	100-240V		12	With ON/OFF Switch
61078/C	Chrome	40W	100-240V		8	With ON/OFF Switch



The Hotel Range

Metal



C-A++

65138 | 3W LED + 40W E27 | Metal + white fabric shade

With 2 x ON/OFF Switches.

LED BUILT IN · ADJUSTABLE · CE · 2 YEAR · IP20



Suitable for E27 LED lamp.





C-A++

61044 | 3W LED + 40W E27 | Metal + white fabric shade

With 2 x ON/OFF Switches.

LED BUILT IN · ADJUSTABLE · CE · 2 YEAR · IP20



Suitable for E27 LED lamp.





C-A++

61074 | 3W LED + 40W E27 | Metal + white fabric shade

With 2 x ON/OFF Switches.

LED BUILT IN · ADJUSTABLE · CE · 2 YEAR · IP20



Suitable for E27 LED lamp.





C-A++ 61080/C/W

61080 | 3W LED + 40W E27 | USB socket | Metal + white fabric shade

With 2 x ON/OFF Switches.

LED BUILT IN · ADJUSTABLE · CE · 2 YEAR · new · IP20



61080/W/W



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
65138/MC/W	Brushed chrome	Warm white	3000K	3W LED + 40W E27	100lm	230V		8	Complete with 500mA driver
61044/C/W	Chrome	Warm white	3000K	3W LED + 40W E27	100lm	230V		6	Complete with 500mA driver
61074/C/W	Chrome	Warm white	3000K	3W LED + 40W E27	100lm	100-240V		8	Complete with 500mA driver
61080/W/W	White	Warm white	3000K	3W LED + 40W E27	150lm	230V		4	Complete with 700mA driver
61080/C/W	Chrome	Warm white	3000K	3W LED + 40W E27	150lm	230V		4	Complete with 700mA driver



61044A/C/W



61042A/MC

The Hotel Range

Metal



61044A | 3W LED + 40W E27 | Metal + white fabric shade

LED BUILT IN

ADJUSTABLE

2 YEAR

IP20



Suitable for E27 LED lamp.







61042A | 40W | E27 | Metal + white fabric shade

2 YEAR

IP20



Suitable for E27 LED lamp.





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
61044A/C/W	Chrome	Warm white	3000K	3W LED + 40W E27	100lm	230V	⧈	1	Complete with driver
61042A/MC	Brushed chrome	-	-	40W	-	100-240V	⧈	1	-

Portable Trendy Light





61082 | 2,2W | LED | Touch switch | Die cast

Rechargeable USB socket.

LED BUILT IN

85 CRI

2 YEAR

new

IP54



Charging time: 5-7Hrs
Working time: 9Hrs





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Class		Notes
61082/W	White	Warm white	3000K	2,2W	190lm		6	2x2200mAh lithium battery





9C006 | LED | Flickering flame | Metal + glass

ON/OFF and 5 hours timer functions.

LED BUILT IN

2 YEAR

IP20







9C008 | LED | Flickering flame | Plastic

ON/OFF and 5 hours timer functions.

LED BUILT IN

2 YEAR

IP20





Order Code	Battery		Notes
9C006/F	2xAA	10	Batteries included
9C008/F	2xC	8	Batteries included



The LED Flickering Candles



9C004A | LED | Flickering candle | Plastic

ON/OFF and 5 hours timer functions.

LED BUILT IN

CE 2 YEAR

IP20







9C004B | LED | Flickering candle | Plastic

ON/OFF and 5 hours timer functions.

LED BUILT IN

CE 2 YEAR

IP20







9C002 | LED | Flickering flame | Wax with aroma

ON/OFF and 4 hours timer functions.

LED BUILT IN

CE 2 YEAR

IP20





Order Code	Battery		Notes
9C004A/F	2xAA	24	Batteries included
9C004B/F	2xAA	24	Batteries included
9C002/F	2xC	24	Batteries not included

Retro Floor Lamp

Metal



61058A | 26W | E27 | Metal

2 YEAR

IP20



Suitable for E27 LED lamp.



Order Code	Colour	Watts	Input	Class		Notes
61058A/C	Chrome	26W	100-240V		1	-



Chrome Classic

Metal



B-A++

61036 | 2x11W | E14 | Metal

2 YEAR

IP20



Suitable for E14 LED lamp.





B-A++

61038 | 20W | E27 | Metal

2 YEAR

IP20



Suitable for E27 LED lamp.





B-A++

61038B | 15W | E14 | Metal

2 YEAR

IP20



Suitable for E14 LED lamp.



Order Code	Colour	Watts	Input	Class		Notes
61036/C	Chrome	2x11W	100-240V		1	-
61038/C	Chrome	20W	100-240V		1	-
61038B/C	Chrome	15W	100-240V		1	-





63046 | 25W | SMD 2835 | Steel + aluminium

Oval shape.

LED BUILT IN
80 CRI
2 YEAR
IP20







63046A | 45W | SMD 2835 | Steel + aluminium

LED BUILT IN
80 CRI
2 YEAR
IP20







63046B | 50W | SMD 2835 | Steel + aluminium

LED BUILT IN
80 CRI
2 YEAR
IP20





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
63046/W	White	Warm white	3000K	25W	1540lm	230V		1	Complete with 24V DC driver
63046A/W	White	Warm white	3000K	45W	2700lm	230V		1	Complete with 24V DC driver
63046B/W	White	Warm white	3000K	50W	3000lm	230V		1	Complete with 24V DC driver





A-A++ 63048/W

63048 | 19W | SMD 2835 | Steel + aluminium

LED BUILT IN

80 CRI

CE

2 YEAR

IP20









A-A++ 63048/B

63048 | 19W | SMD 2835 | Steel + aluminium

LED BUILT IN

80 CRI

CE

2 YEAR

IP20









A-A++ 63048/C

63048 | 19W | SMD 2835 | Steel + aluminium

LED BUILT IN

80 CRI

CE

2 YEAR

IP20







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
63048/W	White	Warm white	3000K	19W	1000lm	230V	⏚	1	Complete with 24V DC driver
63048/B	Black	Warm white	3000K	19W	1000lm	230V	⏚	1	Complete with 24V DC driver
63048/C	Chrome	Warm white	3000K	19W	1000lm	230V	⏚	1	Complete with 24V DC driver



LED Pendant Rings



A-A++ 63050/W

63050 | 40W | SMD 2835 | Steel + aluminium

LED BUILT IN

80 CRI

CE

2 YEAR

IP20



63050/B





A-A++ 62144NB/W/W

62144NB | 50W | SMD 2835 | Metal

LED BUILT IN

80 CRI

CE

2 YEAR

IP20



62144NB/B/W



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
63050/W	White	Warm white	3000K	40W	2250lm	230V		1	Complete with 24V DC driver
63050/B	Black	Warm white	3000K	40W	2250lm	230V		1	Complete with 24V DC driver
62144NB/W/W	White	Warm white	3000K	50W	2750lm	230V		1	Complete with 1200mA driver
62144NB/B/W	Black	Warm white	3000K	50W	2750lm	230V		1	Complete with 1200mA driver



LED Pendant Rings



A-A++ 62142NB/AN/W

62142NB | 42W | SMD 2835 | Aluminium

LED BUILT IN

80 CRI

CE

2 YEAR

IP20



62142NB/W/W







A-A++ 62180NB/B/W

62180NB | 80W | SMD 2835 | Metal base + aluminium + PMMA

new

LED BUILT IN

80 CRI

CE

2 YEAR

IP20



62180NB/W/W





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
62142NB/W/W	White	Warm white	3000K	42W	2520lm	-	230V		1	Complete with 1000mA driver
62142NB/AN/W	Anthracite	Warm white	3000K	42W	2520lm	-	230V		1	Complete with 1000mA driver
62180NB/W/W	White	Warm white	3000K	80W	4400lm	120°	230V		1	Complete with 1000mA drivers
62180NB/B/W	Black	Warm white	3000K	80W	4400lm	120°	230V		1	Complete with 1000mA drivers





62148A | 23W | SMD 2835 | Metal base + PC

new
IP20
LED BUILT IN
80 CRI
3 YEAR









62148B | 40W | SMD 2835 | Metal base + PC

new
IP20
LED BUILT IN
80 CRI
3 YEAR









62148D | 108W | SMD 2835 | Metal base + PC

new
IP20
LED BUILT IN
80 CRI
3 YEAR







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
62148A/W	White	Warm white	3000K	23W	1900lm	230V		1	Complete with 500mA driver
62148B/W	White	Warm white	3000K	40W	3200lm	230V		1	Complete with 1000mA driver
62148D/W	White	Warm white	3000K	108W	8700lm	230V		1	Complete with 1300mA drivers





63110C | 80W | SMD 2835 | Metal base + PC

new

IP20

LED BUILT IN

80 CRI

3 YEAR







63110D | 108W | SMD 2835 | Metal base + PC

new

IP20

LED BUILT IN

80 CRI

3 YEAR





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
63110C/W	White	Warm white	3000K	80W	6400lm	230V		1	Complete with 1000mA drivers
63110D/W	White	Warm white	3000K	108W	8700lm	230V		1	Complete with 1300mA drivers



Reading LED Lamps



61070 | 5W | SMD 2835 | Dimmable | Plastic

LED BUILT IN · DIMMABLE · ADJUSTABLE · CE · 2 YEAR · IP20







61068 | 15W | LED | Variable colour temperature | Dimmable | ABS

LED BUILT IN · DIMMABLE · ADJUSTABLE · CE · 2 YEAR · IP20







61068B | 12W | SMD 2835 | Dimmable | ABS

LED BUILT IN · 80 CRI · DIMMABLE · ADJUSTABLE · CE · 2 YEAR · IP20







61072 | 6W | SMD 2835 | Dimmable | ABS

LED BUILT IN · DIMMABLE · ADJUSTABLE · CE · 2 YEAR · IP20





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
61070/W	White	Cool white	4000K	5W	480lm	100-240V	☐	8	EU socket charger
61070/B	Black	Cool white	4000K	5W	480lm	100-240V	☐	8	EU socket charger
61068/C	White	Variable	3000K-6500K	15W	500lm	100-240V	☐	10	With USB charging socket
61068B/C	Black	Cool white	4000K	12W	600lm	100-240V	☐	10	With USB charging socket
61072/W	White	Cool white	4000K	6W	200lm	100-240V	☐	10	With USB charging socket
61072/B	Black	Cool white	4000K	6W	200lm	100-240V	☐	10	With USB charging socket



The Magnifying Lens LED Lamp



61066 | 8W | SMD 2835 | Plastic

Magnifying lens.

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · 2 YEAR · IP20









61066T | White floor stand for 61066

CE · 2 YEAR



1

Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
61066/W	White	Daylight	6000K	8W	760lm	230V		4	Complete with driver



Hotel Reading Spots



65740 | 6W | SMD 2835 | Aluminium

LED BUILT IN
80 CRI
ADJUSTABLE
CE
2 YEAR
IP20







65740A | 2x6W | SMD 2835 | Aluminium

LED BUILT IN
80 CRI
ADJUSTABLE
CE
2 YEAR
IP20





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
65740/W/W	White	Warm white	3000K	6W	500lm	230V		12	Complete with 300mA driver
65740A/W/W	White	Warm white	3000K	2x6W	2x500lm	230V		12	Complete with 300mA driver

The Retro GU10 Spots





A-A++ 65105N/B

65105N | 10W | MR16 | GU10 | Aluminium

ADJUSTABLE · 5 YEAR · DARK LIGHT · IP20



65105N/W





A-A++ 65205N/B

65205N | 2x10W | MR16 | GU10 | Aluminium

ADJUSTABLE · 5 YEAR · DARK LIGHT · IP20



65205N/W





A-A++ 65305N/B

65305N | 3x10W | MR16 | GU10 | Aluminium

ADJUSTABLE · 5 YEAR · DARK LIGHT · IP20



65305N/W





A-A++ 65105NA/B

65105NA | 10W | MR16 | GU10 | Aluminium

With switch.

ADJUSTABLE · 5 YEAR · DARK LIGHT · IP20



65105NA/W



Order Code	Colour	Reflector	Watts	Input	Class		Notes
65105N/W	White	Black	10W	100-240V		24	-
65105N/B	Black	Brass	10W	100-240V		24	-
65205N/W	White	Black	2x10W	100-240V		12	-
65205N/B	Black	Brass	2x10W	100-240V		12	-
65305N/W	White	Black	3x10W	100-240V		12	-
65305N/B	Black	Brass	3x10W	100-240V		12	-
65105NA/W	White	Black	10W	100-240V		24	-
65105NA/B	Black	Brass	10W	100-240V		24	-



65105A/MC

Decorative Spots

Die cast + glass



E-A++

65105A | 50W | MR16 | GU10 | Die cast + glass

IP20

offer

ADJUSTABLE

3 YEAR



Suitable for GU10 LED lamp.





E-A++

65305B | 3x40W | G9 | Die cast + glass

IP20

offer

ADJUSTABLE

3 YEAR



Suitable for LED lamps.



Order Code	Colour	Watts	Input	Class		Notes
65105A/MC	Brushed chrome	50W	100-240V	⏚	20	-
65305B/MC	Brushed chrome	3x40W	100-240V	⏚	10	-

Outdoor Floor Lamp

Die cast + PC



61040 | 20W | E27 | Die cast + PC



Suitable for E27 LED lamp.



Order Code	Colour	Watts	Input	Class			Notes
61040/AN	Anthracite	20W	100-240V		300cm	1	-

Outdoor E27 String Lights

0994 | 15x60W | E27 | 15xT-lampholders





Order Code	Colour	Watts	Input	Class			Notes
0994/B	Black	15x60W	100-240V		850cm	8	50cm spacing



Moonlights

PC



63028 | 15W | E27 | PC




IP54





l380mml





63028A | 20W | E27 | PC




IP54





l450mml





63028B | 30W | E27 | PC




IP54





l560mml



Order Code	Colour	Watts	Input	Class		Notes
63028	White	15W	100-240V		1	Pendant / Ground / Spike
63028A	White	20W	100-240V		1	Pendant / Ground / Spike
63028B	White	30W	100-240V		1	Pendant / Ground / Spike





19

Wall Recessed & Inground

Pages 515-544

MR16 | GU10 | GX53 | COB LED | SMD LED | LED

Die cast | Natural aluminium | Stainless steel | Gypsum | Plastic

IP20 IP44 IP54 IP65 IP67

ADJUSTABLE DIMMABLE DARK LIGHT QUICK FIX IK08 IK10 80 CRI 85 CRI 90 CRI 2 YEAR 3 YEAR 5 YEAR





Indoor Square Wall Recessed



E-A++

68054 | 50W | MR16 | GU10 | Gypsum

DARK LIGHT

IP20

5 YEAR



Suitable for LED GU10 lamp.





A-A++

68006 | 1W | LED | Die cast

LED BUILT IN

DARK LIGHT

IP44

3 YEAR







A-A++

68007 | 1,5W | LED | Plastic

Supplied with box for concrete installation.

LED BUILT IN

DARK LIGHT

IP20

2 YEAR





Order Code	Colour	Light Colour	CCT (K)	Watts	Input	Class					Notes
68054	White	-	-	50W	100-240V		15cm	121x121mm	95mm	24	-
68006/G/W	Grey	Warm white	3000K	1W	230V		12cm	75x75mm	60mm	100	Complete with 350mA driver
68007/W/W	White	Warm white	3000K	1,5W	100-240V		-	86x86mm	40mm	50	Complete with driver



68005/G/D

68008/G/D

Indoor Dark Light Wall Recessed



A-A++ 68005/G/D

68005 | 1W | LED | Die cast

For concrete installation, order 68005/BOX.

DARK LIGHT · IP20 · LED BUILT IN · DIMMABLE · QUICK FIX · CE · 2 YEAR



68005/G/W



68005/BOX





68005/G/BL

68005 | 1W | LED | Die cast

For concrete installation, order 68005/BOX.

DARK LIGHT · IP20 · offer · LED BUILT IN · DIMMABLE · QUICK FIX · CE · 2 YEAR



offer 68005/G/GR



68005/BOX





A-A++ 68008/G/D

68008 | 1W | LED | Die cast

For concrete installation, order 68008/BOX.

DARK LIGHT · IP20 · offer · LED BUILT IN · DIMMABLE · QUICK FIX · CE · 2 YEAR



offer 68008/G/W



68008/BOX





68008/G/BL

68008 | 1W | LED | Die cast

For concrete installation, order 68008/BOX.

DARK LIGHT · IP20 · offer · LED BUILT IN · DIMMABLE · QUICK FIX · CE · 2 YEAR



68008/BOX



Order Code	Colour	Light Colour	CCT (K)	Watts	Input	Class					Notes
68005/G/D	Grey	Daylight	6000K	1W	350mA		50cm	73x73mm	40mm	50	Requires 350mA driver
68005/G/W	Grey	Warm white	3000K	1W	350mA		50cm	73x73mm	40mm	50	Requires 350mA driver
68005/G/BL	Grey	Blue	-	1W	350mA		50cm	73x73mm	40mm	50	Requires 350mA driver
68005/G/GR	Grey	Green	-	1W	350mA		50cm	73x73mm	40mm	50	Requires 350mA driver
68008/G/D	Grey	Daylight	6000K	1W	350mA		50cm	65x212mm	90mm	20	Requires 350mA driver
68008/G/W	Grey	Warm white	3000K	1W	350mA		50cm	65x212mm	90mm	20	Requires 350mA driver
68008/G/BL	Grey	Blue	-	1W	350mA		50cm	65x212mm	90mm	20	Requires 350mA driver

Outdoor Decorative Wall Recessed

Die cast





A-A++ 68052/AN/W

68052 | 4W | SMD 2835 | Die cast

Supplied with box for concrete installation.

LED BUILT IN

80 CRI

DARK LIGHT

IP65



68052/W/W



68052/G/W





A-A++ 68052A/AN/W

68052A | 5W | SMD 2835 | Die cast

Supplied with box for concrete installation.

LED BUILT IN

80 CRI

DARK LIGHT

IP65



68052A/W/W



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class	Concrete installation	Gypsum installation			Notes
68052/W/W	White	Warm white	3000K	4W	400lm	100-240V		100x70mm	95x70mm	80mm	20	Complete with 350mA driver
68052/AN/W	Anthracite	Warm white	3000K	4W	400lm	100-240V		100x70mm	95x70mm	80mm	20	Complete with 350mA driver
68052/G/W	Grey	Warm white	3000K	4W	400lm	100-240V		100x70mm	95x70mm	80mm	20	Complete with 350mA driver
68052A/W/W	White	Warm white	3000K	5W	500lm	100-240V		205x54mm	205x50mm	80mm	18	Complete with 350mA driver
68052A/AN/W	Anthracite	Warm white	3000K	5W	500lm	100-240V		205x54mm	205x50mm	80mm	18	Complete with 350mA driver



Outdoor Wall Recessed

Die cast



A-A++ 68046/AN/W

68046 | 2x1W | LED | Die cast

Supplied with box for concrete installation.

LED BUILT IN

2 YEAR

IP65



68046/W/W



68046/G/W





A-A++ 68048/AN/W

68048 | 4x1W | LED | Die cast

Supplied with box for concrete installation.

LED BUILT IN

2 YEAR

IP65



68048/W/W



68048/G/W





A-A++ 68050/AN/W

68050 | 6x1W | LED | Die cast

Supplied with box for concrete installation.

LED BUILT IN

2 YEAR

IP65



68050/W/W



68050/G/W



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class				Notes
68046/W/W	White	Warm white	3000K	2x1W	140lm	100-240V		100x100mm	100mm	20	Complete with 350mA driver
68046/AN/W	Anthracite	Warm white	3000K	2x1W	140lm	100-240V		100x100mm	100mm	20	Complete with 350mA driver
68046/G/W	Grey	Warm white	3000K	2x1W	140lm	100-240V		100x100mm	100mm	20	Complete with 350mA driver
68048/W/W	White	Warm white	3000K	4x1W	280lm	100-240V		170x90mm	100mm	12	Complete with 350mA driver
68048/AN/W	Anthracite	Warm white	3000K	4x1W	280lm	100-240V		170x90mm	100mm	12	Complete with 350mA driver
68048/G/W	Grey	Warm white	3000K	4x1W	280lm	100-240V		170x90mm	100mm	12	Complete with 350mA driver
68050/W/W	White	Warm white	3000K	6x1W	420lm	100-240V		220x90mm	100mm	8	Complete with 350mA driver
68050/AN/W	Anthracite	Warm white	3000K	6x1W	420lm	100-240V		220x90mm	100mm	8	Complete with 350mA driver
68050/G/W	Grey	Warm white	3000K	6x1W	420lm	100-240V		220x90mm	100mm	8	Complete with 350mA driver



68004A/W/W

68004B/W/W

68070A/B/W

Indoor Decorative Wall Recessed



A-A++ 68070A/W/W

68070A | 1W | LED | Die cast

Driver can not pass through the cutout hole.

new · LED BUILT IN · 80 CRI · DIMMABLE · QUICK FIX · DARK LIGHT · IP20 · CE · 2 YEAR



68070A/B/W



68070A/AL/W





A-A++ 68004B/W/W

68004B | 1W | LED | Die cast

Driver can not pass through the cutout hole.

new · LED BUILT IN · 80 CRI · DIMMABLE · QUICK FIX · DARK LIGHT · IP20 · CE · 2 YEAR



68004B/B/W



68004B/AL/W



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class					Notes
68070A/W/W	White	Warm white	3000K	1W	60lm	350mA	III	40cm	20mm	45mm	100	Requires 350mA driver
68070A/B/W	Black	Warm white	3000K	1W	60lm	350mA	III	40cm	20mm	45mm	100	Requires 350mA driver
68070A/AL/W	Aluminium	Warm white	3000K	1W	60lm	350mA	III	40cm	20mm	45mm	100	Requires 350mA driver
68004B/W/W	White	Warm white	3000K	1W	50lm	350mA	III	40cm	20mm	50mm	100	Requires 350mA driver
68004B/B/W	Black	Warm white	3000K	1W	50lm	350mA	III	40cm	20mm	50mm	100	Requires 350mA driver
68004B/AL/W	Aluminium	Warm white	3000K	1W	50lm	350mA	III	40cm	20mm	50mm	100	Requires 350mA driver



Indoor/Outdoor Decorative Wall Recessed

Aluminium



A-A++ 68070/W/W

68070 | 1W | COB LED | Aluminium

LED BUILT IN · 80 CRI · DIMMABLE · QUICK FIX · IP65 · IK08 · CE · 2 YEAR



68070/B/W



68070/AL/W





A-A++ 68004/W/W

68004 | 3W | COB LED | Aluminium

LED BUILT IN · 90 CRI · DIMMABLE · CE · DARK LIGHT · IP54 · 2 YEAR



68004/AL/W





A-A++ 68004A/W/W

68004A | 1W | COB LED | Aluminium

Supplied with box for concrete installation.

LED BUILT IN · 85 CRI · DIMMABLE · QUICK FIX · DARK LIGHT · IP54 · CE · 2 YEAR



68004A/AL/W



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Concrete installation		Gypsum installation			Notes
68070/W/W	White	Warm white	3000K	1W	50lm	36°	350mA		200cm	30mm	60mm	30mm	60mm	100	Requires 350mA driver
68070/B/W	Black	Warm white	3000K	1W	50lm	36°	350mA		200cm	30mm	60mm	30mm	60mm	100	Requires 350mA driver
68070/AL/W	Aluminium	Warm white	3000K	1W	50lm	36°	350mA		200cm	30mm	60mm	30mm	60mm	100	Requires 350mA driver
68004/W/W	White	Warm white	3000K	3W	120lm	24°	350mA		100cm	49mm	110mm	49mm	70mm	36	Requires 350mA driver
68004/AL/W	Aluminium	Warm white	3000K	3W	120lm	24°	350mA		100cm	49mm	110mm	49mm	70mm	36	Requires 350mA driver
68004A/W/W	White	Warm white	3000K	1W	40lm	60°	350mA		200cm	36mm	50mm	33mm	30mm	60	Requires 350mA driver
68004A/AL/W	Aluminium	Warm white	3000K	1W	40lm	60°	350mA		200cm	36mm	50mm	33mm	30mm	60	Requires 350mA driver



Indoor/Outdoor Dark Light Wall Recessed



A-A++ 68030/W/W

68030 | 3W | LED | Aluminium

LED BUILT IN

DARK LIGHT

IP54

2 YEAR



Supplied with box for concrete installation.





A-A++ 68030/B/W

68030 | 3W | LED | Aluminium

LED BUILT IN

DARK LIGHT

IP54

2 YEAR



Supplied with box for concrete installation.





A-A++ 68030/AL/W

68030 | 3W | LED | Natural aluminium

LED BUILT IN

DARK LIGHT

IP54

2 YEAR



Supplied with box for concrete installation.



Order Code	Colour	Light Colour	CCT (K)	Watts	Input	Class		Concrete installation	Gypsum installation		Notes
68030/W/W	White	Warm white	3000K	3W	100-240V		52mm	110mm	50mm	30	Complete with 700mA driver
68030/B/W	Black	Warm white	3000K	3W	100-240V		52mm	110mm	50mm	30	Complete with 700mA driver
68030/AL/W	Aluminium	Warm white	3000K	3W	100-240V		52mm	110mm	50mm	30	Complete with 700mA driver



68032/G/W



68032/AL/W



68030/AL/W

Indoor/Outdoor Dark Light Wall Recessed



A-A++ 68032/AL/W

68032 | 3W | LED | Die cast

new
DARK LIGHT
IP54

LED BUILT IN

2 YEAR



Supplied with box for concrete installation.





A-A++ 68032/G/W

68032 | 3W | LED | Die cast

DARK LIGHT
IP54

LED BUILT IN

2 YEAR



Supplied with box for concrete installation.





A-A++ 68032/AL/W

68032 | 3W | LED | Natural aluminium

DARK LIGHT
IP54

LED BUILT IN

2 YEAR



Supplied with box for concrete installation.



Order Code	Colour	Light Colour	CCT (K)	Watts	Input	Class		Concrete installation	Gypsum installation		Notes
68032/B/W	Black	Warm white	3000K	3W	100-240V	⧈	52mm	110mm	50mm	30	Complete with 700mA driver
68032/G/W	Grey	Warm white	3000K	3W	100-240V	⧈	52mm	110mm	50mm	30	Complete with 700mA driver
68032/AL/W	Aluminium	Warm white	3000K	3W	100-240V	⧈	52mm	110mm	50mm	30	Complete with 700mA driver



Dark Light Step Series

Aluminium



A-A++ 68074/B/W

68074 | 2W | COB LED | Aluminium

LED BUILT IN · 85 CRI · DIMMABLE · QUICK FIX · DARK LIGHT · IP65 · IK08 · CE · 2 YEAR



68074/W/W





A-A++ 68074A/B/W

68074A | 2W | COB LED | Aluminium

LED BUILT IN · 85 CRI · DIMMABLE · QUICK FIX · DARK LIGHT · IP65 · IK08 · CE · 2 YEAR



68074A/W/W





A-A++ 68074B/B/W

68074B | 2W | COB LED | Aluminium

LED BUILT IN · 85 CRI · DIMMABLE · QUICK FIX · DARK LIGHT · IP65 · IK08 · CE · 2 YEAR



68074B/W/W



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class					Notes
68074/W/W	White	Warm white	3000K	2W	100lm	700mA		200cm	35mm	55mm	100	Requires 700mA driver
68074/B/W	Black	Warm white	3000K	2W	100lm	700mA		200cm	35mm	55mm	100	Requires 700mA driver
68074A/W/W	White	Warm white	3000K	2W	100lm	700mA		200cm	35mm	55mm	100	Requires 700mA driver
68074A/B/W	Black	Warm white	3000K	2W	100lm	700mA		200cm	35mm	55mm	100	Requires 700mA driver
68074B/W/W	White	Warm white	3000K	2W	110lm	700mA		200cm	35mm	55mm	100	Requires 700mA driver
68074B/B/W	Black	Warm white	3000K	2W	110lm	700mA		200cm	35mm	55mm	100	Requires 700mA driver





A-A++ 68076/W/W

68076 | 4W | SMD LED | Glass + metal

Supplied with box for concrete installation.

new
DARK LIGHT
IP65

LED BUILT IN
80 CRI
CE
2 YEAR



68076/B/W









A-A++ 68076A/W/W

68076A | 5W | SMD LED | Glass + metal

Supplied with box for concrete installation.

new
DARK LIGHT
IP65

LED BUILT IN
80 CRI
CE
2 YEAR



68076A/B/W







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class	Concrete installation	Gypsum installation			Notes
68076/W/W	White	Warm white	3000K	4W	300lm	230V	☐	115x70mm	2x68mm	55mm	12	AC LED
68076/B/W	Black	Warm white	3000K	4W	300lm	230V	☐	115x70mm	2x68mm	55mm	12	AC LED
68076A/W/W	White	Warm white	3000K	5W	350lm	230V	☐	160x70mm	3x68mm	55mm	12	AC LED
68076A/B/W	Black	Warm white	3000K	5W	350lm	230V	☐	160x70mm	3x68mm	55mm	12	AC LED



Wall Recessed Pro Range

68058 | 3,7W | SMD LED | Stainless steel 316



A-A++

LED BUILT IN

80 CRI

IK09

CE

2 YEAR

IP65



Supplied with box
for concrete installation.



68060 | 6,7W | SMD LED | Die cast



A-A++

LED BUILT IN

80 CRI

IK10

CE

2 YEAR

DARK LIGHT

IP65



Supplied with box
for concrete installation.



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
68058/W	Stainless steel	Warm white	3000K	3,7W	46lm	120°	230V	⏚	50cm	180x58mm	97mm	12	Complete with driver
68060/W	Grey	Warm white	3000K	6,7W	56lm	120°	230V	⏚	50cm	240x70mm	88mm	8	Complete with driver



Wall Recessed Pro Range



68072A | 5W | SMD 2835 | Stainless steel 316 + tempered glass

LED BUILT IN · 80 CRI · IK08 · CE · 2 YEAR · IP65



Supplied with box for concrete installation.





68072B | 7W | SMD 2835 | Stainless steel 316 + tempered glass

LED BUILT IN · 80 CRI · IK08 · CE · 2 YEAR · IP65



Supplied with box for concrete installation.





68072C | 10W | SMD 2835 | Stainless steel 316 + tempered glass

LED BUILT IN · 80 CRI · IK08 · CE · 2 YEAR · IP65



Supplied with box for concrete installation.



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class	Concrete installation	Gypsum installation			Notes
68072A/W	Stainless steel	Warm white	3000K	5W	100lm	230V		112x42mm	98x35mm	75mm	24	Complete with 350mA driver
68072B/W	Stainless steel	Warm white	3000K	7W	140lm	230V		182x55mm	164x45mm	75mm	12	Complete with 350mA driver
68072C/W	Stainless steel	Warm white	3000K	10W	200lm	230V		253x55mm	240x45mm	75mm	12	Complete with 350mA driver



Outdoor Dark Light Wall Recessed

Die cast



A-A++ 68068/W/W

68068 | 3W | SMD 2835 | Die cast

Supplied with box for concrete installation.

LED BUILT IN · 80 CRI · CE · 2 YEAR · DARK LIGHT · IP65



68068/AN/W



68068/G/W





A-A++ 68068A/W/W

68068A | 3W | SMD 2835 | Die cast

Supplied with box for concrete installation.

LED BUILT IN · 80 CRI · CE · 2 YEAR · DARK LIGHT · IP65



68068A/AN/W



68068A/B/W



68068A/G/W





A-A++ 68068C/W/W

68068C | 6W | SMD 2835 | Die cast

Supplied with box for concrete installation.

LED BUILT IN · 80 CRI · CE · 2 YEAR · DARK LIGHT · IP65



68068C/AN/W



68068C/B/W



68068C/G/W



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class	Concrete installation	Gypsum installation			Notes
68068/W/W	White	Warm white	3000K	3W	300lm	100-240V		110mm	100mm	60mm	24	Complete with 350mA driver
68068/AN/W	Anthracite	Warm white	3000K	3W	300lm	100-240V		110mm	100mm	60mm	24	Complete with 350mA driver
68068/G/W	Grey	Warm white	3000K	3W	300lm	100-240V		110mm	100mm	60mm	24	Complete with 350mA driver
68068A/W/W	White	Warm white	3000K	3W	300lm	100-240V		110x110mm	100mm	60mm	24	Complete with 350mA driver
68068A/AN/W	Anthracite	Warm white	3000K	3W	300lm	100-240V		110x110mm	100mm	60mm	24	Complete with 350mA driver
68068A/B/W	Black	Warm white	3000K	3W	300lm	100-240V		110x110mm	100mm	60mm	24	Complete with 350mA driver
68068A/G/W	Grey	Warm white	3000K	3W	300lm	100-240V		110x110mm	100mm	60mm	24	Complete with 350mA driver
68068C/W/W	White	Warm white	3000K	6W	550lm	100-240V		220x70mm	210x60mm	80mm	12	Complete with 350mA driver
68068C/AN/W	Anthracite	Warm white	3000K	6W	550lm	100-240V		220x70mm	210x60mm	80mm	12	Complete with 350mA driver
68068C/B/W	Black	Warm white	3000K	6W	550lm	100-240V		220x70mm	210x60mm	80mm	12	Complete with 350mA driver
68068C/G/W	Grey	Warm white	3000K	6W	550lm	100-240V		220x70mm	210x60mm	80mm	12	Complete with 350mA driver


68066/AN/W


68064/G/W


68062/G/W

Outdoor Dark Light Wall Recessed

Die cast


A-A++ 68062/W/W

68062 | 3,6W | LED | Die cast

Supplied with box for concrete installation.

LED BUILT IN · 80 CRI · CE · 2 YEAR · DARK LIGHT · IP65


68062/AN/W


68062/G/W






A-A++ 68064/W/W

68064 | 3,6W | LED | Die cast

Supplied with box for concrete installation.

LED BUILT IN · 80 CRI · CE · 2 YEAR · DARK LIGHT · IP65


68064/AN/W


68064/G/W






A-A++ 68066/W/W

68066 | 8,5W | SMD LED | Die cast

Supplied with box for concrete installation.

LED BUILT IN · 80 CRI · CE · 2 YEAR · DARK LIGHT · IP65


68066/AN/W


68066/G/W





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class	Concrete installation	Gypsum installation			Notes
68062/W/W	White	Warm white	3000K	3,6W	100lm	53°	100-240V		62x97mm	60x95mm	65mm	24	Complete with 350mA driver
68062/AN/W	Anthracite	Warm white	3000K	3,6W	100lm	53°	100-240V		62x97mm	60x95mm	65mm	24	Complete with 350mA driver
68062/G/W	Grey	Warm white	3000K	3,6W	100lm	53°	100-240V		62x97mm	60x95mm	65mm	24	Complete with 350mA driver
68064/W/W	White	Warm white	3000K	3,6W	85lm	44°	100-240V		97x62mm	95x60mm	65mm	24	Complete with 350mA driver
68064/AN/W	Anthracite	Warm white	3000K	3,6W	85lm	44°	100-240V		97x62mm	95x60mm	65mm	24	Complete with 350mA driver
68064/G/W	Grey	Warm white	3000K	3,6W	85lm	44°	100-240V		97x62mm	95x60mm	65mm	24	Complete with 350mA driver
68066/W/W	White	Warm white	3000K	8,5W	160lm	44°	100-240V		238x74mm	238x74mm	80mm	12	Complete with 500mA driver
68066/AN/W	Anthracite	Warm white	3000K	8,5W	160lm	44°	100-240V		238x74mm	238x74mm	80mm	12	Complete with 500mA driver
68066/G/W	Grey	Warm white	3000K	8,5W	160lm	44°	100-240V		238x74mm	238x74mm	80mm	12	Complete with 500mA driver



Outdoor Dark Light Wall Recessed

Die cast



A-A++

68022 | 1,4W | LED | Die cast

LED BUILT IN

DARK LIGHT

IP54

2 YEAR



Supplied with box for concrete installation & kit for gypsum installation.





A-A++

68024 | 1,4W | LED | Die cast

LED BUILT IN

DARK LIGHT

IP54

2 YEAR



Supplied with box for concrete installation & kit for gypsum installation.





A-A++

68012 | 1,5W | LED | Die cast

LED BUILT IN

DARK LIGHT

IP54

2 YEAR



Supplied with box for concrete installation & kit for gypsum installation.





A-A++

68016 | 2W | LED | Die cast

LED BUILT IN

DARK LIGHT

IP54

2 YEAR



Supplied with box for concrete installation & kit for gypsum installation.



Order Code	Colour	Light Colour	CCT (K)	Watts	Input	Class				Notes
68022/G/W	Grey	Warm white	3000K	1,4W	230V	☐	105mm	70mm	24	AC LED
68024/G/W	Grey	Warm white	3000K	1,4W	230V	☐	105mm	70mm	24	AC LED
68012/B/W	Black	Warm white	3000K	1,5W	230V	☐	80x120mm	90mm	24	AC LED
68012/G/D	Grey	Daylight	6000K	1,5W	230V	☐	80x120mm	90mm	24	AC LED
68012/G/W	Grey	Warm white	3000K	1,5W	230V	☐	80x120mm	90mm	24	AC LED
68016/B/W	Black	Warm white	3000K	2W	230V	☐	170x120mm	90mm	18	AC LED
68016/G/W	Grey	Warm white	3000K	2W	230V	☐	170x120mm	90mm	18	AC LED

Wall Recessed Light Line

Die cast





A-A++

68044 | 3W | LED | Die cast

LED BUILT IN

DARK LIGHT

IP65

2 YEAR



Supplied with box for concrete installation.





Order Code	Colour	Light Colour	CCT (K)	Watts	Input	Class				Notes
68044/W/W	White	Warm white	3000K	3W	100-240V		40x185mm	80mm	18	Complete with 700mA driver



69042M | 1W/2W | LED | Aluminium | 1W@350mA / 2W@700mA









69042 | 1W | SMD LED | Natural aluminium

Supplied with box for concrete installation.









Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class	S	Gypsum/Decking	Concrete	Decking	Concrete		Notes
69042M/AL/W	Aluminium	Warm white	3000K	1W/2W	150lm	24°	350mA/700mA	III	200cm	22mm	26mm	60mm	95+300mm drainage	50	Requires 350mA/700mA driver
69042/AL/W	Aluminium	Warm white	3000K	1W	80lm	-	350mA	III	200cm	30mm	35mm	80mm	95+300mm drainage	50	Requires 350mA driver



The Inground Mini Series

Natural aluminium



69042A | 1W | SMD LED | Natural aluminium

Supplied with box for concrete installation.

LED BUILT IN · 85 CRI · DIMMABLE · CE · 2 YEAR · IP67







69042B | 1W | SMD LED | Natural aluminium

Supplied with box for concrete installation.

LED BUILT IN · 85 CRI · DIMMABLE · CE · 2 YEAR · IP67







69044 | 1W | LED | Natural aluminium

Supplied with box for concrete installation.

LED BUILT IN · 85 CRI · DIMMABLE · CE · 2 YEAR · IP67





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Decking	Concrete	Decking	Concrete		Notes
69042A/AL/W	Aluminium	Warm white	3000K	1W	30lm	350mA		200cm	30mm	35mm	80mm	95mm+300mm drainage	50	Requires 350mA driver
69042B/AL/W	Aluminium	Warm white	3000K	1W	50lm	350mA		200cm	30mm	35mm	80mm	95mm+300mm drainage	50	Requires 350mA driver
69044/AL/W	Aluminium	Warm white	3000K	1W	30lm	350mA		200cm	30mm	35mm	80mm	95mm+300mm drainage	50	Requires 350mA driver



Outdoor Wall Recessed

Stainless steel / Brass



68001 | 1,6W | LED | Stainless steel

LED BUILT IN

2 YEAR

IP54



Supplied with box for concrete installation & kit for gypsum installation.





68002 | 1,2W | LED | Brass

LED BUILT IN

2 YEAR

IP54



Supplied with box for concrete installation & kit for gypsum installation.





68003 | 1,6W | LED | Stainless steel

LED BUILT IN

2 YEAR

IP54



Supplied with box for concrete installation & kit for gypsum installation.



Order Code	Colour	Light Colour	CCT (K)	Watts	Input	Class	Concrete installation	Gypsum installation			Notes
68001/W	Stainless steel	Warm white	3000K	1,6W	230V		97x97mm	90x90mm	65mm	18	Complete with driver
68002/BS/W	Brass	Warm white	3000K	1,2W	230V		105x35mm	100x35mm	65mm	40	Complete with driver
68003/D	Stainless steel	Daylight	6000K	1,6W	230V		158x55mm	160x55mm	70mm	18	Complete with driver



Outdoor Wall Colours Recessed

Stainless steel



68001/BL

68001 | 1,6W | LED | Stainless steel

LED BUILT IN

IP54

2 YEAR

offer



Supplied with box for concrete installation & kit for gypsum installation.





68001/R

68001 | 1,6W | LED | Stainless steel

LED BUILT IN

IP54

2 YEAR

offer



Supplied with box for concrete installation & kit for gypsum installation.





68002/R

68002 | 1,2W | LED | Stainless steel

LED BUILT IN

IP54

2 YEAR

offer



Supplied with box for concrete installation & kit for gypsum installation.



Order Code	Colour	Light Colour	Watts	Input	Class	Concrete installation	Gypsum installation			Notes
68001/BL	Stainless steel	Blue	1,6W	230V		97x97mm	90x90mm	65mm	18	Complete with driver
68001/R	Stainless steel	Red	1,6W	230V		97x97mm	90x90mm	65mm	18	Complete with driver
68002/R	Stainless steel	Red	1,2W	230V		105x35mm	100x35mm	65mm	40	Complete with driver



The Inground Medium Series GU10



69016G | 10W | MR16 | GU10 | Aluminium

IK10 · CE · 2 YEAR · IP67







69016AG | 10W | MR16 | GU10 | Aluminium

IK10 · CE · 2 YEAR · IP67







69016BG | 10W | MR16 | GU10 | Aluminium

IK10 · CE · 2 YEAR · IP67





Order Code	Colour	Watts	Input	Class					Notes
69016G	Aluminium	10W	100-240V	⏚	200cm	80mm	130mm+300mm drainage	18	1 gland
69016AG	Aluminium	10W	100-240V	⏚	200cm	80mm	130mm+300mm drainage	18	1 gland
69016BG	Aluminium	10W	100-240V	⏚	200cm	80mm	130mm+300mm drainage	18	1 gland



The Inground Medium Series 3W

Aluminium



69016 | 3W | LED | Aluminium

LED BUILT IN

80 CRI

2 YEAR

IP67







69016A | 3W | LED | Aluminium

LED BUILT IN

80 CRI

2 YEAR

IP67







69016B | 3W | LED | Aluminium

LED BUILT IN

80 CRI

2 YEAR

IP67





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class					Notes
69016/W	Aluminium	Warm white	3000K	3W	120lm	100-240V		200cm	77mm	105mm+300mm drainage	18	Complete with 350mA driver
69016A/W	Aluminium	Warm white	3000K	3W	150lm	100-240V		200cm	77mm	105mm+300mm drainage	18	Complete with 350mA driver
69016B/W	Aluminium	Warm white	3000K	3W	100lm	100-240V		200cm	77mm	105mm+300mm drainage	18	Complete with 350mA driver



The COB Inground Range

2-6W



69028 | 2W | LED | Stainless steel 316

LED BUILT IN
80 CRI
IK08
CE
2 YEAR
IP67







69012 | 3W | COB LED | Stainless steel 316

LED BUILT IN
80 CRI
IK08
CE
2 YEAR
IP67





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
69028/W	Stainless steel	Warm white	3000K	2W	65lm	30°	230V	⏚	50cm	86mm	100mm+300mm drainage	24	Complete with 600mA driver
69012/W	Stainless steel	Warm white	3000K	3W	240lm	35°	100-240V	⏚	200cm	65mm	120mm+300mm drainage	20	Complete with 350mA driver



69052/W

69052A/W

The COB Honeycomb Range



A-A++

69052 | 3W | COB LED | Stainless steel 316 + tempered glass

LED BUILT IN

80 CRI

DIMMABLE

IK08

IP67

2 YEAR



1 gland + Removable honeycomb.





A-A++

69052A | 13W | COB LED | Aluminium

LED BUILT IN

90 CRI

DIMMABLE

IK08

IP67

2 YEAR



1 gland + Removable honeycomb.



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
69052/W	Stainless steel	Warm white	3000K	3W	240lm	36°	24V DC	III	200cm	52mm	100mm+300mm drainage	50	Requires 24V DC driver
69052A/W	Aluminium	Warm white	3000K	13W	1000lm	36°	350mA	III	200cm	75mm	140mm+300mm drainage	24	Requires 350mA driver



The COB Inground Range

10-35W



A-A++

69040 | 10W | COB LED | Stainless steel 316

IP67

LED BUILT IN · 80 CRI · IK10 · CE · 2 YEAR







A-A++

69050 | 20W | COB LED | Stainless steel 316 + tempered glass

Removable honeycomb / TRIAC Dimmable.

IP67

LED BUILT IN · 80 CRI · TRIAC DIMMABLE · IK10 · CE · 2 YEAR



1 gland + honeycomb ring





A-A++

69050A | 20W | COB LED | Stainless steel 316 + tempered glass

Removable honeycomb / TRIAC Dimmable.

IP67

LED BUILT IN · 80 CRI · TRIAC DIMMABLE · IK10 · CE · 2 YEAR



1 gland + honeycomb ring





A-A++

69026 | 35W | COB LED | Stainless steel 316

IP67

LED BUILT IN · 80 CRI · IK09 · CE · 2 YEAR





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
69040/W	Stainless steel	Warm white	3000K	10W	700lm	40°	230V		50cm	106mm	185mm+300mm drainage	6	Complete with 250mA driver
69050/W	Stainless steel	Warm white	3000K	20W	1800lm	25°	230V		200cm	132mm	200mm+300mm drainage	6	AC LED
69050A/W	Stainless steel	Warm white	3000K	20W	1800lm	25°	230V		200cm	132mm	200mm+300mm drainage	6	AC LED
69026/C	Stainless steel	Cool white	4000K	35W	2800lm	40°	100-240V		50cm	220mm	255mm+300mm drainage	4	Complete with 1000mA driver



The COB Inground Adjustable Range



69054 | 15W | COB LED | Stainless steel 316 + tempered glass

TRIAC Dimmable.

LED BUILT IN · 80 CRI · ±15° ADJUSTABLE · TRIAC DIMMABLE · IP67 · IK10 · CE · 2 YEAR



1 gland + connection box.





69054A | 30W | COB LED | Stainless steel 316 + tempered glass

TRIAC Dimmable.

LED BUILT IN · 80 CRI · ±15° ADJUSTABLE · TRIAC DIMMABLE · IP67 · IK10 · CE · 2 YEAR



1 gland + connection box.



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class					Notes
69054/W	Stainless steel	Warm white	3000K	15W	840lm	20°	230V		200cm	230mm	270mm+300mm drainage	2	AC LED
69054A/W	Stainless steel	Warm white	3000K	30W	2000lm	20°	230V		200cm	330mm	330mm+300mm drainage	1	AC LED



The GU10 Inground Range

Stainless steel



69006G | 35W | MR16 | GU10 | Stainless steel 316

2 YEAR

IP67







69008G | 35W | MR16 | GU10 | Stainless steel 316

2 YEAR

IP67





Order Code	Colour	Watts	Input	Class				Notes
69006G	Stainless steel	35W	100-240V	⏚	101mm	160mm+300mm drainage	20	2 glands
69008G	Stainless steel	35W	100-240V	⏚	101mm	160mm+300mm drainage	20	2 glands



The GU10 Inground Adjustable Range

Stainless steel 316



69046G | 10W | MR16 | GU10 | Stainless steel 316 — Removable light guide.

ADJUSTABLE

2 YEAR

IP67







69048G | 10W | MR16 | GU10 | Stainless steel 316 — Removable light guide.

ADJUSTABLE

2 YEAR

IP67





Order Code	Colour	Watts	Input	Class					Notes
69046G	Stainless steel	10W	100-240V	⏚	200cm	115mm	160mm+300mm drainage	12	2 glands
69048G	Stainless steel	10W	100-240V	⏚	200cm	115mm	160mm+300mm drainage	12	2 glands



The GX53 Inground Range

Stainless steel



69006 | 9W | GX53 | Stainless steel

2 YEAR

IP67



Suitable for GX53 LED lamp.





69008 | 9W | GX53 | Stainless steel

2 YEAR

IP67



Suitable for GX53 LED lamp.



Order Code	Colour	Watts	Input	Class				Notes
69006	Stainless steel	9W	100-240V	⏚	110mm	90mm+300mm drainage	20	-
69008	Stainless steel	9W	100-240V	⏚	110mm	90mm+300mm drainage	20	-



Inground Decking Sets



69003 | 3x0,6W | LED | Natural aluminium



Set of 3pcs with connection box, outdoor transformer and boxes for concrete installation.





69002 | 10x0,2W | LED | Stainless steel 304



Set of 10pcs with independent plug + 1m cable.





69002/RGB | 10x0,2W | LED | Stainless steel 304



Set of 10pcs with independent plug + 1m cable, RGB remote, receiver + IR sensor with 3m cable.



Order Code	Colour	Light Colour	CCT (K)	Watts	Input	Class					Notes
69003/W	Aluminium	Warm white	3000K	3x0,6W	230V		2m/2m	33mm	80mm	8	-
69003/GR	Aluminium	Green	-	3x0,6W	230V		2m/2m	33mm	80mm	8	-
69002/BL	Stainless steel	Blue	-	10x0,2W	100-240V		900cm	26mm	50mm	12	Complete with driver
69002/RGB	Stainless steel	RGB	-	10x0,2W	100-240V		900cm	26mm	50mm	12	Complete with driver


one



20

Garden & Underwater

Pages 547-574

MR16 | GU10 | E27 | LED | COB LED

Die cast | Natural aluminium | Stainless steel | Acrylic | Metal | Teak

IP43 IP44 IP54 IP65 IP68





LED Garden Spots



7070/W

7070 | 5W | SMD 2835 | Plastic

Supplied with spike & base.

new

IP65

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · 2 YEAR



7070/C







7068 | 6W | COB LED | Die cast

IP65

LED BUILT IN · 80 CRI · ADJUSTABLE · CE · 2 YEAR



Supplied with spike.







67456 | 3W | COB LED | Aluminium

Supplied with spike.

IP67

LED BUILT IN · 90 CRI · ADJUSTABLE · DIMMABLE · CE · 3 YEAR









67458 | 8W | SMD 2835 | Aluminium

Supplied with spike.

IP65

LED BUILT IN · 80 CRI · ADJUSTABLE · DIMMABLE · CE · 2 YEAR







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class	S		Notes
7070/C	Black	Cool white	4000K	5W	400lm	38°	100-240V		200cm	40	Complete with driver
7070/W	Black	Warm white	3000K	5W	400lm	38°	100-240V		200cm	40	Complete with driver
7068/B/W	Black	Warm white	3000K	6W	380lm	40°	230V		200cm	30	Complete with driver
67456/B/W	Black	Warm white	3000K	3W	170lm	36°	350mA		200cm	36	Requires 350mA driver
67458/B/W	Black	Warm white	3000K	8W	520lm	38°	24V DC		200cm	50	Requires 24V DC driver



GU10 Garden Spots



67198G | 35W | MR16 | GU10 | Aluminium

ADJUSTABLE · 2 YEAR · IP65



Supplied with spike.





67198AG | 35W | MR16 | GU10 | Aluminium

ADJUSTABLE · 2 YEAR · IP65



Supplied with spike
& 400mm pole stand.





67464G | 10W | MR16 | GU10 | Aluminium

new · ADJUSTABLE · 3 YEAR · IP65



Supplied with spike.



Order Code	Colour	Watts	Input	Class			Notes
67198G/AN	Anthracite	35W	100-240V		150cm	12	-
67198G/B	Black	35W	100-240V		150cm	12	-
67198AG/AN	Anthracite	35W	100-240V		150cm	6	-
67464G/B	Black	10W	100-240V		200cm	12	-



The 10W COB Garden Spots

Aluminium



A-A++ 7046/W/W

7046 | 10W | COB LED | Aluminium

LED BUILT IN · 80 CRI · ADJUSTABLE · IP65 · CE · 2 YEAR



Supplied with spike.







A-A++ 7046/AN/W

7046 | 10W | COB LED | Aluminium

LED BUILT IN · 80 CRI · ADJUSTABLE · IP65 · CE · 2 YEAR



Supplied with spike.







A-A++ 7046/AL/W

7046 | 10W | COB LED | Aluminium

LED BUILT IN · 80 CRI · ADJUSTABLE · IP65 · CE · 2 YEAR



Supplied with spike.





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class			Notes
7046/W/W	White	Warm white	3000K	10W	850lm	50°	230V		150cm	12	Complete with 200mA driver
7046/AN/W	Anthracite	Warm white	3000K	10W	850lm	50°	230V		150cm	12	Complete with 200mA driver
7046/AL/W	Aluminium	Warm white	3000K	10W	850lm	50°	230V		150cm	12	Complete with 200mA driver



The 20W COB Garden Spots

Aluminium



A-A++ 7047/W/W

7047 | 20W | COB LED | Aluminium

LED BUILT IN · 80 CRI · ADJUSTABLE · IP65 · CE · 2 YEAR



Supplied with spike.





A-A++ 7047/AN/W

7047 | 20W | COB LED | Aluminium

LED BUILT IN · 80 CRI · ADJUSTABLE · IP65 · CE · 2 YEAR



Supplied with spike.





A-A++ 7047/AL/W

7047 | 20W | COB LED | Aluminium

LED BUILT IN · 80 CRI · ADJUSTABLE · IP65 · CE · 2 YEAR



Supplied with spike.



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class			Notes
7047/W/W	White	Warm white	3000K	20W	1800lm	50°	230V	⏚	150cm	8	Complete with 500mA driver
7047/AN/W	Anthracite	Warm white	3000K	20W	1800lm	50°	230V	⏚	150cm	8	Complete with 500mA driver
7047/AL/W	Aluminium	Warm white	3000K	20W	1800lm	50°	230V	⏚	150cm	8	Complete with 500mA driver



67196C/AN/W



67196BG/G



67196BG/W

The GU10 Garden Round Spots

Die cast



E-A++ 67196BG/W

67196BG | 35W | MR16 | GU10 | Die cast

ADJUSTABLE · CE · 2 YEAR · IP65



Supplied with spike.





E-A++ 67196BG/AN

67196BG | 35W | MR16 | GU10 | Die cast

ADJUSTABLE · CE · 2 YEAR · IP65



Supplied with spike.





E-A++ 67196BG/G

67196BG | 35W | MR16 | GU10 | Die cast

ADJUSTABLE · CE · 2 YEAR · IP65



Supplied with spike.



Order Code	Colour	Watts	Input	Class			Notes
67196BG/W	White	35W	100-240V		150cm	6	-
67196BG/AN	Anthracite	35W	100-240V		150cm	6	-
67196BG/G	Grey	35W	100-240V		150cm	6	-



The Garden Round Spots

Die cast



67196A | 3W | COB LED | Die cast



Supplied with spike.







67196B | 6W | COB LED | Die cast



Supplied with spike.







67196C | 9W | COB LED | Die cast



Supplied with spike.





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class			Notes
67196A/AN/W	Anthracite	Warm white	3000K	3W	240lm	35°	100-240V		150cm	12	Complete with 350mA driver
67196B/AN/W	Anthracite	Warm white	3000K	6W	450lm	35°	230V		150cm	6	Complete with 500mA driver
67196C/AN/W	Anthracite	Warm white	3000K	9W	700lm	35°	230V		150cm	6	Complete with 250mA driver



Garden Spots

Stainless steel



7008L | 3x1W | LED | Stainless steel 304

LED BUILT IN · ADJUSTABLE · CE · 2 YEAR · IP65



Supplied with base & spike.





7008A | 35W | MR16 | GU10 | Stainless steel 316

ADJUSTABLE · CE · 2 YEAR · IP65



Supplied with base & spike.





7010 | 80W | PAR38 | E27 | Stainless steel 304

ADJUSTABLE · CE · 2 YEAR · IP65



Supplied with base & spike.





7010A | 80W | PAR38 | E27 | Stainless steel 316

ADJUSTABLE · CE · 2 YEAR · IP65



Supplied with base & spike.



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class			Notes
7008L/W	Stainless steel	Warm white	3000K	3x1W	245lm	230V	⏚	100cm	18	Complete with driver
7008A	Stainless steel	-	-	35W	-	100-240V	⏚	200cm	20	-
7010	Stainless steel	-	-	80W	-	100-240V	⏚	200cm	8	-
7010A	Stainless steel	-	-	80W	-	100-240V	⏚	200cm	8	-





7052B | 1W | COB LED | Die cast

new
IP65
LED BUILT IN
80 CRI
ADJUSTABLE
CE
2 YEAR



Optional spike.
Order code 7010P.







67432 | 10W | MR16 | GU10 | Aluminium

ADJUSTABLE
CE
2 YEAR
IP65



Supplied with spike.







7052 | 7W | COB LED | Die cast

LED BUILT IN
80 CRI
ADJUSTABLE
IP65
CE
2 YEAR



Supplied with spike.





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class			Notes
7052B/AN/W	Anthracite	Warm white	3000K	1W	80lm	40°	24V DC	◇	100cm	36	Requires 24V DC driver
67432/B	Black	-	-	10W	-	-	100-240V	⏚	-	2	-
7052/AN/W	Anthracite	Warm white	3000K	7W	550lm	47°	100-240V	⏚	100cm	12	Complete with driver

Solar Path Light





A-A++

67428 | 2,2W | LED | Solar powered | Sensor | Die cast

LED BUILT IN

80 CRI

IP54

2 YEAR



Supplied with spike.



LED 100% when movement detected.
LED 15% when no movement detected.

PIR Sensor: Distance up to 6m and within angle 120°
Charging time: 6-8Hrs (solar)
Working time: 2,5-3Hrs in 100% LED brightness
20-25Hrs in 15% LED brightness

Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)		Notes
67428/AN/W	Anthracite	Warm white	3000K	2,2W	200lm	4	1x2200mAh lithium battery



67462/B/W



67428/AN/W

Rechargeable Path Light



67462 | 3W | LED | Rechargeable | Die cast

EU charger included.







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Class		Notes
67462/B/W	Black	Warm white	3000K	3W	190lm		4	2x2200mAh lithium battery



The E27 Tube Lights

Die cast



67094 | 20W | E27 | Die cast

IP54











67098 | 2x20W | E27 | Die cast

IP54







Order Code	Colour	Watts	Input	Class		Notes
67094/AN	Anthracite	20W	100-240V		12	-
67094/B	Black	20W	100-240V		12	-
67094/G	Grey	20W	100-240V		12	-
67094/BR	Rust brown	20W	100-240V		12	-
67098/AN	Anthracite	2x20W	100-240V		12	-
67098/G	Grey	2x20W	100-240V		12	-
67098/BR	Rust brown	2x20W	100-240V		12	-

The E27 Tube Lights

Die cast



67090 | 15W | E27 | Die cast

IP54







67092 | 15W | E27 | Die cast

IP54







67100/B

67100 | 20W | E27 | Die cast

IP54



67100/AN



67100/G



67100/BR





67102/B

67102 | 20W | E27 | Die cast

IP54



67102/AN



67102/G



67102/BR



Order Code	Colour	Watts	Input	Class		Notes
67090/G	Grey	15W	100-240V		12	-
67092/G	Grey	15W	100-240V		6	-
67100/AN	Anthracite	20W	100-240V		4	-
67100/B	Black	20W	100-240V		4	-
67100/G	Grey	20W	100-240V		4	-
67100/BR	Rust brown	20W	100-240V		4	-
67102/AN	Anthracite	20W	100-240V		4	-
67102/B	Black	20W	100-240V		4	-
67102/G	Grey	20W	100-240V		4	-
67102/BR	Rust brown	20W	100-240V		4	-



67180/G

67182/G

67182/AN

The Mushroom Range



B-A++

67180 | 15W | E27 | Die cast + plastic

IP44



Suitable for E27 LED lamp.







B-A++ 67182/AN

67182 | 15W | E27 | Die cast + plastic

IP44



Suitable for E27 LED lamp.







B-A++ 67182/G

67182 | 15W | E27 | Die cast + plastic

IP44



Suitable for E27 LED lamp.





Order Code	Colour	Watts	Input	Class		Notes
67180/G	Grey	15W	100-240V		4	-
67182/AN	Anthracite	15W	100-240V		4	-
67182/G	Grey	15W	100-240V		4	-





67250 | 2x3W | LED | Die cast

DARK LIGHT
IP54
offer

LED BUILT IN

2 YEAR







67250A | 2x3W | LED | Natural aluminium

DARK LIGHT
IP54

LED BUILT IN

2 YEAR





Order Code	Colour	Light Colour	CCT (K)	Watts	Input	Class		Notes
67250/G/D	Grey	Daylight	6000K	2x3W	230V		8	Complete with driver
67250A/AL/W	Aluminium	Warm white	3000K	2x3W	230V		4	Complete with driver

The Natural Aluminium Bollards



67270 | 16W | E27 | Natural aluminium + acrylic

IP54



Suitable for E27 LED lamp.





67236 | 15W | E27 | Natural aluminium

IP54



Suitable for E27 LED lamp.





67236A | 15W | E27 | Natural aluminium

IP54



Suitable for E27 LED lamp.





67238 | 15W | E27 | Natural aluminium

IP54



Suitable for E27 LED lamp.





67238A | 15W | E27 | Natural aluminium

IP54



Suitable for E27 LED lamp.



Order Code	Colour	Watts	Input	Class		Notes
67270/AL	Aluminium	16W	100-240V		10	-
67236/AL	Aluminium	15W	100-240V		4	-
67236A/AL	Aluminium	15W	100-240V		4	-
67238/AL	Aluminium	15W	100-240V		10	-
67238A/AL	Aluminium	15W	100-240V		4	-



The 1W LED Bollards

Natural aluminium + acrylic



67234 | 1W | LED | Natural aluminium + acrylic

LED BUILT IN

2 YEAR

IP54







67234A | 1W | LED | Natural aluminium + acrylic

LED BUILT IN

2 YEAR

IP54





Order Code	Colour	Light Colour	CCT (K)	Watts	Input	Class		Notes
67234/AL/D	Aluminium	Daylight	6000K	1W	230V		10	Complete with driver
67234/AL/W	Aluminium	Warm white	3000K	1W	230V		10	Complete with driver
67234A/AL/W	Aluminium	Warm white	3000K	1W	230V		4	Complete with driver



LED Garden Path Lights

Die cast



67470 | 10W | LED | Die cast

new

IP65

LED BUILT IN

80 CRI

2 YEAR









67470A | 10W | LED | Die cast

new

IP65

LED BUILT IN

80 CRI

2 YEAR







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
67470/B/W	Black	Warm white	3000K	10W	500lm	100-240V	⏚	6	Complete with 260mA driver
67470A/B/W	Black	Warm white	3000K	10W	500lm	100-240V	⏚	6	Complete with 260mA driver



LED Garden Path Lights

Die cast



67460A | 8W | LED | Aluminium

1-side light.

LED BUILT IN

80 CRI

2 YEAR

new

IP54







67460B | 2x6W | LED | Aluminium

2-side light.

LED BUILT IN

80 CRI

2 YEAR

new

IP54





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
67460A/AN/W	Anthracite	Warm white	3000K	8W	640lm	100-240V	⏚	4	Complete with 350mA driver
67460B/AN/W	Anthracite	Warm white	3000K	2x6W	2x500lm	100-240V	⏚	4	Complete with 350mA driver

LED Path Light

Die cast



67358 | 7W | COB LED | Die cast

LED BUILT IN

80 CRI

2 YEAR

IP65







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
67358/AN/W	Anthracite	Warm white	3000K	7W	262lm	49°	100-240V		8	Complete with 700mA driver



The LED Bollards Range

Die cast



A-A++

67036 | 12W | COB LED | Die cast

LED BUILT IN

80 CRI

CE

2 YEAR

IP54









A-A++ 67034/G/W

67034 | 15W | COB LED | Die cast

LED BUILT IN

80 CRI

CE

2 YEAR

IP54



67034/AN/W





Order Code	Colour	Light Colour	CCT (K)	Watts	Beam Angle	Lumen (lm)	Input	Class		Notes
67036/G/W	Grey	Warm white	3000K	12W	50°	450lm	100-240V	⏚	4	Complete with driver
67034/AN/W	Anthracite	Warm white	3000K	15W	50°	450lm	100-240V	⏚	4	Complete with driver
67034/G/W	Grey	Warm white	3000K	15W	50°	450lm	100-240V	⏚	4	Complete with driver

The LED Bollards Range

Cone reflector





67410 | 12W | SMD 2835 | Die cast

LED BUILT IN

80 CRI

CE

3 YEAR

IP65





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
67410/AN/C	Anthracite	Cool white	4000K	12W	1000lm	230V		2	Complete with 250mA driver
67410/AN/W	Anthracite	Warm white	3000K	12W	1000lm	230V		2	Complete with 250mA driver

The LED Bollards Range

Cone reflector



67410A | 20W | SMD 2835 | Die cast

LED BUILT IN

80 CRI

3 YEAR

IP65





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
67410A/AN/C	Anthracite	Cool white	4000K	20W	1600lm	230V	⏚	2	Complete with 250mA driver
67410A/AN/W	Anthracite	Warm white	3000K	20W	1600lm	230V	⏚	2	Complete with 250mA driver



The Teak Wood & Stainless Steel Range



67010W | 15W | E27 | Teak + stainless steel

IP44







67286 | 15W | E27 | Teak + stainless steel 316

IP44







67004 | 15W | E27 | Stainless steel 201

IP44

offer





Order Code	Colour	Watts	Input	Class		Notes
67010W	Teak + stainless steel	15W	100-240V		6	-
67286	Teak + stainless steel	15W	100-240V		4	-
67004	Stainless steel	15W	100-240V		12	-

Retro Wall Lantern





67408 | 40W | E27 | Metal + glass



Suitable for E27 LED lamp.



Order Code	Colour	Watts	Input	Class		Notes
67408/B	Black	40W	100-240V		4	-



The Romantic Outdoor Range



67406 | 40W | E27 | Stainless steel 201 + tempered glass

IP43







67406A | 40W | E27 | Stainless steel 201 + tempered glass

IP43







67406B | 2x40W | E27 | Stainless steel 201 + tempered glass

IP43







67406C | 40W | E27 | Stainless steel 201 + tempered glass

IP43





Order Code	Colour	Watts	Input	Class		Notes
67406/W	White	40W	100-240V		4	-
67406/B	Black	40W	100-240V		4	-
67406A/W	White	40W	100-240V		4	-
67406A/B	Black	40W	100-240V		4	-
67406B/B	Black	2x40W	100-240V		4	-
67406C/W	White	40W	100-240V		4	-
67406C/B	Black	40W	100-240V		4	-





E-A++ 67406D/B

67406D | 2x40W | E27 | Stainless steel 201 + tempered glass

IP43



67406D/W





E-A++ 67406E/B

67406E | 40W | E27 | Stainless steel 201 + tempered glass

IP43



67406E/W



Order Code	Colour	Watts	Input	Class		Notes
67406D/W	White	2x40W	100-240V		2	-
67406D/B	Black	2x40W	100-240V		2	-
67406E/W	White	40W	100-240V		4	-
67406E/B	Black	40W	100-240V		4	-





The LED Underwater Range

Stainless steel



69032 | 3W | LED | Stainless steel 316

Underwater only.

LED BUILT IN · 80 CRI · ADJUSTABLE · IP68 · IK06 · 1m max · CE · 3 YEAR









69036 | 12W | LED | Stainless steel 316

Underwater only.

LED BUILT IN · 80 CRI · ADJUSTABLE · IP68 · IK08 · 1m max · CE · 3 YEAR









69034 | 12W | LED | Stainless steel 316

Underwater only.

LED BUILT IN · 80 CRI · ADJUSTABLE · IP68 · IK08 · 1m max · CE · 3 YEAR







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class			Notes
69032/C	Stainless steel	Cool white	4000K	3W	150lm	30°	24V DC	III	300cm	8	Requires 24V DC driver
69036/C	Stainless steel	Cool white	4000K	12W	1100lm	25°	24V DC	III	300cm	4	Requires 24V DC driver
69034/C	Stainless steel	Cool white	4000K	12W	545lm	30°	24V DC	III	300cm	4	Requires 24V DC driver





21

Industrial & Floodlights

Pages 577-610

T8 | Rx7s | COB LED | SMD LED | LED

Die cast | Aluminium | Metal

IP20 IP44 IP65 IP67

ADJUSTABLE ADJUSTABLE IK06 IK08 70 CRI 75 CRI 80 CRI 2 YEAR 3 YEAR 5 YEAR





The T8 IP65 Fluo Range

PC + PC



38136P | 36W | T8 | PC + PC

IP65 | IK06 | 2 YEAR





38218P | 2x18W | T8 | PC + PC

IP65 | IK06 | 2 YEAR





38236P | 2x36W | T8 | PC + PC

IP65 | IK06 | 2 YEAR



Order Code	Colour	Watts	Input	Class		Notes
38136P	Grey	36W	230V		9	Complete with electronic ballast
38218P	Grey	2x18W	230V		9	Complete with electronic ballast
38236P	Grey	2x36W	230V		8	Complete with electronic ballast



The IP65 Range For T8 LED Tubes

PC + PC



38118E | T8 LED 60cm | PC + PC

38136E | T8 LED 120cm | PC + PC

38158E | T8 LED 150cm | PC + PC

IK06

5 YEAR

IP65







38218E | 2xT8 LED 60cm | PC + PC

38236E | 2xT8 LED 120cm | PC + PC

38258E | 2xT8 LED 150cm | PC + PC

IK06

5 YEAR

IP65





Order Code	Colour	Input	Class		Notes
38118E	Grey	100-240V		15	Only suitable for T8 LED tubes
38136E	Grey	100-240V		9	Only suitable for T8 LED tubes
38158E	Grey	100-240V		9	Only suitable for T8 LED tubes
38218E	Grey	100-240V		9	Only suitable for T8 LED tubes
38236E	Grey	100-240V		9	Only suitable for T8 LED tubes
38258E	Grey	100-240V		9	Only suitable for T8 LED tubes

The High Power IP65 LED Range

Single





38118L | 11,5W | SMD LED | PC + opal PC diffuser

LED BUILT IN | 80 CRI | IK06 | CE | IP65 | 3 YEAR







38118M | 15W | SMD 2835 | PC + opal PC diffuser

LED BUILT IN | 80 CRI | IK08 | CE | IP65 | 3 YEAR







38136M | 30W | SMD 2835 | PC + opal PC diffuser

LED BUILT IN | 80 CRI | IK08 | CE | IP65 | 3 YEAR







38158M | 40W | SMD 2835 | PC + opal PC diffuser

LED BUILT IN | 80 CRI | IK08 | CE | IP65 | 3 YEAR





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
38118L/C	Grey	Cool white	4000K	11,5W	950lm	230V		12	Complete with 450mA driver / Stainless steel clips
38118M/C	Grey	Cool white	4000K	15W	1200lm	230V		12	Complete with 400mA driver / Stainless steel clips
38136M/C	Grey	Cool white	4000K	30W	2400lm	230V		9	Complete with 500mA driver / Stainless steel clips
38158M/C	Grey	Cool white	4000K	40W	3200lm	230V		9	Complete with 700mA driver / Stainless steel clips



The High Power IP65 LED Range

Double



38236M | 60W | SMD 2835 | PC + opal PC diffuser

LED BUILT IN · 80 CRI · IK08 · CE · IP65 · 3 YEAR









38258M | 70W | SMD 2835 | PC + opal PC diffuser

LED BUILT IN · 80 CRI · IK08 · CE · IP65 · 3 YEAR







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class		Notes
38236M/C	Grey	Cool white	4000K	60W	4800lm	230V	⏚	6	Complete with 1050mA driver / Stainless steel clips
38258M/C	Grey	Cool white	4000K	70W	5600lm	230V	⏚	6	Complete with 1400mA driver / Stainless steel clips



The IP65 LED Connectable Range

Single



38118LC | 18W | SMD 2835 | Connectable | PC

Supermarket linear range.

LED BUILT IN · 80 CRI · IK08 · CE · IP65 · 2 YEAR



Optional suspension kit. Order code 050084.



Connect 20 fittings maximum.





38136LC | 36W | SMD 2835 | Connectable | PC

Supermarket linear range.

LED BUILT IN · 80 CRI · IK08 · CE · IP65 · 2 YEAR



Optional suspension kit. Order code 050084.



Connect 10 fittings maximum.





38145LC | 45W | SMD 2835 | Connectable | PC

Supermarket linear range.

new · LED BUILT IN · 80 CRI · IK08 · CE · IP65 · 2 YEAR



Optional suspension kit. Order code 050084.



Connect 10 fittings maximum.



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class			Notes
38118LC/C	White	Cool white	4000K	18W	1550lm	120°	100-240V	☐	50cm	20	Complete with driver
38118LC/W	White	Warm white	3000K	18W	1500lm	120°	100-240V	☐	50cm	20	Complete with driver
38136LC/C	White	Cool white	4000K	36W	3100lm	120°	100-240V	☐	50cm	20	Complete with driver
38136LC/W	White	Warm white	3000K	36W	3000lm	120°	100-240V	☐	50cm	20	Complete with driver
38145LC/C	White	Cool white	4000K	45W	4000lm	120°	100-240V	☐	50cm	20	Complete with driver



The IP65 LED Connectable Range

Double



38236LC | 36W | SMD 2835 | Connectable | PC

Supermarket linear range.

LED BUILT IN

80 CRI

IK08

CE

new

IP65

2 YEAR



Optional suspension kit. Order code 050084.



Connect 10 fittings maximum.





38245LC | 45W | SMD 2835 | Connectable | PC

Supermarket linear range.

LED BUILT IN

80 CRI

IK08

CE

new

IP65

2 YEAR



Optional suspension kit. Order code 050084.



Connect 10 fittings maximum.



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class			Notes
38236LC/D	White	Daylight	6000K	36W	3100lm	120°	100-240V	☐	50cm	10	Complete with driver
38236LC/C	White	Cool white	4000K	36W	3100lm	120°	100-240V	☐	50cm	10	Complete with driver
38245LC/D	White	Daylight	6000K	45W	4000lm	120°	100-240V	☐	50cm	10	Complete with driver
38245LC/C	White	Cool white	4000K	45W	4000lm	120°	100-240V	☐	50cm	10	Complete with driver





38118LA | 18W | SMD 2835 | PC

LED BUILT IN · 80 CRI · IK08 · CE · IP65 · 2 YEAR



Optional suspension kit. Order code 050084.



Complete with 2pcs fixing clips.





38136LA | 36W | SMD 2835 | PC

LED BUILT IN · 80 CRI · IK08 · CE · IP65 · 2 YEAR



Optional suspension kit. Order code 050084.



Complete with 3pcs fixing clips.





38145LA | 45W | SMD 2835 | PC

LED BUILT IN · 80 CRI · IK08 · CE · IP65 · 2 YEAR



Optional suspension kit. Order code 050084.



Complete with 4pcs fixing clips.



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class			Notes
38118LA/D	White	Daylight	6000K	18W	1600lm	120°	100-240V	☐	50cm	20	Complete with driver
38118LA/C	White	Cool white	4000K	18W	1600lm	120°	100-240V	☐	50cm	20	Complete with driver
38136LA/D	White	Daylight	6000K	36W	3200lm	120°	100-240V	☐	50cm	20	Complete with driver
38136LA/C	White	Cool white	4000K	36W	3200lm	120°	100-240V	☐	50cm	20	Complete with driver
38145LA/D	White	Daylight	6000K	45W	4100lm	120°	100-240V	☐	50cm	20	Complete with driver
38145LA/C	White	Cool white	4000K	45W	4100lm	120°	100-240V	☐	50cm	20	Complete with driver



The Supermarket LED Linear Range

Aluminium + PC



38136R | 22W | SMD LED | Single | Aluminium + PC

LED BUILT IN
80 CRI
2 YEAR
IP20







38236R | 43W | SMD LED | Double | Aluminium + PC

LED BUILT IN
80 CRI
2 YEAR
IP20





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class			Notes
38136R/C	Grey	Cool white	4000K	22W	1880lm	120°	100-240V		100cm	10	Complete with driver
38236R/C	Grey	Cool white	4000K	43W	3800lm	120°	100-240V		100cm	10	Complete with driver



The Batten For T8 LED



38120E | 1xT8 LED 60cm | Metal

5 YEAR

IP20







38140E | 1xT8 LED 120cm | Metal

5 YEAR

IP20







38165E | 1xT8 LED 150cm | Metal

5 YEAR

IP20





Order Code	Colour	Input	Class		Notes
38120E	White	100-240V	⏚	20	Only suitable for T8 LED tubes
38140E	White	100-240V	⏚	20	Only suitable for T8 LED tubes
38165E	White	100-240V	⏚	20	Only suitable for T8 LED tubes



The Batten For T8 LED



38220E | 2xT8 LED 60cm | Metal







38240E | 2xT8 LED 120cm | Metal







38265E | 2xT8 LED 150cm | Metal





Order Code	Colour	Input	Class		Notes
38220E	White	100-240V		20	Only suitable for T8 LED tubes
38240E	White	100-240V		20	Only suitable for T8 LED tubes
38265E	White	100-240V		20	Only suitable for T8 LED tubes





7056 | 50W | COB LED | Die cast

LED BUILT IN
70 CRI
CE
3 YEAR
IP65







7056A | 50W | SMD LED | Die cast

LED BUILT IN
80 CRI
CE
3 YEAR
IP65







7056B | 60W | COB LED | Die cast

LED BUILT IN
70 CRI
CE
3 YEAR
IP65





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
7056/C	Black	Cool white	4000K	50W	4000lm	120°	100-240V	⏚	4	Complete with driver
7056A/C	Black	Cool white	4000K	50W	4250lm	120°	230V	⏚	6	Complete with driver
7056B/C	Black	Cool white	4000K	2x30W	4800lm	120°	100-240V	⏚	1	Complete with driver

one

The Industrial IP65 LED High Bay

Waterproof



63200A | 200W | COB LED | High Bay | Die cast

LED BUILT IN

70 CRI

3 YEAR

IP65







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class			Notes
63200A/G/C	Grey	Cool white	4000K	200W	13037lm	90°	100-240V		300cm	1	Complete with driver

The Industrial LED High Bay

Aluminium



A-A++

IP20

63100E | 100W | SMD 3030 | High bay | Aluminium

LED BUILT IN

80 CRI

CE

5 YEAR







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
63100E/C	Black	Cool white	4000K	100W	10000lm	100°	100-240V	⏚	1	Complete with 2700mA driver



63150F/C



63100E/C

The Industrial IP65 LED UFO Range

Waterproof



A-A++

63100F | 100W | SMD 2835 | Die cast

LED BUILT IN · 80 CRI · CE · 5 YEAR · IP65



Optional reflector. Order code 050114FA.



Optional fixing kit. Order code 050116HA.



Optional microwave sensor. Order code 22002.





A-A++

63150F | 150W | SMD 2835 | Die cast

LED BUILT IN · 80 CRI · CE · 5 YEAR · IP65



Optional reflector. Order code 050114FB.



Optional fixing kit. Order code 050116HB.



Optional microwave sensor. Order code 22002.





A-A++

63200F | 200W | SMD 2835 | Die cast

LED BUILT IN · 80 CRI · CE · 5 YEAR · IP65



Optional reflector. Order code 050114FB.



Optional fixing kit. Order code 050116HB.



Optional microwave sensor. Order code 22002.





22002 | Microwave sensor | DIP switch settings

Sensitivity

	1	2	3
100%	●	●	●
75%	○	●	●
50%	●	○	●
25%	○	○	●
10%	○	○	○

ON Time

	4	5	6
5sec	●	●	●
30sec	○	●	●
90sec	●	○	●
3min	○	○	●
20min	●	●	○
30min	○	○	○

Daylight Sensor

	7	8	9
Disabled	●	●	●
200Lux	○	●	○
100Lux	●	○	○
50Lux	○	○	○

● ON
○ OFF

Suitable for

63100F
63150F
63200F

Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class			Notes
63100F/C	Black	Cool white	4000K	100W	10000lm	90°	230V		200cm	2	Complete with 2000mA driver
63150F/C	Black	Cool white	4000K	150W	15000lm	90°	230V		200cm	2	Complete with 2600mA driver
63200F/C	Black	Cool white	4000K	200W	20000lm	90°	230V		200cm	2	Complete with 4000mA driver

The Rx7s Floodlight



7020 | 150W | Rx7s 76mm | Die cast



IP54

offer



Suitable for 7605L LED lamp.



Order Code	Colour	Watts	Input	Class		Notes
7020/G/5	Grey	150W	230V	⏚	8	-



7022/G/D



7030/AN/C

The LED Floodlights



A-A++

7030 | 8x1W | LED | Die cast

IP54 offer

LED BUILT IN · ADJUSTABLE · CE · 2 YEAR









A-A++

7022 | 15x1W | LED | Die cast

IP65 offer

LED BUILT IN · ADJUSTABLE · CE · 2 YEAR







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class			Notes
7030/AN/C	Anthracite	Cool white	4000K	8x1W	600lm	20°	230V	⏚	-	12	Complete with driver
7022/G/D	Grey	Daylight	6000K	15x1W	1125lm	40°	100-240V	⏚	200cm	4	Complete with driver



The RGB & Rechargeable LED Floodlights

Die cast



A-A++

7028A/AN/RGB | 10W | COB LED | Die cast

LED BUILT IN · ADJUSTABLE · CE · IP65 · 2 YEAR



Supplied with remote control.







A-A++

7028B/AN/RGB | 30W | COB LED | Die cast

LED BUILT IN · ADJUSTABLE · CE · IP65 · 2 YEAR



Supplied with remote control.







A-A++

7028AR | 10W | COB LED | Rechargeable 5Hrs | 3Hrs operation

LED BUILT IN · 75 CRI · ADJUSTABLE · CE · IP65 · 2 YEAR



Supplied with AC charger 100-240V, EU/BS plug and car charger 12V.







A-A++

7028BR | 20W | COB LED | Rechargeable 5Hrs | 3Hrs operation

LED BUILT IN · 75 CRI · ADJUSTABLE · CE · IP65 · 2 YEAR



Supplied with AC charger 100-240V, EU/BS plug and car charger 12V.





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class			Notes
7028A/AN/RGB	Anthracite	RGB	-	10W	-	120°	100-240V		100cm	20	Complete with driver
7028B/AN/RGB	Anthracite	RGB	-	30W	-	120°	100-240V		100cm	10	Complete with driver
7028AR/G/C	Grey	Cool white	4000K	10W	700lm	120°	8,4V DC		-	12	Complete with driver and batteries
7028BR/G/C	Grey	Cool white	4000K	20W	1650lm	120°	8,4V DC		-	8	Complete with driver and batteries



The Classic LED Floodlights

Die cast



A-A++

7028A | 10W | COB LED | Die cast

LED BUILT IN | 70 CRI | ADJUSTABLE | IP65 | CE | 2 YEAR







A-A++

7028B | 30W | COB LED | Die cast

LED BUILT IN | 70 CRI | ADJUSTABLE | IP65 | offer | CE | 2 YEAR



Optional stand.
Order code 7028BP/G.

offer





A-A++

7032 | 150W | COB LED | Die cast

LED BUILT IN | 70 CRI | ADJUSTABLE | IP65 | CE | 2 YEAR





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class			Notes
7028A/G/D	Grey	Daylight	6000K	10W	700lm	120°	100-240V		-	30	Complete with driver
7028B/G/W	Grey	Warm white	3000K	30W	2150lm	120°	100-240V		-	4	Complete with driver
7032/AN/C	Anthracite	Cool white	4000K	3x50W	12000lm	120°	100-240V		200cm	1	Complete with driver



The LED Sensor Floodlights



7048 | 12W | COB LED | Sensor | Die cast

LED BUILT IN
70 CRI
ADJUSTABLE
IP54
offer
2 YEAR









7060 | 15W | SMD 2835 | Sensor | Aluminium + PC

LED BUILT IN
70 CRI
ADJUSTABLE
IP44
2 YEAR









7028BE | 30W | COB LED | Sensor | Die cast

LED BUILT IN
75 CRI
ADJUSTABLE
IP65
2 YEAR







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class	S		Notes
7048/G/D	Grey	Daylight	6000K	12W	824lm	90°	230V		-	8	Complete with driver
7060/W/C	White	Cool white	4000K	15W	1400lm	120°	100-240V		-	12	Complete with driver
7028BE/AN/C	Anthracite	Cool white	4000K	30W	2200lm	120°	100-240V		100cm	4	Complete with driver



The Slim Line LED Floodlights

Die cast



A-A++

7038 | 10W | COB LED | Die cast

IP65 offer

LED BUILT IN · 70 CRI · ADJUSTABLE · 2 YEAR







A-A++

7040 | 30W | COB LED | Die cast

IP65 offer

LED BUILT IN · 70 CRI · ADJUSTABLE · 2 YEAR







A-A++

7040E | 30W | COB LED | Sensor | Die cast

IP65

LED BUILT IN · 70 CRI · ADJUSTABLE · 2 YEAR





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class			Notes
7038/G/D	Grey	Daylight	6000K	10W	700lm	120°	100-240V		100cm	10	Complete with driver
7038/G/W	Grey	Warm white	3000K	10W	700lm	120°	100-240V		100cm	10	Complete with driver
7040/G/D	Grey	Daylight	6000K	30W	2100lm	120°	100-240V		100cm	5	Complete with driver
7040E/G/C	Grey	Cool white	4000K	30W	2100lm	120°	100-240V		100cm	5	Complete with driver

The COB LED Slim Line

Die cast





7034B | 50W | COB LED | Die cast

IP65 offer | LED BUILT IN | 75 CRI | ADJUSTABLE | CE | 3 YEAR







7034C | 70W | COB LED | Die cast

IP65 offer | LED BUILT IN | 75 CRI | ADJUSTABLE | CE | 3 YEAR







7034D | 100W | COB LED | Die cast

IP65 offer | LED BUILT IN | 75 CRI | ADJUSTABLE | CE | 3 YEAR





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class			Notes
7034B/G/C	Grey	Cool white	4000K	50W	4050lm	130°	100-240V		100cm	10	Complete with driver
7034C/G/C	Grey	Cool white	4000K	70W	5600lm	130°	100-240V		100cm	6	Complete with driver
7034D/G/C	Grey	Cool white	4000K	2x50W	8000lm	130°	100-240V		100cm	4	Complete with driver



The COB LED Slim Floodlights



7028A | 10W | COB LED | Die cast

LED BUILT IN · 70 CRI · ADJUSTABLE · IP65 · CE · 3 YEAR







7028AB | 20W | COB LED | Die cast

LED BUILT IN · 70 CRI · ADJUSTABLE · IP65 · CE · 3 YEAR







7028E | 100W | COB LED | Die cast

LED BUILT IN · 70 CRI · ADJUSTABLE · IP65 · CE · 3 YEAR





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class			Notes
7028A/AN/C	Anthracite	Cool white	4000K	10W	700lm	120°	100-240V	⏚	100cm	20	Complete with driver
7028A/AN/W	Anthracite	Warm white	3000K	10W	700lm	120°	100-240V	⏚	100cm	20	Complete with driver
7028AB/AN/C	Anthracite	Cool white	4000K	20W	1400lm	120°	100-240V	⏚	100cm	12	Complete with driver
7028E/AN/C	Anthracite	Cool white	4000K	100W	7000lm	120°	100-240V	⏚	100cm	3	Complete with driver

The LED Retro Floodlight

Die cast





A-A++

7062A | 10W | SMD 3030 | Die cast







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class			Notes
7062A/AN/C	Anthracite	Cool white	4000K	10W	900lm	120°	230V		100cm	25	Complete with driver



The COB LED Design Floodlights

Die cast + plastic



7064 | 10W | COB LED | Die cast + plastic









7066 | 30W | COB LED | Die cast + plastic







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class			Notes
7064/W/C	White	Cool white	4000K	10W	1135lm	100°	100-240V		100cm	8	Complete with driver
7066/W/C	White	Cool white	4000K	30W	3030lm	100°	100-240V		100cm	4	Complete with driver



AC LED Floodlights

10-50W

7028CA | 10W | SMD 2835 | Die cast + tempered glass



A-A++ 7028CA/B/C

LED BUILT IN · 80 CRI · ADJUSTABLE · IP65 · CE · 2 YEAR



7028CA/B/W



7028CB | 30W | SMD 2835 | Die cast + tempered glass



A-A++ 7028CB/B/C

LED BUILT IN · 80 CRI · ADJUSTABLE · IP65 · CE · 2 YEAR



7028CB/B/W



7028CC | 50W | SMD 2835 | Die cast + tempered glass



A-A++ 7028CC/B/C

LED BUILT IN · 80 CRI · ADJUSTABLE · IP65 · CE · 2 YEAR



7028CC/B/D



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class			Notes
7028CA/B/D	Black	Daylight	6000K	10W	900lm	110°	230V		30cm	60	AC LED
7028CA/B/C	Black	Cool white	4000K	10W	900lm	110°	230V		30cm	60	AC LED
7028CA/B/W	Black	Warm white	3000K	10W	850lm	110°	230V		30cm	60	AC LED
7028CB/B/D	Black	Daylight	6000K	30W	2700lm	110°	230V		30cm	30	AC LED
7028CB/B/C	Black	Cool white	4000K	30W	2700lm	110°	230V		30cm	30	AC LED
7028CB/B/W	Black	Warm white	3000K	30W	2550lm	110°	230V		30cm	30	AC LED
7028CC/B/D	Black	Daylight	6000K	50W	4500lm	110°	230V		30cm	20	AC LED
7028CC/B/C	Black	Cool white	4000K	50W	4500lm	110°	230V		30cm	20	AC LED



AC LED Floodlights

100-250W



A-A++

7028CD | 100W | SMD 2835 | Die cast + tempered glass

LED BUILT IN · 80 CRI · ADJUSTABLE · IP65 · CE · 2 YEAR







A-A++

7028CE | 150W | SMD 2835 | Die cast + tempered glass

LED BUILT IN · 80 CRI · ADJUSTABLE · IP65 · CE · 2 YEAR







A-A++

7028CF | 250W | SMD 2835 | Die cast + tempered glass

LED BUILT IN · 80 CRI · ADJUSTABLE · IP65 · CE · 2 YEAR





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class			Notes
7028CD/B/C	Black	Cool white	4000K	100W	9000lm	110°	230V	⏚	30cm	10	AC LED
7028CE/B/C	Black	Cool white	4000K	150W	13500lm	110°	230V	⏚	30cm	4	AC LED
7028CF/B/C	Black	Cool white	4000K	250W	22500lm	110°	230V	⏚	30cm	4	AC LED



The Glass Face AC LED Floodlights

7028AG | 10W | SMD 3030 | Die cast + tempered glass



A-A++ 7028AG/W/C

LED BUILT IN · 80 CRI · ADJUSTABLE · IP65 · CE · 2 YEAR



7028AG/B/C



7028BG | 30W | SMD 3030 | Die cast + tempered glass



A-A++ 7028BG/W/C

LED BUILT IN · 80 CRI · ADJUSTABLE · IP65 · CE · 2 YEAR



7028BG/B/C



7028CG | 50W | SMD 3030 | Die cast + tempered glass



A-A++ 7028CG/W/C

LED BUILT IN · 80 CRI · ADJUSTABLE · IP65 · CE · 2 YEAR



7028CG/B/C



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class			Notes
7028AG/W/C	White	Cool white	4000K	10W	800lm	100°	230V		50cm	20	AC LED
7028AG/B/C	Black	Cool white	4000K	10W	800lm	100°	230V		50cm	20	AC LED
7028BG/W/C	White	Cool white	4000K	30W	2400lm	100°	230V		50cm	12	AC LED
7028BG/B/C	Black	Cool white	4000K	30W	2400lm	100°	230V		50cm	12	AC LED
7028CG/W/C	White	Cool white	4000K	50W	4000lm	100°	230V		50cm	8	AC LED
7028CG/B/C	Black	Cool white	4000K	50W	4000lm	100°	230V		50cm	8	AC LED



The COB LED Project Floodlights

Die cast



7050A | 10W | COB LED | Die cast

LED BUILT IN · 70 CRI · ADJUSTABLE · IP65 · CE · 2 YEAR



Can also be suspended.







7050B | 30W | COB LED | Die cast

LED BUILT IN · 70 CRI · ADJUSTABLE · IP65 · CE · 2 YEAR



Can also be suspended.







7050C | 50W | COB LED | Die cast

LED BUILT IN · 70 CRI · ADJUSTABLE · IP65 · CE · 2 YEAR



Can also be suspended.





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class			Notes
7050A/G/C	Grey	Cool white	4000K	10W	850lm	80°	100-240V		100cm	6	Complete with driver
7050B/G/C	Grey	Cool white	4000K	30W	2660lm	80°	100-240V		100cm	4	Complete with driver
7050C/G/C	Grey	Cool white	4000K	50W	4390lm	80°	100-240V		100cm	2	Complete with driver



The LED High Power Boxes

Aluminium



A-A++

7058 | 120W | SMD 3030 | Surface mounted | Aluminium

Ideal for petrol stations, showrooms & warehouses.

LED BUILT IN

70 CRI

CE

5 YEAR

IP65





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class		Notes
7058/W/D	White	Daylight	6000K	120W	10800lm	120°	100-240V	⏚	1	Complete with driver
7058/W/C	White	Cool white	4000K	120W	10200lm	120°	100-240V	⏚	1	Complete with driver



The LED Wall Washers

Aluminium

7055A | 12x1W | LED | Aluminium

Connect maximum 10pcs.



7055A/W

new

LED BUILT IN | 80 CRI | DIMMABLE | IP66 | ADJUSTABLE | CE | 5 YEAR



7055A/C



7055B | 24x1W | LED | Aluminium

Connect maximum 5pcs.



7055B/W

new

LED BUILT IN | 80 CRI | DIMMABLE | IP66 | ADJUSTABLE | CE | 5 YEAR



7055B/C



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class			Notes
7055A/C	Grey	Cool white	4000K	12x1W	850lm	60°x20°	24V DC	III	100cm	30	Requires 24V DC driver
7055A/W	Grey	Warm white	3000K	12x1W	850lm	60°x20°	24V DC	III	100cm	30	Requires 24V DC driver
7055B/C	Grey	Cool white	4000K	24x1W	1700lm	60°x20°	24V DC	III	100cm	15	Requires 24V DC driver
7055B/W	Grey	Warm white	3000K	24x1W	1700lm	60°x20°	24V DC	III	100cm	15	Requires 24V DC driver



70100/AN/C



70101/AN/C

The COB LED Street Light

20-50W



70080 | 20W | COB LED | Die cast

LED BUILT IN 70 CRI

3 YEAR

IP65







70090 | 30W | COB LED | Die cast

LED BUILT IN 70 CRI

3 YEAR

IP65





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class			Notes
70080/AN/C	Anthracite	Cool white	4000K	20W	1500lm	120°x60°	230V	⏚	60cm	2	Complete with driver
70090/AN/C	Anthracite	Cool white	4000K	30W	2250lm	120°x60°	230V	⏚	60cm	2	Complete with driver



The COB LED Street Light

80-120W



70100 | 50W | COB LED | Die cast

LED BUILT IN 70 CRI

3 YEAR

IP65







70101 | 80W | COB LED | Die cast

LED BUILT IN 70 CRI

3 YEAR

IP65





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class			Notes
70100/AN/C	Anthracite	Cool white	4000K	50W	3750lm	120°x60°	230V		60cm	2	Complete with driver
70101/AN/C	Anthracite	Cool white	4000K	80W	6000lm	120°x60°	100-240V		60cm	1	Complete with driver



The LED Park Light

Die cast



A-A++

70108 | 60W | LED | Die cast

LED BUILT IN

70 CRI

5 YEAR

IP66









A-A++

70104 | 30W | COB LED | Die cast

LED BUILT IN

70 CRI

5 YEAR

IP65









A-A++

70105 | 50W | COB LED | Die cast

LED BUILT IN

70 CRI

5 YEAR

IP65







Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class			Notes
70108/AN/C	Anthracite	Cool white	4000K	60W	5300lm	Assymetric	100-240V		100cm	1	Complete with driver
70104/G/C	Grey	Cool white	4000K	30W	2700lm	120°	100-240V		500cm	1	Complete with driver
70105/AN/C	Anthracite	Cool white	4000K	50W	4000lm	60°	100-240V		500cm	1	Complete with driver

The LED Park Lantern

Die cast



70110 | 60W | LED | Die cast

LED BUILT IN

70 CRI

5 YEAR

IP66





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class			Notes
70110/AN/C	Anthracite	Cool white	4000K	60W	4500lm	Assymetric	100-240V		100cm	1	Complete with driver



22

Emergency Lights

Pages 613-620

LED | Emergency 3Hrs Maintained | Recessed

PC | Plastic + aluminium

IP20 IP22 IP44 IP65

80 CRI

2 YEAR



one

Emergency LED Recessed Spot

89002 | 3W | LED | Emergency 3Hrs Maintained | Recessed | Plastic + aluminium



A-A++

LED BUILT IN

2 YEAR

IP20









Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Class	Battery Duration				Notes
89002	White	Daylight	6000K	3W	150lm	230V	⏚	3Hrs	72mm	120mm	12	Supplied with battery

Emergency LED Plafo

67366E | 12W | SMD 2835 | Emergency 3Hrs Maintained | PC



67366E/W/C

LED BUILT IN
80 CRI
CE
2 YEAR
IP54



67366E/W/W





67284LE | 25W/5W | SMD 2835 | Emergency 3Hrs Maintained | PC



67284LE/W/C

LED BUILT IN
80 CRI
CE
2 YEAR
IP65



67284LE/W/W





67280ANE | 15W | SMD 2835 | Emergency 3Hrs Maintained | Plastic



LED BUILT IN
80 CRI
CE
2 YEAR
IP65







67282ANE | 16W | SMD 2835 | Emergency 3Hrs Maintained | Plastic



LED BUILT IN
80 CRI
CE
2 YEAR
IP65







67446EM | 24W | SMD 2835 | Emergency 3Hrs Maintained | Sensor | PC



LED BUILT IN
85 CRI
CE
2 YEAR
IP44

Adjustments
- Detection Sensitivity
- ON Timer
- Daylight Sensor





Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Class	Battery Duration		Notes
67366E/W/C	White	Cool white	4000K	12W	960lm	-	230V	☐	3Hrs	20	Supplied with battery
67366E/W/W	White	Warm white	3000K	12W	900lm	-	230V	☐	3Hrs	20	Supplied with battery
67284LE/W/C	White	Cool white	4000K	25W/5W	1900lm	-	230V	☐	3Hrs	12	Supplied with battery
67284LE/W/W	White	Warm white	3000K	25W/5W	1900lm	-	230V	☐	3Hrs	12	Supplied with battery
67280ANE/G/W	Grey	Warm white	3000K	15W	1000lm	-	230V	☐	3Hrs	10	Supplied with battery
67282ANE/G/W	Grey	Warm white	3000K	16W	1280lm	-	230V	☐	3Hrs	10	Supplied with battery
67446EM/W/W	White	Warm white	3000K	24W	1900lm	160°	230V	☐	3Hrs	5	Supplied with battery

Emergency LED Ceiling Plexiglass Signs



89406 | 1W | LED | Emergency 3Hrs Maintained

LED BUILT IN

2 YEAR

IP44



Supplied with 3 stickers.





89406R | 1W | LED | Emergency 3Hrs Maintained | Recessed

LED BUILT IN

2 YEAR

IP44



Supplied with 3 stickers.



Order Code	Colour	Watts	Input	Class	Battery Type	Battery Duration				Notes
89406/W	White	1W	230V	⧈	Ni-Cd 3,6V 1,5Ah	3Hrs	-	-	12	Ceiling/Wall mounted
89406R/W	White	1W	230V	⧈	Ni-Cd 3,6V 1,5Ah	3Hrs	300x45mm	120mm	16	-



Emergency LED Wall & Ceiling



A-A++

89404 | 7W | LED | Emergency 3Hrs Maintained | PC

LED BUILT IN

2 YEAR

IP65



Supplied with 3 stickers.





A-A++

89402 | 1,2W | LED | Emergency 3Hrs Maintained

LED BUILT IN

2 YEAR

IP22



Supplied with 3 stickers.



Order Code	Colour	Light Colour	CCT (K)	Watts	Input	Class	Battery Type	Battery Duration		Notes
89404	White	Daylight	6000K	7W	230V		Ni-Cd 3,6V 1,5Ah	3Hrs	12	Supplied with battery
89402/W	White	Daylight	6000K	1,2W	230V		-	3Hrs	30	Supplied with battery



Universal LED Emergency Kit



89005A/EME | 5-50W | Built-in Emergency kit for LED fittings | Emergency 3Hrs Maintained

Use inside fittings.

new

IP20



WIRING DIAGRAM



The driver automatically adjusts the output LED current to provide the optimum match between the battery and the load, providing maximum illumination whilst ensuring full battery duration.

Emergency mode light output compared with normal operation:

Luminaire Power	5W	7W	10W	12W	15W	20W	25W	30W	35W	40W	45W	50W
	60%	43%	30%	25%	20%	15%	12%	10%	9%	8%	7%	6%

Order Code	Input	Watts	Class	Battery Type	Charge Period	Battery Duration		Notes
89005A/EME	230V	5-50W		Ni-Cd 3,6V 4,0Ah	24Hrs	3Hrs	12	Supplied with battery



Universal LED Emergency Kit



89005/EME | 5-50W | Emergency kit for LED Downlights and LED strips | Emergency 3Hrs Maintained

IP20



WIRING DIAGRAM



The driver automatically adjusts the output LED current to provide the optimum match between the battery and the load, providing maximum illumination whilst ensuring full battery duration.

Emergency mode light output compared with normal operation:

Luminaire Power	5W	7W	10W	12W	15W	20W	25W	30W	35W	40W	45W	50W
	60%	43%	30%	25%	20%	15%	12%	10%	9%	8%	7%	6%

Order Code	Input	Watts	Class	Battery Type	Charge Period	Battery Duration		Notes
89005/EME	230V	5-50W		Ni-Mh 3,6V 4,0Ah	24Hrs	3Hrs	12	Supplied with battery



GU10/E27 LED Emergency Kit



89009/EME | 3,5-8W | Emergency kit for GU10/E27 LED | Emergency 3Hrs Maintained

IP20



WIRING DIAGRAM





* This kit will only operate with GU10 & E27 LED lamps suitable for 180V DC power supply. Most of the lamps in the market today are compatible however we recommend to test suitability before purchasing the lamps.

Order Code	Input	Watts	Class	Battery Type	Charge Period	Battery Duration		Notes
89009/EME	230V	3,5-8W	⧈	Ni-Cd 7,2V 4,0Ah	Max. 24Hrs	3Hrs	24	Supplied with battery



LED Panels Emergency Kit



89143F | 5-60W | Emergency pack for LED Panels and LED Downlights | Emergency 3Hrs Maintained

A-A++

IP20



WIRING DIAGRAM



The driver automatically adjusts the output LED current to provide the optimum match between the battery and the load, providing maximum illumination whilst ensuring full battery duration.

Emergency mode light output compared with normal operation:

3W Luminaire Power	5W	7W	10W	12W	15W	20W	25W	30W	35W	40W	45W	50W
	60%	43%	30%	25%	20%	15%	12%	10%	9%	8%	7%	6%
6W Luminaire Power	7W	10W	12W	15W	20W	25W	30W	35W	40W	45W	50W	60W
	85%	60%	50%	40%	30%	24%	20%	18%	16%	14%	12%	10%



Order Code	Input	Watts	Class	Battery Type	Charge Period	Battery Duration		Notes
89143F	230V	5-60W		Ni-Cd 7,2V 4,0Ah	24Hrs	3Hrs	9	Supplied with battery





23

LED Drivers

Pages 623-642

Constant voltage | Constant current

IP20

TRIAC DIMMABLE · 1-10V DIMMABLE · DALI DIMMABLE · PUSH TO DIM · QUICK FIX · DALI · 3 YEAR · 5 YEAR





Marine Drivers for Yachts

Constant current



89028M | 9-36V DC | LED Marine driver | 350mA | PWM Dimmable

DIMMABLE

new

IP20





89028AM | 9-36V DC | LED Marine driver | 700mA | PWM Dimmable

DIMMABLE

new

IP20



Order Code	Input	Power	Output	Class	Dimmable		Notes
89028M	9-36V DC	4,2W@12V / 8,4W@24V / 11,2W@36V	350mA	III	YES	240	-
89028AM	9-36V DC	8,4W@12V / 16,8W@24V / 22,4W@36V	700mA	III	YES	240	-



Mini Series Drivers

Constant current



89004 | 1-4W | 350mA

QUICK FIX

3 YEAR

IP66





89004C | 1,5-4,5W | 500mA

QUICK FIX

5 YEAR

IP66





89004A | 2-4W | 700mA

QUICK FIX

5 YEAR

IP66



Order Code	Input	Power	Output	Class	Dimmable		Notes
89004	100-240V	1-4W	350mA		NO	200	-
89004C	100-240V	1,5-4,5W	500mA		NO	200	-
89004A	100-240V	2-4W	700mA		NO	200	-



89020

89015

The 350mA Range

Constant current



89008 | 4-8W | 350mA

QUICK FIX · CE · 5 YEAR

IP20





89015 | 7-15W | 350mA

QUICK FIX · CE · 5 YEAR

IP20





89020 | 13-20W | 350mA

QUICK FIX · CE · 5 YEAR

IP20



Order Code	Input	Power	Output	Class	Dimmable		Notes
89008	230V	4-8W	350mA	⧈	NO	100	-
89015	230V	7-15W	350mA	⧈	NO	100	-
89020	230V	13-20W	350mA	⧈	NO	100	-

The 500mA Range



89030C | 14-28W | 500mA

IP20



The 700mA Range



89006A | 1-6W | 700mA

IP20





89008A | 4-8W | 700mA

new

IP20





89015A | 7-15W | 700mA

IP20





89030A | 15-30W | 700mA

IP20



Order Code	Input	Power	Output	Class	Dimmable		Notes
89030C	100-240V	14-28W	500mA		NO	100	-
89006A	230V	1-6W	700mA		NO	200	-
89008A	230V	4-8W	700mA		NO	100	-
89015A	230V	7-15W	700mA		NO	100	-
89030A	230V	15-30W	700mA		NO	100	-

The TRIAC Dimmable

Constant current



89008CT | 4,8-7W | 320mA | TRIAC | Dimmable

TRIAC DIMMABLE · CE · 3 YEAR · IP20





89012BT | 7,5-10,5W | 250mA | TRIAC | Dimmable

TRIAC DIMMABLE · CE · 3 YEAR · IP20





89016T | 10,5-15W | 350mA | TRIAC | Dimmable

TRIAC DIMMABLE · CE · 3 YEAR · IP20





89018DT | 11,5-18W | 420mA | TRIAC | Dimmable

TRIAC DIMMABLE · CE · 3 YEAR · IP20





89022ET | 15-23W | 540mA | TRIAC | Dimmable

TRIAC DIMMABLE · CE · 3 YEAR · IP20





89030AT | 19-30W | 700mA | TRIAC | Dimmable

TRIAC DIMMABLE · CE · 3 YEAR · IP20



Order Code	Input	Power	Output	Class	Dimmable		Notes
89008CT	230V	4,8-7W	320mA	⧈	YES	50	Use TRIAC dimmer
89012BT	230V	7,5-10,5W	250mA	⧈	YES	50	Use TRIAC dimmer
89016T	230V	10,5-15W	350mA	⧈	YES	1	Use TRIAC dimmer
89018DT	230V	11,5-18W	420mA	⧈	YES	50	Use TRIAC dimmer
89022ET	230V	15-23W	540mA	⧈	YES	30	Use TRIAC dimmer
89030AT	230V	19-30W	700mA	⧈	YES	50	Use TRIAC dimmer

The 350mA TRIAC Dimmable Range

Constant current



89015T | 7-15W | 350mA | TRIAC | Dimmable

TRIAC DIMMABLE · QUICK FIX · CE · 5 YEAR

IP20



The 700mA TRIAC Dimmable Range

Constant current



89006AT | 3,5-6W | 700mA | TRIAC | Dimmable

TRIAC DIMMABLE · QUICK FIX · CE · 5 YEAR

new

IP20





89015AT | 7-15W | 700mA | TRIAC | Dimmable

TRIAC DIMMABLE · QUICK FIX · CE · 5 YEAR

IP20



The 1200mA TRIAC Dimmable Range

Constant current



89048T | 32-48W | 1200mA | TRIAC | Dimmable

TRIAC DIMMABLE · QUICK FIX · CE · 5 YEAR

IP20



Order Code	Input	Power	Output	Class	Dimmable		Notes
89015T	230V	7-15W	350mA	⧈	YES	100	Use TRIAC dimmer
89006AT	230V	3,5-6W	700mA	⧈	YES	100	Use TRIAC dimmer
89015AT	230V	7-15W	700mA	⧈	YES	100	Use TRIAC dimmer
89048T	230V	32-48W	1200mA	⧈	YES	80	Use TRIAC dimmer



The 12V AC Range

Transformers



89109E | 20-105W

TRAILING EDGE
DIMMABLE

IP20





89110E | 35-105W

TRIAC
DIMMABLE

IP20



Order Code	Input	Power	Output	Class	Dimmable		Notes
89109E	230V	20-105W	12V AC	⧈	YES	10	Dimmer trailing edge
89110E	230V	35-105W	12V AC	⧈	YES	100	Dimmer leading & trailing edge

The 12V DC Range

Constant voltage



89008W | 8W | 12V DC

IP20





89015W | 15W | 12V DC

IP20





89030W | 30W | 12V DC

IP20





89075W | 75W | 12V DC

IP20





89200WN | 200W | 12V DC

IP20



Order Code	Input	Power	Output	Class	Dimmable		Notes
89008W	230V	8W	12V DC		NO	200	-
89015W	230V	15W	12V DC		NO	200	-
89030W	230V	30W	12V DC		NO	100	-
89075W	230V	75W	12V DC		NO	50	-
89200WN	230V	200W	12V DC		NO	48	-



The 24V DC Range

Constant voltage

89015V | 15W | 24V DC



IP20



89030V | 30W | 24V DC



IP20



89060V | 60W | 24V DC



IP20



89075V | 75W | 24V DC



IP20



Order Code	Input	Power	Output	Class	Dimmable		Notes
89015V	230V	15W	24V DC	⧈	NO	100	-
89030V	230V	30W	24V DC	⧈	NO	100	-
89060V	230V	60W	24V DC	⧈	NO	50	-
89075V	230V	75W	24V DC	⧈	NO	25	-



The 24V DC Range High Power

Constant voltage



89100V | 100W | 24V DC

IP20





89150V | 150W | 24V DC

IP20





89200V | 200W | 24V DC

new

IP20



Order Code	Input	Power	Output	Class	Dimmable		Notes
89100V	230V	100W	24V DC	⧈	NO	20	-
89150V	230V	150W	24V DC	⧈	NO	25	-
89200V	230V	200W	24V DC	⧈	NO	20	-



89060WD

The 12V DC Dimmable Range

Constant voltage



89060WD | 3 Channels 20W each | 12V DC | 1-10V | Dimmable

1-10V DIMMABLE

5 YEAR

IP20



Order Code	Input	Power	Output	Class	Dimmable		Notes
89060WD	230V	3x20W	12V DC	⏚	YES	18	Use 1-10V dimmer



89100VT

89040VT

The 24V DC Range TRIAC Dimmable

Constant voltage



89040VT | 40W | 24V DC | TRIAC | Dimmable

TRIAC DIMMABLE · CE · 5 YEAR

new

IP20





89075VT | 75W | 24V DC | TRIAC | Dimmable

TRIAC DIMMABLE · CE · 5 YEAR

new

IP20





89100VT | 100W | 24V DC | TRIAC | Dimmable

TRIAC DIMMABLE · CE · 5 YEAR

new

IP20



Order Code	Input	Power	Output	Class	Dimmable		Notes
89040VT	230V	40W	24V DC	⧈	YES	50	Use TRIAC dimmer
89075VT	230V	75W	24V DC	⧈	YES	20	Use TRIAC dimmer
89100VT	230V	100W	24V DC	⧈	YES	20	Use TRIAC dimmer

The 24V DC Slim Range

Constant voltage



89030VL | 30W | 24V DC

Suitable for LED profiles on page 246, 248, 249.

IP20





89060VL | 60W | 24V DC

Suitable for LED profiles on page 246, 248, 249.

IP20





89075VL | 75W | 24V DC

Suitable for LED profiles on page 246, 248, 249.

IP20





89100VL | 100W | 24V DC

Suitable for LED profiles on page 246, 248, 249.

IP20





89150VL | 150W | 24V DC

Suitable for LED profiles on page 246, 248, 249.

IP20



Order Code	Input	Power	Output	Class	Dimmable		Notes
89030VL	230V	30W	24V DC	⧈	NO	100	-
89060VL	230V	60W	24V DC	⧈	NO	50	-
89075VL	230V	75W	24V DC	⧈	NO	50	-
89100VL	230V	100W	24V DC	⧈	NO	50	-
89150VL	230V	150W	24V DC	⧈	NO	25	-



89100VLD

The 24V Slim Range Dimmable

Constant voltage



89060VLD | 60W | 24V DC | Push to DIM | Dimmable

Suitable for LED profiles on page 246, 248, 249.

PUSH TO DIM · CE · 5 YEAR

new

IP20





89100VLD | 100W | 24V DC | Push to DIM | Dimmable

Suitable for LED profiles on page 246, 248, 249.

PUSH TO DIM · CE · 5 YEAR

new

IP20





89150VLD | 150W | 24V DC | Push to DIM | Dimmable

Suitable for LED profiles on page 246, 248, 249.

PUSH TO DIM · CE · 5 YEAR

new

IP20



DALI Dimmable



89100VLL | 100W | 24V DC | DALI & Push to DIM | Dimmable

Suitable for LED profiles on page 246, 248, 249.

PUSH TO DIM · DALI DIMMABLE · CE · 5 YEAR · DALI

new

IP20



Order Code	Input	Power	Output	Class	Dimmable		Notes
89060VLD	230V	60W	24V DC	-	YES	50	Push to DIM
89100VLD	230V	100W	24V DC	-	YES	50	Push to DIM
89150VLD	230V	150W	24V DC	-	YES	50	Push to DIM
89100VLL	230V	100W	24V DC	⧈	YES	50	DALI & Push to DIM

The 24V DC Open Range

Constant voltage



89060VN | 60W | 24V DC

IP20





89100VN | 100W | 24V DC

IP20





89150VN | 150W | 24V DC

IP20





89200VN | 200W | 24V DC

IP20





89350VN | 350W | 24V DC

IP20



Order Code	Input	Power	Output	Class	Dimmable		Notes
89060VN	100-240V	60W	24V DC		NO	120	-
89100VN	100-240V	100W	24V DC		NO	63	-
89150VN	100-240V	150W	24V DC		NO	48	-
89200VN	230V	200W	24V DC		NO	48	-
89350VN	230V	350W	24V DC		NO	36	-



The 24V Open Range Dimmable

Constant voltage



89100VND | 100W | 24V DC | TRIAC & 1-10V | Dimmable

TRIAC DIMMABLE · 1-10V DIMMABLE · CE · 3 YEAR

new

IP20





89200VND | 200W | 24V DC | TRIAC & 1-10V | Dimmable

TRIAC DIMMABLE · 1-10V DIMMABLE · CE · 3 YEAR

new

IP20



Order Code	Input	Power	Output	Class	Dimmable		Notes
89100VND	230V	100W	24V DC	⏚	YES	60	TRIAC & 1-10V
89200VND	230V	200W	24V DC	⏚	YES	40	TRIAC & 1-10V



The 24V DC Waterproof IP67 Range

Constant voltage



89100VP | 100W | 24V DC

IP67





89150VP | 150W | 24V DC

IP67





89200VP | 200W | 24V DC

IP67



Order Code	Input	Power	Output	Class		Dimmable		Notes
89100VP	100-240V	100W	24V DC		100cm	NO	36	-
89150VP	100-240V	150W	24V DC		100cm	NO	35	-
89200VP	100-240V	200W	24V DC		100cm	NO	32	-



The 24V DC Dimmable Range

Constant voltage



89030VD | 30W | 24V DC | Push to DIM & 1-10V | Dimmable

PUSH TO DIM · 1-10V DIMMABLE · CE · 5 YEAR

IP20

149mm · 53mm · 30mm

The 24V DC DALI Dimmable Range

Constant voltage



89075L | 75W | 24V DC | DALI, Push to DIM, 1-10V | Dimmable

PUSH TO DIM · DALI DIMMABLE · 1-10V DIMMABLE · CE · 5 YEAR · DALI

IP20

220mm · 58mm · 42mm

Order Code	Input	Power	Output	Class	Dimmable		Notes
89030VD	230V	30W	24V DC	⧈	YES	20	Push to DIM & 1-10V
89075L	230V	75W	24V DC	⧈	YES	24	DALI, Push to DIM & 1-10V



Universal Push to DIM & 1-10V Dimmable Range



89027D | Push to DIM & 1-10V | Dimmable

Adjustable output using DIP switches.

PUSH TO DIM · 1-10V DIMMABLE · 5 YEAR · IP20

LED Current Selection

900mA ● ● ●
700mA ● ● ○
500mA ● ○ ○
350mA ○ ○ ○
1 2 3



Output Current	350mA	500mA	700mA	900mA
Output Power	2-15W	3-20W	4-27W	6-24W



89030D | Push to DIM & 1-10V | Dimmable

Adjustable output using DIP switches.

PUSH TO DIM · 1-10V DIMMABLE · 5 YEAR · IP20

LED Current Selection and Voltage Selection

	1	2	3	4	5
24V	●	●	●	○	●
12V	●	●	●	●	○
700mA	●	●	●	○	○
600mA	○	●	●	○	○
550mA	●	○	●	○	○
500mA	●	●	○	○	○
450mA	○	○	●	○	○
400mA	○	●	○	○	○
350mA	●	○	○	○	○
250mA	○	○	○	○	○



Output Current / Voltage	250mA	350mA	400mA	450mA	500mA	550mA	600mA	700mA	12V DC	24V DC
Output Power	1,5-15W	2-20W	2,5-22W	2,7-24W	3-27W	3,3-29W	3,6-30W	4,2-30W	8W	16W



89050D | Push to DIM & 1-10V | Dimmable

Adjustable output using DIP switches.

PUSH TO DIM · 1-10V DIMMABLE · 5 YEAR · IP20

LED Current Selection

	1	2	3	4	5
1050mA	●	●	●	●	●
900mA	●	●	○	●	●
800mA	●	●	○	○	●
700mA	○	○	●	●	●
650mA	○	●	●	○	●
600mA	○	○	●	●	○
550mA	●	○	○	○	○
500mA	○	●	○	○	○
350mA	○	○	○	○	○



Output Current	350mA	500mA	550mA	600mA	650mA	700mA	800mA	900mA	1050mA
Output Power	4-25W	5-36W	6-40W	6-43W	7-47W	7-50W	8-50W	9-50W	11-50W

Order Code	Input	Power	Output	Class	Dimmable		Notes
89027D	230V	Refer to table	Adjustable	⧈	YES	40	Push to DIM & 1-10V
89030D	230V	Refer to table	Adjustable	⏚	YES	40	Push to DIM & 1-10V
89050D	230V	Refer to table	Adjustable	⧈	YES	20	Push to DIM & 1-10V

Universal DALI Dimmable Range



89020L | DALI & Push to DIM | Dimmable

Adjustable output using DIP switches.

PUSH TO DIM · DALI DIMMABLE · CE · 5 YEAR · DALI · IP20

LED Current Selection and Voltage Selection

	1	2	3	4	5
24V	○	●	●	●	●
12V	●	○	●	●	●
900mA	○	○	●	●	●
700mA	○	○	●	●	○
500mA	○	○	●	○	○
350mA	○	○	○	○	○



Output Current / Voltage	350mA	500mA	700mA	900mA	12V DC	24V DC
Output Power (Max.)	3,2-15W	4,5-20W	6,3-20W	8,1-20W	10W	20W



89025L | DALI & Push to DIM | Dimmable

Adjustable output using DIP switches.

new · PUSH TO DIM · DALI DIMMABLE · CE · 5 YEAR · DALI · IP20

LED Current Selection

	1	2	3	4	5
450mA	●	●	●		
400mA	○	●	●		
350mA	●	○	●		
300mA	○	○	●		
250mA	○	●	○		
200mA	●	○	○		
150mA	○	○	○		



Output Current / Voltage	150mA	200mA	250mA	300mA	350mA	400mA	450mA
Output Power (Max.)	1-8,4W	1,2-11,2W	1,5-14W	1,8-16,8W	2,1-19,6W	2,4-22,4W	2,7-25,2W



89045L | DALI, Push to DIM, 1-10V | Dimmable

Adjustable output using DIP switches.

PUSH TO DIM · DALI DIMMABLE · 1-10V DIMMABLE · CE · 5 YEAR · DALI · IP20

LED Current Selection

	1	2	3	4	5
350mA	○	○	○	○	○
400mA	●	○	○	○	○
450mA	○	●	○	○	○
500mA	●	●	○	○	○
550mA	○	○	●	○	○
600mA	●	○	●	○	○
650mA	○	●	●	○	○
700mA	●	●	●	○	○
750mA	○	○	○	●	○
800mA	●	○	○	●	○
850mA	○	●	○	●	○
900mA	●	●	○	●	○
950mA	○	○	●	●	○
1000mA	●	○	●	●	○
1050mA	○	●	●	●	○
1100mA	●	●	●	●	○



Output Current	350mA	400mA	450mA	500mA	550mA	600mA	650mA	700mA	750mA	800mA	850mA	900mA	950mA	1000mA	1050mA	1100mA
Output Power	4-20W	5-23W	6-26W	6-29W	7-32W	7-35W	8-38W	9-40W	9-42W	10-45W	10-45W	10-45W	11-45W	12-45W	13-45W	13-45W



89050L | DALI, Push to DIM, 1-10V | Dimmable

Adjustable output using DIP switches.

PUSH TO DIM · DALI DIMMABLE · 1-10V DIMMABLE · CE · 5 YEAR · DALI · IP20

LED Current Selection

	1	2	3	4	5
700mA	○	○	○	○	○
750mA	●	○	○	○	○
800mA	○	●	○	○	○
850mA	●	●	○	○	○
900mA	○	○	●	○	○
950mA	●	○	●	○	○
1000mA	○	●	●	○	○
1050mA	●	●	●	○	○
1100mA	○	○	○	●	○
1150mA	●	○	○	●	○
1200mA	○	●	○	●	○
1250mA	●	●	○	●	○
1300mA	●	○	●	●	○
1350mA	○	●	●	●	○
1400mA	●	●	●	●	○



Output Current	700mA	750mA	800mA	850mA	900mA	950mA	1000mA	1050mA	1100mA	1150mA	1200mA	1250mA	1300mA	1350mA	1400mA
Output Power	8,4-40W	9-43,5W	9,6-46,5W	10,2-49W	10,8-50W	11,4-50W	12-50W	12,6-50W	13,2-50W	13,8-50W	14,4-50W	15-50W	15,6-50W	16,2-50W	16,8-50W

Order Code	Input	Power	Output	Class	Dimmable		Notes
89020L	230V	Refer to table	Adjustable	⧈	YES	40	DALI & Push to DIM
89025L	230V	Refer to table	Adjustable	⧈	YES	40	DALI & Push to DIM
89045L	230V	Refer to table	Adjustable	⏚	YES	30	DALI, Push to DIM, 1-10V
89050L	230V	Refer to table	Adjustable	⏚	YES	24	DALI, Push to DIM, 1-10V





24

LED Control & Dimming

Pages 645-650

RGB Controllers | Remote Controllers | Sensors

IP20

DIMMABLE 0/1-10V DIMMABLE 2 YEAR





Microwave Motion Sensor



22000 | 300W | Microwave motion sensor

Can be installed inside fittings.

IP20

- Can be installed inside fittings
- Adjustable sensitivity 20%-100%
- ON TIME 5s-30mins
- Daylight sensor 2-50lux



Day/Night Photocell Sensor



22020 | 1000W | Photocell Day/Night Sensor | Plastic

Ambient Light:<5-15lux.

new

IP44

Automatic day/night operation.



Order Code	Colour	Input	Power	Output	Class		Notes
22000	-	230V	300W	230V		100	-
22020	Black	100-240V	1000W	100-240V		50	-



Infrared Motion Sensors



22004 | 300W (LED) / 800W (Incandescent) | Surface infrared motion sensor



IP20

Detection Range: 360°
Detection Distance: Max. 6m (<24°C)
Time Delay: 10sec ± 3sec to 15min ± 2 min (adjustable)
Ambient Light: <3-2000lux (adjustable)
Installation height: 2,2-4m





22006 | 400W (LED) / 800W (Incandescent) | Infrared motion sensor



IP44

Detection Angle: 180°
Detection Distance: Max. 12m (<24°C)
Time Delay: 10sec ± 3sec to 15min ± 2 min (adjustable)
Ambient Light: <3-2000lux (adjustable)
Installation height: 1,8-2,5m





22008 | 200W (LED) / 800W (Incandescent) | Recessed infrared motion sensor



IP20

Detection Angle: 360°
Detection Distance: Max. 6m (<24°C)
Time Delay: 10sec ± 3sec to 15min ± 2 min (adjustable)
Ambient Light: <3-2000lux (adjustable)
Installation height: 2,2-4m





22010 | 200W (LED) / 500W (Incandescent) | Infrared switch motion sensor

Compatible with BS/EU Box.



IP20

Detection Angle: 160°
Detection Distance: Max. 9m (<24°C)
Time Delay: 10sec ± 3sec to 7min ± 2 min (adjustable)
Ambient Light: <3 ± 2000lux (adjustable)
Installation height: 1-1,8m



Order Code	Colour	Power	Input	Class		Notes
22004	White	300W (LED) / 800W (Incandescent)	230V		50	-
22006	White	400W (LED) / 800W (Incandescent)	230V		50	-
22008	White	200W (LED) / 800W (Incandescent)	230V		100	-
22010	White	200W (LED) / 500W (Incandescent)	230V		100	-



RGB Controllers



89024D | 24V DC | RGB+W controller | 31W/channel | 24V output

DIMMABLE

2 YEAR

IP20

RGB+W controller with 8 programs.
Maximum total output 124W (31Wx4).
Colour and timing can be changed by remote bell push.





89024E | 100-240V | 0/1-10V output | RGB+W controller

0/1-10V

DIMMABLE

2 YEAR

IP20

RGB+W controller with 8 programs.
0/1-10V output for connecting devices controlled by 0/1-10V input.
Colour and timing can be changed by remote bell push.



Order Code	Input	Power	Output	Class	Dimmable		Notes
89024D	24V DC	4x31W	24V DC	III	YES	96	-
89024E	100-240V	-	0/1-10V	II	YES	96	-



12-24V 1-10V Controller



89010D | Dimmer controller for 12-24V | 180W@12V / 360W@24V | 1-10V | 1 channel

1-10V DIMMABLE

2 YEAR

IP20



12-24V DALI, Push to DIM Controller



89100L | DALI & Push to DIM Dimmer 12-24V | 75W@12V / 150W@24V | PWM dimming only

PUSH TO DIM

DALI DIMMABLE

2 YEAR

DALI

IP20

DALI to PWM
- Built-in push dimming
- Dimming range 0,1-100%

PUSH TO DIM
- No status changing < 0,05sec
- Push ON/OFF 0,1-1sec
- Dimming up or down 1,5-10sec
- Set 100% brightness > 11sec

DALI
- DALI agreement includes 16 groups & 64 addresses
- DALI agreement can be divided into 16 scenarios



Order Code	Input	Power	Output	Class	Dimmable		Notes
89010D	12-24V DC	180W@12V / 360W@24V	12-24V	III	YES	64	Use 1-10V dimmer
89100L	12-24V DC	75W@12V / 150W@24V	12-24V	II	YES	200	DALI & Push to DIM



89302

89100

12-24V Signal Repeaters



89100 | Data repeater 12-24V | 120W@12V / 240W@24V | 1 channel x 10A | PWM dimming only

DIMMABLE

2 YEAR

IP20

Repeats the signal when dimming constant voltage fittings e.g. LED strips.



12-36V RGB+W Repeater



89302 | 12-36V DC | Constant voltage RGB+W data repeater | 4 channels x 5A | PWM dimming only

DIMMABLE

2 YEAR

IP20

Repeats the signal when dimming constant voltage fittings e.g. LED strips.



350mA Signal Repeater



89302A | 12-36V DC | 350mA RGB+W constant current data repeater | 4 channels x 4,2-12,6W | PWM dimming only

DIMMABLE

2 YEAR

IP20

Repeats the signal when dimming constant current 350mA fittings e.g. LED spots.



Order Code	Input	Power	Output	Class	Dimmable		Notes
89100	12-24V DC	120W@12V / 240W@24V	12-24V	III	YES	50	-
89302	12-36V DC	60W@12V / 120W@24V	12-36V	III	YES	100	-
89302A	12-36V DC	4x4,2-12,6W	350mA	III	YES	100	-



Remote Controllers



20030 | 12-24V DC | Constant voltage wireless dimmer | 3 channels x 3A

DIMMABLE

2 YEAR

IP20

Remote controller for dimming any constant voltage 12-24V LED fitting including LED strips, LED lamps, LED modules.
50 meters range, 2 memory settings, dimming by touch.





20032 | 12-24V DC | Variable colour temperature controller & dimmer | 2 channels x 3A

DIMMABLE

2 YEAR

IP20

Remote controller for changing colour temperature from daylight to extra warm white. Suitable for use with LED strips 7835/DEW.
50 meters range, includes dimmer control and programme mode.





20034 | 12-24V DC | RGB wireless controller & dimmer | 3 channels x 3A

DIMMABLE

2 YEAR

IP20

Remote controller for changing colours (RGB). Suitable for use with LED strips 7830/RGB.
50 meters range, includes dimmer control and programme modes.





20036 | 12-24V DC | RGB+W wireless controller & dimmer | 4 channels x 3A

DIMMABLE

2 YEAR

new

IP20

Remote controller for changing colours (RGB+W). Suitable for use with LED strips 7830/RGBW.
50 meters range, includes dimmer control and programme modes.



Order Code	Colour	Input	Power	Output	Class	Dimmable		Notes
20030	White	12-24V DC	36W/ch@12V 72W/ch@24V	12-24V DC	III	YES	50	-
20032	White	12-24V DC	36W/ch@12V 72W/ch@24V	12-24V DC	III	YES	50	-
20034	White	12-24V DC	36W/ch@12V 72W/ch@24V	12-24V DC	III	YES	50	-
20036	White	12-24V DC	36W/ch@12V 72W/ch@24V	12-24V DC	III	YES	50	-





25

Lamps

Pages 653-698

COB LED | SMD LED | MR11 | MR16 | R111 | G9 | G12 | GU5,3 | GU10
PAR38 | R7S | GX53 | E27 | E14 | B15 | B22













G9 & G12



7106GPH | 60W | G9 | Dimmable | PHILIPS

HALO · DIMMABLE · 2 YEAR · offer







9407G | 7W | G9

FLUO · 2 YEAR · offer







8010L | 10W | SMD 2835 | G12

HQI G12 replacement.

LED · 80 CRI · 2 YEAR · 10,00 kWh/1000h





360°

Order Code	Lampholder	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Dimmable	
7106GPH	G9	Extra warm white	2700K	60W	-	-	230V	YES	100
9407G/D	G9	Daylight	6000K	7W	-	-	230V	NO	50
9407G/W	G9	Warm white	3000K	7W	-	-	230V	NO	50
8010L/W	G12	Warm white	3000K	10W	1000lm	360°	100-240V	NO	1

G9 LED



7105BLG/W

7103BLG/W



7103LG | 2,5W | SMD LED | G9

LED 80 CRI

CE 2 YEAR









7103BLG | 3W | SMD LED | G9 | Frosted

LED 80 CRI

CE 2 YEAR









7105BLG | 4W | SMD LED | G9 | Frosted

LED 80 CRI

CE 2 YEAR







Order Code	Lampholder	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Dimmable	
7103LG/W	G9	Warm white	3000K	2,5W	190lm	230V	NO	200
7103BLG/W	G9	Warm white	3000K	3W	220lm	230V	NO	100
7105BLG/W	G9	Warm white	3000K	4W	350lm	230V	NO	100

G9 LED



7102ALG | 2W | COB LED | G9

LED 80 CRI · CE · 2 YEAR







7102LG | 2W | COB LED | G9

LED 80 CRI · CE · 2 YEAR







7103ALG | 4W | SMD LED | G9

LED 80 CRI · CE · 2 YEAR







7106ALG | 6W | SMD LED | G9

LED 80 CRI · CE · 2 YEAR







7109ALG | 9W | SMD LED | G9

LED 80 CRI · CE · 2 YEAR





Order Code	Lampholder	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Dimmable	
7102ALG/W	G9	Warm white	3000K	2W	200lm	230V	NO	100
7102LG/W	G9	Warm white	3000K	2W	100lm	230V	NO	200
7103ALG/D	G9	Daylight	6000K	4W	350lm	230V	NO	100
7103ALG/C	G9	Cool white	4000K	4W	350lm	230V	NO	100
7103ALG/W	G9	Warm white	3000K	4W	350lm	230V	NO	100
7106ALG/C	G9	Cool white	4000K	6W	550lm	230V	NO	100
7106ALG/W	G9	Warm white	3000K	6W	550lm	230V	NO	100
7109ALG/C	G9	Cool white	4000K	9W	900lm	230V	NO	100
7109ALG/W	G9	Warm white	3000K	9W	900lm	230V	NO	100



G9 LED Dimmable & CCT Variable



7103ALGD | 3,5W | SMD LED | G9 | Dimmable

LED · 80 CRI · TRIAC DIMMABLE · CE · 2 YEAR · ENERGY A+ · 3,50 kWh/1000h







7103ALGT | 3W | SMD LED | G9 | 3-Step dimming

LED · 80 CRI · 3-STEP DIMMABLE · CE · 2 YEAR · ENERGY A+ · 3,00 kWh/1000h









7106ALGD | 5W | SMD LED | G9 | Dimmable

LED · 80 CRI · TRIAC DIMMABLE · CE · 2 YEAR · ENERGY A+ · 5,00 kWh/1000h







7103ALG/DW | 3W | SMD LED | G9 | Variable colour temperature

LED · 80 CRI · CE · 2 YEAR · ENERGY A+ · 3,00 kWh/1000h







Order Code	Lampholder	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Dimmable	
7103ALGD/W	G9	Warm white	3000K	3,5W	300lm	230V	YES	100
7103ALGT/W	G9	Warm white	3000K	3W	250lm	230V	YES	100
7106ALGD/W	G9	Warm white	3000K	5W	450lm	230V	YES	100
7103ALG/DW	G9	Warm white-Cool white-Daylight	3000K-4000K-6000K	3W	250lm	230V	NO	100

G4 & GY6,35





7101AL/W



7103A | 35W | G4 | Dimmable

HALO · DIMMABLE · CE · 2 YEAR · offer







7105 | 50W | GY6,35 | Dimmable

HALO · DIMMABLE · CE · 2 YEAR · offer







7105SR | 50W | GY6,35 | Dimmable | OSRAM

HALO · DIMMABLE · CE · 2 YEAR · offer







7101AL | 2W | COB LED | G4 | Silicone

LED · 80 CRI · CE · 2 YEAR







Order Code	Lampholder	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Dimmable	
7103A	G4	Extra warm white	2700K	35W	-	12V AC/DC	YES	1000
7105	GY6,35	Extra warm white	2700K	50W	-	12V AC/DC	YES	100
7105SR	GY6,35	Extra warm white	2700K	50W	-	12V AC/DC	YES	100
7101AL/W	G4	Warm white	3000K	2W	200lm	12V AC/DC	NO	100



7201G/W

7201G/D

MR11 GU10



7201G | 2W | COB LED | MR11 | GU10

LED 80 CRI

CE 2 YEAR







Order Code	Lampholder	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Dimmable	
7201G/D	GU10	Daylight	6000K	2W	110lm	30°	230V	NO	100
7201G/W	GU10	Warm white	3000K	2W	160lm	30°	230V	NO	100



MR16 Halogen



7350/12 | 50W | MR16 | GU5,3 | Dimmable

HALO DIMMABLE CE 2 YEAR offer









7350/38 | 50W | MR16 | GU5,3 | Dimmable

HALO DIMMABLE CE 2 YEAR offer









7350G/38SR | 50W | MR16 | GU10 | Dimmable | OSRAM

HALO DIMMABLE CE 2 YEAR offer









7350G/40 | 42W | MR16 | GU10 | Dimmable

HALO DIMMABLE CE 2 YEAR







Order Code	Lampholder	Light Colour	CCT (K)	Watts	Beam Angle	Input	Dimmable	
7350/12	GU5,3	Extra warm white	2700K	50W	12°	12V AC/DC	YES	200
7350/38	GU5,3	Extra warm white	2700K	50W	38°	12V AC/DC	YES	200
7350G/38SR	GU10	Extra warm white	2700K	50W	38°	230V	YES	100
7350G/40	GU10	Extra warm white	2700K	42W	40°	230V	YES	200



7303/D/30

7304A/W/38

MR16 LED 12V



7303 | 3W | LED | MR16 | GU5,3

LED

2 YEAR

offer









7304A | 5W | SMD LED | MR16 | GU5,3

LED

80 CRI

2 YEAR









Order Code	Lampholder	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Dimmable	
7303/D/30	GU5,3	Daylight	6000K	3W	-	30°	12V AC/DC	NO	100
7303/W/30	GU5,3	Warm white	3000K	3W	-	30°	12V AC/DC	NO	100
7304A/W/38	GU5,3	Warm white	3000K	5W	350lm	38°	12V AC/DC	NO	100



MR16 GU10 LED



7301G | 5W | SMD LED | MR16 | GU10

LED · 90 CRI · CE · 2 YEAR









7303G | 3W | LED | MR16 | GU10

LED · CE · 2 YEAR

offer









7304G | 3W | LED | MR16 | GU10

LED · CE · 2 YEAR

offer









7305G | 3x1W | LED | MR16 | GU10

New 7305G/RGB available.

LED · CE · 2 YEAR

offer







Order Code	Lampholder	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Dimmable	
7301G/W	GU10	Warm white	3000K	5W	350lm	60°	230V	NO	100
7303G/D/30	GU10	Daylight	6000K	3W	-	30°	100-240V	NO	100
7304G/D/30	GU10	Daylight	6000K	3W	-	30°	100-240V	NO	100
7305G/D/15	GU10	Daylight	6000K	3x1W	190lm	15°	100-240V	NO	100



MR16 GU10 LED



7304AG | 4,5W | LED | MR16 | GU10

LED 75 CRI | CE | 2 YEAR









7305AG | 5,5W | SMD LED | MR16 | GU10

LED 80 CRI | CE | 2 YEAR









7306G | 7W | SMD LED | MR16 | GU10

LED 80 CRI | CE | 2 YEAR









7308G | 7W | LED | MR16 | GU10

LED 80 CRI | CE | 2 YEAR

offer







Order Code	Lampholder	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Dimmable	
7304AG/D/36	GU10	Daylight	6000K	4,5W	320m	36°	100-240V	NO	100
7305AG/W/38	GU10	Warm white	3000K	5,5W	380lm	38°	230V	NO	100
7306G/C	GU10	Cool white	4000K	7W	600lm	36°	230V	NO	100
7306G/W/24	GU10	Warm white	3000K	7W	450lm	24°	100-240V	NO	100
7308G/D/45	GU10	Daylight	6000K	7W	330lm	45°	100-240V	NO	100



MR16 GU10 SMD LED



7306LG | 5,5W | SMD LED | MR16 | GU10

LED 80 CRI CE 2 YEAR









7307BG | 7W | SMD LED | MR16 | GU10

LED 80 CRI CE 2 YEAR









7307CG | 7W | SMD LED | MR16 | GU10

LED 80 CRI CE 2 YEAR







Order Code	Lampholder	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Dimmable	
7306LG/C/38	GU10	Cool white	4000K	5,5W	360lm	38°	100-240V	NO	100
7306LG/W/38	GU10	Warm white	3000K	5,5W	345lm	38°	100-240V	NO	100
7307BG/C	GU10	Cool white	4000K	7W	550lm	90°	230V	NO	100
7307BG/W	GU10	Warm white	3000K	7W	550lm	90°	230V	NO	100
7307CG/W	GU10	Warm white	3000K	7W	430lm	100°	230V	NO	100



7301GD/W

MR16 GU10 LED

Dimmable



7301GD | 5,5W | SMD 2835 | MR16 | GU10 | Dimmable

LED · 90 CRI · TRIAC DIMMABLE · CE · 2 YEAR









7306LGD | 5,8W | SMD LED | MR16 | GU10 | Dimmable

LED · 80 CRI · TRIAC DIMMABLE · CE · 2 YEAR









7306GD | 7,5W | COB LED | MR16 | GU10 | Dimmable

LED · 80 CRI · TRIAC DIMMABLE · CE · 2 YEAR









7308GD | 7W | LED | MR16 | GU10 | Dimmable

LED · TRIAC DIMMABLE · CE · 2 YEAR

offer









Order Code	Lampholder	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Dimmable	
7301GD/W	GU10	Warm white	3000K	5,5W	350lm	60°	230V	YES	100
7306LGD/D/38	GU10	Daylight	6500K	5,8W	375lm	38°	230V	YES	100
7306GD/C	GU10	Cool white	4000K	7,5W	575lm	36°	230V	YES	100
7306GD/W	GU10	Warm white	3000K	7,5W	545lm	36°	230V	YES	100
7308GD/D/45	GU10	Daylight	6000K	7W	330lm	45°	230V	YES	100
7308GD/W/45	GU10	Warm white	3000K	7W	260lm	45°	230V	YES	100



MR16 GU10 COB LED



7305CG/C/120 | 5W | COB LED | MR16 | GU10

LED 80 CRI

CE 2 YEAR

ENERGY A+ 5,00 kWh/1000h







7305CG/W | 5W | COB LED | MR16 | GU10

LED 80 CRI

CE 2 YEAR

ENERGY A+ 5,00 kWh/1000h







7306CG | 6W | COB LED | MR16 | GU10

LED 85 CRI

CE 3 YEAR

ENERGY A+ 6,00 kWh/1000h







7306CBG | 6W | COB LED | MR16 | GU10

Black body.

LED 85 CRI

CE 3 YEAR

new

ENERGY A+ 6,00 kWh/1000h





Order Code	Lampholder	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Dimmable	
7305CG/C/120	GU10	Cool white	4000K	5W	360lm	120°	230V	NO	100
7305CG/W	GU10	Warm white	3000K	5W	400lm	120°	230V	NO	100
7306CG/C	GU10	Cool white	4000K	6W	520lm	60°	230V	NO	100
7306CG/W	GU10	Warm white	3000K	6W	500lm	60°	230V	NO	100
7306CG/EW	GU10	Extra warm white	2700K	6W	480lm	60°	230V	NO	100
7306CBG/W	GU10	Warm white	3000K	6W	500lm	60°	230V	NO	100



7306KGD/C/45

7306CGD/W

MR16 GU10 COB LED

Dimmable



7306KGD | 6,5W | COB LED | MR16 | GU10 | Dimmable

LED · 80 CRI · TRIAC DIMMABLE · CE · 2 YEAR









7306CGD | 6W | COB LED | MR16 | GU10 | Dimmable

LED · 85 CRI · TRIAC DIMMABLE · CE · 3 YEAR







Order Code	Lampholder	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Dimmable	
7306KGD/C/45	GU10	Cool white	4000K	6,5W	500lm	45°	230V	YES	50
7306KGD/W/45	GU10	Warm white	3000K	6,5W	500lm	45°	230V	YES	50
7306CGD/C	GU10	Cool white	4000K	6W	520lm	60°	230V	YES	100
7306CGD/W	GU10	Warm white	3000K	6W	500lm	60°	230V	YES	100
7306CGD/EW	GU10	Extra warm white	2700K	6W	480lm	60°	230V	YES	100



7306GCD/EW

7306GC/W

Full Spectrum CRI97



7306GC | 7W | COB LED | MR16 | GU10 — Full spectrum CRI97.

LED 97 CRI











7306GCD | 7,5W | COB LED | MR16 | GU10 | Dimmable — Full spectrum CRI97.

LED 97 CRI TRIAC DIMMABLE









Order Code	Lampholder	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Dimmable	
7306GC/W	GU10	Warm white	3000K	7W	500lm	36°	230V	NO	100
7306GCD/EW	GU10	Extra warm white	2700K	7,5W	500lm	36°	230V	YES	100



MR16 Colours


7301/GR

7301 | 1,5W | LED | MR16 | GU5,3

LED

2 YEAR

offer


7301/Y

offer






7350G/GR

7350G | 50W | MR16 | GU10 | Dimmable

HALO

DIMMABLE

2 YEAR

offer


7350G/Y

offer







7305G/RGB | 2W | LED | MR16 | GU10 | RGB

Auto rotating colours.

LED

2 YEAR









7306CG/BL | 6W | COB LED | MR16 | GU10

LED

2 YEAR







Order Code	Lampholder	Light Colour	Watts	Input	Dimmable	
7301/GR	GU5,3	Green	1,5W	12V AC	NO	100
7301/Y	GU5,3	Yellow	1,5W	12V AC	NO	100
7350G/GR	GU10	Green	50W	230V	YES	200
7350G/Y	GU10	Yellow	50W	230V	YES	200
7305G/RGB	GU10	RGB	2W	230V	NO	100
7306CG/BL	GU10	Blue	6W	230V	NO	100



MR16 LED
Dimmable



7312M/AL/W | 12W | COB LED | 350mA | Dimmable

LED module suitable for MR16 fittings.

LED · 80 CRI · DIMMABLE · QUICK FIX · CE · 3 YEAR



Optional rings.
Order code 050136/W
& 050136/B.





7305M | 3x1W | LED | 350mA | Dimmable

LED module suitable for MR16 fittings.

LED · 75 CRI · DIMMABLE · QUICK FIX · CE · 2 YEAR · offer







7312M/D/30 | 4x3W | CREE LED | 700mA | Dimmable

LED module suitable for MR16 fittings.

LED · 75 CRI · DIMMABLE · QUICK FIX · CE · 2 YEAR · offer





Order Code	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input		Dimmable		Notes
7312M/AL/W	Warm white	3000K	12W	850lm	38°	350mA	40cm	YES	100	Requires 350mA driver
7305M/D/15	Daylight	6000K	3x1W	-	15°	350mA	-	YES	100	Requires 350mA driver
7305M/D/30	Daylight	6000K	3x1W	-	30°	350mA	-	YES	100	Requires 350mA driver
7312M/D/30	Daylight	6000K	4x3W	600lm	30°	700mA	-	YES	100	Requires 700mA driver



7306A/W/35

7310H/C

PAR30 COB LED



7310H | 10W | COB LED | PAR30 | E27

LED 80 CRI

CE 2 YEAR









7306A | 10W | COB LED | PAR30 | E27

LED 80 CRI

CE 2 YEAR







Order Code	Lampholder	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Dimmable	
7310H/C	E27	Cool white	4000K	10W	750lm	40°	230V	NO	20
7310H/W	E27	Warm white	3000K	10W	700lm	40°	230V	NO	20
7306A/W/35	E27	Warm white	3000K	10W	500lm	35°	230V	NO	30



PAR38



9R23 | 23W | PAR38 | E27 | Colour

FLUO

IP65

offer

2 YEAR









9R23 | 23W | PAR38 | E27 | Colour

FLUO

IP65

offer

2 YEAR







Order Code	Lampholder	Light Colour	Watts	Beam Angle	Input	Dimmable	
9R23/BL/E	E27	Blue	23W	60°	230V	NO	40
9R23/R/E	E27	Red	23W	60°	230V	NO	40



E27 Flickering Flame



9G06F | 6W | SMD LED | E27 | Flickering flame effect | Plastic

LED 80 CRI

CE 2 YEAR



Functions:
- Flickering flame
- 100%
- Dimming Up-down





Order Code	Lampholder	Light Colour	CCT (K)	Watts	Input	Dimmable	
9G06F/E	E27	Flame	1600K	6W	100-240V	NO	100



7315GB/W/45

7315G/W/45

R111 GU10 LED



7315G | 13W | SMD LED | R111 | GU10

LED 80 CRI

CE 2 YEAR











7315GB | 13W | LED | R111 | GU10

Black body.

LED 80 CRI

CE 2 YEAR

new









Order Code	Lampholder	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Dimmable	
7315G/C/45	GU10	Cool white	4000K	13W	1200lm	45°	230V	NO	20
7315G/W/45	GU10	Warm white	3000K	13W	1200lm	45°	230V	NO	20
7315GB/C/45	GU10	Cool white	4000K	13W	1200lm	45°	230V	NO	20
7315GB/W/45	GU10	Warm white	3000K	13W	1200lm	45°	230V	NO	20



7315GD/W/45

7513AGD/C/24

R111 GU10

Dimmable



7513AGD | 13W | SMD LED | R111 | GU10 | Dimmable

LED · 80 CRI · TRIAC DIMMABLE · CE · 2 YEAR









7315GD | 15W | SMD LED | R111 | GU10 | Dimmable

LED · 80 CRI · TRIAC DIMMABLE · CE · 2 YEAR









7375R | 75W | R111 | GU10 | Dimmable

HALO · DIMMABLE · CE · 2 YEAR







Order Code	Lampholder	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Dimmable	
7513AGD/C/24	GU10	Cool white	4000K	13W	850lm	24°	230V	YES	24
7315GD/W/45	GU10	Warm white	3000K	15W	1200lm	45°	230V	YES	20
7375R/24	GU10	Extra warm white	2700K	75W	-	24°	230V	YES	60



12V R111 G53 SMD LED



7513A | 13W | SMD LED | R111 | G53









7515A | 15W | SMD LED | R111 | G53







Order Code	Lampholder	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Dimmable	
7513A/C	G53	Cool white	4000K	13W	850lm	24°	12V AC/DC	NO	24
7513A/W	G53	Warm white	3000K	13W	850lm	24°	12V AC/DC	NO	24
7515A/W	G53	Warm white	3000K	15W	1000lm	36°	12V AC/DC	NO	20



7510R/W/45

7510R/D/45

12V R111 G53 COB LED



7510R | 10W | COB LED | R111 | G53

LED 80 CRI

CE 2 YEAR

offer









Order Code	Lampholder	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Dimmable	
7510R/D/45	G53	Daylight	6000K	10W	580lm	45°	12V AC/DC	NO	40
7510R/W/45	G53	Warm white	3000K	10W	540lm	45°	12V AC/DC	NO	40



7521R/C/24

10106NA/W/D/35

10106NA/AL/D/35

R111 LED
Dimmable



10106NA/AL | 6x1W@350mA / 6x3W@700mA | LED | R111 | Dimmable

LED · DIMMABLE · 85 CRI · QUICK FIX · CE · 2 YEAR · ENERGY A · 19,80 kWh/1000h

offer



LED module suitable for R111 fittings.



Use driver 89030A. (non-dimmable).





10106NA/W | 6x1W@350mA / 6x3W@700mA | LED | R111 | Dimmable

LED · DIMMABLE · 85 CRI · QUICK FIX · CE · 2 YEAR · ENERGY A · 19,80 kWh/1000h

offer



LED module suitable for R111 fittings.



Use driver 89030A. (non-dimmable).





7521R | 21W | COB LED | R111 | Dimmable with optional 500mA driver

LED · 80 CRI · QUICK FIX · CE · 2 YEAR · ENERGY A · 23,10 kWh/1000h



LED module suitable for R111 fittings.



Complete with 500mA driver.



Order Code	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Dimmable	
10106NA/AL/D/35	Daylight	6000K	6x1W/6x3W	1100lm@3W	35°	350mA/700mA	YES	20
10106NA/AL/W/35	Warm white	3000K	6x1W/6x3W	1100lm@3W	35°	350mA/700mA	YES	20
10106NA/W/D/35	Daylight	6000K	6x1W/6x3W	1100lm@3W	35°	350mA/700mA	YES	20
7521R/C/24	Cool white	4000K	21W	1625lm	24°	100-240V	NO	20



7524D/W/30

7512D/D/30

R111 LED

Dimmable



7512D | 12x1W | CREE LED | 350mA | R111 | Dimmable

Requires 350mA driver.

LED · DIMMABLE · 80 CRI · QUICK FIX · CE · 2 YEAR · ENERGY · A · 13,20 kWh/1000h

offer



LED module suitable for R111 fittings.



Use driver 89015. (non-dimmable).





7524D | 12x2W | CREE LED | 500mA | R111 | Dimmable

Requires 500mA driver.

LED · DIMMABLE · 80 CRI · QUICK FIX · CE · 2 YEAR · ENERGY · A · 26,40 kWh/1000h

offer



LED module suitable for R111 fittings.



Use driver 89030C. (non-dimmable).





7524BD | 12x2W | LED | 500mA | R111 | Dimmable

Requires 500mA driver.

LED · DIMMABLE · 80 CRI · QUICK FIX · CE · 2 YEAR · ENERGY · A · 26,40 kWh/1000h

offer



LED module suitable for R111 fittings.



Use driver 89030C. (non-dimmable).



Order Code	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Dimmable	
7512D/D/30	Daylight	6000K	12x1W	710lm	30°	350mA	YES	40
7512D/W/30	Warm white	3000K	12x1W	560lm	30°	350mA	YES	40
7524D/W/30	Warm white	3000K	12x2W	830lm	30°	500mA	YES	40
7524BD/W/30	Warm white	3000K	12x2W	860lm	30°	500mA	YES	20



R7s SMD LED



7605L | 5W | SMD 2835 | R7s

Halogen 78mm replacement.

LED 80 CRI CE 2 YEAR





360°



7610L | 10W | SMD 2835 | R7s

Halogen 118mm & 70W HQI replacement.

LED 80 CRI CE 2 YEAR





360°



7612L | 12W | SMD 2835 | R7s

150W HQI replacement.

LED 80 CRI CE 2 YEAR





360°



7615L | 15W | SMD 2835 | R7s

Halogen 189mm (1000W) replacement.

LED 80 CRI CE 2 YEAR





360°

Order Code	Lampholder	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Dimmable	
7605L/W	R7s	Warm white	3000K	5W	400lm	360°	230V	NO	100
7610L/C	R7s	Cool white	4000K	10W	930lm	360°	230V	NO	100
7610L/W	R7s	Warm white	3000K	10W	900lm	360°	230V	NO	100
7612L/W	R7s	Warm white	3000K	12W	1000lm	360°	230V	NO	100
7615L/C	R7s	Cool white	4000K	15W	1350lm	360°	230V	NO	50



7604/C

7610A/C

R7s COB LED



7604 | 4,5W | COB LED | R7s

Halogen 78mm replacement.

LED 80 CRI

CE 2 YEAR

offer









7610A | 10W | COB LED | R7s

150W HQI replacement.

LED 80 CRI

CE 2 YEAR

offer







Order Code	Lampholder	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Dimmable	
7604/C	R7s	Cool white	4000K	4,5W	350lm	180°	100-240V	NO	100
7610A/C	R7s	Cool white	4000K	10W	850lm	180°	100-240V	NO	50



7610

7610A

R7s



7610 | 80W | R7s | Dimmable

HALO · DIMMABLE · CE · 2 YEAR



78mm · 11mm



7615 | 120W | R7s | Dimmable

HALO · DIMMABLE · CE · 2 YEAR



78mm · 11mm



7610A | 120W | R7s | Dimmable

HALO · DIMMABLE · CE · 2 YEAR



118mm · 11mm



7630A | 240W | R7s | Dimmable

HALO · DIMMABLE · CE · 2 YEAR



118mm · 11mm

Order Code	Lampholder	Light Colour	CCT (K)	Watts	Input	Dimmable	
7610	R7s	Extra warm white	2700K	80W	230V	YES	500
7615	R7s	Extra warm white	2700K	120W	230V	YES	500
7610A	R7s	Extra warm white	2700K	120W	230V	YES	500
7630A	R7s	Extra warm white	2700K	240W	230V	YES	500



9F07L/C



9F01/D



9F07LD/C

GX53



9F01 | 1,5W | LED | GX53

LED

CE 2 YEAR

offer







9F01/BL

9F01 | 1,5W | LED | GX53

LED

CE 2 YEAR

offer







9F07L | 7W | SMD LED | GX53

LED 80 CRI

CE 2 YEAR









9F07LD | 7W | SMD LED | GX53 | Dimmable

LED 80 CRI TRIAC DIMMABLE

CE 2 YEAR







Order Code	Lampholder	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Dimmable	
9F01/D	GX53	Daylight	6000K	1,5W	-	230V	NO	100
9F01/W	GX53	Warm white	3000K	1,5W	-	230V	NO	100
9F01/BL	GX53	Blue	-	1,5W	-	230V	NO	100
9F07L/C	GX53	Cool white	4000K	7W	500lm	230V	NO	100
9F07L/W	GX53	Warm white	3000K	7W	500lm	230V	NO	100
9F07LD/C	GX53	Cool white	4000K	7W	480lm	230V	YES	100
9F07LD/W	GX53	Warm white	3000K	7W	480lm	230V	YES	100



E14 LED Candles

9C06BD/EW/SE

9C06B/EW/SE



9C04A | 4W | LED | E14

LED 80 CRI

CE 2 YEAR

offer





118mm

35mm



9C06B | 6W | SMD LED | E14

LED 80 CRI

CE 2 YEAR





100mm

37mm



9C06BD | 6W | SMD LED | E14 | Dimmable

LED 80 CRI

TRIAC - + DIMMABLE

CE 2 YEAR





100mm

37mm

Order Code	Lampholder	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Dimmable	
9C04A/W/SE	E14	Warm white	2700K	4W	220lm	100-240V	NO	100
9C06B/EW/SE	E14	Extra warm white	2700K	6W	450lm	230V	NO	100
9C06BD/EW/SE	E14	Extra warm white	2700K	6W	450lm	230V	YES	100



Classic Lamps LED

9G07B | 6W | SMD LED | E27



LED 80 CRI CE 2 YEAR







9G12B | 10,5W | SMD LED | E27



LED 80 CRI CE 2 YEAR







9G12BD | 10,5W | SMD LED | E27 | Dimmable



LED 80 CRI TRIAC DIMMABLE CE 2 YEAR







9G12D | 12W | SMD LED | E27 | 3-Step dimming | Dimmable



LED 80 CRI DIMMABLE CE 2 YEAR







Order Code	Lampholder	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Dimmable	
9G07B/C/E	E27	Cool white	4000K	6W	510lm	230V	NO	50
9G07B/W/E	E27	Warm white	3000K	6W	500lm	230V	NO	50
9G07B/EW/E	E27	Extra warm white	2700K	6W	480lm	230V	NO	50
9G12B/D/E	E27	Daylight	6000K	10,5W	950lm	230V	NO	50
9G12B/C/E	E27	Cool white	4000K	10,5W	900lm	230V	NO	50
9G12B/W/E	E27	Warm white	3000K	10,5W	880lm	230V	NO	50
9G12B/EW/E	E27	Extra warm white	2700K	10,5W	850lm	230V	NO	50
9G12BD/EW/E	E27	Extra warm white	2700K	10,5W	850lm	230V	YES	50
9G12D/EW/E	E27	Extra warm white	2700K	12W	1050lm	230V	YES	100



9G10M/EW/E

9G09/RGBW

Classic A60 Special Functions



9G10L | 10W | SMD LED | E27 | Night operating

ON when < 5lux, OFF when >300lux

LED 80 CRI | CE | 2 YEAR





Automatic day/night operation



9G10M | 10W | SMD LED | E27 | Microwave motion sensor

Operates only when <5lux

LED 80 CRI | CE | 2 YEAR







9G10V | 10W | SMD LED | E27 | 3-Step colour temperature changing

LED 80 CRI | CE | 2 YEAR







9G09/RGBW | 9W | SMD LED | E27 | RGBW + Remote

LED 80 CRI DIMMABLE | CE | 2 YEAR



Supplied with remote control.



Order Code	Lampholder	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Dimmable	
9G10L/EW/E	E27	Extra warm white	2700K	10W	800lm	230V	NO	100
9G10M/EW/E	E27	Extra warm white	2700K	10W	800lm	230V	NO	100
9G10V/E	E27	Extra warm white - Cool white - Daylight	2700K - 4000K - 6000K	10W	800lm	230V	NO	100
9G09/RGBW	E27	RGB + Warm white	RGB + 3000K	9W	720lm (3000K)	100-240V	YES	100



9G20L/EW/E 9G20LD/D/E

G120 LED Globe Lamps



9G20L | 20W | SMD LED | G120 | E27

LED 80 CRI

CE 2 YEAR







9G20LD | 20W | SMD LED | G120 | E27 | Dimmable

LED 80 CRI DIMMABLE

CE 2 YEAR





Order Code	Lampholder	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Dimmable	
9G20L/EW/E	E27	Extra warm white	2700K	20W	1700lm	230V	NO	40
9G20LD/D/E	E27	Daylight	6000K	20W	1800lm	230V	YES	40
9G20LD/EW/E	E27	Extra warm white	2700K	20W	1700lm	230V	YES	40

Waterproof LED



9G09P/D/E

9G20P/C/E



9G09P/../E | 10W | SMD 2835 | E27

LED 80 CRI

CE 2 YEAR

IP44



9G09P/../B | 10W | SMD 2835 | B22

LED 80 CRI

CE 2 YEAR

IP44



9G20P | 20W | SMD 2835 | E27

LED 80 CRI

CE 2 YEAR

IP64

Order Code	Lampholder	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Dimmable	
9G09P/D/E	E27	Daylight	6000K	10W	1000lm	300°	230V	NO	100
9G09P/C/E	E27	Cool white	4000K	10W	950lm	300°	230V	NO	100
9G09P/D/B	B22	Daylight	6000K	10W	1000lm	300°	230V	NO	100
9G20P/C/E	E27	Cool white	4000K	20W	1610lm	240°	230V	NO	20



High Power LED

E27 & E40



9G20N | 20W | SMD 2835 | E27











9G50N | 50W | SMD 2835 | E40











9G80N | 80W | SMD 2835 | E40









Order Code	Lampholder	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Dimmable	
9G20N/C/E	E27	Cool white	4000K	20W	1610lm	240°	230V	NO	20
9G50N/C/LE	E40	Cool white	4000K	50W	4500lm	240°	230V	NO	12
9G80N/C/LE	E40	Cool white	4000K	80W	7200lm	120°	230V	NO	6



9T05RD/A/E

9G04RAD/A/E

Retro Amber Lamps LED

Dimmable



9G03RAD | 6,5W | LED | E27 | Dimmable

LED · 80 CRI · TRIAC DIMMABLE · 2 YEAR







9T05RD | 5W | LED | T28 | E27 | Dimmable

LED · 80 CRI · TRIAC DIMMABLE · 2 YEAR







9G04RAD | 7W | LED | E27 | Dimmable

LED · 80 CRI · TRIAC DIMMABLE · 2 YEAR







9G06RD | 7W | LED | G125 | E27 | Dimmable

LED · 80 CRI · TRIAC DIMMABLE · 2 YEAR





Order Code	Lampholder	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Dimmable	
9G03RAD/A/E	E27	Amber	2200K	6,5W	550lm	230V	YES	100
9T05RD/A/E	E27	Amber	2200K	5W	380lm	230V	YES	100
9G04RAD/A/E	E27	Amber	2200K	7W	520lm	230V	YES	50
9G06RD/A/E	E27	Amber	2200K	7W	520lm	230V	YES	20



Retro Lamps LED



9C02R | 2W | LED | E14

LED 80 CRI | CE | 2 YEAR







9G03R | 4W | LED | E27

LED 80 CRI | CE | 2 YEAR









9G06R | 6W | LED | G125 | E27

LED 80 CRI | CE | 2 YEAR









9G06RD | 5W | LED | G125 | E27 | Dimmable

LED 80 CRI | TRIAC DIMMABLE | CE | 2 YEAR







Order Code	Lampholder	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Dimmable	
9C02R/EW/SE	E14	Extra warm white	2700K	2W	250lm	230V	NO	100
9G03R/EW/E	E27	Extra warm white	2700K	4W	470lm	230V	NO	100
9G06R/EW/E	E27	Extra warm white	2700K	6W	800lm	230V	NO	20
9G06RD/EW/E	E27	Extra warm white	2700K	5W	600lm	230V	YES	20



G45 LED Ball Lamps



9G01/W | 0,5W | SMD LED | G45 | B22

LED

CE 2 YEAR

offer







9G06M | 6W | SMD LED | G45 | E27

LED 80 CRI

CE 2 YEAR









9G01/../E | 0,5W | SMD LED | G45 | E27

LED

CE 2 YEAR

offer







9G01/../B | 0,5W | SMD LED | G45 | B22

LED

CE 2 YEAR

offer





Order Code	Lampholder	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Dimmable	
9G01/W/B	B22	Warm white	3000K	0,5W	-	230V	NO	200
9G06M/EW/E	E27	Extra warm white	2700K	6W	480lm	230V	NO	100
9G01/BL/E	E27	Blue	-	0,5W	-	230V	NO	200
9G01/BL/B	B22	Blue	-	0,5W	-	230V	NO	200
9G01/GR/E	E27	Green	-	0,5W	-	230V	NO	200
9G01/GR/B	B22	Green	-	0,5W	-	230V	NO	200
9G01/R/E	E27	Red	-	0,5W	-	230V	NO	200
9G01/R/B	B22	Red	-	0,5W	-	230V	NO	200

Spiral Colour CFL E27





9S13/GR/E | 13W | E27

FLUO

CE 2 YEAR

offer



121mm

43mm



9S23/Y/E | 23W | E27

FLUO

CE 2 YEAR



152mm

60mm

Order Code	Lampholder	Light Colour	Watts	Input	Dimmable	
9S13/GR/E	E27	Green	13W	230V	NO	100
9S23/Y/E	E27	Yellow	23W	230V	NO	100



9922L/D

9940L/D

T9C LED



9922L | 11W | LED | T9 | G10Q

LED 80 CRI

CE 2 YEAR









9932L | 16W | LED | T9 | G10Q

LED 80 CRI

CE 2 YEAR









9940L | 20W | LED | T9 | G10Q

LED 80 CRI

CE 2 YEAR







Order Code	Lampholder	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Dimmable	
9922L/D	G10Q	Daylight	6000K	11W	1000lm	230V	NO	20
9922L/W	G10Q	Warm white	3000K	11W	1000lm	230V	NO	20
9932L/D	G10Q	Daylight	6000K	16W	1450lm	230V	NO	20
9940L/D	G10Q	Daylight	6000K	20W	1800lm	230V	NO	10
9940L/W	G10Q	Warm white	3000K	20W	1800lm	230V	NO	10



T8 LED Tubes



9011L | 11W | SMD LED | T8 | Rotating

LED 80 CRI

CE 2 YEAR











9021L | 21W | SMD LED | T8 | Rotating

LED 80 CRI

CE 2 YEAR











9021LB | 21W | SMD LED | T8 | Nonrotating

LED 80 CRI

CE 2 YEAR

offer











9026L | 25W | SMD LED | T8 | Rotating

LED 80 CRI

CE 2 YEAR









Order Code	Lampholder	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Dimmable	
9011L/D	G13	Daylight	6000K	11W	1000lm	180°	100-240V	NO	25
9011L/C	G13	Cool white	4000K	11W	1000lm	180°	100-240V	NO	25
9021L/W	G13	Warm white	3000K	21W	1650lm	120°	230V	NO	20
9021LB/W	G13	Warm white	3000K	21W	1650lm	120°	230V	NO	20
9026L/D	G13	Daylight	6000K	25W	2300lm	180°	100-240V	NO	20
9026L/W	G13	Warm white	3000K	25W	2100lm	120°	230V	NO	20

T8 LED Tubes Glass





9007L | 7W | SMD 2835 | T8 | Glass

LED 80 CRI

CE 2 YEAR











9009L | 9W | SMD 2835 | T8 | Glass

LED 80 CRI

CE 2 YEAR











9012L | 12W | SMD LED | T8 | Glass

LED 80 CRI

CE 2 YEAR









Order Code	Lampholder	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Dimmable	
9007L/D	G13	Daylight	6500K	7W	700lm	320°	230V	NO	25
9009L/D	G13	Daylight	6500K	9W	900lm	320°	230V	NO	25
9009L/C	G13	Cool white	4000K	9W	900lm	320°	230V	NO	25
9009L/W	G13	Warm white	3000K	9W	850lm	320°	230V	NO	25
9012L/D	G13	Daylight	6500K	12W	1200lm	260°	230V	NO	25

T8 LED Tubes Glass



9022L/D



9018L | 18W | SMD 2835 | T8 | Glass

LED 80 CRI

CE 2 YEAR











9022L | 22W | SMD 2835 | T8 | Glass

LED 80 CRI

CE 2 YEAR











9032L | 32W | SMD 2835 | T8 | Glass

LED 80 CRI

CE 2 YEAR









Order Code	Lampholder	Light Colour	CCT (K)	Watts	Lumen (lm)	Beam Angle	Input	Dimmable	
9018L/D	G13	Daylight	6500K	18W	1800lm	320°	230V	NO	25
9018L/C	G13	Cool white	4000K	18W	1800lm	320°	230V	NO	25
9018L/W	G13	Warm white	3000K	18W	1720lm	320°	230V	NO	25
9022L/D	G13	Daylight	6500K	22W	2200lm	320°	230V	NO	25
9022L/C	G13	Cool white	4000K	22W	2200lm	320°	230V	NO	25
9022L/W	G13	Warm white	3000K	22W	2100lm	320°	230V	NO	25
9032L/C	G13	Cool white	4000K	32W	3200lm	260°	230V	NO	12

PL Lamps



8107 | 7W | G23 | 2pins

FLUO

CE 2 YEAR

offer







8213/W/4SR | 13W | G24q | 4pins | OSRAM

FLUO

CE 2 YEAR

offer







8218 | 18W | G24q | 4pins

FLUO

CE 2 YEAR

offer







8218/D/4SR | 18W | G24q | 4pins | OSRAM

FLUO

CE 2 YEAR

offer







8226/W/4SR | 26W | G24q | 4pins | OSRAM

FLUO

CE 2 YEAR

offer





Order Code	Lampholder	Light Colour	CCT (K)	Watts		Notes
8107/D/2	G23	Daylight	6000K	7W	200	Requires ballast
8107/W/2	G23	Warm white	3000K	7W	200	Requires ballast
8213/W/4SR	G24q-1	Warm white	3000K	13W	50	Requires ballast
8218/C/4	G24q-2	Cool white	4000K	18W	100	Requires ballast
8218/W/4	G24q-2	Warm white	3000K	18W	100	Requires ballast
8218/D/4SR	G24q-2	Daylight	6000K	18W	50	Requires ballast
8226/W/4SR	G24q-3	Warm white	3000K	26W	50	Requires ballast



HQI Rx7s 70W & 150W



8007 | 70W | Rx7s | Metal halide

HQI

CE 2 YEAR

offer







8015 | 150W | Rx7s | Metal halide

HQI

CE 2 YEAR

offer





Order Code	Lampholder	Light Colour	CCT (K)	Watts	Lumen (lm)	Input	Dimmable		Notes
8007/W	Rx7s	Warm white	3000K	70W	5250lm	230V	NO	50	Requires ballast
8015/W	Rx7s	Warm white	3000K	150W	11000lm	230V	NO	50	Requires ballast





26

Accessories

Pages 701-706

COB LED | Waterproof | Lampholders | Torch Lights | Handy Lights

IP20 IP67 IP68





LED Accessories



89003/EXT | 3-way extension for 350mA / 500mA LED fittings

200cm

QUICK FIX

2 YEAR

Suitable for all 350mA LED fittings with fast connection system.

100



89006A/EXT | 6-way extension for 700mA LED fittings

200cm

QUICK FIX

2 YEAR

Suitable for all 700mA LED fittings with fast connection system.

100

Accessories



0903F | 3-PIN Female connector

QUICK FIX

2 YEAR



0903M | 3-PIN Male connector



200



0904F | 4-PIN Female connector

QUICK FIX

2 YEAR



0904M | 4-PIN Male connector



200



0800B | Waterproof connection box 1 IN / 1 OUT | Cable diameter 5-12mm

2 YEAR

IP67



100



0800A | Waterproof connection box 1 IN / 2 OUT | Cable diameter 4-14mm

2 YEAR

IP67



100



60000 | Square plate for BS box

2 YEAR

60000/AL Aluminium
60000/W White
60000/G Grey



10



7010P | Plastic spike for garden spots

2 YEAR



200



Lampholders



0950GA | 100-240V | GU10 Lampholder | Double insulated

18cm

50





0950G | 100-240V | GU10 Lampholder with bracket | Double insulated



50





0950GB | 100-240V | GU10 Lampholder with bracket | Double insulated

Loop connector IN/OUT.



40





0802 | Connection box 3-Way IN/OUT fast connector

Loop connector IN/OUT.

IP20

100





Torch Light



70020 | 50W | HID Torch | HID XENON H1 | Rechargeable

1200m range.





70028 | LED Rechargeable Torch | EU Socket | Plastic

LED BUILT IN

offer









70026 | LED Rechargeable Torch | BS Socket | Plastic

LED BUILT IN

offer







Order Code	Colour	Watts	Battery Type	Lumen (lm)	Input	Class		Notes
70020	Black	50W	Li-ion rechargeable battery	3500lm	-	-	5	Complete with AC charger
70028	Grey	-	-	-	230V	⧈	48	-
70026	Grey	-	-	-	230V	⧈	48	-



Accessories



094004 | E27 / GU10 / E14 Testing panel — With power indicator.

2 YEAR

IP20

1





062002 | Display box for LED strips — 7820/W, 7820W/W, 7829/C, 7835/W, 7835W/C, 7823/W, 7825/W, 7870/W, 7845/W

2 YEAR

IP20

1



LED Handy Lights



70038 70036



70038 | COB LED | Wardrobe / Magnet portable light

3xAAA Batteries included.

LED BUILT IN CE 2 YEAR





12

95mm





70036 | COB LED | Wardrobe / Magnet portable light

3xAAA Batteries included.

LED BUILT IN CE 2 YEAR





12

200mm





70034 | LED Portable light

3xAAA Batteries included.

LED BUILT IN CE 2 YEAR



100

165mm





70032 | 1W | SMD 2835 | USB LED light

LED BUILT IN CE 2 YEAR

offer



170mm

18mm



Order Code	Colour	Light Colour	CCT (K)	Watts	Lumen (lm)	
70032	White	Daylight	6000K	1W	50lm	1


one
LIGHT
outdoo



27

Advertising & Marketing

Pages 709-710

Stickers | Packing Tape | Note Pads | Plastic Bags | T-Shirts





Stickers & Tape

060020 | one | Sticker

120mm
140mm

060020A | one | Sticker

290mm
340mm

060016 | switch to one light | Sticker

060018 | one light available here | Sticker

300mm
90mm

060008 | Packing Tape

4500mm
50mm

T-Shirts, Bags & Pads





060010 | A5 Note Pad

148,5mm
210mm



060012 | Small Plastic Bag

340mm
408mm



060014 | Large Plastic Bag

445mm
595mm



060026 | T-Shirt | SMALL

060027 | T-Shirt | MEDIUM

060028 | T-Shirt | LARGE

060029 | T-Shirt | XLARGE

060030 | T-Shirt | XXLARGE

040060 145, 150, 435, 436
050017 153, 154, 155, 156, 159
050042 58
050042A 58
050044 133
050084 581, 582, 583
050086 117
050086A 117
050088 117
050088A 117
050090 313, 314
050097 174
050098 36
050099 35
050100 118
050102 118
050104 46
050106 376
050108 153, 154, 155, 156,159
050108A 157
050108B 158
050112 325, 474, New 2020
050114FA 590
050114FB 590
050116HA 590
050116HB 590
050122 245, 246
050128 438
050136 669
050146 186
050148 186
050150 158
050162 51
050170 315, 317
050170C 315, 317
050176 New 2020
050178 New 2020
050180 New 2020
050182 New 2020
050182R New 2020
050182RA New 2020
050182RB New 2020
060008 709
060010 710
060012 710
060014 710
060016 709
060018 709
060020 709
060020A 709
060026 710
060027 710
060028 710
060029 710
060030 710
062002 705
0730/18 282
0736/15 221
0740/15 278
0742/15 281
0800A 702
0800B 702
0800BA New 2020
0800C New 2020
0802 703
0903F 702
0903M 702
0904F 702
0904M 702
094004 705
0950G 703
0950GA 703
0950GB 703
0990 480
0992 480
0994 511
10004 138
10007 137
10100 174
10101C 65
10101C4 487
10101C5 487
10101D 39
10101G 64
10101L 39
10101LA New 2020
10101TR 67
10102 3
10102GL 3
10102H 57
10103 5
10103A 63
10103B 40
10103BTR 68
10103D 41
10103DE 41
10103DL 42
10103FA 146
10103G 64
10103GL 63
10103L 43
10103N 44
10103NP 56
10103P 56
10103R 41
10103T 161
10103TR 67
10104M 62
10105 5
10105A1 8
10105AC 31
10105AD 16
10105ALG 9, 10
10105AR 31
10105C4 488
10105CJ 25
10105CM 7
10105D1 12
10105D2 12
10105D3 14
10105D4 13
10105D5 13
10105D8 16
10105D9 15
10105DG 12
10105E 177
10105E1 New 2020
10105F 24
10105FD 49, 50
10105GL1 29
10105GL2 29
10105GT1 33
10105GT2 33
10105GU 6
10105H New 2020
10105K 171
10105L 24
10105M 17, 18
10105MD 19, 20
10105R 26
10105R1 28
10105R1P New 2020
10105R2 28
10105R2P New 2020
10105RM 35
10105T 11
10105TG 11
10105TR 34
10105V 27
10105W 52
10105X 4
10105XS 4
10106CF 185
10106DC New 2020
10106DH New 2020
10106G 64
10106NA 677
10106P 56
10106PF 58
10107B 182
10107BT 66
10107C 63
10107CA 165
10107CD 167
10107D 47
10107DA 47
10107DB 54
10107DC 47
10107DF New 2020
10107DL 53
10107H 57
10107HC 54
10107K 46
10107KD 176
10107P 55
10107R 63
10107T 161
10107UV New 2020
10107W 52
10107WD 54
10107WP 53
10107Z 45
10108A New 2020
10108CF 185
10108D New 2020
10108D1 New 2020
10108ED 169, 170
10108F 145
10108FA 146
10108FD 160
10108H New 2020
10108R New 2020
10109D 180
10109FD 181
10110C 164
10110CA 165
10110FD 49, 50
10110G 183
10110K 171
10110T 13
10110U New 2020
10112 175
10112C 48
10112DC New 2020
10112DH New 2020
10112E 48
10112ED 169, 170
10112F 145
10112FA 146
10112H 51
10112KD 176
10112L 46
10112LR 46
10112P 55
10112R 51
10112TD 48
10112TP 53
10112Z 45
10113A 178
10113B 182
10113P 54
10113UV New 2020
10115 163
10115BF 139
10115CA 165
10115CD 167
10115CF 186
10115E 177
10115FD 49, 50
10115G 183
10115T 161
10116FD 160, New 2020
10118B 182
10118DC New 2020
10118FA 147
10120 174
10120C 164
10120CA 166
10120DH New 2020
10120F 145
10120FD 181
10120G 184
10120K 172
10120UV New 2020

10120Z 45
10122D 180
10122FD 160
10124 163
10124T 162
10124U New 2020
10125B 182
10128 175
10130A 177
10130C 164
10130CA 166
10130CD 168
10130CF 186
10130CR 164
10130ED 169, 170
10130FA 147
10130G 184
10130K 172
10130KA 172
10130T 162
10130U New 2020
10130UV New 2020
10140CD 168
10140F 147
10140P 174
10142 174
10148PE 148
10150G 184
10150T 178
10160CA 166
10215D 140
10220BF 139
10220CF 140
10220D 140
10220E 140
10220GT1 142
10220T 141
11070R 200
11070RD 189
11070TR 202
11100R 199
11101B 105
11101D 104
11102 104
11102DB New 2020
11103A 71
11103B 103
11103BD 121
11103C 73
11103D 119
11103E 119
11103L 109
11103LB 109
11103LC 107
11103LW 109
11103M 128
11103N 108
11103P 125
11104K 118
11105 71
11105A1 91, New 2020
11105ABG 80
11105ABGL 81
11105AC 82
11105AL 82
11105B1 91
11105C 73
11105CD 75
11105CDG 85
11105CF 73
11105CGU 74
11105D4 85
11105D5 93
11105D6 93
11105D7 91
11105D8 93
11105DT 85
11105DTR 99
11105E 85
11105GT4 98
11105GT5 98
11105GU 72
11105GU3 76
11105M 89, 90
11105N 94
11105TA 87
11105TG 85
11105TR 99
11105U 83
11105UA 83
11105UB 83
11105UTR 99
11106A 115
11106DB 112
11106K 114
11106KD 114
11106LB 206
11106M New 2020
11106PF 133
11106R 200
11107B 111
11107BT 134
11107C 132
11107D 126
11107DA 121
11107DL 122
11107F 129
11107FD 121
11107H 123
11107K 118
11107P 126
11107R 218
11107RA 130
11107WD 125
11108LA 127
11108M 128
11109KD 114
11109L 206
11110A 115
11110AB 192
11110AD 195
11110ATR 196
11110B 128
11110D 189
11110E New 2020
11110F 220
11110GT1 197
11110H 198
11110N 190
11110R 200
11110TR 202
11110U 191
11111C 131
11112 113
11112D 119
11112DL 120
11112E 122
11112F 220
11112H 117
11112L 206
11112RA 130
11112RB 130
11112TA 120
11112TR 213
11113E 124
11114R 218
11115C 215
11115E 217
11115F 219
11115RA 222
11118H 219
11118L 206
11118TR 213
11120B 210
11120C 215
11120E New 2020
11120F 220
11125B 209
11125F 219
11125R 218
11125RA 222
11130B 221
11130BT 205
11130C 215
11130E New 2020
11135L 221
11138 207
11140B 210
11140L 221
11140TR 213
11150A 209
11150B 210
11150TR 202
11207C 132
11207M 129
11207WD 125
11303L 109
12101 370
12104M 375
12105AB 336
12105AC 336
12105AL 328
12105B 335
12105D 327
12105E 327
12105E1 New 2020
12105E2 New 2020
12105E3 New 2020
12105F New 2020
12105H New 2020
12105M 325, New 2020
12105MA New 2020
12105N 326, New 2020
12105NA 326
12105T 329
12105TA 330
12105Y 331
12105YA 332
12106B New 2020
12106C 375
12106CA 379
12107AL 379
12107B 380, New 2020
12107F 368
12107K 376
12107KA 376
12107LD 382
12107V New 2020
12108C 378
12108FD 383
12108LA 367
12108X New 2020
12108XA New 2020
12109LA 367
12110D 375
12110HA 387
12112LA 368
12112Z 385
12112ZA 386
12115A 375
12115D 377
12115HA 387
12115L 381
12115LA 384
12115LD 382
12116FD 383
12120 337
12120Z 385
12120ZA 386
12122 259
12122C 378
12124 337
12124D 377
12125L 381
12125LA 384
12125LD 382
12126 337
12130LA 384
12130Z 385
12132 337
12134 337
12135L 381
12138G 333
12140 333

12140G 333
12142 333
12144 334
12144A 334
12205B 335
12205NA 326
12205T 329
12205TA 330
12205Y 331
12205YA 332
12207B 380
12208LA 367
12208XA New 2020
12211L 379
12220 427
12307B 380
12406B New 2020
12906B New 2020
20030 650
20032 238, 650
20034 650
20036 650
22000 645
22002 590
22004 646
22006 646
22008 646
22010 646
22020 645
38001A 263
38002A 263
38005A 263
38006A 263
38006B 263
38006C 263
38007A 263
38007B 263
38007C 263
38016 482
38018 482
38101A 260
38101B 260
38101C 260
38101D 260
38102A 260
38102B 260
38102C 260
38103 259
38104B 256
38104L 257
38105 259
38108B 256
38108J 323
38110 259
38110BD 467
38114B 256
38114C 465
38114CE 466
38114CL 464
38114DE 466
38114DL 464
38114EE 466
38114EL 464
38114GE 466
38114GL 467
38115C 463
38115L 257
38118E 578
38118L 579
38118LA 583
38118LC 581
38118M 579
38120C 463
38120E 585
38120L 314
38121D 465
38121EL 464
38124 467
38135A 311
38135L 314
38136E 578
38136LA 583
38136LC 581
38136M 579
38136P 577
38136R 584
38140AU New 2020
38140E 585
38145LA 583
38145LC 581
38150A 315
38150AR New 2020
38150B 316
38150BR New 2020
38150BU 317
38150C 316
38150E 315, 317
38152R New 2020
38152RC New 2020
38152RL New 2020
38154A 318
38154M 318
38158E 578
38158M 579
38165E 585
38207L 258
38215L 258
38218E 578
38218P 577
38220E 586
38225M 313
38230L 258
38236D 312
38236DF 312
38236DL 312
38236E 578
38236LC 582
38236M 580
38236P 577
38236R 584
38240E 586
38245LC 582
38248L 314
38248M 313
38258D 312
38258DF 312
38258E 578
38258M 580
38265E 586
40002A New 2020
40003 307
40003A 303
41002 307
41002A 303
41004 307
41004A 304
41008 307
41008A 304
41010 307
41010A 304
41012 308
41012A 305
41016 308
41016A 305
41018 308
41020 304, 308
41022 308
41022A 305
41024A 305
41026R 306
41030 303
41032 306
50006B New 2020
50101 65
50102B 59
50103GT4 66
50103L 43
50104M 62
50105ALG 9
50105AR 31
50105D7 14
50105GL 30
50105GL1 30
50105GL4 32
50105GT1 33
50105GT2 33
50105K 173
50105M 22
50105MA 21
50105R 26
50105RM 36
50105T 11
50105TG 11
50106B New 2020
50107B 61
50108A New 2020
50108F 149
50108FA 151
50115BF 139
50116F 149
50116FA 151
50120B 179
50120K 173
50122D 180
50122F 150
50122FA 151
50130B 179
50130F 150
50130FA 152
50130K 173
50136P 157
50136RP 158
50140AE 153
50140AU 155
50140AW 156
50140E 153
50140U 155
50140W 156
50143F 154
50148AE 154
50148AU 155
50148E 154
50148PE 152
50148RE 159
50148U 155
50160E 159
50202B 59
50205D 23
50207B 61
50220B 179
50220BF 139
50220GT1 142
50220T 141
50302B 60
50306B New 2020
50307B 61
50401L 43
50406B New 2020
50502B 60
50506B New 2020
50507B 61
50601L 43
50902B 60
50906B New 2020
51010TR 100
51020TR 100
51100R 199
51100TR 201
51101AL 105
51101B 105
51101W 105
51103 77
51103AB 82
51103L 110
51103LB 110
51103LC 107
51103LW 110
51105 77
51105AB 79
51105ABG 80
51105B 95
51105B1 92
51105CD 75
51105CDG 86

51105CGU 74
51105D 86
51105D5 93
51105D7 92
51105DG 86
51105F 97
51105GA 78
51105GT4 98
51105GU 78
51105N 94
51105R 96
51105TA 88
51105TG 86
51105TR 99
51105U 84
51105UA 84
51106A 116
51106M New 2020
51107 111
51109B 211
51110 191
51110A 116
51110AB 193
51110AD 195
51110ATR 196
51110GT1 197
51110N 190
51111C 131
51112 113
51112E 122
51112H 117
51112TA 120
51113E 124
51115TR 214
51120 208
51120B 211
51120TR 214
51125 207
51125A 209
51130 208
51138 207
51140 216
51140B 211
51140TR 214
51145 216
51200AR 199
51200R 199
51200TR 201
51201AL 106
51205ABG 80
51205B 95
51205N 94
51206M New 2020
51209B 212
51210AB 194
51210N 190
51211C 131
51212E 122
51220 208
51220TR 214
51230 208
51240B 212
51300AR 199
51300R 199
51301AL 106
51305B 95
51306M New 2020
51310AB 194
51310N 190
51400AR 199
51400R 199
51401AL 106
51401R 199
51406B New 2020
51506B New 2020
60000 702
60001 370
60004 370
60008 362
60008A 362
60010 370
60012A 421
60012B 421
60014C 421
60016B 421
60032 369
60034 369
60038 324
60040 324
60042 324
6005 340
60054 324
60056 339
60106 468
60106A 468
60107A 469
60107B 469
60107C 470
60107D 470
6012 340
6017 339
6017A 339
6017G 340
60204 468
6022 340
6028 369
6030 339
61036 498
61038 498
61038B 498
61040 510
61042A 493
61044 492
61044A 493
61046 491
61048A 489
61048B 489
61050A 490
61050B 490
61058A 497
61066 506
61066T 506
61068 505
61068B 505
61070 505
61072 505
61074 492
61076 491, New 2020
61078 491, New 2020
61080 492
61082 494
61082A New 2020
61084 New 2020
62010 429
62010A 429
62012 430
62014 430
62018 434
62018A 434
62018AF 439
62018F 439
62022A 432
62022AM 432
62022B 432
62022C 432
62024A 431
62024B 431
62024C 431
62025 459
62026A New 2020
62026B New 2020
62026C New 2020
62030F 440
62038F 440
62046F 440
62100 451
62102 428
62104 428
62110 322
62110A 322
62110B 321
62115F 435
62118D 458
62122F 436
62125D 458
62130AF 436
62130F 435
62130N 455
62132N 455
62132NA 456
62134N New 2020
62135NA 456
62140AE 437
62140AF 438
62140F 438
62140FB 441
62140RE 437
62140RF 438
62142N 455
62142NA 456
62142NB 502
62144N 455, New 2020
62144NB 501, New 2020
62146 New 2020
62146A New 2020
62148A 503
62148B 503
62148D 503
62150D 458
62152 New 2020
62152A New 2020
62154 New 2020
62156C New 2020
62156D New 2020
62160 457
62160A 457
62160FB 441
62180NB 502
62200 451
62210A 322
62210B 321
62300 451
62310A 322
62401AL 362
63001 475
63002 475
63016A 479
63020 478
63022 479
63022A 479
63022B 479
63025L 484
63026 478
63028 512
63028A 512
63028B 512
63030L 484
63034 484
63036 473
63038 473
63040 477
63042 477
63044 477
63046 499
63046A 499, New 2020
63046B 499
63048 500
63050 501
63052 490
63070D 483
63100E 589
63100F 590
63105L 474
63105M 474, New 2020
63105MA New 2020
63105N 474
63108 476
63108A 476
63110C 504
63110D 504
63112 New 2020
63114 New 2020
63150F 590
63200A 588

63200F 590
63270 483
64002 453
64004 453
64006 453
64008 454
64010 454
65008T 294
65009T 288
65010B 288
65010T 288
65011T 293
65012T 293
65013T 294
65016T 293
65018T 285
65019T 293
65020T 287
65024T 286
65024TA New 2020
65025T 285
65026T 286
65042T 287
65100/BASE 304
65102 362
65105A 509
65105N 508, New 2020
65105NA 508, New 2020
65105NAT 298
65105NT 298, New 2020
65107 368
65108T 277
65110A 365
65110B 365
65110C 365
65110D 365
65110E 366
65110F 366
65110P 481
65111AT 299
65112T 289
65114T 289
65118AT 300
65138 492
65142 New 2020
65205N 508, New 2020
65226T 282
65234T 296
65235T 296
65305B 509
65305N 508, New 2020
65306BT New 2020
65506BT New 2020
65510T 287
65514T 295
65518T 297
65519T 297
65520T 297
65522T 298
65524T New 2020
65534T 295
65608T 269
65610AT 270
65611NT 273, 274
65611T 271
65612NT 273, 274
65612T 271
65614NT 273, 274
65614T 272
65616T 272
65618T 281
65619T 281
65620AT 270
65620T 279
65620T2 279
65620TA 279
65622T 282
65624T 281
65626T 280
65628T 280
65630T 280
65632CT 277
65632T 277
65638T 281
65640AT 278
65640BT 278
65642AT 275, 276
65642BT 275, 276
65642CT 275, 276
65644T 283
65646T 277
65648T 284
65650T 284
65652T 283
65719T 290
65736T 290
65738 364, New 2020
65738A 364
65740 507
65740A 507
65742 363
65744 364
65746 363
65746A 363
65746B 364
65746R 363
65834T 291
65835T 291
65934T 292
65935T 292
67004 569
67010W 569
67030 358
67032 357
67034 566
67036 566
67076 398
67076A 398
67090 558
67092 558
67094 557
67098 557
67100 558
67102 558
67104P 353
67106P 353
67116 420
67118 420
67124 407
67126 419
67128 419
67130 347
67130A 348
67130C 347
67130CD 346
67130D/W 348
67130DD 346
67130E 347
67130F 348
67132 349
67132A 350
67132C 349
67132D 350
67132E 349
67132F 350
67134A 353
67134E 353
67138 393
67138A 393
67138C/G 389
67138C/W 390
67138D/G 389
67138D/W 390
67138E 391
67138EL 394
67138F 392
67138L 394
67160 342
67162 338
67163 342
67164 338
67170 415
67172 415
67174 418
67176 418
67180 559
67182 559
67196A 552
67196B 552
67196BG 551
67196C 552
67198AG 548
67198G 548
67204 351
67204B 351
67206 351
67208 352
67208B 352
67210 352
67214 354
67216 354
67220A 422
67228 341
67234 562
67234A 562
67236 561
67236A 561
67238 561
67238A 561
67250 560
67250A 560
67256 422
67270 561
67274 403
67274A 403
67274B 404
67274C 404
67280AN 445
67280ANE 445, 614
67280BN 445
67280E 443
67280EA 443
67280N 445
67282 444
67282A 444
67282AN 446
67282ANE 446, 614
67282BN 446
67282E 444
67282EA 444
67282N 446
67284L 433
67284LA 433
67284LE 433, 614
67286 569
67292 355
67298 403
67300 338
67302 341
67302A 341
67304 407
67308 416
67316A 452
67328 355
67328A 355
67334 422
67336 422
67340A 405
67342 399
67346 374
67346A 374
67354 416
67356 399
67358 565
67359 411
67359A 412
67359B 412
67360 411
67360A 412
67362 447
67362A 447
67362B 400
67362C 400
67363 447

67363A 447
67364 371
67366 449
67366E 449, 614
67368 449
67368M 449
67370 450
67372 450
67374 399
67374A 399
67376 402
67376A 402
67378 401
67378A 401
67380 388
67380A 388
67384 448
67384A 448
67386A 408
67386C 408
67388A 410
67388B 410
67388C 410
67390 460
67392 400
67394 409
67394A 409
67394B 409
67396 408
67396A 408
67398 406
67398A 406
67398C 406
67400A 343
67400B 343
67400D 344
67400E 344
67402 460
67404 459
67404A 459
67404M 459
67406 571
67406A 571
67406B 571
67406C 571
67406D 572
67406E 572
67408 570
67410 567
67410A 568
67412 402
67414 414
67416 414
67418 414
67420 356
67420A 356
67420AL 395
67420B 356
67420BL 396
67420L 395
67422 417
67422A 417
67424 371
67424A 371
67424B 371
67426 345
67426A 345
67428 555
67430A 413
67430B 413
67432 554
67434 369
67436 442
67436A 442
67438 442
67438A 442
67440 397
67440A 397
67442 372
67442B 372
67442C 372
67444C 372
67446EM 614
67448 460
67448A 460
67450 423
67450A 423
67452 New 2020
67454 361
67456 548
67458 548
67460A 564
67460B 564
67462 556
67464G 548
67466A 424
67466B 424
67466C 424
67468 407
67470 563
67470A 563
67472 New 2020
67472A New 2020
67474 New 2020
67474A New 2020
67474B New 2020
68001 533, 534
68002 533, 534
68003 533
68004 520
68004A 520
68004B 519
68005 516
68005/BOX 516
68006 515
68006N New 2020
68007 515
68008 516
68008/BOX 516
68012 529
68016 529
68022 529
68024 529
68030 521
68032 522
68044 530
68046 518
68048 518
68050 518
68052 517
68052A 517
68054 515
68058 525
68060 525
68062 528
68064 528
68066 528
68068 527
68068A 527
68068C 527
68070 520
68070A 519
68072A 526
68072B 526
68072C 526
68074 523
68074A 523
68074B 523
68076 524
68076A 524
68078 New 2020
69002 544
69002/RGB 544
69003 544
69006 543
69006G 541
69008 543
69008G 541
69012 537
69016 536
69016A 536
69016AG 535
69016B 536
69016BG 535
69016G 535
69026 539
69028 537
69032 574
69034 574
69036 574
69040 539
69042 531
69042A 532
69042B 532
69042M 531
69044 532
69046G 542
69048G 542
69050 539
69050A 539
69052 538
69052A 538
69054 540
69054A 540
69056A New 2020
69056B New 2020
69056C New 2020
70020 704
70026 704
70028 704
70032 706
70034 706
70036 706
70038 706
70080 607
7008A 553
7008L 553
70090 607
7010 553
70100 608
70101 608
70104 609
70105 609
70108 609
7010A 553
7010P 702
70110 610
7020 591
7022 592
7028A/AN 598
7028A/AN/RGB 593
7028A/G 594
7028AB 598
7028AG 603
7028AR 593
7028B/AN/RGB 593
7028B/G 594
7028BE 595
7028BG 603
7028BP 594
7028BR 593
7028CA 601, New 2020
7028CB 601, New 2020
7028CC 601, New 2020
7028CD 602, New 2020
7028CE 602
7028CF 602
7028CG 603
7028E 598
7030 592
7032 594
7034B 597
7034C 597
7034D 597
7038 596
7040 596
7040E 596
7046 549
7046P 373
7047 550
7048 595
7050A 604
7050B 604
7050C 604

7052 554
7052B 554
7055A 606
7055B 606
7055B/RGB New 2020
7056 587
7056A 587
7056B 587
7058 605
7060 595
7062A 599
7064 600
7066 600
7068 547
7070 547
7101AL 657
7102ALG 655
7102LG 655
7103A 657
7103ALG 655
7103ALG/DW 656
7103ALGD 656
7103ALGT 656
7103BLG 654
7103LG 654
7105 657
7105BLG 654
7105SR 657
7106ALG 655
7106ALGD 656
7106GPH 653
7109ALG 655
7201G 658
7301 668
7301G 661
7301GD 664
7303 660
7303G 661
7304A 660
7304AG 662
7304G 661
7305AG 662
7305CG/C/120 665
7305CG/W 665
7305G 661
7305G/RGB 668
7305M 669
7306A 670
7306CBG 665
7306CG 665
7306CG/BL 668
7306CGD 666
7306G 662
7306GC 667
7306GCD 667
7306GD 664
7306KGD 666
7306LG 663
7306LGD 664
7307BG 663
7307CG 663
7308G 662
7308GD 664
7310H 670
7312M 669
7315G 673
7315GB 673
7315GD 674
7350 659
7350G 659, 668
7350G/38SR 659
7375R 674
7510R 676
7512D 678
7513A/C 675
7513AGD 674
7515A 675
7521R 677
7524BD 678
7524D 678
7604 680
7605L 679
7610 681
7610A 681
7610A/C 680
7610L 679
7612L 679
7615 681
7615L 679
7630A 681
7810 265
7811 264
7811E 264
7811F 264
7812 266
7813L 233
7814 266
7815 266
7815B 266
7817 266
7818 266
7820 227, New 2020
7820/BL 239
7820A/RGB 240
7820AW 228
7820C 240
7820L 233
7820V 234
7820W 228
7820W/BL 239
7820WL 233
7821 225
7822 225, 227
7823 226
7824 225, 227
7825 235
7826 228
7827 232, 242
7828 228
7829 229
7830 231
7830/RGB 241
7830/RGBW 241
7830A/RGBW 240
7830W/RGB 242
7831 225
7832 225, 231
7832/RGB 241
7833 226
7834 225, 231
7834/RGB 241
7835 231, New 2020
7835/DEW 238
7835C 230
7835P 230, 231
7835V 234
7835W 232
7836 243
7836A 243
7837 230, 231
7838M 245, 246
7840 255
7841 New 2020
7841F New 2020
7842 255
7844 New 2020
7845 236
7850/BL 261
7850C 261
7850E 261
7850F 261
7850L 261
7850P 261
7860 261
7860C 261
7860E 261
7860F 261
7860L 261
7860P 261
7860R 261
7862 262
7862C 262
7862E 262
7862F 262
7862L 262
7862P 262
7862R 262
7866 New 2020
7866E New 2020
7866F New 2020
7868 New 2020
7868C New 2020
7868E New 2020
7868F New 2020
7868P New 2020
7870 235
7875 235
7880 237
7882 237
7885 237
7887 236
7900C 245, 246, 248
7900P 245, 246, 248
7900R 245, 246
7900TR 253
7901 243
7901R 250
7901TR 253
7902 243
7902R 250
7904 244
7904ATR 253
7904R 250
7904TR 253
7905 244
7906 248
7906A 248
7906B 248
7906C 248
7906D 248
7906R 251
7906TR 253
7908 247
7908A 247
7910 246
7910A 246
7910AR 252
7910R 252
7912 245
7912A 245
7912R 251
7914R 254
7915R 254
7916 249
7918 254
7937T 247
8007 698
8010L 653
8015 698
8107 697
8213/../4SR 697
8218 697
8218/../4SR 697
8226/../4SR 697
89002 613
89003/EXT 701
89004 624
89004A 624
89004C 624
89005/EME 618
89005A/EME 617
89006A 626
89006A/EXT 701
89006AT 628
89006P New 2020
89006PA New 2020
89006PC New 2020
89008 625
89008A 626
89008CT 627
89008W 630
89009/EME 619
89010D 648
89012BT 627

89015 625
89015A 626
89015AT 628
89015CT New 2020
89015T 628
89015V 631
89015W 630
89016T 627
89018DT 627
89020 625
89020L 642
89022ET 627
89024D 647
89024E 647
89025L 642
89027D 641
89028AM 623
89028M 623
89030A 626
89030AT 627
89030C 626
89030D 641
89030V 631
89030VD 640
89030VL 635
89030W 630
89040VT 634
89045L 642
89048 148, 152, 154, 155, 159, 178
89048T 628
89050D 641
89050L 642
89060 159
89060V 631
89060VL 635
89060VLD 636
89060VN 637
89060WD 633
89075L 640
89075V 631
89075VL 635
89075VT 634
89075W 630
89100 649
89100L 648
89100V 632
89100VL 635
89100VLD 636
89100VLL 636
89100VN 637
89100VND 638
89100VP 639
89100VT 634
89109E 629
89110E 629
89143F 620
89150V 632
89150VL 635
89150VLD 636
89150VN 637
89150VP 639
89200V 632
89200VN 637
89200VND 638
89200VP 639
89200WN 630
89302 649
89302A 649
89304B New 2020
89304F New 2020
89350VN 637
89402 616
89404 616
89406 615
89406R 615
9007L 695
9009L 695
9011L 694
9012L 695
9018L 696
9021L 694
9021LB 694
9022L 696
9026L 694
9032L 696
9407G 653
9922L 693
9932L 693
9940L 693
9C002 496
9C004A 496
9C004B 496
9C006 495
9C008 495
9C02R 690
9C04A 683
9C06B 683
9C06BD 683
9F01 682
9F07L 682
9F07LD 682
9G01 691
9G02H/RGB New 2020
9G03R 690
9G03RAD 689
9G04A New 2020
9G04D New 2020
9G04E New 2020
9G04F New 2020
9G04H New 2020
9G04RAD 689
9G06F 672
9G06M 691
9G06R 690
9G06RD 690
9G06RD/A/E 689
9G07B 684
9G08B New 2020
9G08C New 2020
9G08D New 2020
9G08E New 2020
9G08K New 2020
9G09/RGBW 685
9G09P 687
9G10L 685
9G10M 685
9G10V 685
9G12B 684
9G12BD 684
9G12D 684
9G20L 686
9G20LD 686
9G20N 688
9G20P 687
9G50N 688
9G80N 688
9R23 671
9S13 692
9S23 692
9T05RD 689

HEADQUARTERS

CYPRUS

ONE LIGHT LIMITED
www.1-light.eu
one@1-light.eu
0035722450833

UK

ONE-LIGHT (UK) LIMITED
www.1-lightuk.com
info@one-lightuk.com
00448445561515

AGENTS / DISTRIBUTORS

ALBANIA

BROTECH BRANDS SH.P.K.
www.brotechbrands.com
info@brotechbrands.com
00355674092746

AUSTRALIA

LIGHTMODO LIGHTING
www.lightmodo.com.au
sales@lightmodo.com.au
0061490365525

AUSTRIA

ELUX LICHTSYSTEME GMBH
www.elux-licht.at
office@elux-licht.at
004316154690

BAHRAIN

ELAMES LIGHTING B.S.C. (C)
www.behzad-group.com
lightestimator@behzad-group.com
lighting@behzad-group.com
0097317701166

ILLUMINATI FOR LIGHTING & ELECTRICAL SOLUTIONS EST
sales@illuminati-solutions.net
0097366765467

LIGHTEX W.L.L.
www.lightex.com.bh
info@lightex.com.bh
0097316014455

YATEEM COMMERCIAL CO. WLL
www.yateemcommercial.com
lighting@yateemcommercial.com
0097317262601

BOSNIA HERZEGOVINA

ELEKTRO JURIC D.O.O
www.elektrojuric.ba
info@elektrojuric.ba
0038736347462

BULGARIA

ATG PLC
www.atg.bg
sales@atg.bg
0035929624655

CANADA

SOLAVANTI LIGHTING
www.solavantilighting.com
sales@solavantilighting.com
0012142219405

CHILE

HOME CONTROL S.A.
www.homecontrol.cl
iluminacion@homecontrol.cl
0056229502000

CROATIA

ART-RASVJETA D.O.O.
www.art-rasvjeta.hr
info@art-rasvjeta.hr
0038513697901

CYPRUS

DIMCO LTD
www.dimco.eu
dimco@dimco.eu
0035722446565

CZECH REPUBLIC

ATEH spol. s r.o.
www.ateh.eu
ateh@ateh.eu
00420777304460
00420777304463

ESTONIA

ELEKTRI EKSPERT LTD
www.ledekspert.eu
info@ledekspert.eu
003726386416

GHANA

DEBBAS GHANA LIMITED
www.debbas.com
jsaadeh@debbas.com
00233242666600

GREECE

ZAMPELIS SA
www.zambelislights.gr
info@zambelislights.gr
00302299063519

HUNGARY

REVOLUM LIGHTING ZRT
www.revolum.hu
info@revolum.hu
0036708843830

ICELAND

PFAFF
www.pfaff.is
esm@pfaff.is
003544140400

IRELAND

RICHMOND ELECTRICAL WHOLESALE LTD
www.rew.ie
sales@rew.ie
0035316527036

JORDAN

BUILDING TECHNOLOGY SUPPLIERS
www.hudalighting.com
suleiman@hudalighting.com
0096265854660

KAZAKHSTAN

VMA GROUP LLP
www.vma.kz
info@vma.kz
0077272314393

AGENTS / DISTRIBUTORS

KUWAIT

[hōm] INTERIORS
www.homkw.com
info@homkw.com
0096592298018

Q EIGHTY UNITED GENERAL TRADING & CONTRACTING COMPANY
www.q80united.com
helpdesk@q80united.com
0096522450286

LEBANON

AYANIAN GROUP S.A.L
www.ayaniangroup.com
info@ayaniangroup.com
009619855790
0096176479974

LITHUANIA

ENERGY GREEN UAB
www.energygreen.lt
info@energygreen.lt
0037065644823

MALTA

VCT LTD
www.vct.com.mt
info@vct.com.mt
0035621432571

MAURITIUS

MUBELO ELECTRICAL LTD
www.mubelo.mu
contact@mubelo.mu
002306985200

MOLDOVA

TOP LIGHT SRL
www.smartlight.md
office@smartlight.md
0037378202020

MONTENEGRO

DC LIGHT SYSTEMS D.O.O.
www.dclightsystems.me
office@rasvjeta.co.me
0038267257533

IQ ENERGY D.O.O.
www.iqenergy.me
info@iqenergy.me
0038269202936

MOROCCO

SOCIETE LEDS PLAY
fbahechar@ledsplay.ma
00212619994444

NETHERLANDS

SPINLIGHT
www.spinlight.nl
info@spinlight.nl
0031548521188

NIGERIA

SOLUTION LUMIERE LTD
www.lumieregroup.net
nigeria@lumieregroup.net
002348112112112

NORTH MACEDONIA

MANEKS DOO
www.maneks.mk
manex1@t.mk
003892642742

NORWAY

BELYSNINGS GRUPPEN AS
www.belysningsgruppen.no
torgeir@belysningsgruppen.no
004793414555

OMAN

M/S AL KHALILI ELECTRICAL
www.alkhalili.com
info@alkhalili.com
0096822035000

POLAND

LUXLIGHT
www.luxlight.co
biuro@luxlight.co
0048602577183

PORTUGAL

DISLAMP Lighting
www.dislamp.pt
encomendas@dislamp.pt
00351234644148

QATAR

CUBE LIGHT W.L.L.
www.cubelight.net
info@cubelight.net
0097444510660

ROMANIA

LUMIDEX EXPERT SRL
www.lumidex.ro
contact@lumidex.ro
0040723751731

ATAS Lighting
www.atas.ro
office@atas.ro
0040726262604

RUSSIA

KD-TREND
irapan@mail.ru
0079114731867

SERBIA

KINETIC LIGHTING DOO
www.kinetic-lighting.rs
office@kinetic-lighting.rs
00381638038767

LIGHT SYSTEMS DESIGN DOO
www.lsdesign.rs
snezana@lsdesign.rs
00381695002616

LIGHT DESIGN CENTER
www.ldc.rs
info@ldc.rs
00381112630799

SELBI d.o.o.
www.selbi.rs
office@selbi.rs
00381113392636

SLOVAKIA

ATEH spol. s r.o.
www.ateh.eu
ateh@ateh.eu
00420777304460
00420777304463

SLOVENIA

DIMCO TRADE D.O.O
www.dimco-svetila.si
info@dimco-svetila.si
0038617296422

AGENTS / DISTRIBUTORS

SPAIN

GRUPO MCI
www.grupo-mci.com
nacional@grupo-mci.com
0034936302800

SUDAN

NORTY TRADING
www.nortiinvest.com
w.asim@nortiinvest.com
sales1@nortiinvest.com
00249900388090

SWITZERLAND

AXTRON GmbH
www.axtron.ch
info@axtron.ch
0041527215858

ELEKTRO-MATERIAL AG
www.e-m.ch/licht
licht@e-m.ch
0041564197070

UAE

PROJECTS AND SUPPLIES CO. LTD L.L.C.
www.projectsandsupplies.com
mailbox@projectsandsupplies.com
0097142898828

UK

ONE-LIGHT (UK) LIMITED
www.1-lightuk.com
info@one-lightuk.com
00448445561515

UKRAINE

ELEKOMP
www.elekomp.com
elekomp@ukr.net
00380673533757

URUGUAY

TRIOS LIGHTING
www.trioslighting.com
info@trioslighting.com
0059827119260

USA

SOLAVANTI LIGHTING
www.solavantilighting.com
sales@solavantilighting.com
0012142219405

NOTES





Please note:

Prices are subject to change without notification. ONE Light may change product specifications without notifying customers. ONE Light does not accept any responsibility for mistakes in this catalogue, we strongly advise customers to contact us to confirm specifications. Fitting sizes in catalogue may vary from actual fitting dimensions. Always check the actual fitting before cutting holes. ONE Light may discontinue any item from this catalogue without prior notice. No images or information may be copied or reproduced without written permission from ONE Light.

5 291889 063889 >

one
LIGHT

www.1-light.eu